

FCC TEST REPORT

(PART 24)


Applicant:	MUNIC
Address:	100 Avenue de Stalingrad 94800 Villejuif – France

Manufacturer or Supplier:	MUNIC
Address:	100 Avenue de Stalingrad 94800 Villejuif – France
Product:	telematics embedded system
Brand Name:	MUNIC
Model Name:	C4MAX-4MUSAA_V8
FCC ID:	A6GC4MAX-4MUSAAV8
Date of tests:	Nov. 01, 2022 ~ Nov. 14, 2022

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 24, Subpart E** ☒ **FCC PART 2**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Nov. 14, 2022	Date: Nov. 14, 2022

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	5
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 CONFIGURATION OF SYSTEM UNDER TEST	10
2.3 DESCRIPTION OF SUPPORT UNITS	11
2.4 TEST ITEM AND TEST CONFIGURATION.....	11
2.5 EUT OPERATING CONDITIONS	14
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3 TEST TYPES AND RESULTS	15
3.1 OUTPUT POWER MEASUREMENT	15
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	15
3.1.2 TEST PROCEDURES	15
3.1.3 TEST SETUP	16
3.1.4 TEST RESULTS	16
3.2 FREQUENCY STABILITY MEASUREMENT	24
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	24
3.2.2 TEST PROCEDURE	24
3.2.3 TEST SETUP	24
3.2.4 TEST RESULTS	25
3.3 OCCUPIED BANDWIDTH MEASUREMENT	33
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	33
3.3.2 TEST SETUP	33
3.3.3 TEST PROCEDURES	33
3.3.4 TEST RESULTS	34
3.4 BAND EDGE MEASUREMENTC	41
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	41
3.4.2 TEST SETUP	41
3.4.3 TEST PROCEDURES	42
3.4.4. TEST RESULTS	43
3.5 CONDUCTED SPURIOUS EMISSIONS	56
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	56
3.5.2 TEST PROCEDURE	56
3.5.3 TEST SETUP	56
3.5.4 TEST RESULTS	57
3.6 RADIATED EMISSION MEASUREMENT	67
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	67
3.6.2 TEST PROCEDURES	67



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

3.6.3 DEVIATION FROM TEST STANDARD	67
3.6.4 TEST SETUP	68
3.6.5 TEST RESULTS	70
3.7 PEAK TO AVERAGE RATIO	100
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	100
3.7.2 TEST SETUP	100
3.7.3 TEST PROCEDURES	100
3.7.4 TEST RESULTS	101
4 INFORMATION ON THE TESTING LABORATORIES	113
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB....	114



Test Report No.: W7L-P22100017RF02

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P22100017RF02	Original release	Nov. 14, 2022

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
§2.1046	Coducted Output Power	Compliance
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance
§2.1055 §24.235	Frequency Stability	Compliance
§2.1049	Occupied Bandwidth	Compliance
§24.232(d)	Peak to average ratio	Compliance
§24.238(a)(b)	Band Edge Measurements	Compliance
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	Compliance
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9kHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GMHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GMHz ~6GMHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GMHz ~18GMHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GMHz ~40GMHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 18,22	Feb. 17,23
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.15,22	May.14,23
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.04,22	Sep.03,23
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Mar. 06,22	Mar. 05,23
Horn Antenna	ETS-LINDGRE N	3117	00168692	Mar. 06,22	Mar. 05,23
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Aug. 24, 22	Aug. 23, 23
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 15,22	Feb. 14,23
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.12,22	May.11,23
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 21,22	Feb.20,23
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	May. 19,20	May. 18,23
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	May. 07,22	May. 06,23
Power Meter	Anritsu	ML2495A	1506002	Feb. 22,22	Feb. 21,23
Power Sensor	Anritsu	MA2411B	1339352	May. 07,22	May. 06,23
Temperature Chamber	ESPEC	SH-242	93000855	May. 12,22	May. 11,23
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 18,22	Feb. 17,23
Base station R&S CMW500	Rohde&Schwa rz	CMW500	153085	May.12,22	May.11,23
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 24,22	Aug. 23,23

- NOTE:** 1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	telematics embedded system	
BRAND NAME	MUNIC	
MODEL NAME	C4MAX-4MUSAA_V8	
NOMINAL VOLTAGE	5.0/13.0/27.0Vdc(DC source) 3.7Vdc (Li-ion, battery)	
MODULATION TYPE	GPRS: GMSK EDGE: 8PSK LTE Band 2: QPSK, 16QAM	
FREQUENCY RANGE	GPRS, EDGE	1850.2MHz ~ 1909.8MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	GPRS	413.05mW
	EDGE	141.91mW
	LTE Band 2 Channel Bandwidth: 1.4MHz	77.98mW
	LTE Band 2 Channel Bandwidth: 3MHz	77.98mW
	LTE Band 2 Channel Bandwidth: 5MHz	77.98mW
	LTE Band 2 Channel Bandwidth: 10MHz	77.8mW
	LTE Band 2 Channel Bandwidth: 15MHz	78.16mW
	LTE Band 2 Channel Bandwidth: 20MHz	78.34mW
EMISSION DESIGNATOR	GPRS	245KGXW
	EDGE	246KG7W



	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M11G7D 16QAM: 1M10W7D
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 1M27G7D 16QAM: 1M27W7D
	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 1M10G7D 16QAM: 1M10W7D
	LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 1M09G7D 16QAM: 1M10W7D
	LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 1M09G7D 16QAM: 1M09W7D
	LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 1M10G7D 16QAM: 1M10W7D
ANTENNA TYPE	External Antenna with -3.79dBi gain for GSM1900 External Antenna with -3.24dBi gain for LTE B2	
HW VERSION	HC4MAX-4MUSAA_V8.01	
SW VERSION	SC4MAX-4MUSAA_V8.01	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	
EXTREME TEMPERATURE	-20-55 °C	
EXTREME VOLTAGE	8V - 32V	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	1TX/1RX
LTE	1TX/1RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.


4. List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery 1	Howell	HWE711260H	Capacity : 450mAh
Battery 2	Akkutronics	711260-PTLC	Capacity : 450mAh



2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	Kikusui/JP	PMX18-5A	0000001	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Battery with GPRS or LTE link
B	EUT + DC Source with GPRS or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GPRS, EDGE
B	FREQUENCY STABILITY	512 to 810	512, 661, 810	GPRS, EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GPRS, EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GPRS, EDGE
A	BAND EDGE	512 to 810	512, 810	GPRS, EDGE
A	CONDUCTED EMISSION	512 to 810	512, 661, 810	GPRS, EDGE
B	RADIATED EMISSION	512 to 810	512, 661, 810	GPRS, EDGE

LTE BAND 2 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	6 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	6 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
A	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			19193	1.4MHz	QPSK, 16QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			19185	3MHz	QPSK, 16QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset 6 RB / 0 RB Offset
			19175	5MHz	QPSK, 16QAM	1 RB / 5 RB Offset 6 RB / 0 RB Offset



BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

		18650 to 19150	18650	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
			19150	10MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK, 16QAM	1 RB / 5 RB Offset
			19125	15MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
			19100	20MHz	QPSK, 16QAM	6 RB / 0 RB Offset
						1 RB / 5 RB Offset
						6 RB / 0 RB Offset
A	CONDCUDET D EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset
B	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	DC 3.7V By Battery	Jace Hu
FREQUENCY STABILITY	23deg. C, 61%RH	DC 5/13.5/27V By DC Source	James Fu
OCCUPIED BANDWIDTH	23deg. C, 61%RH	DC 3.7V By Battery	James Fu
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	DC 3.7V By Battery	James Fu
BAND EDGE	23deg. C, 61%RH	DC 3.7V By Battery	James Fu
CONDCUDED EMISSION	23deg. C, 61%RH	DC 3.7V By Battery	James Fu
RADIATED EMISSION	23deg. C, 70%RH	DC 5/13.5/27V By DC Source	Jace Hu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GPRS1900		
Channel	512	661	810
Frequency	1850.2	1880	1909.8
GPRS (GMSK, 1Tx-slot)	29.84	29.95	29.53
GPRS (GMSK, 2Tx-slot)	29.73	29.82	29.48
GPRS (GMSK, 3Tx-slot)	29.64	29.71	29.34
GPRS (GMSK, 4Tx-slot)	29.54	29.62	29.20
EDGE (8PSK, 1Tx-slot)	24.93	25.10	25.31
EDGE (8PSK, 2Tx-slot)	24.88	24.98	25.16
EDGE (8PSK, 3Tx-slot)	24.74	24.91	25.01
EDGE (8PSK, 4Tx-slot)	24.54	24.71	24.83



LTE BAND 2

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18607	18900	19193
		Frequency(MHz)		1850.7	1880	1909.3
2/ 1.4	QPSK	1	0	21.92	22.01	22.10
		1	5	21.93	21.96	22.16
		3	0	21.92	21.98	22.14
		3	3	21.98	22.06	22.10
		6	0	21.97	22.03	22.11
	16QAM	1	0	21.86	21.94	22.03
		1	5	21.91	21.96	22.08
		3	0	21.91	21.99	22.05
		3	3	21.85	22.01	22.07
		5	0	21.90	22.04	22.02

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18615	18900	19185
		Frequency(MHz)		1851.5	1880	1908.5
2/ 3	QPSK	1	0	21.91	22.00	22.13
		1	5	21.94	21.94	22.16
		3	0	21.94	22.01	22.11
		3	3	21.91	22.07	22.13
		6	0	21.92	22.07	22.08
	16QAM	1	0	21.84	21.96	22.06
		1	5	21.85	22.02	22.05
		3	0	21.87	21.98	22.02
		3	3	21.87	22.00	22.06
		5	0	21.90	21.99	22.02

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18625	18900	19175
		Frequency(MHz)		1852.5	1880	1907.5
2/ 5	QPSK	1	0	21.91	22.06	22.09
		1	5	21.89	21.97	22.16
		3	0	21.91	22.01	22.14
		3	3	21.91	22.06	22.12
		6	0	21.94	22.04	22.05
	16QAM	1	0	21.83	22.00	22.06
		1	5	21.88	21.99	22.06
		3	0	21.87	22.00	22.05
		3	3	21.90	21.96	22.10
		5	0	21.90	21.98	22.05

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18650	18900	19150
		Frequency(MHz)		1855	1880	1905
2/ 10	QPSK	1	0	21.96	22.04	22.07
		1	5	21.92	21.99	22.12
		3	0	21.92	22.01	22.15
		3	3	21.98	22.06	22.13
		6	0	21.97	22.05	22.10
	16QAM	1	0	21.88	22.00	22.02
		1	5	21.89	21.99	22.08
		3	0	21.93	21.96	22.09
		3	3	21.85	21.98	22.07
		5	0	21.95	22.01	21.99

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18675	18900	19125
		Frequency(MHz)		1857.5	1880	1902.5
2/ 15	QPSK	1	0	21.89	22.04	22.10
		1	5	21.94	21.94	22.17
		3	0	21.95	22.00	22.14
		3	3	21.97	22.01	22.13
		6	0	21.97	22.07	22.05
	16QAM	1	0	21.84	21.93	22.02
		1	5	21.90	21.98	22.08
		3	0	21.89	21.96	22.08
		3	3	21.91	21.94	22.11
		5	0	21.94	21.98	22.06

		RB Size	RB Offset	Low	Mid	High
Band/BW	Modulation	Channel		18700	18900	19100
		Frequency(MHz)		1860	1880	1900
2/ 20	QPSK	1	0	21.97	22.08	22.15
		1	5	21.96	22.02	22.18
		3	0	21.98	22.06	22.16
		3	3	21.99	22.08	22.18
		6	0	21.98	22.09	22.13
	16QAM	1	0	21.91	22.01	22.08
		1	5	21.93	22.04	22.10
		3	0	21.95	22.04	22.10
		3	3	21.93	22.02	22.12
		5	0	21.96	22.06	22.07



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

EIRP POWER (dBm)

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	29.84	-3.79	26.05	402.72	2
661	1880.0	29.95	-3.79	26.16	413.05	2
810	1909.8	29.53	-3.79	25.74	374.97	2

EDGE

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	24.93	-3.79	21.14	130.02	2
661	1880.0	25.1	-3.79	21.31	135.21	2
810	1909.8	25.31	-3.79	21.52	141.91	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	21.98	-3.24	18.74	74.82	2
18900	1880.0	22.06	-3.24	18.82	76.21	2
19193	1909.3	22.16	-3.24	18.92	77.98	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	21.91	-3.24	18.67	73.62	2
18900	1880.0	22.04	-3.24	18.8	75.86	2
19193	1909.3	22.08	-3.24	18.84	76.56	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	21.94	-3.24	18.7	74.13	2
18900	1880.0	22.07	-3.24	18.83	76.38	2
19185	1908.5	22.16	-3.24	18.92	77.98	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	21.9	-3.24	18.66	73.45	2
18900	1880.0	22.02	-3.24	18.78	75.51	2
19185	1908.5	22.06	-3.24	18.82	76.21	2



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	21.94	-3.24	18.7	74.13	2
18900	1880.0	22.06	-3.24	18.82	76.21	2
19175	1907.5	22.16	-3.24	18.92	77.98	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	21.9	-3.24	18.66	73.45	2
18900	1880.0	22	-3.24	18.76	75.16	2
19175	1907.5	22.1	-3.24	18.86	76.91	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	21.98	-3.24	18.74	74.82	2
18900	1880.0	22.06	-3.24	18.82	76.21	2
19150	1905.0	22.15	-3.24	18.91	77.8	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	21.95	-3.24	18.71	74.3	2
18900	1880.0	22.01	-3.24	18.77	75.34	2
19150	1905.0	22.09	-3.24	18.85	76.74	2



BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	21.97	-3.24	18.73	74.64	2
18900	1880.0	22.07	-3.24	18.83	76.38	2
19125	1902.5	22.17	-3.24	18.93	78.16	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	21.94	-3.24	18.7	74.13	2
18900	1880.0	21.98	-3.24	18.74	74.82	2
19125	1902.5	22.11	-3.24	18.87	77.09	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	21.99	-3.24	18.75	74.99	2
18900	1880	22.09	-3.24	18.85	76.74	2
19100	1900	22.18	-3.24	18.94	78.34	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	21.96	-3.24	18.72	74.47	2
18900	1880	22.06	-3.24	18.82	76.21	2
19100	1900	22.12	-3.24	18.88	77.27	2



3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





3.2.4 TEST RESULTS

GSM1900

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
V_{nor}	0.0009	0.0012	2.5
V_{min}	-0.0012	-0.0012	2.5
V_{max}	0.0009	0.0011	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0055	-0.0052	2.5
-20	-0.0050	-0.0048	2.5
-10	-0.0046	-0.0044	2.5
0	-0.0037	-0.0035	2.5
10	-0.0030	-0.0028	2.5
20	-0.0023	-0.0021	2.5
30	-0.0017	-0.0015	2.5
40	-0.0014	-0.0012	2.5
50	-0.0005	-0.0003	2.5

EDGE 1900

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
V_{nor}	0.0013	0.0011	2.5
V_{min}	-0.0013	-0.0012	2.5
V_{max}	0.0009	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0057	-0.0054	2.5
-20	-0.0052	-0.0049	2.5
-10	-0.0046	-0.0043	2.5
0	-0.0039	-0.0036	2.5
10	-0.0030	-0.0028	2.5
20	-0.0024	-0.0022	2.5
30	-0.0016	-0.0015	2.5
40	-0.0012	-0.0011	2.5
50	-0.0005	-0.0005	2.5



LTE BAND 2

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0021	0.0023	2.5
V _{min}	-0.0031	-0.0030	2.5
V _{max}	0.0022	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0053	-0.0049	2.5
-20	-0.0050	-0.0043	2.5
-10	-0.0037	-0.0036	2.5
0	-0.0034	-0.0034	2.5
10	-0.0023	-0.0020	2.5
20	-0.0019	-0.0018	2.5
30	-0.0020	-0.0013	2.5
40	-0.0009	-0.0008	2.5
50	-0.0002	-0.0001	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0021	0.0020	2.5
V _{min}	-0.0022	-0.0025	2.5
V _{max}	0.0018	0.0018	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0046	-0.0053	2.5
-20	-0.0041	-0.0048	2.5
-10	-0.0032	-0.0035	2.5
0	-0.0028	-0.0032	2.5
10	-0.0018	-0.0021	2.5
20	-0.0011	-0.0019	2.5
30	-0.0006	-0.0018	2.5
40	-0.0002	-0.0007	2.5
50	0.0006	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0021	0.0026	2.5
V _{min}	-0.0023	-0.0030	2.5
V _{max}	0.0021	0.0020	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0044	-0.0054	2.5
-20	-0.0042	-0.0044	2.5
-10	-0.0031	-0.0036	2.5
0	-0.0026	-0.0033	2.5
10	-0.0016	-0.0023	2.5
20	-0.0011	-0.0017	2.5
30	-0.0011	-0.0014	2.5
40	-0.0003	-0.0009	2.5
50	0.0005	-0.0001	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0024	0.0024	2.5
V _{min}	-0.0031	-0.0030	2.5
V _{max}	0.0027	0.0024	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0044	-0.0052	2.5
-20	-0.0040	-0.0048	2.5
-10	-0.0031	-0.0038	2.5
0	-0.0027	-0.0033	2.5
10	-0.0016	-0.0019	2.5
20	-0.0011	-0.0018	2.5
30	-0.0010	-0.0018	2.5
40	-0.0003	-0.0005	2.5
50	0.0005	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0024	0.0025	2.5
V _{min}	-0.0031	-0.0030	2.5
V _{max}	0.0026	0.0024	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0057	-0.0052	2.5
-20	-0.0051	-0.0048	2.5
-10	-0.0039	-0.0038	2.5
0	-0.0035	-0.0034	2.5
10	-0.0024	-0.0020	2.5
20	-0.0019	-0.0018	2.5
30	-0.0013	-0.0011	2.5
40	-0.0007	-0.0006	2.5
50	-0.0004	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V _{nor}	0.0026	0.0025	2.5
V _{min}	-0.0031	-0.0030	2.5
V _{max}	0.0026	0.0025	2.5

NOTE: The applicant defined the normal working voltage of the EUT is from V_{min} to V_{max} .

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0055	-0.0052	2.5
-20	-0.0050	-0.0045	2.5
-10	-0.0037	-0.0037	2.5
0	-0.0034	-0.0033	2.5
10	-0.0021	-0.0020	2.5
20	-0.0018	-0.0016	2.5
30	-0.0011	-0.0011	2.5
40	-0.0007	-0.0009	2.5
50	-0.0001	-0.0002	2.5




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

3.3.2 TEST SETUP




3.3.3 TEST PROCEDURES


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS


Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		GSM	EDGE			GSM	EDGE
512	1850.2	0.24522	0.24493	512	1850.2	0.3095	0.3121
661	1880.0	0.24058	0.24312	661	1880.0	0.3110	0.3156
810	1909.8	0.24392	0.24587	810	1909.8	0.3096	0.3122




LTE band 2			
Channel Bandwidth : 1.4MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18607	1850.7	1.10	1.10
18900	1880	1.09	1.10
19193	1909.3	1.11	1.10
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18607	1850.7	1.23	1.22
18900	1880	1.22	1.24
19193	1909.3	1.26	1.23




LTE band 2			
Channel Bandwidth : 3MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18615	1851.5	1.27	1.27
18900	1880	1.27	1.27
19185	1908.5	1.27	1.27
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18615	1851.5	1.42	1.43
18900	1880	1.41	1.42
19185	1908.5	1.43	1.39




LTE band 2			
Channel Bandwidth : 5MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18625	1852.5	1.09	1.09
18900	1880	1.08	1.09
19175	1907.5	1.10	1.10
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18625	1852.5	1.42	1.42
18900	1880	1.35	1.35
19175	1907.5	1.45	1.43




LTE band 2			
Channel Bandwidth : 10MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18650	1855	1.09	1.10
18900	1880	1.09	1.10
19150	1905	1.09	1.10
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18650	1855	1.44	1.51
18900	1880	1.50	1.50
19150	1905	1.51	1.53



LTE band 2			
Channel Bandwidth : 15MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18675	1857.5	1.09	1.09
18900	1880	1.09	1.09
19125	1902.5	1.09	1.09
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18675	1857.5	1.50	1.53
18900	1880	1.47	1.50
19125	1902.5	1.53	1.53



LTE band 2			
Channel Bandwidth : 20MHz			
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)	
		QPSK	16QAM
18700	1860	1.09	1.09
18900	1880	1.10	1.10
19100	1900	1.10	1.10
CHANNEL	Frequency (MHz)	26 dB bandwidth (MHz)	
		QPSK	16QAM
18700	1860	1.59	1.61
18900	1880	1.56	1.53
19100	1900	1.51	1.49






3.4 BAND EDGE MEASUREMENTC

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP





Test Report No.: W7L-P22100017RF02

3.4.3 TEST PROCEDURES


- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is $\geq 1\% \cdot \text{EBW kHz}$ and VBW of the spectrum is $3 \cdot \text{RBW kHz}$. (LTE bandwidth 1.4M/3M/5M/10M/15M/20MHz).
- c. Record the max trace plot into the test report.



BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

3.4.4. TEST RESULTS






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

LTE BAND 2


Channel Bandwidth: 1.4MHz QPSK





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02


LTE BAND 2





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

LTE BAND 2


Channel Bandwidth: 5MHz QPSK





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02


LTE BAND 2





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02


LTE BAND 2






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02




LTE BAND 2





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02





3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.5.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30MHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP





3.5.4 TEST RESULTS

NOTE : 1.The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.


2. All modulation modes (QPSK & 16QAM) of LTE were tested. The worst case was found in QPSK modulation. So only show the worst mode data.





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

EDGE


CHANNEL 512

FREQUENCY RANGE : 30MHz~1000MHz




CHANNEL 661

FREQUENCY RANGE : 30MHz~1000MHz



CHANNEL 810


FREQUENCY RANGE : 30MHz~1000MHz





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

LTE BAND 2





BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

3MHz / QPSK


CHANNEL 18615

FREQUENCY RANGE : 30MHz~19.1GHz





CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19185

FREQUENCY RANGE : 30MHz~19.1GHz






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

5MHz / QPSK

CHANNEL 18625

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19175

FREQUENCY RANGE : 30MHz~19.1GHz






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

10MHz / QPSK

CHANNEL 18650

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19150

FREQUENCY RANGE : 30MHz~19.1GHz






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

15MHz / QPSK


CHANNEL 18675

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19125

FREQUENCY RANGE : 30MHz~19.1GHz






20MHz / QPSK


CHANNEL 18700

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19100

FREQUENCY RANGE : 30MHz~19.1GHz



3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.6.3 DEVIATION FROM TEST STANDARD


No deviation

3.6.4 TEST SETUP

< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

3.6.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

GPRS 1900:

CHANNEL BANDWIDTH: 512 ~ 810


MODE	TX channel 810	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	62.010	-52.47	-33.22	-13.00	-39.47	-19.25	Peak	Horizontal
2	159.980	-64.73	-48.88	-13.00	-51.73	-15.85	Peak	Horizontal
3	251.160	-57.33	-45.85	-13.00	-44.33	-11.48	Peak	Horizontal
4	305.480	-53.13	-40.80	-13.00	-40.13	-12.33	Peak	Horizontal
5 PP	355.920	-51.26	-40.16	-13.00	-38.26	-11.10	Peak	Horizontal
6	414.120	-53.93	-44.16	-13.00	-40.93	-9.77	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	62.980	-52.57	-29.62	-13.00	-39.57	-22.95	Peak	Vertical
2	98.870	-58.09	-50.67	-13.00	-45.09	-7.42	Peak	Vertical
3	159.010	-70.09	-53.15	-13.00	-57.09	-16.94	Peak	Vertical
4	305.480	-62.73	-52.01	-13.00	-49.73	-10.72	Peak	Vertical
5 PP	417.030	-51.43	-42.59	-13.00	-38.43	-8.84	Peak	Vertical
6	487.840	-60.34	-52.15	-13.00	-47.34	-8.19	Peak	Vertical





**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

ABOVE 1GHz DATA

Note: For higher frequency, the emission is too low to be detected.


WORST-CASE DATA

GPRS 1900:

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3700.400	-52.52	-60.36	-13.00	-39.52	7.84	Peak	Horizontal
2		5550.600	-52.75	-63.32	-13.00	-39.75	10.57	Peak	Horizontal



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3700.400	-53.74	-61.35	-13.00	-40.74	7.61	Peak	Vertical
2 PP	5560.000	-51.40	-62.30	-13.00	-38.40	10.90	Peak	Vertical



CH 661


MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-51.75	-59.74	-13.00	-38.75	7.99	Peak	Horizontal
2 PP	5636.000	-51.70	-62.43	-13.00	-38.70	10.73	Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-53.44	-61.13	-13.00	-40.44	7.69	Peak	Vertical
2 PP	5640.000	-51.06	-62.19	-13.00	-38.06	11.13	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

CH 810


MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3819.600	-49.72	-57.86	-13.00	-36.72	8.14	Peak	Horizontal
2		5731.000	-50.07	-60.98	-13.00	-37.07	10.91	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-51.81	-59.58	-13.00	-38.81	7.77	Peak	Vertical
2 PP	5729.400	-49.73	-61.11	-13.00	-36.73	11.38	Peak	Vertical




EDGE 1900:

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3700.400	-52.87	-60.71	-13.00	-39.87	7.84	Peak	Horizontal
2 PP	5560.000	-51.91	-62.50	-13.00	-38.91	10.59	Peak	Horizontal




MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3698.000	-51.52	-59.13	-13.00	-38.52	7.61	Peak	Vertical
2		5550.600	-51.54	-62.41	-13.00	-38.54	10.87	Peak	Vertical




CH 661

MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			




MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-52.22	-59.91	-13.00	-39.22	7.69	Peak	Vertical
2 PP	5640.000	-49.47	-60.60	-13.00	-36.47	11.13	Peak	Vertical




CH 810

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3819.600	-51.52	-59.30	-13.00	-38.52	7.78	Peak	Vertical
2 PP	5731.000	-50.01	-61.40	-13.00	-37.01	11.39	Peak	Vertical




LTE Band 2

CHANNEL BANDWIDTH: 1.4MHz / QPSK

CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-52.83	-60.81	-13.00	-39.83	7.98	Peak	Horizontal
2 PP	5640.000	-51.91	-62.65	-13.00	-38.91	10.74	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-51.79	-59.49	-13.00	-38.79	7.70	Peak	Vertical
2 PP	5636.000	-51.02	-62.14	-13.00	-38.02	11.12	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P22100017RF02

CHANNEL BANDWIDTH: 3MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-52.67	-60.66	-13.00	-39.67	7.99	Peak	Horizontal
2 PP	5636.000	-52.04	-62.77	-13.00	-39.04	10.73	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3755.000	-50.85	-58.54	-13.00	-37.85	7.69	Peak	Vertical
2	5640.000	-51.42	-62.55	-13.00	-38.42	11.13	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

CHANNEL BANDWIDTH: 5MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3755.000	-51.44	-59.42	-13.00	-38.44	7.98	Peak	Horizontal
2		5640.000	-51.63	-62.37	-13.00	-38.63	10.74	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-51.57	-59.27	-13.00	-38.57	7.70	Peak	Vertical
2 PP	5636.000	-50.84	-61.96	-13.00	-37.84	11.12	Peak	Vertical





BUREAU
VERITAS


Test Report No.: W7L-P22100017RF02

CHANNEL BANDWIDTH: 10MHz / QPSK

CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3760.000	-51.02	-59.01	-13.00	-38.02	7.99	Peak	Horizontal
2	5636.000	-51.29	-62.02	-13.00	-38.29	10.73	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-52.58	-60.27	-13.00	-39.58	7.69	Peak	Vertical
2 PP	5640.000	-51.10	-62.23	-13.00	-38.10	11.13	Peak	Vertical



CHANNEL BANDWIDTH: 15MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-52.37	-60.36	-13.00	-39.37	7.99	Peak	Horizontal
2 PP	5636.000	-52.11	-62.84	-13.00	-39.11	10.73	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.25	-58.94	-13.00	-38.25	7.69	Peak	Vertical
2 PP	5640.000	-50.82	-61.95	-13.00	-37.82	11.13	Peak	Vertical



CHANNEL BANDWIDTH: 20MHz / QPSK
CH18700


MODE	TX channel 18700	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-52.06	-60.05	-13.00	-39.06	7.99	Peak	Horizontal
2 PP	5579.000	-51.83	-62.46	-13.00	-38.83	10.63	Peak	Horizontal



MODE	TX channel 18700	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3717.000	-52.11	-59.74	-13.00	-39.11	7.63	Peak	Vertical
2 PP	5580.000	-51.04	-61.99	-13.00	-38.04	10.95	Peak	Vertical



CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.90	-59.88	-13.00	-38.90	7.98	Peak	Horizontal
2 PP	5640.000	-51.58	-62.32	-13.00	-38.58	10.74	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.98	-58.68	-13.00	-37.98	7.70	Peak	Vertical
2 PP	5636.000	-50.41	-61.53	-13.00	-37.41	11.12	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P22100017RF02

CH19100


MODE	TX channel 19100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3793.000	-50.72	-58.79	-13.00	-37.72	8.07	Peak	Horizontal
2	5700.000	-51.28	-62.14	-13.00	-38.28	10.86	Peak	Horizontal



MODE	TX channel 19100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 13.5V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3800.000	-51.58	-59.33	-13.00	-38.58	7.75	Peak	Vertical
2 PP	5693.000	-49.79	-61.07	-13.00	-36.79	11.28	Peak	Vertical




3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP




3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.


3.7.4 TEST RESULTS

GSM


CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
512	1850.2	2.68



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	2.78




CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
810	1909.8	2.67




EDGE


CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
512	1850.2	2.67



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
661	1880	2.67



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
810	1909.8	2.66






BUREAU
VERITAS


Test Report No.: W7L-P22100017RF02

LTE BAND 2


CHANNEL BANDWIDTH: 1.4MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18607	1850.7	5.30	5.19
18900	1880	5.04	5.03
19193	1909.3	5.02	4.96




CHANNEL BANDWIDTH: 3MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18615	1851.5	4.76	4.99
18900	1880	4.34	4.28
19185	1908.5	4.19	4.31




CHANNEL BANDWIDTH: 5MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18625	1852.5	4.89	4.98
18900	1880	4.65	4.77
19175	1907.5	4.19	4.29




CHANNEL BANDWIDTH: 10MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18650	1855	5.34	5.29
18900	1880	5.11	5.15
19150	1905	5.13	5.05



CHANNEL BANDWIDTH: 15MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18675	1857.5	5.13	5.17
18900	1880	5.13	5.08
19125	1902.5	5.10	5.33



CHANNEL BANDWIDTH: 20MHz			
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM
18700	1860	5.09	5.23
18900	1880	4.93	5.09
19100	1900	4.52	4.52





Test Report No.: W7L-P22100017RF02

4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: W7L-P22100017RF02

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.