

Label Location Information

Refer to the below red arrow:

(For M/N: BEJ/120/432) Label

BEB/120/432
ELECTRONIC BALLAST
USE WITH LAMPS
4x F32T8 4x F25T8 4x F17T8



MADE IN CHINA

120V60Hz

LISTED BALLAST
4GM8
E344994

DUNMONG

FCC ID: A6H1204332

BRIGHT BEGINNING

ELECTRICAL PRODUCTS CO., LTD.

NORMAL POWER FACTOR
SOUND RATING CLASS A
CLASS P TYPE HL
NO PCB'S
INSTANT START
OUTDOOR TYPE 1
FCC TITLE 47 PART 18
CONSUMER EQUIPMENT
MIN. STARTING TEMP. -18°C
OPEN CIRCUIT VOLTAGE 600V
VOLTAGE TO GROUND < 600V

LAMPS	CURRENT	POWER
4x F32T8	1.63A	105W
4x F25T8	1.34A	83W
4x F17T8	0.99A	58W
3x F32T8	1.38A	82W
3x F25T8	1.15A	63W
3x F17T8	0.86A	43W

CAUTION

DISCONNECT LINE VOLTAGE
BEFORE INSTALLING OR REPLACING
BALLAST CASE MUST BE GROUNDED TO
AVOID POSSIBLE SHOCK HAZARD

FOR THREE LAMP, CAP ONE OF THE
BLUE LEAD AND INSULATE FOR 600V

(For M/N: BEJ/120/332) Label

BEB/120/332
ELECTRONIC BALLAST
USE WITH LAMPS
3x F32T8 3x F25T8 3x F17T8



MADE IN CHINA

120V60Hz

LISTED BALLAST
4GM8
E344994

DUNMONG

FCC ID: A6H1204332

BRIGHT BEGINNING

ELECTRICAL PRODUCTS CO., LTD.

NORMAL POWER FACTOR
SOUND RATING CLASS A
CLASS P TYPE HL
NO PCB'S
INSTANT START
OUTDOOR TYPE 1
FCC TITLE 47 PART 18
CONSUMER EQUIPMENT
MIN. STARTING TEMP. -18°C
OPEN CIRCUIT VOLTAGE 600V
VOLTAGE TO GROUND < 600V

LAMPS	CURRENT	POWER
3x F32T8	1.25A	82W
3x F25T8	1.02A	65W
3x F17T8	0.79A	45W
2x F32T8	1.01A	55W
2x F25T8	0.83A	44W
2x F17T8	0.64A	34W

CAUTION

DISCONNECT LINE VOLTAGE
BEFORE INSTALLING OR REPLACING
BALLAST CASE MUST BE GROUNDED TO
AVOID POSSIBLE SHOCK HAZARD

FOR TWO LAMP, CAP ONE OF THE
BLUE LEAD AND INSULATE FOR 600V

Location

