

Label Location Information

Refer to the below red arrow:

(For M/N: BEB/120/40+32/1) Label

BEB/120/40+32/1 ELECTRONIC BALLAST USE WITH LAMPS FC16T9(40W)+FC12T9(32W) or 2×FC12T9(32W) MADE IN CHINA  BALLAST	120V60Hz LAMPS FC16T9(40W)+FC12T9(32W) CURRENT:0.82A POWAER:58W LAMPS FC12T9(32W)+FC12T9(32W) CURRENT:0.72A POWAER:50W FCC ID:A6H120FC403222  LISTED BALLAST 4GMS E344994  BRIGHT BEGINNING ELECTRICAL PRODUCTS CO., LTD.	NORMAL POWER FACTOR SOUND RATING CLASS A CLASS P TYPE HL NO PCB'S INSTANT START OUTDOOR TYPE 1 FCC TITLE 47 PART 18 CONSUMER EQUIPMENT MIN.STARTING TEMP. -18°C OPEN CIRCUIT VOLTAGE 600V VOLTAGE TO GROUND < 600V CAUTION DISCONNECT LINE VOLTAGE BEFORE INSTALLING OR REPLACING. BALLAST CASE MUST BE GROUNDED TO AVOID POSSIBLE SHOCK HAZARD
---	---	---

(For M/N: BEB/120/32+22/1) Label

BEB/120/32+22/1 ELECTRONIC BALLAST USE WITH LAMPS FC12T9(32W)+FC8T9(22W) or 2×FC8T9(22W) MADE IN CHINA  BALLAST	120V60Hz LAMPS FC12T9(32W)+FC8T9(22W) CURRENT:0.68A POWAER:45W LAMPS FC8T9(22W)+FC8T9(22W) CURRENT:0.60A POWAER:38W FCC ID:A6H120FC403222  LISTED BALLAST 4GMS E344994  BRIGHT BEGINNING ELECTRICAL PRODUCTS CO., LTD.	NORMAL POWER FACTOR SOUND RATING CLASS A CLASS P TYPE HL NO PCB'S INSTANT START OUTDOOR TYPE 1 FCC TITLE 47 PART 18 CONSUMER EQUIPMENT MIN.STARTING TEMP. -18°C OPEN CIRCUIT VOLTAGE 600V VOLTAGE TO GROUND < 600V CAUTION DISCONNECT LINE VOLTAGE BEFORE INSTALLING OR REPLACING. BALLAST CASE MUST BE GROUNDED TO AVOID POSSIBLE SHOCK HAZARD
--	--	---

(For M/N: BEB/120/22) Label

BEB/120/22 ELECTRONIC BALLAST USE WITH LAMP FC8T9(22W) MADE IN CHINA  BALLAST	120V60Hz LAMPS FC8T9(22W) CURRENT:0.36A POWAER:20W FCC ID:A6H120FC403222  LISTED BALLAST 4GMS E344994  BRIGHT BEGINNING ELECTRICAL PRODUCTS CO., LTD.	NORMAL POWER FACTOR SOUND RATING CLASS A CLASS P TYPE HL NO PCB'S INSTANT START OUTDOOR TYPE 1 FCC TITLE 47 PART 18 CONSUMER EQUIPMENT MIN.STARTING TEMP. -18°C OPEN CIRCUIT VOLTAGE 600V VOLTAGE TO GROUND < 600V CAUTION DISCONNECT LINE VOLTAGE BEFORE INSTALLING OR REPLACING. BALLAST CASE MUST BE GROUNDED TO AVOID POSSIBLE SHOCK HAZARD
--	---	---

Location

