



Nemko Test Report: Q1023275RUS1

Applicant: SyChip, Inc.
2805 North Dallas Parkway
Plano, TX 75093
USA

Equipment Under Test: SN3020
(E.U.T.)

In Accordance With: FCC Part 15, Subpart C, 15.247 and
Industry Canada, RSS-210, Issue 8
Digital Transmission Systems

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

TESTED BY: 

David Light, Senior Wireless Engineer

DATE: 07 January 2011

APPROVED BY: 

Tom Tidwell, Telecom Direct

DATE: 11 January 2011

Number of Pages: 36

Table of Contents

SECTION 1. SUMMARY OF TEST RESULTS	3
SECTION 2. EQUIPMENT UNDER TEST (E.U.T.)	5
SECTION 3. OCCUPIED BANDWIDTH	6
SECTION 4. MAXIMUM PEAK OUTPUT POWER	9
SECTION 5. OUT OF BAND EMISSIONS	13
SECTION 6. RADIATED EMISSIONS	16
SECTION 7. PEAK POWER SPECTRAL DENSITY	18
SECTION 8. POWERLINE CONDUCTED EMISSIONS	21
SECTION 9. RECEIVER EMISSIONS	23
SECTION 10. TEST EQUIPMENT LIST	25
ANNEX A - TEST DETAILS	26
ANNEX B - TEST DIAGRAMS	34

Section 1. Summary of Test Results

Manufacturer: SyChip, Inc/

Model No.: SN3020

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with CFR 47, Part 15, Subpart C, Paragraph 15.247 and Industry Canada RSS-210, Issue 8 for Digital Transmission Systems. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.**THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.**

See "Summary of Test Data".



NVLAP Lab Code 100426-0

Nemko USA, Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety, for use by the company's employees only.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. Nemko USA, Inc. is a NVLAP accredited laboratory.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA, Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Summary Of Test Data

NAME OF TEST	PARA. NO.	RESULT
Powerline Conducted Emissions	15.207(a)/RSS-Gen 7.2.4	Complies
Minimum 6 dB Bandwidth	15.247(a)(2) RSS-210 A8.2(a)	Complies
Maximum Peak Power Output	15.247(b)(3)/RSS-210/RSS-210 A8.4(4)	Complies
Spurious Emissions (Antenna Conducted)	15.247(d)?RSS-210 A8.5	Complies
Spurious Emissions (Restricted Bands)	15.247(d)/15.209(a)/RSS-Gen 7.2.2	Complies
Peak Power Spectral Density	15.247(e)/RSS-210 A8.2(a)	Complies
Receiver Spurious Emissions	RSS-Gen 6.2	Complies

Footnotes:

Section 2. Equipment Under Test (E.U.T.)**General Equipment Information**

Frequency Band (MHz): 902-928 2400-2483.5 5725-5850

Operating Frequency of Test Sample: 2405 to 2480 MHz*

Channel Spacing: 5 MHz

User Frequency Adjustment: Software controlled

*Note – To achieve compliance in the restricted band at the upper band edge, power was lowered. Software/firmware will be installed during manufacturing to maintain these levels for end use.

Power level setting = 20 for channels 11 through 24, setting 14 for channel 25 and 4 for channel 26 using manufacturers test tool. Testing was performed at channels 11, 18 and 24 (full power). Upper band edge measurements were also made at channels 25 and 26 (reduced power) to show compliance with restricted band limits.

Nemko USA, Inc.

FCC PART 15, SUBPART C and RSS 210, Issue 8

EQUIPMENT: SN3020

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Section 3. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth	PARA. NO.: FCC 15.247(a)(2) RSS-210 A8.2(a)
TESTED BY: David Light	DATE: 06 January 2011

Test Results: Complies.

Measurement Data: See 6 dB BW plot
Measured 6 dB bandwidth: 1.65 MHz Max


Test Conditions: 45 %RH
22 °C

Measurement Uncertainty: $\pm 1 \times 10^{-7}$ ppm


Test Equipment Used: 1464-1082-1472

Test Data – Occupied Bandwidth

Low Channel




Mid Channel



Test Data – Occupied Bandwidth

High Channel



Section 4. Maximum Peak Output Power

NAME OF TEST: Maximum Peak Output power	PARA. NO.: FCC 15.247(b)(3) RSS-210 A8.4(4)
TESTED BY: David Light	DATE: 06 January 2011


Test Results: Complies.**Measurement Data:** Refer to attached data**Test Conditions:** 45 %RH
22 °C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1464-1082-1472

Manufacturers stated antenna gain = -1.0 dBi


- This device was tested at +/- 15% input power per 15.31(e), with no variation in output power.
- For battery powered equipment, the device was tested with a fresh battery per 15.31(e).
- The device was tested on three channels per 15.31(l).
- This test was performed radiated.

Test Data – Peak Power

Low Channel




Mid Channel




Test Data – Peak Power

Third highest channel (full power)




Second Highest Channel (Channel 25)



Test Data – Peak Power

Highest Channel (Channel 26)



Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Section 5 Out of Band Emissions

NAME OF TEST: Out of Band Emissions	PARA. NO.: FCC 15.247 (d) RSS-210 A8.5
TESTED BY: David Light	DATE: 06 January 2011



Test Results: Complies.

Measurement Data: See attached plots.

Test Conditions: 45 %RH
 22 °C


Measurement Uncertainty: +/-1.7 dB

Test Equipment Used: 1464-1082-1472


Test Data – Spurious Emissions at Antenna Terminals**Lower Band Edge****Low Channel**

Test Data – Spurious Emissions at Antenna Terminals

Mid Channel



High Channel



Section 6. Radiated Emissions

NAME OF TEST: Radiated Emissions	PARA. NO.: FCC 15.247 (d) RSS-Gen 7.2.2
TESTED BY: David Light	DATE: 06 January 2011

Test Results: Complies.**Measurement Data:** See attached table.**Test Conditions:** 45 %RH
22 °C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1464-1484-1485-1016-791-993-1480

Notes:

- For handheld devices, the EUT was tested on three orthogonal axis'
- The device was tested from 30 MHz to the tenth harmonic of the highest fundamental frequency per 15.33
- The device was tested on three channels per 15.31(l).
- All emissions with 20 dB of the specification limit are reported.
- There were no emission in the restricted bands of operation that were within 20 dB of the specification limit. Band edge measurements are presented.

RBW=VBW=100 kHz below 1000 MHz

RBW=VBW=1 MHz above 1000 MHz (Peak)

RBW= 1 MHz VBW=1 kHz (Average)

Radiated Emissions

Readings 1&2 = 2475 MHz at power setting 14

Readings 3&4 = 2480 MHz at power setting 4

Measurement Data:

Test Distance: 3 Meters

#	Freq MHz	Rdng dB μ V	Horn dB	Pre-A dB	Cable dB	Cable dB	Dist Table	Corr dB μ V/m	Spec dB μ V/m	Margin dB	Polar Ant
2483.5	62.2	+29.0 +0.0	-33.0	+0.8	+2.3	+0.0	61.3	74.0	-12.7	Vert	
2483.5	51.0	+29.0 -3.4	-33.0	+0.8	+2.3	+0.0	46.7	54.0	-7.3	Vert	
2483.5	59.0	+29.0 +0.0	-33.0	+0.8	+2.3	+0.0	58.1	74.0	-15.9	Horiz	
2483.5	47.8	+29.0 -3.4	-33.0	+0.8	+2.3	+0.0	43.5	74.0	-10.5	Horiz	
2483.5	66.0	+29.0 +0.0	-33.0	+0.8	+2.3	+0.0	65.1	74.0	-8.9	Vert	
2483.5	57.8	+29.0 -3.4	-33.0	+0.8	+2.3	+0.0	53.5	54.0	-0.5	Vert	
2483.5	51.0	+29.0 +0.0	-33.0	+0.80	+2.3	+0.0	46.7	74.0	-27.3	Horiz	
2483.5	40.0	+29.0 -3.4	-33.0	+0.8	+2.3	+0.0	35.7	54.0	-18.3	Horiz	

Corrected reading(dB μ V/m)=Rdng(dB μ V)+AF(dB)+PreAmp(dB)+Cable(dB)+Duty cycle(dB)

Note - Please refer to separate confidential document for reasoning on duty cycle correction.

Nemko USA, Inc.

FCC PART 15, SUBPART C and RSS 210, Issue 8

EQUIPMENT: SN3020

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Section 7. Peak Power Spectral Density

NAME OF TEST: Peak Power Spectral Density	PARA. NO.: FCC 15.247(e) RSS-210 A8.2(b)
TESTED BY: David Light	DATE: 06 January 2011

Test Results: Complies.

Measurement Data: See attached data..


Test Conditions: 45 %RH
22 °C

Measurement Uncertainty: +/-1.7 dB


Test Equipment Used: 1464-1082-1472

Peak Power Spectral Density

Low Channel




Mid Channel



Peak Power Spectral Density

High Channel



Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Section 8. Powerline Conducted Emissions

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a) RSS-Gen 7.2.4
TESTED BY: David Light	DATE: 06 January 2011

Test Results: Complies.

Measurement Data: See attached plots.

Measurement Uncertainty: +/- 1.7 dB


Test Equipment Used: 1659-1258-704-674-1484

Temperature: 22°C


Relative Humidity: 45%

Test Data – Powerline Conducted Emissions

Line 1



Line 2



Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

Section 9. Receiver Emissions

NAME OF TEST: Receiver Emissions	PARA. NO.: FCC 15.207(a) RSS-Gen 6.2
TESTED BY: David Light	DATE: 06 January 2011

Test Results: Complies.

Measurement Data: See attached plots.

Measurement Uncertainty: +/- 1.7 dB

Test Equipment Used: 1464-1082-1472

Temperature: 22°C

Relative Humidity: 45%

Nemko USA, Inc.

FCC PART 15, SUBPART C and RSS 210, Issue 8



Digital Transmission Systems

EQUIPMENT: SN3020

Test Report No.:

Q1023275RUS1

Test Data - Receiver Emissions



Section 10. Test Equipment List

Asset Tag	Description	Manufacturer	Model	Serial #	Last Cal	Next Cal
674	Limiter	Hewlett Packard	11947A	3107A02200	26-Oct-2010	26-Oct-2011
704	Filter, High Pass, 5KHz	Solar Electronics	7930-5.0	933126	29-Sep-2010	29-Sep-2011
993	Antenna, Horn	A.H. Systems	SAS-200/571	162	09-Sep-2009	09-Sep-2011
1016	Preamplifier	Hewlett Packard	8449A	2749A00159	19-Jun-2010	19-Jun-2011
1082	Cable, 2m	Astrolab	32027-2-29094-72TC		N/R	
1258	LISN .	EMCO	3825/2	1305	25-Oct-2010	25-Oct-2011
1464	Spectrum Analyzer	Hewlett Packard	8563E	3551A04428	27-Feb-2009	27-Feb-2011
1472	Attenuator	Omni Spectra	20600-20db		N/R	
1480	Antenna, Bilog	Schaffner-Chase	CBL6111C	2572	18-Jan-2010	18-Jan-2011
1484	Cable	Storm	PR90-010-072		19-Jun-2010	19-Jun-2011
1485	Cable	Storm	PR90-010-216		19-Jun-2010	19-Jun-2011
1659	Spectrum Analyzer	Rohde & Schwartz	FSP	973353	27-Sep-2010	27-Sep-2012
791	PreAmp	Nemko, USA			08-Mar-2010	08-Mar-2011

Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

ANNEX A - TEST DETAILS

NAME OF TEST: Powerline Conducted Emissions

PARA. NO.: 15.207(a)

Minimum Standard: §15.207 Conducted limits.

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 mH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of Conducted Emission (MHz)	Limit (dBmV) Quasi-peak	Limit (dBmV) Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current systems containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 mV within the frequency band 535-1705 kHz, as measured using a 50 mH/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits as provided in §15.205 and §§15.209, 15.221, 15.223, 15.225 or 15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

Nemko USA, Inc.

EQUIPMENT: SN3020

FCC PART 15, SUBPART C and RSS 210, Issue 8

Digital Transmission Systems

Test Report No.:

Q1023275RUS1

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 15.247(a)(2)

Minimum Standard: The minimum 6 dB bandwidth shall be at least 500 kHz

NAME OF TEST: Maximum Peak Output Power

PARA. NO.: 15.247(b)(3)

Minimum Standard: The maximum peak output power shall not exceed 1 watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point to point operation may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceed 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operation may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Direct Measurement Method For Detachable Antennas:

If the antenna is detachable, a peak power meter is used to measure the power output with the transmitter operating into a 50 ohm load. The dBi gain of the antenna(s) employed shall be reported.

Substitution Antenna Method for Integral Antennas:

The peak field strength of the carrier is measured in a worst-case configuration with a RBW > 5 times the occupied bandwidth of the transmitted waveform. For cases where the RBW of the test instrument is not sufficient, the power is measured using a peak power meter instead of the spectrum analyzer.

The RBW of the spectrum analyzer shall be set to a value greater than the measured 6 dB occupied bandwidth of the E.U.T.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 15.247(a)(2)

Minimum Standard: Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Method Of Measurement:

The spectrum analyzer is set as follows:

RBW = VBW = 100 kHz.

Span: Sufficient to display 6 dB bandwidth

LOG dB/div.: 10 dB

Sweep: Auto

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Spurious Emissions(conducted) PARA. NO.: 15.247(d)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits. Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM IS SEARCHED TO THE 10th HARMONIC OF THE HIGHEST FREQUENCY GENERATED IN THE EUT.

Method Of Measurement:

30 MHz - 10th harmonic plot

RBW: 100 kHz

VBW: 300 kHz

Sweep: Auto

Display line: -20 dBc

Lower Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 902 MHz, 2400 MHz, or 5725 MHz

Marker: Peak of fundamental emission

Marker Δ : Peak of highest spurious level below center frequency.

Upper Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 928 MHz, 2483.5 MHz, or 5850 MHz

Marker: Peak of fundamental emission

Marker Δ : Peak of highest spurious level above center frequency.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Radiated Spurious Emissions

PARA. NO.: 15.247(c)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits:

Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM WAS SEARCHED TO THE 10th HARMONIC

15.205 Restricted Bands

MHz	MHz	MHz	GHz
0.09-0.11	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.125-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41	1718		

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Transmitter Power Density

PARA. NO.: 15.247(d)

Minimum Standard: The transmitted power density averaged over any 1 second interval shall not be greater than +8 dBm in any 3 kHz bandwidth.

Method Of Measurement: The spectrum analyzer is set as follows:

RBW: 3 kHz
VBW: >3 kHz
Span: => measured 6 dB bandwidth
Sweep: Span(kHz)/3 (i.e. for a span of 1.5 MHz the sweep rate is 1500/3 = 500 sec.
LOG dB/div.: 2 dB

Note: For devices with spectrum line spacing =< 3 kHz, the RBW of the analyzer is reduced until the spectral lines are resolved. The measurement data is normalized to 3 kHz by summing the power of all the individual spectral lines within a 3 kHz band in linear power units.

For Devices With Integral Antenna:

For devices with non-detachable antennas, the received field strength is peaked and the spectrum analyzer is set as above. The peak emission level is then measured and converted to a field strength by adding the appropriate antenna factor and cable loss. This field strength is then converted to an equivalent isotropic radiated power using the same method as described for Peak Power output.

Number of channels tested:

Tuning Range	Number Of Channels Tested	Channel Location In Band
1 MHz or Less	1	Middle
1 to 10 MHz	2	Top And Bottom
More Than 10 MHz	3	Top, Middle, Bottom

Nemko USA, Inc.

EQUIPMENT: SN3020



FCC PART 15, SUBPART C and RSS 210, Issue 8


Digital Transmission Systems

Test Report No.:

Q1023275RUS1

ANNEX B - TEST DIAGRAMS

Test Site For Radiated Emissions**Conducted Emissions**

Peak Power At Antenna Terminals

Note: A spectrum analyzer may be substituted for Peak Power Meter given that the measurement bandwidth is sufficient to capture the 60 dB bandwidth of the transmitter.

**Minimum 6 dB Bandwidth
Peak Power Spectral Density
Spurious Emissions (conducted)**