

Antenna test report

Manufacturer:Shenzhen Divoom Technology Co.,Ltd.

Address:1st Floor,5th Building,Xinlianhe Industrial Park, Jincheng Road,Shajing Town, Bao'an,

Shenzhen,China

Model:Ditoo-5M


APPlications

※Bluetooth Home RF

※ISM band 2.4GHz applications

1. Dimensions

Picture of antenna



2. Specifications

number	Item	Specifications
1	Working Central Frequency	2441 MHz
2	Band Width	(2402-2480)MHz
3	Gain	0dBi
4	VSWR	≤2.0
5	Antenna type	PCB antenna
6	Azimuth Beam width	Omni - directional
7	Impedance	50 Ω
8	Modulation mode	GFSK

3. Instrument testing, software simulation parameters


① VSWR

Mkr1: 2397MHz 1.47 Mkr2: 2450MHz 1.51 Mkr3: 2482 MHz 1.59




② Smith Char

Mkr1: 2397MHz 73.4 Mkr2: 2450MHz 62.7 Mkr3: 2482MHz 66.8




③Return Loss

Mkr1: 2397MHz -15 Mkr2: 2450MHz -18 Mkr3: 2482 MHz -16



④Smith Char simulation


Mkr1: 2400MHz 1.234 Mkr2: 2500MHz 1.051 Mkr3: 2600MHz 1.322



⑤ Return Loss simulation


Mkr1: 2400MHz -19.59 Mkr2: 2450MHz -27.70 Mkr3: 2500MHz -31.97

Mkr4: 2550MHz -21.83



⑥ Phase simulation

Mkr1: 2400MHz -54.89 Mkr2: 2500MHz -82.03 Mkr3: 2600MHz -102.6



Radiation pattern@2.441GHZ

Phi	0	45	90	135	180	235	270	315
Gain(dBi)	0	-0.1	-0.3	-0.6	-0.1	-0.2	-0.5	-0.4

