



# PCTEST Engineering Laboratory, Inc.

**6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.**  
**TEL (410) 290-6652 · FAX (410) 290-6654**  
**<http://www.pctestlab.com>**



## **CERTIFICATE OF COMPLIANCE** **FCC Part 24 Certification**

**NEC AMERICA INC.**  
6535 N. State Hwy. 161  
Irving, TX 75039-2402

**Dates of Tests: April 17-18, 2006**  
**Test Report S/N: 0604100250-R1**  
**Test Site: PCTEST Lab, Columbia MD**

**FCC ID**

**A 98-KMP6J1CH**

**APPLICANT**

**NEC AMERICA INC.**

**Classification:**

Licensed Portable Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§24(E), §2

**EUT Type:**

Single-Band PCS GSM/ EDGE Phone with Bluetooth

**Model(s):**

KMP6J1CH1-4A

**Tx Frequency Range:**

1850.20MHz - 1909.80MHz (GSM1900)

**Rx Frequency Range:**

1930.20MHz - 1989.80MHz (GSM1900)

**Max. RF Output Power:**

1.906 W EIRP GSM1900 (32.801 dBm)

0.796 W EIRP EDGE1900 (29.011 dBm)

**Max. SAR Measurement:**

1.26 W/kg GSM1900 Head SAR; 0.93 W/kg GSM1900 Body SAR

**Emission Designator(s):**

268KGXW / 268KG7W

**Test Device Serial No.**

Identical Prototype [S/N: #004401040005783]

**This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.**

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant conditions:** Power output listed is EIRP. SAR compliance for body-worn operating configuration is based on a separation distance of 1.5 cm between the back of the unit and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President



PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 1 of 18	


## TABLE OF CONTENTS

---

<b>ATTACHMENT A:</b>	<b>COVER LETTER(S)</b>	
<b>ATTACHMENT B:</b>	<b>ATTESTATION STATEMENT(S)</b>	
<b>ATTACHMENT C:</b>	<b>TEST REPORT</b>	
<b>1.1 SCOPE</b>		<b>3</b>
<b>2.1 INTRODUCTION</b>		<b>4</b>
<b>3.1 INSERTS</b>		<b>5</b>
<b>4.1 DESCRIPTION OF TESTS</b>		<b>6-8</b>
<b>5.1 EQUIVALENT ISOTROPIC RADIATED POWER</b>		<b>9</b>
<b>6.1 RADIATED MEASUREMENTS</b>		<b>10-12</b>
<b>7.1 FREQUENCY STABILITY</b>		<b>13-14</b>
<b>8.1 PLOTS OF EMISSIONS</b>		<b>15</b>
<b>9.1 LIST OF TEST EQUIPMENT</b>		<b>16</b>
<b>10.1 SAMPLE CALCULATIONS</b>		<b>17</b>
<b>11.1 CONCLUSION</b>		<b>18</b>
<b>ATTACHMENT D:</b>	<b>TEST PLOTS</b>	
<b>ATTACHMENT E:</b>	<b>FCC ID LABEL / LOCATION</b>	
<b>ATTACHMENT F:</b>	<b>TEST SETUP PHOTOGRAPHS</b>	
<b>ATTACHMENT G:</b>	<b>EXTERNAL PHOTOGRAPHS</b>	
<b>ATTACHMENT H:</b>	<b>INTERNAL PHOTOGRAPHS</b>	
<b>ATTACHMENT I:</b>	<b>BLOCK DIAGRAM(S)</b>	
<b>ATTACHMENT J:</b>	<b>SCHEMATIC DIAGRAM(S)</b>	
<b>ATTACHMENT K:</b>	<b>OPERATIONAL / CIRCUIT DESCRIPTION</b>	
<b>ATTACHMENT L:</b>	<b>PARTS LIST/TUNE UP PROCEDURE</b>	
<b>ATTACHMENT M:</b>	<b>USER'S MANUAL</b>	
<b>ATTACHMENT N:</b>	<b>SAR MEASUREMENT REPORT</b>	
<b>ATTACHMENT O:</b>	<b>SAR TEST DATA</b>	
<b>ATTACHMENT P:</b>	<b>SAR TEST SETUP PHOTOGRAPHS</b>	
<b>ATTACHMENT Q:</b>	<b>DIPOLE VALIDATION</b>	
<b>ATTACHMENT R:</b>	<b>PROBE CALIBRATION</b>	

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1		Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 2 of 18

# MEASUREMENT REPORT



## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.


## §2.1033 General Information

<b>Applicant Name:</b>	NEC AMERICA INC.
<b>Address:</b>	6535 N. State HWY 161 Irving, TX 75039-2402


- FCC ID: A98-KMP6J1CH
- Quantity: Quantity production is planned
- Emission Designators: 268KGXW/ 268KG7W
- Tx Freq. Range: 1850.20 – 1909.80 MHz (GSM1900)
- Rx Freq. Range: 1930.20 – 1989.80 MHz (GSM1900)
- Max. Power Rating: 1.906 W EIRP GSM1900 (32.801 dBm)  
0.796 W EIRP EDGE1900 (29.011 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Single-Band PCS GSM/ EDGE Phone with Bluetooth
- Modulation(s): GSM/ EDGE
- Frequency Tolerance:  $\pm 0.00025\%$  (2.5 ppm)
- FCC Rule Part(s): § 24(E)
- Dates of Tests: April 17-18, 2006
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 0604100250-R1
- Deviation from measurement procedure - None

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1		Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 3 of 18

## 2.1 INTRODUCTION



**Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.**



**Figure 2. Diagram of 3-meter outdoor test range**

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

### Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure 2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

PCTEST® PT. 24 REPORT	FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 4 of 18

### **3.1 INSERTS**

---

#### **Function of Active Devices (Confidential)**

The Function of active devices are shown in Attachment K.

#### **Block & Schematic Diagrams (Confidential)**

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

#### **Operating Instructions**

The instruction manual is shown in Attachment M.

#### **Parts List & Tune-Up Procedure (Confidential)**

The parts list & tune-up procedure is shown in Attachment L.

#### **Description of Freq. Stabilization Circuit (Confidential)**

The description of frequency stabilization circuit is shown in Attachment K.

#### **Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Supresion Circuits (Confidential)**

The description of suppression stabilization circuits is shown in Attachment K.


<b>PCTEST PT. 24 REPORT</b>		<b>FCC MEASUREMENT REPORT</b>			<b>Reviewed By:</b> Quality Manager
<b>Test Report S/N:</b> 0604100250-R1	<b>Test Dates:</b> April 17-18, 2006	<b>Phone Type:</b> Single-Band PCS GSM/ EDGE w/ Bluetooth	<b>FCC ID:</b> A98-KMP6J1CH	Page 5 of 18	

## 4.1 DESCRIPTION OF TESTS


### 4.2 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### 4.3 PCS - Base Frequency Blocks



### 4.4 PCS - Mobile Frequency Blocks



PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 6 of 18	

## **4.1 DESCRIPTION OF TESTS (CONTINUED)**

---

### **4.5 Radiation Spurious and Harmonic Emissions**

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

<b>PCTEST PT. 24 REPORT</b>		<b>FCC MEASUREMENT REPORT</b>			<b>Reviewed By:</b> Quality Manager
<b>Test Report S/N:</b> 0604100250-R1	<b>Test Dates:</b> April 17-18, 2006	<b>Phone Type:</b> Single-Band PCS GSM/ EDGE w/ Bluetooth	<b>FCC ID:</b> A98-KMP6J1CH	Page 7 of 18	

## 5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025$  ( $\pm 2.5$  ppm) of the center frequency.*

### Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

**NOTE: The EUT is tested down to the battery endpoint.**

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 8 of 18	

## 6.1 Test Data

### 6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

Radiated measurements at 3 meters

Supply Voltage: 3.7 VDC

Modulation: PCS GSM

FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Mode	Battery
1850.20	-10.280	H	95	32.801	1.906	GSM1900	Standard
1880.00	-11.060	H	95	32.191	1.656	GSM1900	Standard
1909.80	-12.430	H	95	30.991	1.256	GSM1900	Standard
1850.20	-14.240	H	95	29.011	0.796	EDGE1900	Standard

Note: Standard batteries are the only options for this phone

#### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to  
ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1		Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 9 of 18

## 7.1 Test Data

### 7.2 PCS GSM Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 32.801 dBm = 1.906 W  
 MODULATION SIGNAL: GSM  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  45.80 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-56.20	6.10	-50.10	H	82.9
5550.60	-45.35	6.70	-38.65	H	71.4
7400.80	-48.27	6.80	-41.47	H	74.3

#### NOTES:

##### Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 10 of 18	

## 7.1 Test Data (Continued)

### 7.3 PCS GSM Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 32.801 dBm = 1.906 W  
 MODULATION SIGNAL: GSM  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  45.80 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-51.75	6.10	-45.65	H	78.4
5640.00	-41.53	6.70	-34.83	H	67.6
7520.00	-48.32	6.80	-41.52	H	74.3

#### NOTES:

##### Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	NEC	Page 11 of 18

## 7.1 Test Data (Continued)

### 7.4 PCS GSM Radiated Measurements

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 32.801 dBm = 1.906 W  
 MODULATION SIGNAL: GSM  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  45.80 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-51.99	6.10	-45.89	H	78.7
5729.40	-37.37	6.70	-30.67	H	63.5
7639.20	-47.15	6.80	-40.35	H	73.1

#### NOTES:

##### Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 12 of 18	

## 7.1 Test Data

### 7.2 FREQUENCY STABILITY (PCS GSM)

OPERATING FREQUENCY: 1,880,000,005 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.7 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,880,000,005	0.00	0.000000
100 %		- 30	1,879,999,949	56.40	0.000003
100 %		- 20	1,879,999,911	94.00	0.000005
100 %		- 10	1,880,000,099	-94.00	-0.000005
100 %		0	1,879,999,685	319.60	0.000017
100 %		+ 10	1,879,999,855	150.40	0.000008
100 %		+ 20	1,880,000,005	0.00	0.000000
100 %		+ 25	1,879,999,873	131.60	0.000007
100 %		+ 30	1,879,999,892	112.80	0.000006
100 %		+ 40	1,879,999,892	112.80	0.000006
100 %		+ 50	1,879,999,873	131.60	0.000007
100 %		+ 60	1,879,999,873	131.60	0.000007
85 %	3.15	+ 20	1,880,000,005	0.00	0.000000
115 %	4.26	+ 20	1,880,000,005	0.00	0.000000
BATT. ENDPOINT	3.00	+ 20	1,880,000,005	0.00	0.000000

PCTEST® PT. 24 REPORT	FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 13 of 18

## 7.1 Test Data (Continued)

### 7.3 FREQUENCY STABILITY (PCS GSM)



PCTEST <sup>®</sup> PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1		Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 14 of 18

## 8.1 PLOT(S) OF EMISSIONS

---

(SEE ATTACHMENT D)

PCTEST <sup>®</sup> PT. 24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1	Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 15 of 18

## 9.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	8566B (100Hz-22GHz) HP	08/15/06	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/07	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/06	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/06	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/07	0792-032
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/07	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/06	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/06	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/07	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5S1G4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30μW-3W)		2237A02084
Harmonic/Flicker	Test System HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton9445/Eaton9445-1/Sing9445-1/ComlineDesign		1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB	Gain HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

\* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST® PT. 24 REPORT	FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
<b>Test Report S/N:</b> 0604100250-R1	<b>Test Dates:</b> April 17-18, 2006	<b>Phone Type:</b> Single -Band PCS GSM/ EDGE w/ Bluetooth	<b>FCC ID:</b> A98-KMP6J1CH	Page 16 of 18

## 10.1 SAMPLE CALCULATIONS

---

### **A. Emission Designator**

**Emission Designator = 250KGXW**

GSM BW = 250 KHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

Emission Designator = 250KGXW

<b>PCTEST PT. 24 REPORT</b>		<b>FCC MEASUREMENT REPORT</b>			<b>Reviewed By:</b> Quality Manager
<b>Test Report S/N:</b> 0604100250-R1	<b>Test Dates:</b> April 17-18, 2006	<b>Phone Type:</b> Single-Band PCS GSM/ EDGE w/ Bluetooth	<b>FCC ID:</b> A98-KMP6J1CH	Page 17 of 18	

## 11.1 CONCLUSION

---

The data collected shows that the **NEC AMERICA INC. Single-Band PCS GSM/ EDGE Phone FCC ID: A98-KMP6J1CH** complies with all the requirements of Parts 24 of the FCC rules.

PCTEST <sup>®</sup> PT. 24 REPORT		FCC MEASUREMENT REPORT			Reviewed By: Quality Manager
Test Report S/N: 0604100250-R1		Test Dates: April 17-18, 2006	Phone Type: Single-Band PCS GSM/ EDGE w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 18 of 18

