

## TEST REPORT

**Report No.: HK11020870-1**

**RadioShack Corporation**

Application  
For  
Certification  
(Original Grant)  
**(FCC ID: AAO1500044T)**

Transmitter

Prepared and Checked by:

Approved by:

Wong Kwok Yeung, Kenneth  
Engineer

---

Chan Chi Hung, Terry  
Assistant Supervisor  
Date: March 25, 2011

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

---

## INTERTEK TESTING SERVICES

---

### GENERAL INFORMATION

RadioShack Corporation  
**BRAND NAME: AUVIO, MODEL: 1500044**

**FCC ID: AAO1500044T**

Grantee:	RadioShack Corporation
Grantee Address:	300 RadioShack Circle, Mail Stop WF4-136, Fort Worth, Texas, 76102-2802, USA.
Contact Person:	Pat Loehr
Tel:	(817) 415-6221
Fax:	(817) 415-9247
e-mail:	N/A
Manufacturer:	N/A
Manufacturer Address:	N/A
Brand Name:	AUVIO
Model:	1500044
Type of EUT:	Transmitter
Description of EUT:	2.4GHz Digital Wireless Rear Speaker Kit - Transmitter
Serial Number:	N/A
FCC ID:	AAO1500044T
Date of Sample Submitted:	February 28, 2011
Date of Test:	March 08, 2011
Report No.:	HK11020870-1
Report Date:	March 25, 2011
Environmental Conidtions:	Temperature: +10 to 40°C Humidity: 10 to 90%

---

---

## INTERTEK TESTING SERVICES

---

---

### SUMMARY OF TEST RESULT

**RadioShack Corporation**  
**BRAND NAME: AUVIO, MODEL: 1500044**

**FCC ID: AAO1500044T**

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b)	Pass
20 dB Bandwidth	15.247(a)	Pass
Number of Hopping Frequencies	15.247(a)	Pass
Channel Separation	15.247(a)	Pass
Average Channel Occupancy Time	15.247(a)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
Radiated Spurious Emissions	15.247(d)	Pass
Transmitter Power Line Conducted Emissions	15.207	Pass
Antenna Requirement	15.203	Pass (See Note 1)
Digital Device Radiated Emission	15.109	Pass
Digital Device Conducted Emission	15.107	Pass

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0</b>	<b><u>General Description</u></b> .....	1
1.1	Product Description .....	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology .....	1
1.4	Test Facility .....	1
<b>2.0</b>	<b><u>System Test Configuration</u></b> .....	2
2.1	Justification .....	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories .....	2
2.4	Equipment Modification .....	2
2.5	Measurement Uncertainty.....	2
2.6	Support Equipment List and Description .....	2
<b>3.0</b>	<b><u>Emission Results</u></b> .....	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph.....	4
3.3	Radiated Emission Data .....	4
3.4	Conducted Emission Configuration Photograph.....	4
3.5	Conducted Emission Data .....	4
<b>4.0</b>	<b><u>Measurement Results</u></b> .....	5
4.1	Maximum Conducted Output Power at Antenna Terminals .....	5
4.2	Hopping Channel 20dB RF Bandwidth .....	5
4.3	Minimum Number of Hopping Frequencies .....	6
4.4	Minimum Hopping Channel Carrier Frequency Separation.....	6
4.5	Average Channel Occupancy Time .....	7
4.6	Out of Band Conducted Emissions .....	7
4.7	Out of Band Radiated Emissions .....	8
4.8	General radiated emission limit for spurious emissions at bandedge and within restricted band .....	8
4.9	Radiated Spurious Emissions.....	9
4.10	Transmitter Duty Cycle Calculation and Measurements .....	13
<b>5.0</b>	<b><u>Equipment Photographs</u></b> .....	14
<b>6.0</b>	<b><u>Product Labelling</u></b> .....	14
<b>7.0</b>	<b><u>Technical Specifications</u></b> .....	14
<b>8.0</b>	<b><u>Instruction Manual</u></b> .....	14
<b>9.0</b>	<b><u>Miscellaneous Information</u></b> .....	14
9.1	Measured Bandwidth.....	14
9.2	Discussion of Pulse Desensitization.....	15
9.3	Calculation of Average Factor.....	15
9.4	Emissions Test Procedures .....	16
<b>10.0</b>	<b><u>Confidentiality Request</u></b> .....	17
<b>11.0</b>	<b><u>Equipment List</u></b> .....	18

---

## INTERTEK TESTING SERVICES

---

### 1.0 General Description

#### 1.1 Product Description

The Equipment Under Test (EUT) is a 2.4GHz Frequency Hopping Spread Spectrum wireless speaker kit system (Transmitter unit). It operates at frequency range of 2406MHz to 2476MHz with 15 physical hopping frequencies. The transmitter is energized by an AC/DC adaptor (Model: U090020D12, Input 120VAC 60Hz 6.5W, Output 9VDC 200mA). The transmitter unit have channel slide switch, SPK Jack and Line in Jack. The channel slide switch is used for 3 channels selection. After plug in the AC/DC adaptor, the transmitter will transmit the audio signal to associated receiver unit automatically. The audio signal will be transmitted continuously once the audio signal connected via either Line jack or SPK Jack inputs.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

The receiver for this transmitter is exempted from the Part 15 technical rules per 15.101(b).

#### 1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

#### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

---

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered by a AC/DC adaptor (Model: U090020D12, Input: 120VAC 60Hz 6.5W, Output 9VDC 200mA).

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the devices. Once the unit enters test mode, it transmits the RF Signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Equipment Modification

Any modifications installed previous to testing by RadioShack Corporation will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

#### 2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.6 Support Equipment List and Description

1. AC/DC Adaptor (Model: U090020D12, Input: 120VAC 60Hz 6.5W, Output: 9VDC 200mA) (Provided by Applicant)
2. Audio cable (Provided by Intertek)
3. Cassette Walkman EW-1738b (Provided by Intertek)

---

## INTERTEK TESTING SERVICES

---

### 3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB $\mu$ V/m
- RR = RA - AG - AV in dB $\mu$ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

RA = 52.0 dB $\mu$ V/m	
AF = 7.4 dB	RR = 18.0 dB $\mu$ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB $\mu$ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 9904.000MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 3.2 dB

### 3.4 Conducted Emission Configuration Photograph

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photos.pdf.

### 3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Passed by more than 20 dB

---

## INTERTEK TESTING SERVICES

---

### 4.0 Measurement Results

#### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 0.125 watt (+21 dBm). Maximum antenna gain for this transmitter is 0 dBi.

Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 2406	15.5	35.247
Middle Channel: 2434	16.8	47.547
High Channel: 2476	16.9	48.654

EUT dBm max. output level = 16.9 dBm (Limit:  $\leq$  21dBm)

For RF Safety, the information is saved with filename: RF exposure.pdf.

#### 4.2 Hopping Channel 20dB RF Bandwidth, FCC Rule 15.247(a)(1)(i):

Setting:

- Hopping function turned off
- Span = ~ 2 to 3 times the 20dB bandwidth, centred on a hopping channel
- RBW  $\geq$  1% of 20dB bandwidth, VBW  $\geq$  RBW
- Repeat the test with different mode of operation (e.g. maximum data rate, modulation formats etc)

Frequency (MHz)	20 dB Bandwidth (KHz)
Lowest Channel: 2406	1410
Middle Channel: 2434	1410
Highest Channel: 2476	1410

Limit: N/A

Refer to the following plots for 20 dB bandwidth sharp:

Plot B2A: Low Channel 20dB RF Bandwidth

Plot B2B: Middle Channel 20dB RF Bandwidth

Plot B2C: High Channel 20dB RF Bandwidth

For electronic filing, the above plots are saved with filename: 20dB.pdf

---

## INTERTEK TESTING SERVICES

---

### 4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(i):

Setting:

- Hopping function enabled
- Span = frequency band of operation
- RBW  $\geq$  1% of the span, VBW  $\geq$  RBW
- It may be necessary to break the span into sections, in order to show all of the hopping frequencies:

Mode of operation	No. of hopping channels
Transmission	15

Limit: Number of hopping channels  $\geq$  15

For electronic filing, the above plots are saved with filename: chno.pdf

### 4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Setting:

- Hopping function enabled
- Span = wide enough to capture the peaks of two adjacent channels
- RBW  $\geq$  1% of the span, VBW  $\geq$  RBW

Channel Separation (KHz)
2000

Limit:  $\geq$  2/3 20dB bandwidth of hopping channel = 940KHz

For electronic filing, the above plots are saved with filename: fsepa.pdf

---

## INTERTEK TESTING SERVICES

---

### 4.5 Average Channel Occupancy Time, FCC Ref.: 15.247(a)(1)(iii):

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 2ms for transmitter unit, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (0.4 seconds  $\times$  Number of hopping channels employed” seconds for 2400-2483.5MHz). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Transmitter Unit (Worst-case: Operation)
Average occupancy time in the period of 6.0s = 3.71 ms $\times$ 104 = 385.84 ms

Limit:  $\leq$  0.4 seconds

For electronic filing, the above plots are saved with filename: avetime.pdf

### 4.6 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

- Plot B6A.1 – B6A.2: Lowest Channel Emissions
- Plot B6B.1 – B6B.2: Middle Channel Emissions
- Plot B6C.1 – B6C.2: Highest Channel Emissions
- Plot B6D.1 – B6D.2: Modulation Products Emission at bandedges

The plots showed all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

For electronic filing, the above plots are saved with filenames: obantcon.pdf.

---

## INTERTEK TESTING SERVICES

---

### 4.7 Out of Band Radiated Emissions, FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

Not required, since all emissions are more than 20 dB below fundamental.

### 4.8 General radiated emission limit for spurious emissions at bandedge and within restricted band, FCC Rule 15.257(d):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The following data list the significant emission frequencies, the limit and the margin of compliance.

Frequency (MHz)	OATS radiated field strength at carrier frequency measured at 3m (dB $\mu$ V/m)		Attenuation (dBc)	Calculated radiated field strength at the bandage (dB $\mu$ V/m)	
	Peak	Average		Peak	Average
2483.5	115.3	98.7	58.02	57.28	40.68

#### Limit:

The average radiated field strength at bandedge should be smaller than 54 dB $\mu$ V/m and the peak radiated field strength at bandedge should be smaller than 74 dB $\mu$ V/m.

## INTERTEK TESTING SERVICES

---

### 4.9 Radiated Spurious Emissions

Applicant: RadioShack Corporation

Date of Test: March 08, 2011

Model: 1500044

Worst-Case Operating Mode: Transmitting (Lowest Channel)

Table 1

#### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2406.000	114.6	33	29.4	111.0	16.6	94.4	-	-
H	4812.000	60.4	33	34.9	62.3	16.6	45.7	54.0	-8.3
V	7218.000	47.4	33	37.9	52.3	16.6	35.7	54.0	-18.3
H	9624.000	55.4	33	40.4	62.8	16.6	46.2	54.0	-7.8
H	12030.000	52.5	33	40.5	60.0	16.6	43.4	54.0	-10.6
V	14436.000	59.0	33	40.0	66.0	16.6	49.4	54.0	-4.6
V	16842.000	57.9	33	37.6	62.5	16.6	45.9	54.0	-8.1

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2406.000	114.6	33	29.4	111.0	-	-
H	4812.000	60.4	33	34.9	62.3	74.0	-11.7
V	7218.000	47.4	33	37.9	52.3	74.0	-21.7
H	9624.000	55.4	33	40.4	62.8	74.0	-11.2
H	12030.000	52.5	33	40.5	60.0	74.0	-14.0
V	14436.000	59.0	33	40.0	66.0	74.0	-8.0
V	16842.000	57.9	33	37.6	62.5	74.0	-11.5

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

## INTERTEK TESTING SERVICES

Applicant: RadioShack Corporation  
 Model: 1500044

Date of Test: March 08, 2011

Worst-Case Operating Mode: Transmitting (Middle Channel)

Table 2

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2434.000	115.1	33	29.4	111.5	16.6	94.9	-	-
H	4868.000	60.6	33	34.9	62.5	16.6	45.9	54.0	-8.1
V	7302.000	47.3	33	37.9	52.2	16.6	35.6	54.0	-18.4
H	9736.000	58.9	33	40.4	66.3	16.6	49.7	54.0	-4.3
H	12170.000	53.0	33	40.5	60.5	16.6	43.9	54.0	-10.1
V	14604.000	60.8	33	38.4	66.2	16.6	49.6	54.0	-4.4
V	17038.000	60.4	33	37.6	65.0	16.6	48.4	54.0	-5.6

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2434.000	1115.1	33	29.4	111.5	-	-
H	4868.000	60.6	33	34.9	62.5	74.0	-11.5
V	7302.000	47.3	33	37.9	52.2	74.0	-21.8
H	9736.000	58.9	33	40.4	66.3	74.0	-7.7
H	12170.000	53.0	33	40.5	60.5	74.0	-13.5
V	14604.000	60.8	33	38.4	66.2	74.0	-7.8
V	17038.000	60.4	33	37.6	65.0	74.0	-9.0

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

## INTERTEK TESTING SERVICES

---

Applicant: RadioShack Corporation  
 Model: 1500044

Date of Test: March 08, 2011

Worst-Case Operating Mode: Transmitting (Highest Channel)

Table 3

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2476.000	115.3	33	29.4	111.7	16.6	95.1	-	-
H	4952.000	56.7	33	34.9	58.6	16.6	42.0	54.0	-12.0
V	7428.000	51.2	33	37.9	56.1	16.6	39.5	54.0	-14.5
H	9904.000	60.0	33	40.4	67.4	16.6	50.8	54.0	-3.2
H	12380.000	55.3	33	40.5	62.8	16.6	46.2	54.0	-7.8
V	14856.000	57.6	33	38.4	63.0	16.6	46.4	54.0	-7.6
V	17332.000	57.8	33	37.6	62.4	16.6	45.8	54.0	-8.2

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	2476.000	115.3	33	29.4	111.7	-	-
H	4952.000	56.7	33	34.9	58.6	74.0	-15.4
V	7428.000	51.2	33	37.9	56.1	74.0	-17.9
H	9904.000	60.0	33	40.4	67.4	74.0	-6.6
H	12380.000	55.3	33	40.5	62.8	74.0	-11.2
V	14856.000	57.6	33	38.4	63.0	74.0	-11.0
V	17332.000	57.8	33	37.6	62.4	74.0	-11.6

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

---

## INTERTEK TESTING SERVICES

---

Applicant: RadioShack Corporation

Date of Test: March 08, 2011

Model: 1500044

Worst-Case Operating Mode: Transmitting (Digital Portion)

### Data Table Radiated Scan Pursuant to FCC 15.109: Emissions Requirement

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	36.580	39.3	16	10.0	33.3	40.0	-6.7
V	47.955	37.8	16	11.0	32.8	40.0	-7.2
V	84.030	39.7	16	8.0	31.7	40.0	-8.3
V	135.040	33.1	16	14.0	31.1	43.5	-12.4
V	160.015	30.8	16	16.0	30.8	43.5	-12.7
V	240.050	27.0	16	19.0	30.0	46.0	-16.0

Notes: 1. Peak Detector Data.

2. Negative sign (-) in the margin column signify levels below the limit.

3. Only emissions significantly above equipment noise floor are reported.

## INTERTEK TESTING SERVICES

---

### 4.10 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

For the electronic filing, the above plots are saved with filename: timing.pdf

---

## INTERTEK TESTING SERVICES

---

### 5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

### 6.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

### 7.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

### 9.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

#### 9.1 Measured Bandwidth

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

## INTERTEK TESTING SERVICES

---

### 9.2 Discussion Pulse Desensitivity

Pulse desensitivity is not applicable for this device. The effective period ( $T_{eff}$ ) is approximately 3.72ms for a digital "1" bit which is illustrated on technical specification, with a resolution bandwidth (3dB) of 100kHz, so the pulse desensitivity factor is 0dB.

### 9.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 100 ms

Effective period of the cycle =  $3.64\text{ms} \times 2 + 3.72\text{ms} \times 2$

DC =  $14.72/100 = 0.1472$

Therefore, the averaging factor is found by  $20\log(0.1472) = -16.6\text{dB}$ .

---

## INTERTEK TESTING SERVICES

---

### 9.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

---

## INTERTEK TESTING SERVICES

---

### 9.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

### 10.0 Confidentiality Request

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

## INTERTEK TESTING SERVICES

---

### 11.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	Biconical Antenna
Registration No.	EW-2251	EW-2188	EW-0954
Manufacturer	R&S	AGILENTTECH	EMCO
Model No.	ESCI	E4407B	3104C
Calibration Date	Oct. 22, 2009	Dec. 27, 2010	Apr. 14, 2010
Calibration Due Date	Apr. 22, 2011	Dec. 31, 2011	Oct. 14, 2011

Equipment	Log Periodic Antenna	RF Amplifiers (100MHz to 12GHz) 2 Pieces	Double Ridged Guide Antenna
Registration No.	EW-0446	EW-1779	EW-1015
Manufacturer	EMCO	MITEQ	EMCO
Model No.	3146	AMF-4D-001120-34-13P	3115
Calibration Date	Apr. 26, 2010	Jul. 27, 2009	Feb. 09, 2010
Calibration Due Date	Oct. 26, 2011	Aug. 01, 2010	Aug. 09, 2011

#### 2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN	Pulse Limiter
Registration No.	EW-2666	EW-0192	EW-0699
Manufacturer	R&S	R&S	R&S
Model No.	ESCI7	ESH3-Z5	ESH3-Z2
Calibration Date	Oct. 12, 2010	Nov. 30, 2010	Dec. 24, 2009
Calibration Due Date	Oct. 12, 2011	Nov. 30, 2011	Jun. 24, 2011

#### 3) 15.247 Test

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	ROHDESCHWARZ
Model No.	FSP30
Calibration Date	Oct. 22, 2010
Calibration Due Date	Oct. 22, 2011