

## GENERAL INFORMATION

General Information in accordance with the Federal Communications Commission Rules and Regulations, Volume II, Part 2.

(1) Applicant:

RadioShack, A Division of Tandy Corporation  
100 Throckmorton St Ste 1300  
Fort Worth, TX 76102-2802

(2) FCC Identifier: FCC ID: AA02000311A  
MODEL NO.: 20-311A

(3) Instruction Manual: Refer to User Manual

(4) Circuit Description: Refer to Operational Description

(5) Circuit & Block Diagrams: Refer to Schematics & Block diagrams

(6) Measurement Data: Refer to Test Report

Standard Test Conditions:

The following conditions and procedures were followed during testing of the equipment.

Room Temperature: 23 - 27 Degrees Celsius

Room Humidity: 40 - 60 %

Note 1: This equipment is intended to use with "AA" batteries or AC adapter.

Note 2: Prior to testing, the unit is tuned-up according to the manufacturer's alignment procedure.

All presented data will represent the "worst case" parameter being measured.

(7) Photographs & Equipment Identification:

Refer to ID Label/Location Info & External Photos

(8) Peripheral or Accessory Device: Not used

(9) Transition provisions in section 15.37 Rules:

This equipment complies with the new Part 15 of FCC rules and is not affected by section 15.37.

(10) Decoding the Emergency Broadcast System Attention Signal:

Not Applicable

(11) Direct Sequence Spread Spectrum Transmitter:

Not Applicable

(12) Compliance to Cellular Band Exclusion:

Pursuant to the requirements contained in Part 15.121 of the Commission's Rules, this scanning receiver does not have the capability of tuning the frequencies assigned to the Domestic Public Cellular Radio Telecommunications Service.

In this circuitry, this device is not readily alterable to restore the cellular band coverage because the inventory of frequencies contained within this band are not available in the microprocessor. Also, the microprocessor is fixed soldered and not easily removable.

Therefore, since the clipping of leads; or the installation of a simple component such as a diode, resistor, or a jumper wire; or the reprogramming of any semiconductor device contained within this unit cannot be accomplished using a special access code or a personal computer; Uniden certifies that the conditions mandated in part 15.121 have been met.