



- NOTES:
1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K=KILG OHM, M=MEG OHM)
  2. RESISTOR WATTAGES ARE [1/16W] UNLESS OTHERWISE NOTED.
  3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P=MICRO-MICRO FARAD)
  4. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE [C0] (LESS THAN 100PPM) OR [D] (MORE THAN 100PPM) UNLESS OTHERWISE NOTED.
  5. CHIP PARTS ARE NOT SPECIFIED IN THIS DRAWING PLEASE REFER TO THE PARTS LIST FOR THE CHIP PARTS.
  6. CHIP CAPACITORS TYPE ARE [1600] UNLESS OTHERWISE NOTED.

DESIGN	DRAWN BY	UNIDEN No.	MODEL No.
APR. 21, 99	AUB. 95, 99	UB-308Z	FIG-78 (28-313)
NISHI	NISHI	TITLE	PLL ASS'Y
CHECK BY	APPROV BY	SCHEMATIC DIAGRAM	
		DRAWING No.	
REV. No.	UNIDEN CORP.		