

TEST REPORT

Report No.: HK12110659-2

RadioShack Corporation

Application
For
Certification
(Class II Permissive Change)
(FCC ID: AAO3201258AR)

Superheterodyne Receiver

Prepared and Checked by:

Approved by:

Signed On File
Wong Cheuk Ho, Herbert
Engineer

Chan Chi Hung, Terry
Assistant Supervisor
Date: January 14, 2013

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

RadioShack Corporation
BRAND NAME: RadioShack, MODEL: 3201258

FCC ID: AAO3201258AR

| | |
|---------------------------|---|
| Grantee: | RadioShack Corporation |
| Grantee Address: | 300 RadioShack Circle, Mail Stop WF4-136, Fort Worth, Texas 76102-2802, USA. |
| Contact Person: | Pat Loehr |
| Tel: | 817-415-6221 |
| Fax: | 817-415-9247 |
| e-mail: | N/A |
| Manufacturer: | N/A |
| Manufacturer Address: | N/A |
| Brand Name: | RadioShack |
| Model: | 3201258 |
| Type of EUT: | Superheterodyne Receiver |
| Description of EUT: | FM Wireless Microphone System |
| Serial Number: | N/A |
| FCC ID: | AAO3201258AR |
| Date of Sample Submitted: | November 19, 2012 |
| Date of Test: | December 12, 2012 |
| Report No.: | HK12110659-2 |
| Report Date: | January 14, 2013 |
| Environmental Conditions: | Temperature: +10 to 40°C Humidity: 10 to 90% |

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

RadioShack Corporation
BRAND NAME: RadioShack, MODEL: 3201258

FCC ID: AAO3201258AR

| TEST SPECIFICATION | REFERENCE | RESULTS |
|--|-------------------------------|---------|
| Maximum Peak Output Power | 15.247(b), (c) / RSS-210 A8.4 | N/A |
| Hopping Channel Carrier Frequencies Separation | 15.247(e) / RSS-210 A8.1 | N/A |
| 20dB Bandwidth of the Hopping Channel | 15.247(a) / RSS-210 A8.1 | N/A |
| Number of Hopping Frequencies | 15.247(e) / RSS-210 A8.1 | N/A |
| Average Time of Occupancy of Hopping Frequency | 15.247(e) / RSS-210 A8.1 | N/A |
| Antenna Conducted Spurious Emissions | 15.247(d) / RSS-210 A8.5 | N/A |
| Radiated Spurious Emissions | 15.247(d) / RSS-210 A8.5 | N/A |
| RF Exposure Compliance | 15.247(i) / RSS-Gen 5.6 | N/A |
| Transmitter Power Line Conducted Emissions | 15.207 / RSS-Gen 7.2.4 | N/A |
| Transmitter Field Strength | 15.227 / RSS-310 3.8 | N/A |
| Transmitter Field Strength | 15.229 / RSS-210 A2.7 | N/A |
| Transmitter Field Strength, Bandwidth and Timing Requirement | 15.231(a) / RSS-210 A1.1.1 | N/A |
| Transmitter Field Strength, Bandwidth and Timing Requirement | 15.231(e) / RSS-210 A1.1.5 | N/A |
| Transmitter Field Strength and Bandwidth Requirement | 15.239 / RSS-210 A2.8 | N/A |
| Transmitter Field Strength and Bandwidth Requirement | 15.249 / RSS-210 A2.9 | N/A |
| Transmitter Field Strength and Bandwidth Requirement | 15.235 / RSS-310 3.9 | N/A |
| Receiver / Digital Device Radiated Emissions | 15.109 / RSS-210 2.5 | Pass |
| Digital Device Conducted Emissions | 15.107 / ICES-003 | Pass |

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

| | | |
|------|---|----|
| 1.0 | <u>General Description</u> | 1 |
| 1.1 | Product Description | 1 |
| 1.2 | Purpose of Change | 1 |
| 1.3 | Test Methodology | 1 |
| 1.4 | Test Facility | 1 |
| 2.0 | <u>System Test Configuration</u> | 2 |
| 2.1 | Justification | 2 |
| 2.2 | EUT Exercising Software | 2 |
| 2.3 | Special Accessories | 2 |
| 2.4 | Equipment Modification | 2 |
| 2.5 | Measurement Uncertainty | 2 |
| 2.6 | Support Equipment List and Description | 2 |
| 3.0 | <u>Emission Results</u> | 3 |
| 3.1 | Field Strength Calculation | 3 |
| 3.2 | Radiated Emission Configuration Photograph | 4 |
| 3.3 | Radiated Emission Data | 4 |
| 3.4 | Conducted Emission Configuration Photograph | 4 |
| 3.5 | Conducted Emission Data | 4 |
| 4.0 | <u>Equipment Photographs</u> | 7 |
| 5.0 | <u>Product Labelling</u> | 7 |
| 6.0 | <u>Technical Specifications</u> | 7 |
| 7.0 | <u>Instruction Manual</u> | 7 |
| 8.0 | <u>Miscellaneous Information</u> | 8 |
| 8.1 | Discussion of Pulse Desensitization | 8 |
| 8.2 | Calculation of Average Factor | 8 |
| 8.3 | Emissions Test Procedures | 9 |
| 9.0 | <u>Confidentiality Request</u> | 10 |
| 10.0 | <u>Equipment List</u> | 11 |

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is an audio receiver for its corresponding wireless microphone. The main function of the EUT is used to receive the modulated signal that can be transmitting by its corresponding wireless microphone. And it can receive the transmitting signal in three difference channels, 169.505MHz, 170.245MHz and 171.905MHz. But it can receive only one channel for each receiver and need to change the crystal for the other two frequencies, the change of crystal can only be done by manufacturer. It's powered by an AC/DC adaptor (Model: U090025D12, Input: AC 120V, Output: DC 9V 250mA) and there are two power indicator (green and red LED) in the front of the EUT's body. The green and red LED will be lighted while received signal from the microphone and the power switch was on respectively.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Purpose of Change

The RF portion, which is previously fabricated as separate module, is now integrated into the main PCB board. The hardware and parameter setting of the RF portion remains unchanged.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by RadioShack Corporation will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

1 x Line out cable with length 0.96 m
1 x Microphone cable with length 0.89 m
(Provided by Applicant)

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB μ V/m
- RR = RA - AG - AV in dB μ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

| | |
|-------------------------------|----------------------|
| RA = 52.0 dB μ V/m | |
| AF = 7.4 dB | RR = 18.0 dB μ V |
| CF = 1.6 dB | LF = 9.0 dB |
| AG = 29.0 dB | |
| AV = 5.0 dB | |
| FS = RR + LF | |
| FS = 18 + 9 = 27 dB μ V/m | |

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 158.805 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 6.7 dB

3.4 Conducted Emission Configuration Photograph

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by more than 20 dB

INTERTEK TESTING SERVICES

Applicant: RadioShack Corporation

Date of Test: December 12, 2012

Model: 3201258

Worst-Case Operating Mode: Rx (169.505MHz)

Table 1

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.109 Requirement**

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-amp (dB) | Antenna Factor (dB) | Net at 3m (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|--------------|---------------------|--------------------------|----------------------------|-------------|
| H | 52.936 | 33.6 | 16 | 11.0 | 28.6 | 40.0 | -11.4 |
| H | 105.872 | 31.4 | 16 | 13.0 | 28.4 | 43.5 | -15.1 |
| H | 158.805 | 36.8 | 16 | 16.0 | 36.8 | 43.5 | -6.7 |
| H | 317.610 | 26.4 | 16 | 23.0 | 33.4 | 46.0 | -12.6 |
| H | 476.415 | 20.8 | 16 | 26.0 | 30.8 | 46.0 | -15.2 |
| H | 635.220 | 17.4 | 16 | 29.0 | 30.4 | 46.0 | -15.6 |
| H | 794.025 | 16.4 | 16 | 31.0 | 31.4 | 46.0 | -14.6 |
| H | 952.830 | 13.9 | 16 | 33.0 | 30.9 | 46.0 | -15.1 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: RadioShack Corporation
Model: 3201258
Worst-Case Operating Mode: Rx (171.905MHz)

Date of Test: December 12, 2012

Table 2

**Radiated Emissions
Pursuant to FCC Part 15 Section 15.109 Requirement**

| Polarization | Frequency (MHz) | Reading (dB μ V) | Pre-amp (dB) | Antenna Factor (dB) | Net at 3m (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|--------------|-----------------|----------------------|--------------|---------------------|--------------------------|----------------------------|-------------|
| H | 53.736 | 33.4 | 16 | 11.0 | 28.4 | 40.0 | -11.6 |
| H | 107.472 | 30.2 | 16 | 14.0 | 28.2 | 43.5 | -15.3 |
| H | 161.205 | 34.1 | 16 | 16.0 | 34.1 | 43.5 | -9.4 |
| H | 322.410 | 30.5 | 16 | 23.0 | 37.5 | 46.0 | -8.5 |
| H | 483.615 | 24.8 | 16 | 26.0 | 34.8 | 46.0 | -11.2 |
| H | 644.820 | 21.1 | 16 | 29.0 | 34.1 | 46.0 | -11.9 |
| H | 806.025 | 17.6 | 16 | 31.0 | 32.6 | 46.0 | -13.4 |
| H | 967.230 | 18.0 | 16 | 33.0 | 35.0 | 54.0 | -19.0 |

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure.

8.1 Discussion Pulse Desensitivity

This device is a superheterodyne receiver. No desensitization of the measurement equipment is required as the received signals are continuously.

8.2 Calculation of Average Factor

This device is a superheterodyne receiver. It is not necessary to apply average factor to the measurement result.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of superheterodyne receivers operating under the Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 (2009). A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

9.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

10.0 Equipment List

1) Radiated Emissions Test

| Equipment | EMI Test Receiver | Biconical Antenna | Log Periodic Antenna |
|----------------------|-------------------|-------------------|----------------------|
| Registration No. | EW-2500 | EW-2512 | EW-0446 |
| Manufacturer | R&S | EMCO | EMCO |
| Model No. | ESCI | 3104C | 3146 |
| Calibration Date | Feb. 24, 2012 | Nov. 15, 2011 | Oct. 31, 2011 |
| Calibration Due Date | Feb. 24, 2013 | May 15, 2013 | Apr. 30, 2013 |

| Equipment | Spectrum Analyzer | Double Ridged Guide Antenna |
|----------------------|-------------------|-----------------------------|
| Registration No. | EW-2253 | EW-1015 |
| Manufacturer | R&S | EMCO |
| Model No. | FSP40 | 3115 |
| Calibration Date | Jan. 12, 2012 | Aug. 24, 2011 |
| Calibration Due Date | Jan. 12, 2013 | Feb. 24, 2013 |

2) Conducted Emissions Test

| Equipment | EMI Test Receiver | LISN |
|----------------------|-------------------|---------------|
| Registration No. | EW-2500 | EW-2874 |
| Manufacturer | R&S | R&S |
| Model No. | ESCI | ENV-216 |
| Calibration Date | Feb. 24, 2012 | Aug. 15, 2012 |
| Calibration Due Date | Feb. 24, 2013 | Aug. 15, 2013 |