

**KTL Test Report:** 8001229.1

**Applicant:** VTECH Engineering Canada Ltd.  
200-7671 Alderbridge Way  
Richmond, BC  
V6X 1Z9

**Equipment Under Test:  
(E.U.T.)** 43-1106 (900 MHz Cordless Telephone)

**FCC ID:** AAO4301106

**In Accordance With:** **FCC Part 15, Subpart C, 15.249**  
For 900 MHz Cordless Telephones

**Tested By:** KTL Ottawa Inc.  
3325 River Road, R.R. 5  
Ottawa, Ontario K1V 1H2

**Authorized By:** \_\_\_\_\_  
T. Tidwell, Wireless Group Manager

**Date:** \_\_\_\_\_

**Total Number of Pages:** 28

## **Table Of Contents**

### **Section 1. Summary of Test Results**

- General
- Summary of Test Data

### **Section 2. General Equipment Specification**

- Specifications
- Modifications
- Theory of Operation
- System Diagram

### **Section 3. Powerline Conducted Emissions**

- Test Results
- Graphs
- Photographs

### **Section 4A. Radiated Emissions (Base)**

- Base Test Results
- Base Data Table
- Base Photographs

### **Section 4B. Radiated Emissions (Handset)**

- Handset Test Results
- Handset Data Table
- Handset Photographs

### **Section 5. Test Equipment List**

#### **Annex A. Test Diagrams**

- Conducted Emissions
- Radiated Prescan
- Test Site for Radiated Emissions

#### **Annex B. Restricted Bands**

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 1. Summary Of Test Results**

Manufacturer: VTECH Engineering Canada Ltd.

Model No.: 43-1106

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 15.249. All tests were conducted using measurement procedure ANSI C63.4-1992. Radiated Emissions were made on an open area test site.

New Submission

Production Unit

Class II Permissive Change

Pre-Production Unit

E	T	S
---	---	---

Equipment Code

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See " Summary of Test Data".



**NVLAP LAB CODE: 100351-0**

TESTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

Kevin Carr, Technologist

KTL Ottawa Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. KTL Ottawa Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Summary Of Test Data**

**Base:**

<b>NAME OF TEST</b>	<b>PARA. NO.</b>	<b>RESULT</b>
Conducted Emissions	15.207	Complies
Radiated Emissions	15.249	Complies

**Handset:**

<b>NAME OF TEST</b>	<b>PARA. NO.</b>	<b>RESULT</b>
Radiated Emissions	15.249	Complies

**Footnotes For N/A's:**

**Test Conditions:**

**Indoor**                      Temperature: 22 °C  
   Humidity: 23 %

**Outdoor**                     Temperature: 5 °C  
   Humidity: 23 %

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 2A. General Equipment Specification**

**Base:**

**Equipment:** 900 MHz Cordless Telephone  
**Model Number:** 43-1106  
**Serial Number:** None  
**Frequency Range:** 902.3 / 905.0 MHz  
**Operating Frequency(ies) of Sample:** 902.6 & 904.7 MHz  
**Tunable Bands:** 1  
**Number of Channels:** 10  
**Channel Spacing:** 30 kHz  
**Emission Designator:** 100KF1D  
**Crystal Frequencies:** 18.25 MHz  
**User Frequency Adjustment:** None, Software Controlled

**Integral Antenna** **Yes** **No**

*Note: If antenna is not integral to transmitter explain method of attachment and type of unique connector:*

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 2B. General Equipment Specification**

**Handset**

**Equipment:** 900 MHz Cordless Telephone  
**Model Number:** 43-1106  
**Serial Number:** None  
**Frequency Range:** 925.05 / 927.75 MHz  
**Operating Frequency(ies) of Sample:** 925.35 & 927.45 MHz  
**Tunable Bands:** 1  
**Number of Channels:** 10  
**Channel Spacing:** 30 kHz  
**Emission Designator:** 100KF1D  
**Crystal Frequencies:** 18.25 MHz  
**User Frequency Adjustment:** None, Software Controlled

**Integral Antenna** **Yes**  **No**

*Note: If antenna is not integral to transmitter explain method of attachment and type of unique connector:*

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*

*FCC ID: AAO4301106*

---

**Description of Modification for Class II Permissive Change**

**NOT APPLICABLE**

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*

*FCC ID: AAO4301106*

---

**Modifications Made During Testing**

**NOT APPLICABLE**

EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)  
FCC ID: AAO4301106


---

### Theory of Operation

The E.U.T. is a 900 MHz cordless telephone. The carrier frequency is generated from the second harmonic of a VCO operating at roughly 450 MHz. The unit has 10 channel capability.

### System Diagram

#### Base Block Diagram




EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)  
FCC ID: AAO4301106

---

**System Diagram, continued**

**Handset Block Diagram**



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 3. Powerline Conducted Emissions**

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207
TESTED BY: Kevin Carr	DATE: February 1, 1999

**Minimum Standard:**

Frequency (MHz)	Maximum Powerline Conducted RF Voltage	
	( $\mu$ V)	(dB $\mu$ V)
0.45 - 30.0	250	48

**Test Results:** Complies. See attached graph(s).


**Measurement Data:** See attached graph(s).

**Method of Measurement:** (Procedure ANSI C63.4-1992)

Measurements were made using a spectrum analyzer with 10 kHz RBW, Peak Detector. Any emissions that are close to the limit are measured using a test receiver with 10 kHz bandwidth, CISPR Quasi-Peak Detector.


*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---



EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)  
FCC ID: AAO4301106

---



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Conducted Photographs (Worst Case Configuration)**

SIDE VIEW



FRONT VIEW



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

**Section 4A. Radiated Emissions (Base)**

NAME OF TEST: Radiated Emissions (Base)	PARA. NO.: 15.249
TESTED BY: Kevin Carr	DATE: February 4, 1999

**Minimum Standard:** Para no. 15.249

(a) The field strengths shall not exceed the following:

Fundamental (MHz)	Field Strength (mV/m)	Field Strength (dBµV)	Harmonic (mV/m)	Harmonic (dBµV)
902-928	50	94	0.5	54

(b) Field strength limits are specified at a distance of 3 metres.

(c) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated limits of 15.209 whichever is the less attenuation.

(d) The emission limits shown above are based on measurement instrumentation employing a CISPR quasi-peak detector below 1000 MHz and an averaging detector above 1000 MHz. However, the peak field strength of any emission shall not exceed the average limit by more than 20 dB.

**Test Results:** Complies. The worst-case emission level is 52.1 dBµV/m @ 3m at 9047.0 MHz. This is 1.9 dB below the specification limit.

**Measurement Data:** See attached table.

**Maximizing Emission Levels:**

For hand held equipment or equipment that may be mounted in a variety of positions, the E.U.T. was tested on three orthogonal axis to determine orientation of worst-case emission levels.

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

**Test Data - Radiated Emissions: Base, Channel 2**

Test Distance (meters) : 3		Range: A Tower		Receiver: ESVP, HP8566B		RBW: 120 kHz, 1 MHz		Detector: CISPR, Peak			
Freq. (MHz)	Ant. *	Pol. (V/H)	Ant. HGT. (m)	Table (deg.)	RCVD Signal (dBµV/m)	Ant. Factor (dB)**	Amp. Gain (dB)***	Dist. Corr. (dB)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
902.6	E/D4	V			54.4	34.9			89.3	94.0	4.7
902.6	E/D4	H			47.5	34.9			82.4	94.0	11.6
1805.2	Hrn2	V			49.4	30.1	-43.8		35.7	54.0	18.3
1805.2	Hrn2	H			48.6	30.1	-43.8		34.9	54.0	19.1
2707.8	Hrn2	V			45.0	31.9	-45.2		31.7	54.0	22.3
2707.8	Hrn2	H			45.4	31.9	-45.2		32.1	54.0	21.9
3610.0	Hrn2	V			44.6	35.4	-42.3		37.7	54.0	16.3
3610.0	Hrn2	H			44.3	35.4	-42.3		37.4	54.0	16.6
4513.0	Hrn2	V			45.9	37.4	-43.4		39.9	54.0	14.1
4513.0	Hrn2	H			45.6	37.4	-43.4		39.6	54.0	14.4
5415.6	Hrn2	V			43.4	39.9	-43.8		39.5	54.0	14.5
5415.6	Hrn2	H			44.6	39.9	-43.8		40.7	54.0	13.3
6318.0	Hrn2	V			43.3	42.7	-40.8		45.2	54.0	8.8
6318.0	Hrn2	H			44.3	42.7	-40.8		46.2	54.0	7.8
7220.8	Hrn2	V			42.8	44.4	-42.3		44.9	54.0	9.1
7220.8	Hrn2	H			42.7	44.4	-42.3		44.8	54.0	9.2
8123.4	Hrn2	V			38.2	46.8	-43.6		41.4	54.0	12.6
8123.4	Hrn2	H			38.7	46.8	-43.6		41.9	54.0	12.1
9026.0	Hrn2	V			37.9	50.5	-43.4		45.0	54.0	9.0
9026.0	Hrn2	H			37.6	50.5	-43.4		44.7	54.0	9.3

Notes:

B/C = Biconical, B/L = Biconilog, L/P = Log-Periodic, H = Horn, D/P = Dipole

\* Re-measured using dipole antenna. ( ) Denotes failing emission level.

(1) 120 kHz, Q-Peak, (2) 10 kHz, Peak, (3) 100 kHz RBW, 300 kHz VBW, Peak,

(4) 300 kHz RBW, 1 MHz VBW, Peak, (5) 1 MHz RBW, 3 MHz VBW, Peak, (6) 1 MHz RBW, 10 Hz VBW, Peak

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

**Test Data - Radiated Emissions: Base, Channel 9**

Test Distance (meters) : 3		Range: A Tower		Receiver: ESVP, HP8566B		RBW: 120 kHz, 1 MHz		Detector: CISPR, Peak			
Freq. (MHz)	Ant. *	Pol. (V/H)	Ant. HGT. (m)	Table (deg.)	RCVD Signal (dBµV/m)	Ant. Factor (dB)**	Amp. Gain (dB)***	Dist. Corr. (dB)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
904.7	E/D4	V			55.4	34.9			90.3	94.0	3.7
904.7	E/D4	H			51.3	34.9			86.2	94.0	7.8
1809.4	Hrn2	V			48.6	30.1	-43.9		34.8	54.0	19.2
1809.4	Hrn2	H			49.6	30.1	-43.9		35.8	54.0	18.2
2714.1	Hrn2	V			45.6	31.9	-45.2		32.3	54.0	21.7
2714.1	Hrn2	H			46.7	31.9	-45.2		33.4	54.0	20.6
3618.8	Hrn2	V			47.2	35.5	-42.3		40.4	54.0	13.6
3618.8	Hrn2	H			45.9	35.5	-42.3		39.1	54.0	14.9
4523.5	Hrn2	V			46.1	37.4	-43.4		40.1	54.0	13.9
4523.5	Hrn2	H			45.8	37.4	-43.4		39.8	54.0	14.2
5428.2	Hrn2	V			45.7	39.9	-43.8		41.8	54.0	12.2
5428.2	Hrn2	H			44.2	39.9	-43.8		40.3	54.0	13.7
6332.9	Hrn2	V			45.3	42.7	-40.8		47.2	54.0	6.8
6332.9	Hrn2	H			46.8	42.7	-40.8		48.7	54.0	5.3
7237.6	Hrn2	V			46.5	44.4	-42.3		48.6	54.0	5.4
7237.6	Hrn2	H			45.7	44.4	-42.3		47.8	54.0	6.2
8142.3	Hrn2	V			46.3	47.0	-43.7		49.6	54.0	4.4
8142.3	Hrn2	H			44.7	47.0	-43.7		48.0	54.0	6.0
9047.0	Hrn2	V			45.0	50.5	-43.4		52.1	54.0	1.9
9047.0	Hrn2	H			44.4	50.5	-43.4		51.5	54.0	2.5

Notes:

B/C = Biconical, B/L = Biconilog, L/P = Log-Periodic, H = Horn, D/P = Dipole

\* Re-measured using dipole antenna. ( ) Denotes failing emission level.

(1) 120 kHz, Q-Peak, (2) 10 kHz, Peak, (3) 100 kHz RBW, 300 kHz VBW, Peak,

(4) 300 kHz RBW, 1 MHz VBW, Peak, (5) 1 MHz RBW, 3 MHz VBW, Peak, (6) 1 MHz RBW, 10 Hz VBW, Peak

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*


---

**Radiated Photographs - Base (Worst Case Configuration)**

FRONT VIEW



REAR VIEW



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 4B. Radiated Emissions (Handset)**

NAME OF TEST: Radiated Emissions (Handset)	PARA. NO.: 15.249
TESTED BY: Kevin Carr	DATE: February 4, 1999

**Minimum Standard:** Para no. 15.249

(a) The field strengths shall not exceed the following:

Fundamental (MHz)	Field Strength (mV/m)	Field Strength (dBµV)	Harmonic (mV/m)	Harmonic (dBµV)
902-928	50	94	0.5	54

(b) Field strength limits are specified at a distance of 3 metres.

(c) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated limits of 15.209 whichever is the less attenuation.

(d) The emission limits shown above are based on measurement instrumentation employing a CISPR quasi-peak detector below 1000 MHz and an averaging detector above 1000 MHz. However, the peak field strength of any emission shall not exceed the average limit by more than 20 dB.

**Test Results:** Complies. The worst-case emission level is 87.9 dBµV/m @ 3m at 925.35 MHz. This is 6.1 dB below the specification limit.

**Measurement Data:** See attached table.

**Maximizing Emission Levels:**

For hand held equipment or equipment that may be mounted in a variety of positions, the E.U.T. was tested on three orthogonal axis to determine orientation of worst-case emission levels.

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

**Test Data - Radiated Emissions: Handset, Channel 2**

Test Distance (meters) : 3		Range: A Tower		Receiver: ESVP, HP8566B		RBW: 120 kHz, 1 MHz		Detector: CISPR, Peak			
Freq. (MHz)	Ant. *	Pol. (V/H)	Ant. HGT. (m)	Table (deg.)	RCVD Signal (dBµV/m)	Ant. Factor (dB)**	Amp. Gain (dB)***	Dist. Corr. (dB)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
925.35	E/D4	V			52.6	35.3			87.9	94.0	6.1
925.35	E/D4	H			41.2	35.3			76.5	94.0	17.5
1850.7	Hrn2	V			48.4	30.3	-44.6		34.1	54.0	19.9
1850.7	Hrn2	H			49.7	30.3	-44.6		35.4	54.0	18.6
2776.05	Hrn2	V			44.4	32.0	-45.0		31.4	54.0	22.6
2776.05	Hrn2	H			44.8	32.0	-45.0		31.8	54.0	22.2
3701.4	Hrn2	V			46.4	35.6	-42.4		39.6	54.0	14.4
3701.4	Hrn2	H			45.2	35.6	-42.4		38.4	54.0	15.6
4626.75	Hrn2	V			45.8	37.8	-43.7		39.9	54.0	14.1
4626.75	Hrn2	H			45.2	37.8	-43.7		39.3	54.0	14.7
5552.1	Hrn2	V			41.3	40.3	-43.4		38.2	54.0	15.8
5552.1	Hrn2	H			42.3	40.3	-43.4		39.2	54.0	14.8
6477.45	Hrn2	V			42.3	42.8	-40.8		44.3	54.0	9.7
6477.45	Hrn2	H			42.5	42.8	-40.8		44.5	54.0	9.5
7402.8	Hrn2	V			41.6	44.7	-42.1		44.2	54.0	9.8
7402.8	Hrn2	H			41.3	44.7	-42.1		43.9	54.0	10.1
8328.15	Hrn2	V			38.4	48.4	-44.0		42.8	54.0	11.2
8328.15	Hrn2	H			38.4	48.4	-44.0		42.8	54.0	11.2
9253.5	Hrn2	V			36.6	50.6	-43.4		43.8	54.0	10.2
9253.5	Hrn2	H			36.2	50.6	-43.4		43.4	54.0	10.6

Notes:

B/C = Biconical, B/L = Biconilog, L/P = Log-Periodic, H = Horn, D/P = Dipole

\* Re-measured using dipole antenna. ( ) Denotes failing emission level.

(1) 120 kHz, Q-Peak, (2) 10 kHz, Peak, (3) 100 kHz RBW, 300 kHz VBW, Peak,

(4) 300 kHz RBW, 1 MHz VBW, Peak, (5) 1 MHz RBW, 3 MHz VBW, Peak, (6) 1 MHz RBW, 10 Hz VBW, Peak

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

**Test Data - Radiated Emissions: Handset, Channel 9**

Test Distance (meters) : 3		Range: A Tower		Receiver: ESVP, HP8566B		RBW: 120 kHz, 1 MHz		Detector: CISPR, Peak			
Freq. (MHz)	Ant. *	Pol. (V/H)	Ant. HGT. (m)	Table (deg.)	RCVD Signal (dBµV/m)	Ant. Factor (dB)**	Amp. Gain (dB)***	Dist. Corr. (dB)	Field Strength (dBµV/m)	Limit (dBµV/m)	Margin (dB)
927.45	E/D4	V			49.5	35.3			84.8	94.0	9.2
927.45	E/D4	H			41.4	35.3			76.7	94.0	17.3
1854.9	Hrn2	V			46.9	30.3	-44.6		32.6	54.0	21.4
1854.9	Hrn2	H			48.6	30.3	-44.6		34.3	54.0	19.7
2782.35	Hrn2	V			43.4	32.0	-45.0		30.4	54.0	23.6
2782.35	Hrn2	H			44.4	32.0	-45.0		31.4	54.0	22.6
3709.8	Hrn2	V			45.2	35.6	-42.4		38.4	54.0	15.6
3709.8	Hrn2	H			45.5	35.6	-42.4		38.7	54.0	15.3
4637.25	Hrn2	V			45.7	37.9	-43.7		39.9	54.0	14.1
4637.25	Hrn2	H			45.4	37.9	-43.7		39.6	54.0	14.4
5564.7	Hrn2	V			42.0	40.4	-43.3		39.1	54.0	14.9
5564.7	Hrn2	H			44.3	40.4	-43.3		41.4	54.0	12.6
6492.15	Hrn2	V			42.7	42.8	-40.8		44.7	54.0	9.3
6492.15	Hrn2	H			42.6	42.8	-40.8		44.6	54.0	9.4
7419.6	Hrn2	V			41.4	44.7	-42.1		44.0	54.0	10.0
7419.6	Hrn2	H			43.1	44.7	-42.1		45.7	54.0	8.3
8347.05	Hrn2	V			38.0	48.6	-44.0		42.6	54.0	11.4
8347.05	Hrn2	H			37.4	48.6	-44.0		42.0	54.0	12.0
9274.5	Hrn2	V			36.2	50.6	-43.4		43.4	54.0	10.6
9274.5	Hrn2	H			36.9	50.6	-43.4		44.1	54.0	9.9

Notes:  
 B/C = Biconical, B/L = Biconilog, L/P = Log-Periodic, H = Horn, D/P = Dipole  
 \* Re-measured using dipole antenna. ( ) Denotes failing emission level.  
 (1) 120 kHz, Q-Peak, (2) 10 kHz, Peak, (3) 100 kHz RBW, 300 kHz VBW, Peak,  
 (4) 300 kHz RBW, 1 MHz VBW, Peak, (5) 1 MHz RBW, 3 MHz VBW, Peak, (6) 1 MHz RBW, 10 Hz VBW, Peak

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*

*FCC ID: AAO4301106*

---

**Radiated Photographs - Handset (Worst Case Configuration)**

FRONT VIEW



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Section 5. Test Equipment List**

CAL CYCLE	EQUIPMENT	MANUFACTURER	MODEL	SERIAL	LAST CAL.	NEXT CAL.	
1 Year	Spectrum Analyzer-1	Hewlett Packard	8566B	2311A02238	Oct. 22/98	Oct. 22/99	
1 Year	Spectrum Analyzer Display-1	Hewlett Packard	8566B	2314A04759	Oct. 22/98	Oct. 22/99	
1 Year	Quasi-peak adapter-1	Hewlett-Packard	85650A	2043A00302	Oct. 22/98	Oct. 22/99	
1 Year	Spectrum Analyzer-2	Hewlett Packard	8566B	1950A00400	July 22/98	July 22/99	
1 Year	Spectrum Analyzer Display-2	Hewlett Packard	85662A	1950A01177	July 22/98	July 22/99	
1 Year	Quasi Peak Adaptor-2	Hewlett Packard	85650A	2251A00620	July 22/98	July 22/99	
1 Year	LISN	Rohde & Schwarz	ESH2-Z5	890485/017	July 23/98	July 23/99	
1 Year	Receiver	Rohde & Schwarz	ESVP	892661/014	Mar. 31/98	Mar. 31/99	
	Biconilog Antenna	EMCO	3143	1038	NCR	NCR	
2 Year	Horn Antenna	EMCO #2	3115	4336	Oct. 30/97	Oct. 30/99	
1 Year	Dipole Antenna Set	EMCO	3121C	1029	Oct. 28/98	Oct. 28/99	
1 Year	Low Noise Amplifier	Avantek	AWT-8035	1005	Aug. 4/98	Aug. 4/99	
1 Year	Low Noise Amplifier	DBS Microwave	DWT-13035	9623	Aug. 4/98	Aug. 4/99	

NA: Not Applicable  
 NCR: No Cal Required

**KTL Ottawa**

FCC PART 15, SUBPART C  
FOR 900 MHz CORDLESS TELEPHONES  
PROJECT NO.: 8001229.1  
ANNEX A

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*


---

**ANNEX A**  
**TEST DIAGRAMS**


*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Conducted Emissions**




**Radiated Prescan**



*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

**Test Site For Radiated Emissions**



**KTL Ottawa**

FCC PART 15, SUBPART C  
FOR 900 MHz CORDLESS TELEPHONES  
PROJECT NO.: 8001229.1  
ANNEX B

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AAO4301106*

---

## **ANNEX B**

### **RESTRICTED BANDS OF OPERATION**

*EQUIPMENT: 43-1106 (900 MHz Cordless Telephone)*  
*FCC ID: AA04301106*

**Section B      Restricted Bands of Operation**

(a) Except as shown in paragraph (d) of this section , only spurious emissions are permitted in any of the frequency bands listed below:

<b>MHz</b>	<b>MHz</b>	<b>MHz</b>	<b>GHz</b>
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.49 - 0.51	16.69475-16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425-16.80475	960-1240	7.25-7.75
3.020 - 3.026	25.5-25.67	1300-1427	8.025-8.5
4.125 - 4.128	37.5-38.25	1435-1626.6	9.0-9.2
4.17725 - 4.17775	73-74.6	1645.5-1646.5	9.3-9.5
4.20725 - 4.20775	74.8-75.2	1660-1710	10.6-12.7
6.215 - 6.218	108-121.94	1718.8-1722.2	13.25-13.4
6.31175 - 6.31225	123-138	2220-2300	14.47-14.5
8.291 - 8.294	149.9-150.05	2310-2390	15.35-16.2
8.362 - 8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625 - 8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425 - 8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29 - 12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975 - 12.52025	240-285	3345.8-3358	36.43-36.5
12.57675 - 12.57725	322-335.4	3600-4400	Above 38.6
13.36 - 13.41			