

BASE RF MODULE

- 1. VTX = 4.5VDC
 - 2. VRX = 5.0VDC
 - 3. VCC = 5.0VDC
- P1: VTX
 P2: GND
 P3: TX-AF
 P4: VCC
 P5: REFCLK
 P6: PCLK
 P7: PDATA
 P8: PSTB
 P9: V-RSSI
 P10: NA-RSSI
 P11: TX-AF
 P12: GND


NOTES:

1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K=KILO OHM, M=MEG OHM)
2. RESISTOR WATTAGES ARE (1/16W) UNLESS OTHERWISE NOTED.
3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (U=MICRO FARAD, P=PICO-FARAD)
4. INDUCTANCE VALUES ARE INDICATED IN NANOHENRYS UNLESS OTHERWISE NOTED.
5. CHIP PARTS ARE NOT SPECIFIED IN THIS SCHEMATIC DIAGRAM. PLEASE REFER TO THE PART LIST FOR THE CHIP PART.

DATE: 7/20/00
 DRAWN BY: J. L. BROWN
 CHECKED BY: J. L. BROWN
 APPROVED BY: J. L. BROWN
 TITLE: INCORPORATION

WORKING ANALOG BASE OF MODULE
 PART NUMBER: 42-1110
 REV: C
 DATE: 7/20/00
 DRAWN BY: J. L. BROWN

APPROVED: _____
 CHECKED: _____
 PREPARED: _____



Daley and Business Electronics Co. Inc.
 1000 S. Main Street, Suite 100
 San Jose, CA 95128
 TEL: (415) 281-1111
 FAX: (415) 281-1112
 WWW: www.daley.com
 © 1998 Daley and Business Electronics Co. Inc.
 All rights reserved.

APPROVED: _____
 CHECKED: _____
 PREPARED: _____

