


PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.

TEL (410) 290-6652 · FAX (410) 290-6654

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 90 Certification

Motorola Inc.
1301 East Algonquin, Room 1726
Schaumburg, IL 60196

Dates of Tests: March 6-10, 2006
Test Report S/N: 0603010131-R1
Test Site: PCTEST Lab, MD U.S.A.

FCC ID:	ABZ89FT7616
APPLICANT:	MOTOROLA INC.

FCC Classification:	Licensed Non-Broadcast Station Transmitter (TNB)
FCC Rule Part(s):	§ 90
EUT Type:	Motorola Broadband Wireless Router for ML900 Series Notebook
Model(s):	ML900
Tx/Rx Frequency Range:	4950 - 4965 MHz
Max. RF Output Power:	0.397 W ERP (24.983 dBm) with 12.1 LCD/ 0.388 W ERP (25.883 dBm) with 13.3 LCD/ 0.404 W Conducted
Frequency Tolerance:	2.5 ppm
Emission Designator:	17M2F1D

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947 and RSS-119. If the EUT contains any additional embedded transmitters, then those transmitter were active during all tests.

The Motorola MESH Modem Module is electrically identical to previously authorized FCC ID: QJEW MC73000705. RF conducted data is shown in that test report, included in this application.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortaez
President




PCTEST REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131-R1	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 1 of 25

TABLE OF CONTENTS

ATTACHMENT A:	COVER LETTER(S)	
ATTACHMENT B:	ATTESTATION STATEMENT(S)	
ATTACHMENT C:	TEST REPORT	
	SCOPE	3
	INTRODUCTION	4
	INSERTS	5
	DESCRIPTION OF TESTS	6-7
	RADIATED MEASUREMENTS	8-11
	RADIATED SPURIOUS MEASUREMENTS	12-18
	FREQUENCY STABILITY	19-20
	PLOTS OF EMISSIONS	21
	LIST OF TEST EQUIPMENT	22
	SAMPLE CALCULATIONS	23
	CONCLUSION	24
ATTACHMENT D:	TEST PLOTS	
ATTACHMENT E:	FCC ID LABEL & LOCATION	
ATTACHMENT F:	TEST SETUP PHOTOGRAPHS	
ATTACHMENT G:	EXTERNAL PHOTOGRAPHS	
ATTACHMENT H:	INTERNAL PHOTOGRAPHS	
ATTACHMENT I:	BLOCK DIAGRAM(S)	
ATTACHMENT J:	SCHEMATIC DIAGRAM(S)	
ATTACHMENT K:	PARTS LIST & TUNE UP PROCEDURE	
ATTACHMENT L:	OPERATIONAL DESCRIPTION	
ATTACHMENT M:	USER'S MANUAL	
ATTACHMENT N:	MPE REPORT	

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola A/B/G Wireless LAN Module for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 2 of 30

MEASUREMENT REPORT



1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

General Information

Applicant Name:	Motorola Inc.
Address:	1301 East Algonquin, Room 1726 Schaumburg, IL 60196

- FCC ID:** ABZ89FT7616
- Model(s):** ML900
- Quantity:** Quantity production is planned
- Emission Designator:** 17M2F1D
- Tx/Rx Freq. Range:** 4950 - 4965 MHz
- Equipment Class:** Licensed Non-Broadcast Station Transmitter (TNB)
- Equipment Type:** Motorola Broadband Wireless Router for ML900 Series Notebook
- Modulation:** QDMA
- Frequency Tolerance:** ± 2.5 ppm
- Max. Power:** 0.397 W ERP (25.983 dBm) with 12.1 LCD/
0.388 W ERP (25.883 dBm) with 13.3 LCD/
0.404 W Conducted
- FCC Rule Part(s):** § 90
- Power Supply:** 3.8V (3.4 to 4.2V range)
- Dates of Tests:** March 6-10, 2006
- Place of Tests:** PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N:** 0603010131-R1

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 3 of 24

2.1 INTRODUCTION




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under testing was placed on a wooden turntable, 3meters from the receive antenna. The receive antenna height and turntable rotations was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level was recorded.

For readings above 1 GHZ, the above procedure would be repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 2. 3-meter outdoor test site

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 4 of 24

3.1 INSERTS

Block Diagram(s) & Circuit Diagram(s)

The block diagram is shown in Attachment I, and the circuit diagram is shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment K.

PCTEST® REPORT PART 90 & RSS-119	FCC Measurement Report			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 5 of 24

4.1 DESCRIPTION OF TESTS

4.2 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions above 1 GHz is measured at our 3-meter indoor site. The EUT is placed on the turntable connected to a dummy load in normal operation using the intended power source. A receiving antenna located 3 meters from the turntable receives any signal radiated from the transmitter and its operating accessories. The antenna is varied from 1 to 4 meters and the polarization is varied (horizontal and vertical) to determine the worst-case emission level. To obtain actual radiated signal strength, a signal generator is adjusted in output until a reading identical to that obtained with the actual transmitter is obtained at the receiver. Signal strength is read directly from the generator and recorded on the attached table.

4.3 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.4 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		 Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 6 of 24

5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at -30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 7 of 24

5.1 Test Data w/ 12.1 LCD

5.2 Output Power

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
4950.00	-23.000	H	0.397	25.983	Standard
4955.00	-23.300	H	0.374	25.733	Standard
4960.00	-24.000	H	0.325	25.123	Standard
4965.00	-23.900	H	0.337	25.273	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 8 of 24

5.1 Test Data w/ 13.3 LCD

5.3 Output Power

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
4950.00	-23.100	H	0.388	25.883	Standard
4955.00	-23.200	H	0.383	25.833	Standard
4960.00	-23.500	H	0.365	25.623	Standard
4965.00	-23.700	H	0.353	25.473	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		 Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 9 of 24

6.1 Test Data - w/ 12.1 LCD (Continued)

6.2 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4950.00 MHz
 CHANNEL: (Low)
 MEASURED OUTPUT POWER: 25.983 dBm = 0.397 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.98 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9900.00	-75.63	6.10	-69.53	H	95.5
14850.00	-93.28	6.70	-86.58	H	112.6

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 10 of 24	

6.1 Test Data - w/ 12.1 LCD (Continued)

6.3 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4955.00 MHz
 CHANNEL: (Mid)
 MEASURED OUTPUT POWER: 25.983 dBm = 0.397 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.98 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9910.00	-75.98	6.10	-69.88	H	95.9
14865.00	-93.08	6.70	-86.38	H	112.4

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 				Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 11 of 24	

6.1 Test Data - w/ 12.1 LCD (Continued)

6.4 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4960.00 MHz
 CHANNEL: (Mid)
 MEASURED OUTPUT POWER: 25.983 dBm = 0.397 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.98 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9920.00	-78.38	6.10	-72.28	H	98.3
14880.00	-92.78	6.70	-86.08	H	112.1

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 12 of 24

6.1 Test Data - w/ 12.1 LCD (Continued)

6.5 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4965.00 MHz
 CHANNEL: (High)
 MEASURED OUTPUT POWER: 25.983 dBm = 0.397 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.98 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9930.00	-79.48	6.10	-73.38	H	99.4
14895.00	-92.78	6.70	-86.08	H	112.1

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 13 of 24

6.1 Test Data - w/ 13.3 LCD (Continued)

6.6 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4950.00 MHz
 CHANNEL: (Low)
 MEASURED OUTPUT POWER: 25.883 dBm = 0.388 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.88 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9900.00	-75.63	6.10	-69.53	H	95.4
14850.00	-93.28	6.70	-86.58	H	112.5

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 14 of 24

6.1 Test Data - w/ 13.3 LCD (Continued)

6.7 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4955.00 MHz
 CHANNEL: (Mid)
 MEASURED OUTPUT POWER: 25.883 dBm = 0.388 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.88 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9910.00	-75.98	6.10	-69.88	H	95.8
14865.00	-93.08	6.70	-86.38	H	112.3

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 15 of 24

6.1 Test Data - w/ 13.3 LCD (Continued)

6.8 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4960.00 MHz
 CHANNEL: (Mid)
 MEASURED OUTPUT POWER: 25.883 dBm = 0.388 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.88 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9920.00	-78.38	6.10	-72.28	H	98.2
14880.00	-92.78	6.70	-86.08	H	112.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 16 of 24

6.1 Test Data - w/ 13.3 LCD (Continued)

6.9 Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 4965.00 MHz
 CHANNEL: (High)
 MEASURED OUTPUT POWER: 25.883 dBm = 0.388 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 38.88 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
9930.00	-79.48	6.10	-73.38	H	99.3
14895.00	-92.78	6.70	-86.08	H	112.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method _____
 according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001: _____

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.


PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 				Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 17 of 24	

6.1 TEST DATA

Radiated Spurious Measurements

Freq. (MHz)	Level (dBm)	AFCL (dB)	POL (H/V)	Height (m)	Azimuth (°angle)	F/S (uV/m)	Margin (dB)
166.64	-84.89	14.70	H	2.7	180	69.23	-6.7
300.00	-89.39	20.60	V	1.4	225	81.33	-7.8
400.5	-92.31	23.71	H	1.3	200	83.23	-7.6
433.3	-92.89	24.50	V	1.2	135	85.16	-7.4
466.7	-94.50	25.30	V	1.1	180	77.67	-8.2
702.5	-97.83	29.94	H	1.0	190	90.21	-6.9

Table A-1. Radiated Measurements at 3-meters



NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The radiated limits are shown on Figure A-1. Above 1 GHz the limit is 500µV/m.

Figure A-1. Limits at 3 meters

- ¹ All readings are calibrated by HP8640B signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
- ² AFCL = Antenna Factor (Roberts dipole) and Cable Loss (30 ft. RG58C/U).
- ³ Measurements using CISPR quasi-peak mode. Above 1GHz, peak detector function mode is used with a resolution bandwidth of 1MHz and a video bandwidth of 1MHz. The peak level complies with the average limit. Peak mode is used with linearly polarized horn antenna and low-loss microwave cable.

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report 			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 18 of 24

6.1 Test Data

6.2 Part 90 FREQUENCY STABILITY

OPERATING FREQUENCY: 4,955 Hz

CHANNEL: (Mid)

REFERENCE VOLTAGE: 3.7 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	4955.0000	0.0000	0.000000
100 %		- 30	4954.9989	0.0011	0.000023
100 %		- 20	4954.9990	0.0010	0.000021
100 %		- 10	4954.9995	0.0005	0.000010
100 %		0	4954.9996	0.0004	0.000008
100 %		+ 10	4954.9996	0.0004	0.000009
100 %		+ 20	4955.0000	0.0000	0.000000
100 %		+ 25	4954.9996	0.0004	0.000008
100 %		+ 30	4954.9996	0.0004	0.000008
100 %		+ 40	4955.0010	-0.0010	-0.000020
100 %		+ 50	4955.0005	-0.0005	-0.000011
100 %		+ 60	4955.0010	-0.0010	-0.000020
85 %	4.25	+ 20	4954.9999	0.0001	0.000002
115 %	5.75	+ 20	4955.0000	0.0000	0.000001
BATT. ENDPOINT	3.50	+ 20	4955.0000	0.0000	0.000000

PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report				Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 19 of 24	

6.1 Test Data (Continued)

6.3 Part 90 FREQUENCY STABILITY



PCTEST® REPORT PART 90 & RSS-119	 FCC Measurement Report			Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 20 of 24

7.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT D)

PCTEST REPORT PART 90 & RSS-119		FCC Measurement Report		 Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 21 of 24

8.1 TEST EQUIPMENT

8.2 Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	08/15/06	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/06	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/06	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/06	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/06	0792-03271
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/06	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/06	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/06	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/06	0194-04082
RG58 Coax Test Cable	No. 167		n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Transient Limiter	HP 11947A (9kHz-200MHz)	2820A00300	
Horn Antenna	EMCO Model 3115 (1-18GHz)	9704-5182	
Horn Antenna	EMCO Model 3115 (1-18GHz)	9205-3874	
Horn Antenna	EMCO Model 3116 (18-40GHz)	9203-2178	
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design	1295, 1332, 0355	
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1	0608, 1103, 1104	
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN	3816/2		1079
EMCO LISN	3816/2		1077
EMCO LISN	3725/2		2009
Microwave Preamplifier 40dB Gain	HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM 37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Modulation Analyzer	HP 8901A		2432A03467
NTSC Pattern Generator	Leader 408		0377433
Noise Figure Meter	HP 8970B		3106A02189
Noise Figure Meter	Ailtech 7510		TE31700
Noise Generator	Ailtech 7010		1473
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305	426966	
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0	6710 (PCT270)	
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 22 of 24

9.1 SAMPLE CALCULATIONS

Occupied Bandwidth

The audio signal generator is adjusted to 1kHz. The output level is increased until deviation limiting takes place. With the level constant, the freq. is set to 2,500Hz. Then the audio signal level is increased by 16dB.

The limits are specified in Section 2.1049.

Bandwidth Calculations (2M + 2D):

$$2(3.0) + 2 (5.0)$$

$$6 + 10.0 = 16.0 \text{ kHz}$$

Emission Designator = 16K0F1D

M = maximum modulation frequency

D = maximum deviation from modulating limiting plot

Bandwidth Calculations (2M + 2D):

$$2(3.0) + 2 (2.5)$$

$$6 + 5.0 = 11.0 \text{ kHz}$$

Emission Designator = 11K0F1D

M = maximum modulation frequency

D = maximum deviation from modulating limiting plot

PCTEST® REPORT PART 90 & RSS-119		FCC Measurement Report		 Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 23 of 24

10.1 CONCLUSION

The data collected shows that the **Motorola Broadband Wireless Router for ML900 Series Notebook** complies with all the requirements of Part 90 of the FCC rules and RSS-119 of the Industry Canada rules.

PCTEST REPORT PART 90 & RSS-119		FCC Measurement Report		 Reviewed By: Quality Manager
Test Report S/N: 0603010131	Test Dates: March 6-10, 2005	EUT Type: Motorola Broadband Wireless Router for ML900 Series Notebook	FCC ID: ABZ89FT7616	Page 24 of 24