




Measurement of RF Emissions from a Model PMLN5792A Wireless Dongle Transceiver

For	Motorola, Inc. 1301 E. Algonquin Road Schaumburg, IL 60196
P.O. Number	NP5308463
Date Tested	March 7 through 17, 2011
Test Personnel	Richard King
Test Specification	FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Sections 15.247 for Frequency Hopping Spread Spectrum Intentional Radiators Operating within the band 2400-2483.5MHz Industry Canada RSS-GEN Industry Canada RSS-210
Test Report By:	 Richard King EMC Engineer
Requested By:	Larry Larsen Motorola, Inc.
Approved By:	 Raymond J. Klouda Registered Professional Engineer of Illinois - 44894

**TABLE OF CONTENTS**

PARAGRAPH	DESCRIPTION OF CONTENTS	PAGE NO.
1	Introduction.....	5
1.1	Scope of Tests.....	5
1.2	Purpose	5
1.3	Deviations, Additions and Exclusions.....	5
1.4	EMC Laboratory Identification	5
1.5	Laboratory Conditions.....	5
2	Applicable Documents.....	5
3	EUT Setup and Operation	6
3.1	General Description	6
3.1.1	Power Input	6
3.1.2	Peripheral Equipment.....	6
3.1.3	Signal Input/Output Leads.....	6
3.1.4	Grounding.....	6
3.2	Operational Mode	6
3.3	EUT Modifications.....	6
4	Test Facility and Test Instrumentation	6
4.1	Shielded Enclosure.....	6
4.2	Test Instrumentation.....	6
4.3	Calibration Traceability	7
4.4	Measurement Uncertainty	7
5	Test Procedures	7
5.1	Receiver.....	7
5.1.1	Radiated Measurements	7
5.1.1.1	Requirements	7
5.1.1.2	Procedures	8
5.1.1.3	Results.....	8
5.2	Transmitter.....	9
5.2.1	20dB Bandwidth	9
5.2.1.1	Requirement	9
5.2.1.2	Procedures	9
5.2.1.3	Results.....	9
5.2.2	Carrier Frequency Separation	9
5.2.2.1	Requirements	9
5.2.2.2	Procedures	9
5.2.2.3	Results.....	9
5.2.3	Number of Hopping Frequencies	10
5.2.3.1	Requirements	10
5.2.3.2	Procedures	10
5.2.3.3	Results.....	10
5.2.4	Time of Occupancy	10
5.2.4.1	Requirements	10
5.2.4.2	Procedures	10
5.2.4.3	Results.....	10

THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF ELITE ELECTRONIC ENGINEERING INCORPORATED.



TABLE OF CONTENTS

PARAGRAPH	DESCRIPTION OF CONTENTS	PAGE NO.
5.2.5	Peak Output Power	11
5.2.5.1	Requirements	11
5.2.5.2	Procedures	11
5.2.5.3	Results	11
5.2.6	Duty Cycle Factor Measurements	11
5.2.6.1	Procedures	11
5.2.6.2	Results	11
5.2.7	Radiated Spurious Emissions Measurements	12
5.2.7.1	Requirements	12
5.2.7.2	Procedures	12
5.2.7.3	Results	13
5.2.8	Band Edge Compliance	13
5.2.8.1	Requirement	13
5.2.8.2	Procedures	14
5.2.8.3	Results	14
5.2.9	Power Spectral Density	15
5.2.9.1	Requirements	15
5.2.9.2	Procedures	15
5.2.9.3	Results	15
6	Other Test Conditions	15
6.1	Test Personnel and Witnesses	15
6.2	Disposition of the EUT	15
7	Conclusions	15
8	Certification	16
9	Equipment List	17

THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE
WRITTEN APPROVAL OF ELITE ELECTRONIC ENGINEERING INCORPORATED.



REVISION HISTORY

Revision	Date	Description
—	3/21/2011	Initial release

Measurement of RF Emissions from a Wireless Dongle, Model No. PMLN5792A Transceiver

1 INTRODUCTION

1.1 Scope of Tests

This report represents the results of the series of radio interference measurements performed on a Motorola, Inc. Wireless Dongle, Model No. PMLN5792A, Serial No. 24, transceiver (hereinafter referred to as the EUT). The EUT is a Bluetooth hybrid frequency hopping spread spectrum transceiver. The transmitter was designed to transmit and receive in the 2400-2483.5 MHz band using an internal antenna. The EUT was manufactured and submitted for testing by Motorola, Inc. located in Schaumburg, IL.

1.2 Purpose

The test series was performed to determine if the EUT meets the radiated RF emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.247 for Intentional Radiators Operating within the 2400-2483.5 MHz band.

The test series was also performed to determine if the EUT meets the radiated RF emission requirements of the Industry Canada Radio Standards Specification, RSS-Gen and the Industry Canada Radio Standards Specification RSS-210 for transmitters.

Testing was performed in accordance with ANSI C63.4-2003.

1.3 Deviations, Additions and Exclusions

There were no deviations, additions to, or exclusions from the test specification during this test series.

1.4 EMC Laboratory Identification

This series of tests was performed by Elite Electronic Engineering Incorporated of Downers Grove, Illinois. The laboratory is accredited by The American Association for Laboratory Accreditation (A2LA). A2LA Certificate Number: 1786.01.

1.5 Laboratory Conditions

The temperature at the time of the test was 21.5°C and the relative humidity was 33%.

2 APPLICABLE DOCUMENTS

The following documents of the exact issue designated form part of this document to the extent specified herein:

- Federal Communications Commission "Code of Federal Regulations", Title 47, Part 15, Subparts B and C, dated 1 October 2010
- ANSI C63.4-2003, "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"
- FCC Public Notice, DA 00-705, "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems", Released March 30, 2000
- Industry Canada Radio Standards Specification, RSS-Gen, "General Requirements and Information for the Certification of Radiocommunication Equipment", Issue 3, December 2010
- Industry Canada Radio Standards Specification, RSS-210, "Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment", Issue 8, June 2010



3 EUT SETUP AND OPERATION

3.1 General Description

The EUT is a Motorola, Inc., Wireless Dongle, Model No. PMLN5792A. The EUT was submitted for testing with a Motorola XTS 2500 portable radio model number H46QDC9PW5BN serial number 407CHH0879.

A block diagram of the EUT setup is shown as Figure 1.

3.1.1 Power Input

The EUT obtained 5VDC from the Motorola XTS 2500 portable radio.

3.1.2 Peripheral Equipment

The following peripheral equipment was submitted with the EUT:

Item	Description
Motorola XTS 2500 M/N: H46QDC9PW5BN S/N: 407CHH0879	Portable radio

3.1.3 Signal Input/Output Leads

No interconnect cables were submitted with the EUT for testing.

3.1.4 Grounding

The EUT was ungrounded during the tests.

3.2 Operational Mode

For all tests, the EUT was placed on an 80cm high non-conductive stand. The EUT was energized. The unit was programmed to operate in one of the following modes:

- Transmit at 2402 MHz
- Transmit at 2441 MHz
- Transmit at 2480 MHz
- Receive at 2441 MHz
- Frequency Hopping Enabled
- Inquiry Mode

3.3 EUT Modifications

No modifications were required for compliance.

4 TEST FACILITY AND TEST INSTRUMENTATION

4.1 Shielded Enclosure

All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. With the exception of the floor, the reflective surfaces of the shielded chamber are lined with ferrite tiles on the walls and ceiling. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4-2003 for site attenuation.

4.2 Test Instrumentation

The test instrumentation and auxiliary equipment used during the tests are listed in Table 9-1.

4.3 Calibration Traceability

Test equipment is maintained and calibrated on a regular basis. All calibrations are traceable to the National Institute of Standards and Technology (NIST).

4.4 Measurement Uncertainty

All measurements are an estimate of their true value. The measurement uncertainty characterizes, with a specified confidence level, the spread of values which may be possible for a given measurement system.

The measurement uncertainty for these tests is presented below:

Conducted Emissions Measurements		
Combined Standard Uncertainty	1.07	-1.07
Expanded Uncertainty (95% confidence)	2.1	-2.1
Radiated Emissions Measurements		
Combined Standard Uncertainty	2.26	-2.18
Expanded Uncertainty (95% confidence)	4.5	-4.4

5 TEST PROCEDURES

5.1 Receiver

5.1.1 Radiated Measurements

5.1.1.1 Requirements

Per the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart B, Section 15.101(b), receivers operating above 960MHz are exempt from complying with the technical provisions of part 15.

Per Industry Canada RSS-Gen all radio frequency emissions from a receiver shall be below the limits shown on the following table:

RADIATION LIMITS FOR A RECEIVER

Frequency MHz	Distance between EUT And Antenna in Meters	Field Strength uV/m	Field Strength dBuV/m
30-88	3	100	40
88-216	3	150	43.5
216-960	3	200	46
Above 960	3	500	54

Note: The tighter limit shall apply at the edge between the two frequency bands.

5.1.1.2 Procedures

Per the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart B, Section 15.101(b), receivers operating above 960MHz are exempt from complying with the technical provisions of part 15.

For Industry Canada, testing was performed on a middle channel. The emissions in the frequency range of 30MHz to 3 times the highest tunable or local oscillator frequency, whichever is the higher, were measured and plotted.

All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. The walls and ceiling of the shielded chamber are lined with ferrite tiles. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4-2003 for site attenuation.

The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Since a quasi-peak detector and an average detector require long integration times, it is not practical to automatically sweep through the quasi-peak and average levels. Therefore, radiated emissions from the EUT were first scanned using a peak detector and automatically plotted. The frequencies where significant emission levels were noted were then remeasured using the quasi-peak detector or average detector.

Preliminary radiated emissions tests were performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3 meter distance from the EUT. The entire frequency range from 30MHz to 7.5GHz was investigated using a peak detector function.

Final radiated emissions were performed on all significant broadband and narrowband emissions found in the preliminary sweeps using the following methods:

- 1) Measurements from 30MHz to 1GHz were made using a quasi-peak detector and a broadband bilog antenna. Measurements above 1GHz were made using an average detector and a broadband double ridged waveguide antenna.
- 2) To ensure that maximum or worst case, emission levels were measured, the following steps were taken:
 - a) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - b) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - c) The measuring antenna was raised and lowered from 1 to 4 meters for each antenna polarization to maximize the readings.
 - d) For hand-held or body-worn devices, the EUT was rotated through three orthogonal axes to determine which orientation produces the highest emission relative to the limit.

5.1.1.3 Results

The preliminary plots are presented on pages 21 through 24. The plots are presented for a reference only, and are not used to determine compliance. The final radiated levels are presented on page 25. As can be seen from the data, all emissions measured from the EUT were within the specification limits. Photographs of the

test configuration for radiated emission levels are shown in Figure 2.

5.2 Transmitter

5.2.1 20dB Bandwidth

5.2.1.1 Requirement

Per section 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate within an output power no greater than 125mW.

5.2.1.2 Procedures

The EUT was setup inside the chamber. With the hopping function disabled, the EUT was allowed to transmit continuously. The frequency hopping channel was set separately to low, middle, and high hopping channels. The resolution bandwidth (RBW) was set to > to 1% of the 20 dB BW. The span was set to approximately 2 to 3 times the 20 dB bandwidth.

The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined. The analyzer's display was plotted using a 'screen dump' utility.

5.2.1.3 Results

The plots on pages 26 through 28 show that the maximum 20 dB bandwidth was 885kHz. The 99% bandwidth was measured to be 838kHz.

5.2.2 Carrier Frequency Separation

5.2.2.1 Requirements

Per section 15.247 (a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Per section 15.247(a)(1), alternatively, frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate within an output power no greater than 125mW.

5.2.2.2 Procedures

The EUT was setup inside the chamber. With the hopping function enabled, the EUT was allowed to transmit continuously.

The resolution bandwidth (RBW) was set to > to 1% of the span. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the peaks of at least two adjacent channels. When the trace had stabilized after multiple scans, the marker-delta function was used to determine the separation between the peaks of the adjacent channels. The analyzer's display was plotted using a 'screen dump' utility

5.2.2.3 Results

Page 29 shows the carrier frequency separation. As can be seen from this plot, the carrier frequency separation is 1MHz which is greater than the 20dB bandwidth of the hopping channel (885kHz).

5.2.3 Number of Hopping Frequencies

5.2.3.1 Requirements

Per section 15.247(a)(1)(iii), frequency hopping systems operating in the 2400-2483.5MHz band that employ at least 15 hopping channels must have a maximum peak conducted output power that does not exceed 0.125W (21dBm).

Per 15.247(b)(1), frequency hopping systems operating in the 2400- 2483.5MHz band that employ at least 75 non-overlapping hopping channels must have a maximum peak conducted output power that does not exceed 1W (30dBm).

5.2.3.2 Procedures

The EUT was setup inside the chamber. With the hopping function enabled, the EUT was allowed to transmit continuously.

The resolution bandwidth (RBW) was set to > to 1% of the span. The peak detector and 'Max-Hold' function were engaged. The span was set wide enough to capture the entire frequency band of operation.

The EUT's signal was allowed to stabilize after multiple scans. The number of hopping frequencies was counted. The analyzer's display was plotted using a 'screen dump' utility.

5.2.3.3 Results

Page 30 shows the number of hopping frequencies. As can be seen from this plot, the number of hopping frequencies is 79 which is greater than 75 which is the minimum number of required hopping frequencies for systems operating in the 2400-2483.5MHz band that have a maximum peak conducted output power that does not exceed 1W (30dBm).

5.2.4 Time of Occupancy

5.2.4.1 Requirements

Per section 15.247(a)(1)(iii), for frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

5.2.4.2 Procedures

The EUT was setup inside the chamber. With the hopping function enabled, the EUT was allowed to transmit continuously.

The resolution bandwidth (RBW) was set to 1 MHz. The peak detector and 'Max-Hold' function were engaged. With the span set to 0Hz, the sweep time was adjusted to capture a single event in order to measure the dwell time per hop. The analyzer's display was plotted using a 'screen dump' utility. Then, the sweep time was expanded to 0.4 seconds multiplied by the number of hopping channels employed to capture the number of hops in the appropriate sweep time. A single sweep was made. The analyzer's display was plotted using a 'screen dump' utility. The dwell time in the specified time period was then calculated from dwell time per hop multiplied by the number of hops in the specified time period.

5.2.4.3 Results

Pages 33 and 34 show the plots for the time of occupancy (dwell time). As can be seen from the plots, the time of occupancy can be determined by 397usec/hop multiplied by 324 hops. This calculated value is equal to 0.1286 seconds which is less than the 0.4 seconds maximum allowed.

5.2.5 Peak Output Power

5.2.5.1 Requirements

Per section 15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5MHz band and employing at least 75 non-overlapping hopping channels, the maximum peak output conducted power shall not be greater than 1W (30dBm). Per section 15.247(b)(4), this limit is based on the use of antennas with directional gains that do not exceed 6dBi. Since the limit allows for a 6dBi antenna gain, the maximum EIRP can be increased by 6dB to 4 Watt (36dBm).

If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below 30dBm by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2.5.2 Procedures

The EUT was placed on the non-conductive stand and set to transmit. A double ridged waveguide antenna was placed at a test distance of 3 meters from the EUT. The resolution bandwidth (RBW) of the spectrum analyzer was set to greater than the 20dB bandwidth. The span was set to approximately 5 times the 20 dB bandwidth. The EUT was maximized for worst case emissions (or maximum output power) at the measuring antenna. The maximum meter reading was recorded. The peak power output was measured for the low, middle and high hopping frequencies.

The equivalent power was determined from the field intensity levels measured at 3 meters using the substitution method. To determine the emission power, a double ridged waveguide antenna was then set in place of the EUT and connected to a calibrated signal generator. The output of the signal generator was adjusted to match the received level at the spectrum analyzer. The signal level was recorded. The reading was then corrected to compensate for cable loss and antenna gain, as required. The peak power output was calculated for low, middle, and high hopping frequencies.

5.2.5.3 Results

The results are presented on page 35. The maximum EIRP measured from the transmitter was 7.6dBm or 0.006W which is below the 4 Watt limit.

5.2.6 Duty Cycle Factor Measurements

5.2.6.1 Procedures

The duty cycle factor is used to convert peak detected readings to average readings. This factor is computed from the time domain trace of the pulse modulation signal.

With the transmitter set up to transmit for maximum pulse density, the time domain trace is displayed on the spectrum analyzer. This trace is obtained by tuning center frequency to the transmitter frequency and then setting a zero span width with 1msec/div (adjust this for what you need). The amplitude settings are adjusted so that the on/off transitions clear the 4th division from the bottom of the display. The markers are set at the beginning and end of the "on-time". The trace is recorded.

Next the spectrum analyzer center frequency is set to the transmitter frequency with a zero span width and 10msec/div. This shows if the word is longer than 100msec or shorter than 100msec. If the word period is less than 100msec, the display is set to show at least one word. The on-time and off-time are then measured. The on-time is total time signal level exceeds the 4th division. Off-time is time under for the word period. The duty cycle is then computed as the (On-time/ word period) where the word period = (On-time + Off-time).

5.2.6.2 Results

The plots of the duty cycle are shown on data pages 31 and 32. Duty Cycle Correction Factor = $20 \times \log((\text{pulse width}) \times (\text{number of times the channel is used in a 100msec period}) / 100) = 20 \times (\log(397\text{usec}) \times (2) / 100\text{msec}) = -42.0\text{dB}$

5.2.7 Radiated Spurious Emissions Measurements

5.2.7.1 Requirements

Per section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated emissions measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Paragraph 15.209(a) has the following radiated emission limits:

Frequency MHz	Field Strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30.0-88.0	100	3
88.0-216.0	150	3
216.0-960.0	200	3
Above 960	500	3

5.2.7.2 Procedures

All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. The walls and ceiling of the shielded chamber are lined with ferrite tiles. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4-2003 for site attenuation.

The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

Preliminary radiated emissions tests were performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3 meter distance from the EUT. The entire frequency range from 30MHz to 25GHz was investigated using a peak detector function.

The final open field emission tests were then manually performed over the frequency range of 30MHz to 25GHz.

For all harmonics not in the restricted bands, the following procedure was used:

- The field strength of the fundamental was measured using a double ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- The field strengths of all of the harmonics not in the restricted band were then measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
- To ensure that maximum or worst case emission levels at the fundamental and harmonics were measured, the following steps were taken when measuring the fundamental emissions and the spurious emissions:
 - The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.

- iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
 - d) All harmonics not in the restricted bands must be at least 20 dB below levels measured at the fundamental. However, attenuation below the general limits specified in §15.209(a) is not required.
- 2) For all emissions in the restricted bands, the following procedure was used:
- a) The field strengths of all emissions below 1 GHz were measured using a bi-log antenna. The bi-log antenna was positioned at a 3 meter distance from the EUT. A peak detector with a resolution bandwidth of 100 kHz was used on the spectrum analyzer.
 - b) The field strengths of all emissions above 1 GHz were measured using a double-ridged waveguide antenna. The waveguide antenna was positioned at a 3 meter distance from the EUT. A peak detector with a resolution bandwidth of 1 MHz was used on the spectrum analyzer.
 - c) To ensure that maximum or worst case emission levels were measured, the following steps were taken when taking all measurements:
 - i) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - ii) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - iii) The measuring antenna was raised and lowered for each antenna polarization to maximize the readings.
 - iv) In instances where it was necessary to use a shortened cable between the measuring antenna and the spectrum analyzer, the measuring antenna was not raised or lowered to ensure maximized readings. Instead the EUT was rotated through all axis to ensure the maximum readings were recorded for the EUT.
 - d) For all radiated emissions measurements below 1 GHz, if the peak reading is below the limits listed in 15.209(a), no further measurements are required. If however, the peak readings exceed the limits listed in 15.209(a), then the emissions are remeasured using a quasi-peak detector.
 - e) For all radiated emissions measurements above 1 GHz, the peak readings must comply with the 15.35(b) limits. 15.35(b) states that when average radiated emissions measurements are specified, there also is a limit on the peak level of the radiated emissions. The limit on the peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, all peak readings above 1 GHz must be no greater than 20 dB above the limits specified in 15.209(a).
 - f) Next, for all radiated emissions measurements above 1GHz, the resolution bandwidth was set to 1MHz. The analyzer was set to linear mode with a 10Hz video bandwidth in order to simulate an average detector. An average reading was taken. If the dwell time per channel of the hopping signal is less than 100msec, then the reading obtained with the 10 Hz video bandwidth may be further adjusted by a “duty cycle correction factor”, derived from $20 \cdot \log(\text{dwell time}/100\text{msec})$. These readings must be no greater than the limits specified in 15.209(a).

5.2.7.3 Results

Preliminary radiated emissions plots with the EUT transmitting at 2402MHz, 2441MHz, 2480MHz are shown on pages 36 through 59. Final radiated emissions data are presented on data pages 60 through 68. As can be seen from the data, all emissions measured from the EUT were within the specification limits. Photographs of the test configuration which yielded the highest, or worst case, radiated emission levels are shown on Figure 2.

5.2.8 Band Edge Compliance

5.2.8.1 Requirement

Per section 15.247(d), the emissions at the band-edges must be at least 20dB below the highest level measured within the band but attenuation below the general limits listed in 15.209(a) is not required.

In addition, the radiated emissions which fall in the restricted band beginning at 2483.5 MHz must meet the general limits of 15.209(a).

5.2.8.2 Procedures

5.2.8.2.1 Low Band Edge

- 1) The EUT was setup on a non-conductive stand.
- 2) The EUT was set to transmit continuously at the channel closest to the low band-edge (hopping function disabled).
- 3) To determine the bandedge compliance, the following spectrum analyzer settings were used:
 - a. Center frequency = low band-edge frequency.
 - b. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation.
 - c. Resolution bandwidth (RBW) $\geq$ 1% of the span.
 - d. The 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined.
 - e. The marker was set on the peak of the in-band emissions. A display line was placed 20dB down from the peak of the in-band emissions. All emissions which fall outside of the authorized band of operation must be below the 20dB down display line. (All emissions to the left of the center frequency (band-edge) must be below the display line.)
 - f. The analyzer's display was plotted using a 'screen dump' utility.
- 4) Step 5) was repeated with the frequency hopping function enabled.

5.2.8.2.2 High Band Edge

- 1) The EUT was set to transmit continuously at the channel closest to the high band-edge (hopping function disabled).
- 2) A double ridged waveguide was placed 3 meters away from the EUT. The antenna was connected to the input of a spectrum analyzer.
- 3) The center frequency of the analyzer was set to the high band edge (2483.5MHz)
- 4) The resolution bandwidth was set to 1MHz.
- 5) To ensure that the maximum or worst case emission level was measured, the following steps were taken:
 - a. The EUT was rotated so that all of its sides were exposed to the receiving antenna.
 - b. Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
 - c. The measuring antenna was raised and lowered from 1 to 4 meters for each antenna polarization to maximize the readings.
- 6) The highest measured peak reading was recorded.
- 7) The highest measured average reading was recorded.
- 8) Steps (2) through (7) were repeated with the hopping function enabled.

5.2.8.3 Results

Pages 69 through 70 show the radiated band-edge results at the low frequency band-edge. Pages 71 through 74 show the radiated band-edge results at the high frequency band-edge. As can be seen from these plots, the radiated emissions at the low frequency band edge are within the 20 dB down limits. The radiated emissions at the high frequency band edge are within the general limits.

5.2.9 Power Spectral Density

5.2.9.1 Requirements

Per section 15.247(d), the peak power spectral density from the intentional radiator shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2.9.2 Procedures

- 1) The EUT was placed on the non-conductive stand and set to transmit at a mid-channel.
- 2) A probe was placed near the EUT.
- 3) To determine the power spectral density, the following spectrum analyzer settings were used for

Channel 1:

- a. Center frequency = transmit frequency
 - b. Span = 1MHz
 - c. Resolution bandwidth (RBW) greater than the 20dB bandwidth.
 - d. Sweep time = auto
 - e. The peak detector and 'Max-Hold' function was engaged. The analyzer was allowed to scan until the envelope of the transmitter bandwidth was defined.
 - f. Channel 1 of the spectrum analyzer was placed in 'View' mode.
- 4) This reading corresponds to the peak output power measured for the mid channel.
 - 5) The EUT was then placed in the inquiry mode.
 - 6) To determine the power spectral density, the following spectrum analyzer settings were used for

Channel 2:

- a. Center frequency = transmit frequency
- b. Span = 1MHz
- c. Resolution bandwidth (RBW) = 3kHz
- d. Sweep time = span divided by RBW = (for example :1MHz/3kHz = 333 seconds)
- e. The peak detector and 'Max-Hold' function was engaged.
- f. The analyzer's display was plotted using a 'screen dump' utility.

5.2.9.3 Results

Page 75 shows the power spectral density results. As can be seen from this plot, the peak power density is less than 8dBm in a 3kHz band during any time interval of continuous transmission.

6 OTHER TEST CONDITIONS

6.1 Test Personnel and Witnesses

Qualified personnel from Elite Electronic Engineering Incorporated performed all tests. The test series was partially witnessed by Motorola, Inc. personnel.

6.2 Disposition of the EUT

The EUT and all associated equipment were returned to Motorola, Inc. upon completion of the tests.

7 CONCLUSIONS

It was determined that the Motorola, Inc. Wireless Dongle Transceiver, Model No. PMLN5792A, Serial No. 24, did fully meet the radiated emission requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.247 for Intentional Radiators Operating within the 2400-2483.5 MHz band when tested per ANSI C63-4:2003.

It was also determined that the Motorola, Inc. Wireless Dongle Transceiver, Model No. PMLN5792A, Serial No. 24, did fully meet the conducted and radiated RF emission requirements of the Industry Canada Radio Standards Specification, RSS-Gen and the Industry Canada Radio Standards Specification RSS-210 Annex 8,



section A8.1 for transmitters when tested per ANSI C63-4-2003.

8 CERTIFICATION

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the test specifications.

The data presented in this test report pertains to the EUT at the test. Any electrical or mechanical modification made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification. This report must not be used to claim product endorsement by NVLAP or any agency of the US Government.



9 EQUIPMENT LIST


Table 9-1 Equipment List

Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Due Date
APW0	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-30-20G20R6G	PL2926/0646	20GHZ-26.5GHZ	8/27/2010	8/27/2011
APW2	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-35-120-5R0-10	PL2925	1GHZ-20GHZ	8/27/2010	8/27/2011
APW3	PREAMPLIFIER	PLANAR ELECTRONICS	PE2-35-120-5R0-10-12	PL2924	1GHZ-20GHZ	8/27/2010	8/27/2011
CDS2	COMPUTER	GATEWAY	MFATXPNT NMZ 500L	0028483108	1.8GHZ	N/A	
CMA1	Controllers	EMCO	2090	9701-1213	---	N/A	
GRE0	SIGNAL GENERATOR	AGILENT TECHNOLOGIES	E4438C	MY42083127	250KHZ-6GHZ	2/16/2010	2/16/2011
NHG1	STANDARD GAIN HORN ANTENNA	NARDA	638	---	18-26.5GHZ	NOTE 1	
NTA2	BILOG ANTENNA	TESEQ	6112D	28040	25-1000MHz	6/7/2010	6/7/2011
NWH0	RIDGED WAVE GUIDE	TENSOR	4105	2081	1-12.4GHZ	8/31/2010	8/31/2011
NWQ2	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS LINDGREN	3117	66659	1GHZ-18GHZ	1/29/2011	1/29/2012
RBB0	EMI TEST RECEIVER 20HZ TO 40 GHZ	ROHDE & SCHWARZ	ESIB40	100250	20 HZ TO 40GHZ	3/16/2010	3/16/2011
XOB1	ADAPTER	HEWLETT PACKARD	K281C	10422	18-26.5GHZ	NOTE 1	
XPR0	HIGH PASS FILTER	K&L MICROWAVE	11SH10-4800/X20000	001	4.8-20GHZ	7/19/2010	7/19/2011

I/O: Initial Only

N/A: Not Applicable

Note 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.







Figure 2



Test Setup for Radiated Emissions, above 1GHz – Horizontal Polarization



Test Setup for Radiated Emissions, above 1GHz – Vertical Polarization



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIU RCU EMI RUN 7

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Rx @ 2441MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 15:20:05 R. KING
ANT. POLARIZ. : HORIZONTAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100

START = 30



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIV RCU EMI RUN 8

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Rx @ 2441MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 15:21:41 R. KING
ANT. POLARIZ. : VERTICAL

— PEAK DETECTOR TRACE




STOP = 1000

FREQUENCY MHz

100

START = 30






ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 13

UKA1 10/20/10



SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Rx @ 2441MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CH0879
TEST DATE : 7 Mar 2011 15:52:51 R. KING
ANT. POLARIZ. : VERTICAL

STOP = 10000

FREQUENCY MHz

START = 1000



MANUFACTURER : Motorola
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Receive at 2441MHz
TEST DATE : March 9, 2010
TEST PARAMETERS : Industry Canada RSS-Gen Spurious Radiated Emissions
NOTES : Tested with Motorola XTS 2500 Portable Radio


Frequency MHz	Ant Pol	Meter Reading dBuV	Ambient	Cbl Fac dB	Ant Fac dB	Pre Amp Gain dB	Total dBuV/m at 3 m	Total uV/m at 3 m	Limit uV/m at 3 m	Margin dB
2442.500	H	38.9		3.8	29.3	-39.7	32.2	40.9	500	-21.7
2442.500	V	32.0	*	3.8	29.3	-39.7	25.4	18.5	500	-28.6
4885.000	H	29.9	*	5.8	34.5	-38.3	31.9	39.3	500	-22.1
4885.000	V	29.8	*	5.8	34.5	-38.3	31.8	38.9	500	-22.2
7327.500	H	31.0	*	7.7	37.8	-38.4	38.1	79.9	500	-15.9
7327.500	V	31.1	*	7.7	37.8	-38.4	38.1	80.8	500	-15.8

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB)

Checked BY RICHARD E. KING :


Richard E. King



Date: 9.MAR.2011 12:14:49

20dB Bandwidth


MANUFACTURER : Motorola Inc.
 MODEL NUMBER : PMLN5792A
 TEST SPEC. : 15.247 20dB Bandwidth
 TEST PARAMETERS : 20dBc
 EUT FREQUENCY : 2402MHz
 NOTES : 20dB BW = 875 kHz
 :



Date: 9.MAR.2011 12:06:26

20dB Bandwidth


MANUFACTURER : Motorola Inc.
MODEL NUMBER : PMLN5792A
TEST SPEC. : 15.247 20dB Bandwidth
TEST PARAMETERS : 20dBc
EUT FREQUENCY : 2441MHz
NOTES : 20dB BW = 881 kHz
:



Date: 9.MAR.2011 11:56:10

20dB Bandwidth


MANUFACTURER : Motorola Inc.
 MODEL NUMBER : PMLN5792A
 TEST SPEC. : 15.247 20dB Bandwidth
 TEST PARAMETERS : 20dBc
 EUT FREQUENCY : 2480MHz
 NOTES : 20dB BW = 885 kHz
 :
 :



Date: 9.MAR.2011 11:09:50

Carrier Frequency Separation

MANUFACTURER : Motorola Inc.
MODEL NUMBER : PMLN5792A
TEST SPEC. : 15.247 Carrier Frequency Separation
TEST PARAMETERS : Carrier Frequency Separation = 1MHz
EUT FREQUENCY : Frequency Hopping Enabled
NOTES :
:




Date: 9.MAR.2011 10:58:40

Number of Hopping Frequencies

MANUFACTURER : Motorola Inc.
MODEL NUMBER : PMLN5792A
TEST MODE : Number of Hopping Frequencies
TEST PARAMETERS : Number of Hopping Frequencies = 79
:

NOTES




Date: 9.MAR.2011 11:19:23

Duty Cycle Correction Factor

MANUFACTURER : Motorola
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Frequency Hopping Enabled
TEST DATE : March 9, 2011
TEST PARAMETERS : Duty Cycle Correction Factor
NOTES : 1 pulse = 397usec


NOTES



Date: 9.MAR.2011 11:23:00

Duty Cycle Correction Factor

MANUFACTURER : Motorola
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Frequency Hopping Enabled
TEST DATE : March 9, 2011
TEST PARAMETERS : Duty Cycle Correction Factor
NOTES : Duty Cycle Correction Factor = $20 \cdot \log((\text{pulse width}) \times (\text{number of times the channel is used in a 100msec period}) / 100) = 20 \cdot (\log(397 \text{ usec}) \times (2) / 100 \text{ msec}) = -42.0 \text{ dB}$




Date: 9.MAR.2011 11:14:14

Time of Occupancy

MANUFACTURER : Motorola Inc.
MODEL NUMBER : PMLN5792A
TEST MODE : Frequency Hopping Enabled
TEST PARAMETERS : Time of Occupancy
NOTES : 1 pulse = 397uS
:

NOTES



Date: 9.MAR.2011 11:39:59

Time of Occupancy

MANUFACTURER : Motorola Inc.
MODEL NUMBER : PMLN5792A
TEST SPEC. : 15.247 Time of Occupancy
TEST MODE : Frequency Hopping Enabled
TEST PARAMETERS : For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Number of hopping channels = 79. $79 \times 0.4 = 31.6$ sec.

NOTES : Number of pulses in 4 seconds = 41. Therefore the number of pulses in 31.6 seconds = $41 \times ((31.6\text{sec})/4\text{sec}) = 324$ pulses. Each pulse is 397μsec. Therefore time of occupancy = $397\mu\text{sec} \times 324 \text{ pulses} = 0.1286$ sec.



MANUFACTURER : Motorola, Inc.
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
TEST MODE : See Below
TEST DATE : March 9, 2011
TEST PARAMETERS : Peak EIRP
NOTES :

Freq MHz	Ant Pol	Meter Reading dBuV	Matched	Ant Gain dB	Cable Factor dB	EIRP Total dBm	Limit dBm
			Signal Generator dB				
2402.00	H	64.6	-4.5	8.7	3.0	1.1	36.0
2402.00	V	68.8	1.3	8.7	3.0	6.9	36.0
2441.00	H	65.1	-4.6	8.7	3.1	1.1	36.0
2441.00	V	69.1	1.9	8.7	3.1	7.6	36.0
2480.00	H	63.7	-5.3	8.8	3.1	0.4	36.0
2480.00	V	68.1	1.3	8.8	3.1	7.0	36.0

Checked BY RICHARD E. King :

Richard E. King



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIV RCU EMI RUN 2

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Tx @ 2402MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 14:49:09 R. KING
ANT. POLARIZ. : HORIZONTAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100

START = 30



ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU RCU EMI RUN 1

UKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS

MANUFACTURER : MOTOROLA INC.

MODEL No. : PMLN5792A

SERIAL No. : 24

MODE : Tx @ 2402MHz


SCANS/BAND : 1

NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879

TEST DATE : 7 Mar 2011 14:44:28 R. KING

ANT. POLARIZ. : VERTICAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100


START = 30



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 8

UKA1 10/20/10



STOP = 3000

FREQUENCY MHz


START = 1000



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIU RCU EMI RUN 7


UKA1 10/20/10



STOP = 3000

FREQUENCY MHz

START = 1000






ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 15

WKA1 10/20/10



STOP = 18000


START = 2000



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIU RCU EMI RUN 20

WKA1 10/20/10






ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 21

WKA1 10/20/10





ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIV RCU EMI RUN 3

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Tx @ 2441MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 14:52:54 R. KING
ANT. POLARIZ. : HORIZONTAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100

START = 30



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIU RCU EMI RUN 4

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Tx @ 2441MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 14:54:35 R. KING
ANT. POLARIZ. : VERTICAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100

START = 30




ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU RCU EMI RUN 9

UKA1 10/20/10



START = 1000

FREQUENCY MHz


STOP = 3000




ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIU RCU EMI RUN 10

UKA1 10/20/10








ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 14

WKA1 10/20/10



STOP = 18000

START = 2000




ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIU RCU EMI RUN 19

WKA1 10/20/10



START = 18000

FREQUENCY MHz

STOP = 25000




ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIV RCU EMI RUN 18

WKA1 10/20/10



START = 18000

FREQUENCY MHz

STOP = 25000



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIV RCU EMI RUN 6

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Tx @ 2480MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 15:12:16 R. KING
ANT. POLARIZ. : HORIZONTAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100

START = 30



ELITE ELECTRONIC ENGINEERING Inc.


Downers Grove, Ill. 60515

UNIV RCU EMI RUN 5

WKA1 10/20/10

SPEC / TEST : PRELIM RADIATED EMISSIONS
MANUFACTURER : MOTOROLA INC.
MODEL No. : PMLN5792A
SERIAL No. : 24
MODE : Tx @ 2480MHz
SCANS/BAND : 1
NOTES : TESTED w/ M/N: H46QDC9PU5BN S/N: 407CHH0879
TEST DATE : 7 Mar 2011 15:10:28 R. KING
ANT. POLARIZ. : VERTICAL

— PEAK DETECTOR TRACE



STOP = 1000

FREQUENCY MHz

100


START = 30



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 12

UKA1 10/20/10



STOP = 3000

START = 1000




ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIV RCU EMI RUN 11


UKA1 10/20/10



START = 1000

FREQUENCY MHz

STOP = 3000






ELITE ELECTRONIC ENGINEERING Inc.

Downers Grove, Ill. 60515

UNIV RCU EMI RUN 11

WKA1 10/20/10



START = 2000

10000

FREQUENCY MHz


STOP = 18000



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 16

WKA1 10/20/10



START = 18000

FREQUENCY MHz


STOP = 25000



ELITE ELECTRONIC ENGINEERING Inc.
Downers Grove, Ill. 60515

UNIV RCU EMI RUN 17

WKA1 10/20/10



START = 18000 FREQUENCY MHz STOP = 25000



MANUFACTURER : Motorola, Inc.
 EUT : Wireless Dongle
 MODEL NUMBER : PMLN5792A
 TEST MODE : Transmit at 2402MHz
 TEST DATE : March 9, 2011
 TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
 : FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
 NOTES : Peak Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2402.00	H	64.2	3.4	32.6	0.0	100.2	102022.7		
2402.00	V	68.5	3.4	32.6	0.0	104.5	167570.1		
4804.00	H	62.8	4.9	34.8	-40.1	62.3	1306.4	5000.0	-11.7
4804.00	V	62.9	4.9	34.8	-40.1	62.4	1321.6	5000.0	-11.6
7206.00	H	47.7	6.1	36.4	-39.8	50.5	334.5	16757.0	-34.0
7206.00	V	47.1	6.1	36.4	-39.8	49.9	311.1	16757.0	-34.6
9608.00	H	46.0	6.8	37.4	-38.8	51.5	373.8	16757.0	-33.0
9608.00	V	40.5	6.8	37.4	-38.8	45.9	197.8	16757.0	-38.6
12010.00	H	46.9	8.0	39.9	-39.6	55.2	573.5	5000.0	-18.8
12010.00	V	45.2	8.0	39.9	-39.6	53.5	472.1	5000.0	-20.5
14412.00	H	35.3	8.7	39.3	-39.9	43.4	147.7	16757.0	-41.1
14412.00	V	35.8	8.7	39.3	-39.9	43.9	156.2	16757.0	-40.6
16814.00	H	35.6	9.4	41.7	-38.8	47.9	248.8	16757.0	-36.6
16814.00	V	35.0	9.4	41.7	-38.8	47.3	232.2	16757.0	-37.2
19216.00	H	35.7	2.2	40.4	-27.5	50.8	345.8	5000.0	-23.2
19216.00	V	35.7	2.2	40.4	-27.5	50.8	345.8	5000.0	-23.2
21618.00	H	25.9	2.2	40.6	-27.5	41.1	114.1	16757.0	-43.3
21618.00	V	25.9	2.2	40.6	-27.5	41.1	114.1	16757.0	-43.3
24020.00	H	26.4	2.2	40.6	-27.5	41.8	122.7	16757.0	-42.7
24020.00	V	26.4	2.2	40.6	-27.5	41.8	122.7	16757.0	-42.7

Gray rows indicate emissions in a restricted band

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB)



Checked BY RICHARD E. KING :

Richard E. King



MANUFACTURER : Motorola
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Transmit at 2402MHz
TEST DATE : March 9, 2011
TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
: FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
NOTES : Average Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
4804.0	H	58.9		4.9	34.3	-40.1	-42.0	16.0	6.3	500.0	-37.9
4804.0	V	58.3		4.9	34.3	-40.1	-42.0	15.4	5.9	500.0	-38.5
12010.0	H	32.7	*	8.0	41.4	-39.6	-42.0	0.4	1.0	500.0	-53.6
12010.0	V	32.7	*	8.0	41.4	-39.6	-42.0	0.5	1.1	500.0	-53.5
19216.0	H	22.4	*	2.2	40.4	-27.5	-42.0	-4.5	0.6	500.0	-58.5
19216.0	V	22.4	*	2.2	40.4	-27.5	-42.0	-4.5	0.6	500.0	-58.5

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB) + Duty Cycle(dB)

Checked BY RICHARD E. KING :

Richard E. King



MANUFACTURER : Motorola, Inc.
 EUT : Wireless Dongle
 MODEL NUMBER : PMLN5792A
 TEST MODE : Transmit at 2441MHz
 TEST DATE : March 9, 2011
 TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
 : FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
 NOTES : Peak Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2441.00	H	64.9		3.4	32.6	0.0	100.9	111474.7		
2441.00	V	68.3		3.4	32.6	0.0	104.3	164503.9		
4882.00	H	59.7		4.9	34.7	-40.1	59.2	916.3	5000.0	-14.7
4882.00	V	60.7		4.9	34.7	-40.1	60.2	1028.1	5000.0	-13.7
7323.00	H	59.2		6.2	36.5	-39.7	62.1	1277.2	5000.0	-11.9
7323.00	V	57.7		6.2	36.5	-39.7	60.6	1067.3	5000.0	-13.4
9764.00	H	45.2		6.9	37.6	-38.7	51.0	354.2	16450.4	-33.3
9764.00	V	44.8		6.9	37.6	-38.7	50.6	340.2	16450.4	-33.7
12205.00	H	46.0	*	8.0	39.9	-39.4	54.4	525.7	5000.0	-19.6
12205.00	V	46.1	*	8.0	39.9	-39.4	54.6	534.3	5000.0	-19.4
14646.00	H	35.4	*	8.8	39.5	-40.1	43.7	152.5	16450.4	-40.7
14646.00	V	35.6	*	8.8	39.5	-40.1	43.9	156.6	16450.4	-40.4
17087.00	H	36.2	*	9.5	41.7	-38.7	48.8	275.2	16450.4	-35.5
17087.00	V	36.3	*	9.5	41.7	-38.7	48.9	278.4	16450.4	-35.4
19528.00	H	35.6	*	2.2	40.4	-27.2	51.0	355.5	5000.0	-23.0
19528.00	V	35.6	*	2.2	40.4	-27.2	51.0	355.5	5000.0	-23.0
21969.00	H	27.2	*	2.2	40.6	-26.9	43.0	142.0	16450.4	-41.3
21969.00	V	27.2	*	2.2	40.6	-26.9	43.0	142.0	16450.4	-41.3
24410.00	H	26.8	*	2.2	40.6	-27.5	42.2	128.6	16450.4	-42.1
24410.00	V	26.8	*	2.2	40.6	-27.5	42.2	128.6	16450.4	-42.1

Gray rows indicate emissions in a restricted band

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB)



Checked BY RICHARD E. KING :

Richard E. King



MANUFACTURER : Motorola
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Transmit at 2441MHz
TEST DATE : March 9, 2011
TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
: FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
NOTES : Average Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
4882.0	H	57.3		4.9	34.5	-40.1	-42.0	14.6	5.4	500.0	-39.3
4882.0	V	56.3		4.9	34.5	-40.1	-42.0	13.6	4.8	500.0	-40.3
7323.0	H	57.0		6.2	37.8	-39.7	-42.0	19.2	9.1	500.0	-34.8
7323.0	V	56.0		6.2	37.8	-39.7	-42.0	18.2	8.1	500.0	-35.8
12205.0	H	34.5	*	8.0	41.5	-39.4	-42.0	2.5	1.3	500.0	-51.5
12205.0	V	34.5	*	8.0	41.5	-39.4	-42.0	2.5	1.3	500.0	-51.5
19528.0	H	22.7	*	2.2	40.4	-27.2	-42.0	-3.9	0.6	500.0	-57.9
19528.0	V	22.7	*	2.2	40.4	-27.2	-42.0	-3.9	0.6	500.0	-57.9

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB) + Duty Cycle(dB)

Checked BY RICHARD E. KING :

Richard E. King



MANUFACTURER : Motorola, Inc.
 EUT : Wireless Dongle
 MODEL NUMBER : PMLN5792A
 TEST MODE : Transmit at 2480MHz
 TEST DATE : March 9, 2011
 TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
 : FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
 NOTES : Peak Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2480.0	H	62.8	3.8	29.3	0.0	0.0	96.0	62904.2		
2480.0	V	68.7	3.8	29.3	0.0	0.0	101.8	123361.5		
4960.0	H	57.9	5.8	34.7	-38.3	0.0	60.1	1016.5	5000.0	-13.8
4960.0	V	58.8	5.8	34.7	-38.3	0.0	61.0	1127.5	5000.0	-12.9
7440.0	H	54.2	7.7	38.0	-38.5	0.0	61.5	1187.1	5000.0	-12.5
7440.0	V	54.5	7.7	38.0	-38.5	0.0	61.7	1223.1	5000.0	-12.2
9920.0	H	36.3	8.5	39.0	-38.6	0.0	45.3	183.2	12336.2	-36.6
9920.0	V	38.6	8.5	39.0	-38.6	0.0	47.6	239.1	12336.2	-34.3
12400.0	H	46.6	9.9	41.3	-38.4	0.0	59.5	939.2	5000.0	-14.5
12400.0	V	46.1	9.9	41.3	-38.4	0.0	58.9	883.6	5000.0	-15.1
14880.0	H	36.6	11.2	44.5	-39.0	0.0	53.3	461.0	12336.2	-28.5
14880.0	V	34.7	11.2	44.5	-39.0	0.0	51.4	372.2	12336.2	-30.4
17360.0	H	36.1	11.9	44.4	-38.4	0.0	54.0	500.3	12336.2	-27.8
17360.0	V	35.8	11.9	44.4	-38.4	0.0	53.7	482.2	12336.2	-28.2
19840.0	H	29.6	2.2	40.4	-26.9	0.0	45.3	185.1	5000.0	-28.6
19840.0	V	29.6	2.2	40.4	-26.9	0.0	45.3	185.1	5000.0	-28.6
22320.0	H	32.1	2.2	40.6	-27.1	0.0	47.8	246.6	5000.0	-26.1
22320.0	V	32.1	2.2	40.6	-27.1	0.0	47.8	246.6	5000.0	-26.1
24800.0	H	23.2	2.2	40.7	-27.2	0.0	38.8	87.5	12336.2	-43.0
24800.0	V	23.2	2.2	40.7	-27.2	0.0	38.8	87.5	12336.2	-43.0

Gray rows indicate emissions in a restricted band

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB)



Checked BY RICHARD E. KING :

Richard E. King



MANUFACTURER : Motorola
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Transmit at 2480MHz
TEST DATE : March 9, 2011
TEST PARAMETERS : Industry Canada RSS-210 Annex 8 Spurious Radiated Emissions
: FCC CFR Title 47 Part 15, Subpart C, Paragraph 15.247 Spurious Radiated Emissions
NOTES : Average Detector


Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
4960.0	H	52.3		5.0	34.7	-40.2	-42.0	9.8	3.1	500.0	-44.1
4960.0	V	50.8		5.0	34.7	-40.2	-42.0	8.3	2.6	500.0	-45.6
7440.0	H	48.5		6.2	38.0	-39.7	-42.0	11.0	3.6	500.0	-42.9
7440.0	V	51.3		6.2	38.0	-39.7	-42.0	13.8	4.9	500.0	-40.1
12400.0	H	34.9	*	8.0	41.5	-39.3	-42.0	3.2	1.4	500.0	-50.8
12400.0	V	34.9	*	8.0	41.5	-39.3	-42.0	3.2	1.4	500.0	-50.8
19840.0	H	22.5	*	2.2	40.4	-26.9	-42.0	-3.8	0.6	500.0	-57.7
19840.0	V	22.5	*	2.2	40.4	-26.9	-42.0	-3.8	0.6	500.0	-57.7
22320.0	H	23.2	*	2.2	40.6	-27.1	-42.0	-3.1	0.7	500.0	-57.1
22320.0	V	23.2	*	2.2	40.6	-27.1	-42.0	-3.1	0.7	500.0	-57.1

H – Horizontal V – Vertical

Total (dBuV/m) = Meter Reading (dBuV) + Cbl Fac (dB) + Ant Fac (dB) + Pre Amp Gain (dB) + Duty Cycle(dB)

Checked BY RICHARD E. KING :


Richard E. King



Date: 9.MAR.2011 12:19:30

Bandedge Compliance

MANUFACTURER : Motorola Inc.
 MODEL NUMBER : PMLN5792A
 TEST SPEC. : 15.247 Bandedge Compliance
 TEST PARAMETERS : 20dBc
 TEST MODE : 2402MHz
 NOTES : 20dBc at 2400MHz
 :



Date: 9.MAR.2011 12:26:53

Bandedge Compliance

MANUFACTURER : Motorola Inc.
 MODEL NUMBER : PMLN5792A
 TEST SPEC. : 15.247 Bandedge Compliance
 TEST PARAMETERS : (20dBc) The band edge must be at least 20dB below the highest level measured within the band
 TEST MODE : Frequency Hopping Enabled
 NOTES : 20dBc at 2400MHz
 :



MANUFACTURER : Motorola, Inc.
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Transmit at 2480MHz
TEST DATE : March 9, 2011
TEST PARAMETERS : Band Edge at 2483.5MHz
NOTES : Peak Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2483.50	H	24.8		3.5	29.3	0.0	57.6	759.8	5000.0	-16.4
2483.50	V	25.7		3.5	29.3	0.0	58.5	844.7	5000.0	-15.4

Checked BY RICHARD E. King :

Richard E. King



MANUFACTURER : Motorola, Inc.
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Transmit at 2480MHz
TEST DATE : March 9, 2011
TEST PARAMETERS : Band Edge at 2483.5MHz
NOTES : Average Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2483.5	H	11.5		3.5	29.3	0.0	44.3	163.6	500.0	-9.7
2483.5	V	11.6		3.5	29.3	0.0	44.4	166.6	500.0	-9.5

Checked BY RICHARD E. King :

Richard E. King



MANUFACTURER : Motorola, Inc.
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Hopping Enabled
TEST DATE : March 9, 2011
TEST PARAMETERS : Band Edge at 2483.5MHz
NOTES : Peak Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2483.50	H	28.4		3.5	29.3	0.0	61.2	1147.3	5000.0	-12.8
2483.50	V	29.9		3.5	29.3	0.0	62.7	1366.7	5000.0	-11.3

Checked BY Richard E. King :

Richard E. King




MANUFACTURER : Motorola, Inc.
EUT : Wireless Dongle
MODEL NUMBER : PMLN5792A
SERIAL NUMBER : 24
TEST MODE : Hopping Enabled
TEST DATE : March 9, 2011
TEST PARAMETERS : Band Edge at 2483.5MHz
NOTES : Average Detector

Freq (MHz)	Ant Pol	Meter Reading (dBuV)	Ambient	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Total dBuV/m at 3 M	Total uV/m at 3M	Limit uV/m at 3M	Margin (dB)
2483.5	H	13.7		3.5	29.3	0.0	46.5	211.2	500.0	-7.5
2483.5	V	13.8		3.5	29.3	0.0	46.6	213.9	500.0	-7.4

Checked BY RICHARD E. King :

Richard E. King



Date: 16.MAR.2011 16:33:56

Power Spectral Density

MANUFACTURER : Motorola, Inc.
MODEL NUMBER : PMLN5792A
TEST MODE : Inquiry Mode
TEST DATE : March 16, 2011
TEST PARAMETERS : Power Spectral Density
NOTES : Top Trace = 73.5 dBuV represents the 7.6dBm matched EIRP in a 3MHz RBW.
Display line (D1) is equal to 8dBm (8dBm - 7.6dBm = 0.4dBm above the 7.6dBm EIRP). Bottom trace = power spectral density in 3kHz RBW with 340 second sweep time.
EQUIPMENT USED : RBB0, PHA0