

Test Report No. 7191073686-EEC13/01
dated 03 Dec 2013



PSB Singapore

Note: This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.

Choose certainty.
Add value.

FORMAL REPORT ON TESTING IN ACCORDANCE WITH
47 CFR FCC Parts 15B & C : 2012
OF A
CD STEREO SYSTEM
[Model : SC-AKX18]
[FCC ID : ACJ-B21R1401]

TEST FACILITY TÜV SÜD PSB Pte Ltd,
Electrical & Electronics Centre (EEC), Product Services,
No. 1 Science Park Drive, Singapore 118221

TÜV SÜD PSB Pte Ltd,
Electrical & Electronics Centre (EEC), Product Services,
13 International Park, Singapore 609932

FCC REG. NO. 99142 (3m and 10m Semi-Anechoic Chamber, Science Park)

IND. CANADA REG. NO. 2932I-1 (3m and 10m Semi-Anechoic Chamber, Science Park)

PREPARED FOR Panasonic AVC Networks Singapore
202 Bedok South Avenue 1
Singapore 469332

Tel : +65 6240 1891 Fax : +65 6245 8804

QUOTATION NUMBER 219182519

JOB NUMBER 7191073686

TEST PERIOD 17 Sep 2013 - 25 Nov 2013

PREPARED BY


Quek Keng Huat
Higher Associate Engineer

APPROVED BY

Lim Cher Hwee
Assistant Vice President



Laboratory:
TÜV SÜD PSB Pte. Ltd.
No.1 Science Park Drive
Singapore 118221



LA-2007-0380-A
LA-2007-0381-F
LA-2007-0382-B
LA-2007-0383-G
LA-2007-0384-G
LA-2007-0385-E
LA-2007-0386-C
LA-2010-0464-D

The results reported herein have been performed in accordance with the laboratory's terms of accreditation under the Singapore Accreditation Council - Singapore Laboratory Accreditation Scheme. Tests/Calibrations marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our laboratory.

Phone : +65-6885 1333
Fax : +65-6776 8670
E-mail: testing@tuv-sud-psb.sg
www.tuv-sud-psb.sg
Co. Reg : 199002667R

Regional Head Office:
TÜV SÜD Asia Pacific Pte. Ltd.
3 Science Park Drive, #04-01/05
The Franklin, Singapore 118223
TUV®



TABLE OF CONTENTS

TEST SUMMARY	3
PRODUCT DESCRIPTION	5
SUPPORTING EQUIPMENT DESCRIPTION.....	6
EUT OPERATING CONDITIONS.....	7
CONDUCTED EMISSION TEST	8
RADIATED EMISSION TEST.....	12
CARRIER FREQUENCY SEPARATION TEST	21
SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST	25
NUMBER OF HOPPING FREQUENCIES TEST	34
AVERAGE FREQUENCY DWELL TIME TEST.....	38
MAXIMUM PEAK POWER TEST	47
RF CONDUCTED SPURIOUS EMISSIONS TEST	49
BAND EDGE COMPLIANCE (CONDUCTED) TEST.....	60
BAND EDGE COMPLIANCE (RADIATED) TEST.....	65
PEAK POWER SPECTRAL DENSITY TEST.....	76
MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST	85
ANNEX A EUT PHOTOGRAPHS / DIAGRAMS	87
ANNEX B USER MANUAL TECHNICAL DESCRIPTION BLOCK & CIRCUIT DIAGRAMS.....	98
ANNEX C FCC LABEL & POSITION.....	99



TEST SUMMARY

The product was tested in accordance with the customer's specifications.

Test Results Summary

Test Standard	Description	Pass / Fail
47 CFR FCC Part 15: 2012		
15.107(a), 15.207	Conducted Emissions	Pass
15.109(a), 15.205, 15.209	Radiated Emissions (Spurious Emissions inclusive Restricted Bands Requirement)	Pass
15.247(a)(1)	Carrier Frequency Separation	Pass
	Spectrum Bandwidth (20dB Bandwidth Measurement)	Pass
15.247(a)(1)(iii)	Number of Hopping Frequencies	Pass
	Average Frequency Dwell Time	Pass
15.247(b)(1)	Maximum Peak Power	Pass
15.247(d)	RF Conducted Spurious Emissions	Pass
15.247(d)	Band Edge Compliance (Conducted)	Pass
15.247(d)	Band Edge Compliance (Radiated)	Pass
15.247(e)	Peak Power Spectral Density	Pass
1.1310	Maximum Permissible Exposure	Refer to page 85 for details



TEST SUMMARY

Notes


1. Three channels as listed below, which respectively represent the lower, middle and upper channels of the Equipment Under Test (EUT) were chosen and tested. For each channel, the EUT was configured to operate in the test mode.

<u>Transmit Channel</u>	<u>Frequency (GHz)</u>
Channel 0	2.402
Channel 39	2.441
Channel 78	2.480

2. All the measurements in section 15.247 were done based on conducted measurements except Band Edge Compliance (Radiated) test.
3. The EUT is a Class B device when in non-transmitting state and meets the 47 CFR FCC Part15B Class B requirements.
4. All test measurement procedures are according to ANSI C63.4: 2003.
5. The maximum measured RF power of the Equipment Under Test is 2.05dBm.

Modifications

No modifications were made.




PRODUCT DESCRIPTION

Description	: The Equipment Under Test (EUT) is a CD STEREO SYSTEM.
Applicant	: Panasonic AVC Networks Singapore 202, Bedok South Avenue 1 Singapore 469332
Manufacturer	: Panasonic Corporation 1006 Oaza Kadoma Kadoma City - Osaka 571 8501, Japan
Factor (ies)	: Panasonic AVC Networks Johor Malaysia Sdn. Bhd. IE PLO 460, Jalan Bandar, 81700 Pasir Gudang, Johor, Malaysia
Model Number	: SC-AKX18
Contains FCC ID	: ACJ-B21R1401
Serial Number	: Nil
Microprocessor	: BM94801KUT-Rohm Semiconductor Pte Ltd
Operating / Transmitting Frequency	: Bluetooth - 2.402MHz (lower channel) to 2.480MHz (upper channel) - 79 channels AM 522kHz - 1629kHz FM 87.5MHz - 108MHz
Clock / Oscillator Frequency	: 128kHz / 45kHz (FM/AM), 26MHz (Bluetooth), 16MHz & 32kHz
Modulation	: DH1 (1Mbps): Gaussian Frequency Shift Keying (GFSK) DH3 (2Mbps): $\pi/4$ Differential-Quadrature Phase Shift Keying (DQPSK) DH5 (3Mbps): 8 Differential Phase-Shift keying Keying (DPSK)
Antenna Gain	: 2.0 dBi
Port / Connectors	: Refer to manufacturer's user manual / operating manual.
Rated Input Power	: 110-127V / 220-240V 50/60Hz 50W.
Accessories	: Remote Control FM/AM Antenna AC Cord AA Size Batteries



SUPPORTING EQUIPMENT DESCRIPTION


Equipment Description (Including Brand Name)	Model, Serial & FCC ID Number	Cable Description (List Length, Type & Purpose)
Apple iPhone 5	M/N: MD298ZA/A S/N: C36J91R9DTWF FCC ID: BCG-E2599A	
Fujitsu Lifebook	M/N: S6310 S/N: R6Z00061 FCC ID: DoC	2.00m power cable
Fujitsu AC Adapter	M/N: CP293662-01 S/N: 06X00159B FCC ID: DoC	2.00m power cable
Pihong Switching Power Supply	M/N: PSAC05R-050 S/N: Nil FCC ID: DoC	2.00m power cable





EUT OPERATING CONDITIONS

47 CFR FCC Part 15
<ol style="list-style-type: none">1. Conducted Emissions2. Radiated Emissions (Spurious Emissions inclusive Restricted Bands Requirement)3. Spectrum Bandwidth (20dB Bandwidth Measurement)4. Maximum Peak Power5. RF Conducted Spurious Emissions6. Peak Power Spectral Density7. Maximum Permissible Exposure
The EUT was exercised by operating in maximum continuous transmission with frequency hopping off, i.e transmitting at lower, middle and upper channels respectively at one time for RF mode and CD playback, USB playback and AUX IN mode for non-RF mode.
47 CFR FCC Part 15
<ol style="list-style-type: none">1. Carrier Frequency Separation2. Number of Hopping Frequencies3. Average Frequency Dwell Time4. Band Edge Compliance (Conducted)5. Band Edge Compliance (Radiated)
The EUT was exercised by operating in maximum continuous transmission with frequency hopping on.





CONDUCTED EMISSION TEST

47 CFR FCC Parts 15.107(a) and 15.207 Conducted Emission Limits

Frequency Range (MHz)	Limit Values (dBµV)	
	Quasi-peak (Q-P)	Average (AV)
0.15 - 0.5	66 – 56 *	56 – 46 *
0.5 - 5.0	56	46
5.0 - 30.0	60	50

* Decreasing linearly with the logarithm of the frequency

47 CFR FCC Parts 15.107(a) and 15.207 Conducted Emission Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Schaffner EMI Receiver	SMR4503	040	20 Nov 2014
Agilent EMC Analyzer-SA7	E7403A	US41160167	28 May 2014
Schaffner LISN –LISN7 (Ref)	NNB42	00008	28 Jan 2014
EMCO LISN (for supporting) – LISN6	3825/2	9309-2127	31 Oct 2014



CONDUCTED EMISSION TEST

47 CFR FCC Parts 15.107(a) and 15.207 Conducted Emission Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table.
2. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipment were powered separately from another LISN.

47 CFR FCC Parts 15.107(a) and 15.207 Conducted Emission Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 9kHz. Both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line.

Sample Calculation Example

At 20 MHz

Q-P limit = 60.0 dBμV

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.2 dB

Q-P reading obtained directly from EMI Receiver = 40.0 dBμV
(Calibrated for system losses)

Therefore, Q-P margin = 60.0 - 40.0 = 20.0

i.e. 20.0 dB below Q-P limit



CONDUCTED EMISSION TEST

Conducted Emissions Test Setup (Front View)

Conducted Emissions Test Setup (Rear View)



CONDUCTED EMISSION TEST

47 CFR FCC Parts 15.107(a) and 15.207 Conducted Emission Results

Test Input Power	120V 60Hz	Temperature	24°C
Line Under Test	AC Mains	Relative Humidity	60%
Non RF Mode	USB Playback (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Stephen Chng

Frequency (MHz)	Q-P Value (dBµV)	Q-P Limit (dBµV)	Q-P Margin (dB)	AV Value (dBµV)	AV Limit (dBµV)	AV Margin (dB)	Line
0.1543	34.6	65.8	31.2	18.2	55.8	37.6	Neutral
0.3824	32.7	58.2	25.5	32.5	48.2	15.7	Neutral
19.2888	16.4	60.0	43.6	14.6	50.0	35.4	Live
23.1464	19.7	60.0	40.3	17.7	50.0	32.3	Live
25.0742	23.1	60.0	36.9	16.7	50.0	33.3	Neutral
27.0040	23.1	60.0	36.9	21.4	50.0	28.6	Live

Test Input Power	120V 60Hz	Temperature	24°C
Line Under Test	AC Mains	Relative Humidity	60%
Data Rate	EDR 3Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Stephen Chng

Frequency (MHz)	Q-P Value (dBµV)	Q-P Limit (dBµV)	Q-P Margin (dB)	AV Value (dBµV)	AV Limit (dBµV)	AV Margin (dB)	Line	Channel
0.1577	37.7	65.6	27.9	26.6	55.6	29.0	Live	39
0.2068	32.7	63.3	30.6	26.8	53.3	26.5	Live	39
13.0914	21.9	60.0	38.1	10.3	50.0	39.7	Live	39
15.4334	25.6	60.0	34.4	23.6	50.0	26.4	Live	39
19.2878	25.6	60.0	34.4	23.9	50.0	26.1	Live	39
25.0772	25.6	60.0	34.4	24.4	50.0	25.6	Live	39

Notes

- All possible modes of operation were investigated from 150kHz to 30MHz. Only the worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- A "positive" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency. Conversely, a "negative" margin indicates a FAIL.
- EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:
9kHz - 30MHz
RBW: 9kHz VBW: 30kHz
- Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 9kHz – 30MHz is ±2.2dB.



RADIATED EMISSION TEST

47 CFR FCC Part 15.205 Restricted Bands

MHz		MHz		MHz		GHz	
0.090	- 0.110	16.42	- 16.423	399.9	- 410	4.5	- 5.15
0.495	- 0.505	16.69475	- 16.69525	608	- 614	5.35	- 5.46
2.1735	- 2.1905	16.80425	- 16.80475	960	- 1240	7.25	- 7.75
4.125	- 4.128	25.5	- 25.67	1300	- 1427	8.025	- 8.5
4.17725	- 4.17775	37.5	- 38.25	1435	- 1626.5	9.0	- 9.2
4.20725	- 4.20775	73	- 74.6	1645.5	- 1646.5	9.3	- 9.5
6.215	- 6.218	74.8	- 75.2	1660	- 1710	10.6	- 12.7
6.26775	- 6.26825	108	- 121.94	1718.8	- 1722.2	13.25	- 13.4
6.31175	- 6.31225	123	- 138	2200	- 2300	14.47	- 14.5
8.291	- 8.294	149.9	- 150.05	2310	- 2390	15.35	- 16.2
8.362	- 8.366	156.52475	- 156.52525	2483.5	- 2500	17.7	- 21.4
8.37625	- 8.38675	156.7	- 156.9	2690	- 2900	22.01	- 23.12
8.41425	- 8.41475	162.0125	- 167.17	3260	- 3267	23.6	- 24.0
12.29	- 12.293	167.72	- 173.2	3332	- 3339	31.2	- 31.8
12.51975	- 12.52025	240	- 285	3345.8	- 3358	36.43	- 36.5
12.57675	- 12.57725	322	- 335.4	3600	- 4400	Above 38.6	
13.36	- 13.41						

47 CFR FCC Parts 15.109(a) and 15.209 Radiated Emission Limits

Frequency Range (MHz)	Quasi-Peak Limit Values (dBµV/m) @ 3m
30 - 88	40.0
88 - 216	43.5
216 - 960	46.0
Above 960	54.0*

* Above 1GHz, average detector was used. A peak limit of 20dB above the average limit does apply.

47 CFR FCC Parts 15.109(a) and 15.209 Radiated Emission Test Instrumentation

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver – ESI1	ESI40	100010	09 Jul 2014
TDK RF Solutions Hybrid Log Periodic Antenna (30MHz-3GHz)	HLP-3003C	130238	09 May 2014
Sonoma Preamplifier (9kHz – 1GHz)	310N	270640	09 Jun 2014
Agilent Preamplifier(1GHz-26.5GHz) (PA18)	8449D	3008A02305	04 Oct 2014
Eletro-Metrics Double Ridged Antenna (Horn) Antenna (1-18GHz)	EM-6961	6525	12 Apr 2014
ETS Horn Antenna(18GHz-40GHz)(Ref)	3116	0004-2474	12 Oct 2014
Toyo Preamplifier (26.5GHz-40GHz)	HAP26-40W	00000005	12 Oct 2014
Micro-Tronics Bandstop Filter (2.4-2.5 GHz)	BRM50701	017	13 Aug 2014



RADIATED EMISSION TEST

47 CFR FCC Parts 15.109(a) and 15.209 Radiated Emission Test Setup

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.

47 CFR FCC Parts 15.109(a) and 15.209 Radiated Emission Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A prescan was carried out to pick the worst emission frequencies from the EUT. For EUT which is a portable device, the prescan was carried out by rotating the EUT through three orthogonal axes to determine which altitude and equipment arrangement produces such emissions.
3. The test was carried out at the selected frequency points obtained from the prescan in step 2. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
 - a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
 - b. The EUT was then rotated to the direction that gave the maximum emission.
 - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
4. A Quasi-peak measurement was made for that frequency point if it was less than or equal to 1GHz. For frequency point that above 1GHz, both Peak and Average measurements were carried out.
5. Steps 3 and 4 were repeated for the next frequency point, until all selected frequency points were measured.
6. The frequency range covered was from 30MHz to 10th harmonics of the EUT fundamental frequency, using the Bi-log antenna for frequencies from 30MHz up to 1GHz, and the Horn antenna above 1GHz.

Sample Calculation Example

At 300 MHz	Q-P limit = 46.0 dB μ V/m
Log-periodic antenna factor & cable loss at 300 MHz = 18.5 dB	
Q-P reading obtained directly from EMI Receiver = 40.0 dB μ V/m (Calibrated level including antenna factors & cable losses)	
Therefore, Q-P margin = 46.0 - 40.0 = 6.0	i.e. 6.0 dB below Q-P limit



RADIATED EMISSION TEST

30MHz-1GHz

Radiated Emissions Test Setup (Front View)

Radiated Emissions Test Setup (Rear View)



RADIATED EMISSION TEST

1GHz – 26GHz

Radiated Emissions Test Setup (Front View)

Radiated Emissions Test Setup (Rear View)



RADIATED EMISSION TEST

47 CFR FCC Parts 15.109(a), 15.205 and 15.209 Radiated Emission Results

Test Input Power	120V 60Hz	Temperature	24°C
Test Distance	3m	Relative Humidity	56%
Non RF Mode	USB Playback (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Derrick Ng

Spurious Emissions ranging from 30MHz – 1GHz

Frequency (MHz)	Q-P Value (dBµV/m)	Q-P Limit (dBµV/m)	Q-P Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)
96.0220	40.7	43.5	2.8	226	271	H
294.9390	37.8	46.0	8.2	101	296	H
368.6240	40.7	46.0	5.3	101	346	H
442.3490	38.0	46.0	8.0	227	66	H
479.9730	44.8	46.0	1.2	101	10	V
516.0730	45.6	46.0	0.4	100	8	V

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)
3.6012	46.2	74.0	27.8	--	--	--	100	2	V
3.6013	48.3	74.0	25.7	--	--	--	100	24	H
5.4970	48.8	74.0	25.2	--	--	--	100	19	V
5.5410	49.0	74.0	25.0	--	--	--	100	13	H
6.6213	51.0	74.0	23.0	--	--	--	100	7	V
6.9520	51.3	74.0	22.7	--	--	--	100	45	H

Test Input Power	120V 60Hz	Temperature	24°C
Test Distance	3m	Relative Humidity	56%
Data Rate	EDR 3Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Derrick Ng

Spurious Emissions ranging from 30MHz – 1GHz

Frequency (MHz)	Q-P Value (dBµV/m)	Q-P Limit (dBµV/m)	Q-P Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Channel
73.7440	36.3	40.0	3.7	100	210	V	39
96.0220	37.0	43.5	6.5	100	270	V	39
288.0070	38.1	46.0	7.9	100	268	H	39
516.0930	45.1	46.0	0.9	100	10	V	39
575.9950	36.6	46.0	9.4	100	331	V	39
737.2490	40.6	46.0	5.4	100	33	H	39



RADIATED EMISSION TEST

47 CFR FCC Parts 15.109(a), 15.205 and 15.209 Radiated Emission Results

Test Input Power	120V 60Hz	Temperature	24°C
Test Distance	3m	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Derrick Ng

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0000	49.8	74.0	24.2	--	--	--	100	312	H	0
1.1620	45.5	74.0	28.5	--	--	--	100	95	H	0
1.5364	51.5	74.0	22.5	--	--	--	100	29	H	0
1.6073	48.5	74.0	25.5	--	--	--	100	13	H	0
1.9817	45.8	74.0	28.2	--	--	--	100	329	H	0
4.8053	53.5	74.0	20.5	45.6	54.0	8.4	100	227	V	0

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0000	46.4	74.0	27.6	--	--	--	100	52	H	39
1.5364	51.6	74.0	22.4	--	--	--	100	14	H	39
1.5769	48.1	74.0	25.9	--	--	--	100	13	H	39
1.5971	47.8	74.0	26.2	--	--	--	100	16	H	39
1.9918	46.2	74.0	27.8	--	--	--	100	133	H	39
4.8862	52.2	74.0	21.8	41.3	54.0	12.7	100	216	V	39

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1000.0	47.3	74.0	26.7	--	--	--	100	7	H	78
1536.4	52.4	74.0	21.6	--	--	--	100	25	H	78
1607.2	46.4	74.0	27.6	--	--	--	100	16	H	78
1647.7	46.9	74.0	27.1	--	--	--	100	11	H	78
1991.8	46.2	74.0	27.8	--	--	--	100	134	H	78
4967.1	52.9	74.0	21.1	40.5	54.0	19.5	100	213	V	78



RADIATED EMISSION TEST

47 CFR FCC Parts 15.109(a), 15.205 and 15.209 Radiated Emission Results

Test Input Power	120V 60Hz	Temperature	24°C
Test Distance	3m	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Derrick Ng

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	PoI (H/V)	Ch
1.0101	45.1	74.0	28.9	--	--	--	100	301	H	0
1.1619	45.2	74.0	28.8	--	--	--	100	62	V	0
1.5566	53.3	74.0	20.7	42.9	54.0	11.1	100	14	H	0
1.5971	48.9	74.0	25.1	--	--	--	100	18	H	0
1.6578	45.1	74.0	28.9	--	--	--	100	7	H	0
4.8052	52.4	74.0	21.6	--	--	--	100	227	V	0

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	PoI (H/V)	Ch
1.0000	47.6	74.0	26.4	--	--	--	100	316	H	39
1.1518	45.0	74.0	29.0	--	--	--	100	113	H	39
1.5566	50.7	74.0	23.3	--	--	--	100	20	H	39
1.6173	47.5	74.0	26.5	--	--	--	100	13	H	39
2.0019	45.9	74.0	28.1	--	--	--	100	188	H	39
4.8862	51.4	74.0	22.6	--	--	--	100	216	V	39

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	PoI (H/V)	Ch
1.0000	47.8	74.0	26.2	--	--	--	100	309	H	78
1.5465	54.3	74.0	19.7	43.3	54.0	10.7	100	16	H	78
1.6275	46.7	74.0	27.3	--	--	--	100	16	H	78
1.6578	49.3	74.0	24.7	--	--	--	100	23	H	78
1.9817	46.9	74.0	27.1	--	--	--	100	321	H	78
4.9671	52.2	74.0	21.8	--	--	--	100	213	V	78



RADIATED EMISSION TEST

47 CFR FCC Parts 15.109(a), 15.205 and 15.209 Radiated Emission Results

Test Input Power	120V 60Hz	Temperature	24°C
Test Distance	3m	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Derrick Ng

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0000	48.3	74.0	25.7	--	--	--	100	224	H	0
1.5364	51.2	74.0	22.8	--	--	--	100	13	H	0
1.5566	51.0	74.0	23.0	--	--	--	100	32	H	0
1.6072	48.0	74.0	26.0	--	--	--	100	14	H	0
1.9817	47.1	74.0	26.9	--	--	--	100	320	H	0
4.8052	51.9	74.0	22.1	--	--	--	100	228	V	0

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0101	48.5	74.0	25.5	--	--	--	100	357	H	39
1.1619	44.7	74.0	29.3	--	--	--	100	114	H	39
1.5566	52.0	74.0	22.0	--	--	--	100	20	H	39
1.6173	46.8	74.0	27.2	--	--	--	100	10	H	39
1.6477	48.3	74.0	25.7	--	--	--	100	106	H	39
4.8862	52.7	74.0	21.3	--	--	--	100	215	V	39

Spurious Emissions above 1GHz – 26GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 2	AV Limit (dBµV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0000	47.8	74.0	26.2	--	--	--	191	250	H	78
1.1619	44.8	74.0	29.2	--	--	--	100	101	H	78
1.5465	52.6	74.0	21.4	--	--	--	100	16	H	78
1.6072	46.0	74.0	28.0	--	--	--	100	11	H	78
1.9918	44.9	74.0	29.1	--	--	--	100	356	H	78
4.9671	52.7	74.0	21.3	--	--	--	100	213	V	78



RADIATED EMISSION TEST

Notes

1. All possible modes of operation were investigated. Only the worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. As the measured peak shows compliance to the average limit, as such no average measurement was required.
3. Quasi-peak measurement was used for frequency measurement up to 1GHz. Average and peak measurements were used for emissions above 1GHz. The average measurement was done by averaging over a complete cycle of the pulse train, including the blanking interval as the pulse train duration does not exceed 0.1 second.
4. A "positive" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency. Conversely, a "negative" margin indicates a FAIL.
5. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:
30MHz - 1GHz
RBW: 120kHz VBW: 1MHz
>1GHz
RBW: 1MHz VBW: 1MHz
6. The upper frequency of radiated emission investigations was according to requirements stated in Section 15.33(a) for intentional radiators & Section 15.33(b) for unintentional radiators.
7. The channel in the table refers to the transmit channel of the EUT.
8. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25GHz is ± 4.0 dB.





CARRIER FREQUENCY SEPARATION TEST

47 CFR FCC Part 15.247(a)(1) Carrier Frequency Separation Limits

The EUT shows compliance to the requirements of this section, which states the adjacent carrier frequencies must be separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, the EUT may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW (21dBm).

47 CFR FCC Part 15.247(a)(1) Carrier Frequency Separation Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(a)(1) Carrier Frequency Separation Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(a)(1) Carrier Frequency Separation Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with frequency hopping sequence on.
2. The start and stop frequencies of the spectrum analyser were set to 2.400GHz and 2.405GHz.
3. The spectrum analyser was set to max hold to capture the two adjacent transmitting frequencies within the span. The signal capturing was continuous until no further signals were detected.
4. The carrier frequency separation of the two adjacent transmitting / operating frequency was measured by finding the carrier frequency difference between the two adjacent channels.
5. The steps 2 to 4 were repeated with the following start and stop frequencies settings:
 - a. 2.4385GHz to 2.4435GHz
 - b. 2.478GHz to 2.481GHz



CARRIER FREQUENCY SEPARATION TEST

Carrier Frequency Separation Test Setup


47 CFR FCC Part 15.247(a)(1) Carrier Frequency Separation Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	1 – 4	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit


Adjacent Channels	Channel Separation (MHz)
0 and 1 (2.402GHz and 2.403GHz)	1.000
38 and 39 (2.440GHz and 2.441GHz)	1.000
39 and 40 (2.441GHz and 2.442GHz)	1.000
77 and 78 (2.479GHz and 2.480GHz)	1.005

CARRIER FREQUENCY SEPARATION TEST

Carrier Frequency Separation Plots




Plot 1 - Channels 0 (lower ch) and 1 (ch after lower ch) Separation




Plot 2 - Channels 38 (preceding mid ch) and 39 (mid ch) Separation

CARRIER FREQUENCY SEPARATION TEST

Carrier Frequency Separation Plots



Plot 3 - Channels 39 (*mid ch*) and 40 (*ch after mid ch*) Separation



Plot 4 - Channels 77 (*preceding upper ch*) and 78 (*upper ch*) Separation



SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

47 CFR FCC Part 15.247(a)(1) Spectrum Bandwidth (20dB Bandwidth Measurement) Limits

The EUT shows compliance to the requirements of this section, which states that the 20dB bandwidth of the hopping channel shall be the channel frequency separation by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

47 CFR FCC Part 15.247(a)(1) Spectrum Bandwidth (20dB Bandwidth Measurement) Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(a)(1) Spectrum Bandwidth (20dB Bandwidth Measurement) Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 10kHz and 30kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(a)(1) Spectrum Bandwidth (20dB Bandwidth Measurement) Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, non-hopping with transmitting frequency at Channel 0 (2.402GHz) (*lower ch*).
2. The center frequency of the spectrum analyser was set to the transmitting frequency with the frequency span wide enough to capture the 20dB bandwidth of the transmitting frequency.
3. The spectrum analyser was set to max hold to capture the transmitting frequency. The signal capturing was continuous until no further changes were observed.
4. The peak of the transmitting frequency was detected with the marker peak function of the spectrum analyser. The frequencies below the 20dB peak frequency at lower (f_L) and upper (f_H) sides of the transmitting frequency were marked and measured by using the marker-delta function of the spectrum analyser.
5. The 20dB bandwidth of the transmitting frequency is the frequency difference between the marked lower and upper frequencies, $|f_H - f_L|$.
6. The steps 2 to 5 were repeated with the transmitting frequency was set to Channel 39 (2.441GHz) (*mid ch*) and Channel 78 (2.480GHz) (*upper ch*) respectively.



SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Test Setup





SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

47 CFR FCC Part 15.247(a)(1) Spectrum Bandwidth (20dB Bandwidth Measurement) Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	5 – 7	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

Channel	Channel Frequency (GHz)	20dB Bandwidth (MHz)
0 (lower ch)	2.402	0.968
39 (mid ch)	2.441	0.938
78 (upper ch)	2.480	0.953

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	8 – 10	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit


Channel	Channel Frequency (GHz)	20dB Bandwidth (MHz)
0 (lower ch)	2.402	1.332
39 (mid ch)	2.441	1.324
78 (upper ch)	2.480	1.324

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	11– 13	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit


Channel	Channel Frequency (GHz)	20dB Bandwidth (MHz)
0 (lower ch)	2.402	1.332
39 (mid ch)	2.441	1.332
78 (upper ch)	2.480	1.332

SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 1Mbps



Plot 5 – Channel 0 (lower ch)




Plot 6 – Channel 39 (mid ch)



SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 1Mbps




Plot 7 – Channel 78 (upper ch)




SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 2Mbps




Plot 8 – Channel 0 (lower ch)



Plot 9 – Channel 39 (mid ch)

SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 2Mbps




Plot 10 – Channel 78 (upper ch)




SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 3Mbps




Plot 11 – Channel 0 (lower ch)



Plot 12 – Channel 39 (mid ch)

SPECTRUM BANDWIDTH (20dB BANDWIDTH MEASUREMENT) TEST

Spectrum Bandwidth (20dB Bandwidth Measurement) Plots – 3Mbps



Plot 13 – Channel 78 (upper ch)

SUD



NUMBER OF HOPPING FREQUENCIES TEST

47 CFR FCC Part 15.247(a)(1)(iii) Number of Hopping Frequencies Limits

The EUT shows compliance to the requirements of this section, which states the EUT shall use at least 15 channels.

47 CFR FCC Part 15.247(a)(1)(iii) Number of Hopping Frequencies Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(a)(1)(iii) Number of Hopping Frequencies Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(a)(1)(iii) Number of Hopping Frequencies Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with frequency hopping sequence on.
2. The start and stop frequencies of the spectrum analyser were set to 2.39GHz and 2.42GHz.
3. The spectrum analyser was set to max hold to capture all the transmitting frequencies within the span. The signal capturing was continuous until all the transmitting frequencies were captured and no further signals were detected.
4. The numbers of transmitting frequencies were counted and recorded.
5. The steps 2 to 4 were repeated with the following start and stop frequencies settings:
 - a. 2.420GHz to 2.441GHz
 - b. 2.441GHz to 2.461GHz
 - c. 2.461GHz to 2.4835GHz
6. The total number of hopping frequencies is the sum of the number of the hopping frequencies found for each span.



NUMBER OF HOPPING FREQUENCIES TEST

Number of Hopping Frequencies Test Setup

47 CFR FCC Part 15.247(a)(1)(iii) Number of Hopping Frequencies Results


Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	14 – 17	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

The EUT was found to have 79 hopping frequencies. Please refer to the attached plots.




NUMBER OF HOPPING FREQUENCIES TEST

Number Of Hopping Frequencies Plots




Plot 14 - Channels 0 to 18




Plot 15 - Channels 18 to 39

NUMBER OF HOPPING FREQUENCIES TEST

Number Of Hopping Frequencies Plots



Plot 16 - Channels 39 to 59



Plot 17 - Channels 59 to 78



AVERAGE FREQUENCY DWELL TIME TEST

47 CFR FCC Part 15.247(a)(1)(iii) Average Frequency Dwell Time Limits

The EUT shows compliance to the requirements of this section, which states the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

47 CFR FCC Part 15.247(a)(1)(iii) Average Frequency Dwell Time Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(a)(1)(iii) Average Frequency Dwell Test Setup


1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 1MHz and 3MHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(a)(1)(iii) Average Frequency Dwell Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with frequency hopping sequence on.
2. The center frequency of the spectrum analyser was set to 2.402GHz (*lower ch*) with zero frequency span (spectrum analyser acts as an oscilloscope).
3. The sweep time of the spectrum analyser was adjusted until a stable signal can be seen on the spectrum analyser.
4. The duration (dwell time) of a packet was measured using the marker-delta function of the spectrum analyser. The average dwell time of the transmitting frequency was computed based on general expression as shown below:
$$\text{Average Frequency Dwell Time} = \frac{\text{measured time slot length} \times \text{hopping rate}}{\text{number of hopping channels}} \times [0.4 \times \text{number of hopping channels}]$$
5. The steps 2 to 4 were repeated with the center frequency of the spectrum analyser were set to 2.441GHz (*mid ch*) and 2.4835GHz (*upper ch*) respectively.



AVERAGE FREQUENCY DWELL TIME TEST





AVERAGE FREQUENCY DWELL TIME TEST

47 CFR FCC Part 15.247(a)(1)(iii) Average Frequency Dwell Time Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	18 – 20	Relative Humidity	60%
Hopping Rate	1600 hops / s	Atmospheric Pressure	1030mbar
Number of Hopping Channels	79 channels	Tested By	Chang Wai Kit
Data Rate	BDR 1Mbps		

Channel	Channel Frequency (GHz)	Measured Time Slot Length (ms)	Average Frequency Dwell Time (s)	Average Occupancy Limit (s)
0 (lower ch)	2.402	1.2500	0.200	0.4
39 (mid ch)	2.441	1.2500	0.200	0.4
78 (upper ch)	2.480	1.2375	0.198	0.4

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	21 – 23	Relative Humidity	60%
Hopping Rate	533.3 hops / s	Atmospheric Pressure	1030mbar
Number of Hopping Channels	79 channels	Tested By	Chang Wai Kit
Data Rate	EDR 2Mbps		

Channel	Channel Frequency (GHz)	Measured Time Slot Length (ms)	Average Frequency Dwell Time (s)	Average Occupancy Limit (s)
0 (lower ch)	2.402	2.5125	0.134	0.4
39 (mid ch)	2.441	2.5125	0.134	0.4
78 (upper ch)	2.480	2.5125	0.134	0.4

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	24 – 26	Relative Humidity	60%
Hopping Rate	320 hops / s	Atmospheric Pressure	1030mbar
Number of Hopping Channels	79 channels	Tested By	Chang Wai Kit
Data Rate	EDR 3Mbps		


Channel	Channel Frequency (GHz)	Measured Time Slot Length (ms)	Average Frequency Dwell Time (s)	Average Occupancy Limit (s)
0 (lower ch)	2.402	3.7500	0.120	0.4
39 (mid ch)	2.441	3.7500	0.120	0.4
78 (upper ch)	2.480	3.7500	0.120	0.4

Notes


- The EUT operates based on 1-slot transmission and 1-slot reception basis. As such, there are [1600 / (1 + 1)] transmissions per second and the time occupancy per channel is [measured time slot length / 2].
- Average Frequency Dwell Time = [measured time slot length / 2 x hopping rate / 2 / number of hopping channels] x [0.4 x number of hopping channels]

AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - BDR 1Mbps



Plot 18 – Channel 0 (lower ch)




Plot 19 – Channel 39 (mid ch)



AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - BDR 1Mbps




Plot 20 – Channel 78 (upper ch)






AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - EDR 2Mbps



Plot 21 – Channel 0 (lower ch)




Plot 22 – Channel 39 (mid ch)



AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - EDR 2Mbps




Plot 23 – Channel 78 (upper ch)




AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - EDR 3Mbps



Plot 24 – Channel 0 (lower ch)




Plot 25 – Channel 39 (mid ch)



AVERAGE FREQUENCY DWELL TIME TEST

Average Frequency Dwell Time Plots - EDR 3Mbps



Plot 26 - Channel 78 (upper ch)





MAXIMUM PEAK POWER TEST

47 CFR FCC Part 15.247(b)(1) Maximum Peak Power Limits

The EUT shows compliance to the requirements of this section, which states the EUT employing at least 75 non-overlapping hopping channels shall not exceed 1W (30dBm). For the EUT employs other frequency hopping systems, the peak power shall not greater than 0.125W (21dBm).

47 CFR FCC Part 15.247(b)(1) Maximum Peak Power Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Boonton RF Power Meter	4532	72901	13 Dec 2013
Boonton Power Sensor	56218-S/1	32097	13 Dec 2013

47 CFR FCC Part 15.247(b)(1) Maximum Peak Power Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the Universal Radio Communication Tester, which set into power analyser mode via a low-loss coaxial cable.
4. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(b)(1) Maximum Peak Power Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, non-hopping with transmitting frequency at Channel 0 (2.402GHz) (*lower ch*).
2. The maximum peak power of the transmitting frequency was detected and recorded.
3. The Equivalent Isotropic Radiated Power (EIRP) of the EUT was computed by adding its antenna gain to the measured maximum peak power.
4. The steps 2 to 3 were repeated with the transmitting frequency was set to Channel 39 (2.441GHz) (*mid ch*) and Channel 78 (2.480GHz) (*upper ch*) respectively.



MAXIMUM PEAK POWER TEST

Maximum Peak Power Test Setup

47 CFR FCC Part 15.247(b)(1) Maximum Peak Power Results

Test Input Power	120V 60Hz	Temperature	26°C
Antenna Gain	2.0 dBi	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

Channel	Channel Frequency (GHz)	Data Rate (Mbps)	Maximum Peak Power (W)	Maximum EIRP (W)	Limit (W)
0 (lower ch)	2.402	1.0	0.0016	0.0025	1.0
39 (mid ch)	2.441		0.0016	0.0025	1.0
78 (upper ch)	2.480		0.0016	0.0025	1.0
0 (lower ch)	2.402	2.0	0.0012	0.0019	1.0
39 (mid ch)	2.441		0.0012	0.0019	1.0
78 (upper ch)	2.480		0.0012	0.0019	1.0
0 (lower ch)	2.402	3.0	0.0012	0.0019	1.0
39 (mid ch)	2.441		0.0012	0.0019	1.0
78 (upper ch)	2.480		0.0012	0.0019	1.0



RF CONDUCTED SPURIOUS EMISSIONS TEST

47 CFR FCC Part 15.247(d) RF Conducted Spurious Emissions Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

47 CFR FCC Part 15.247(d) RF Conducted Spurious Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(d) RF Conducted Spurious Emissions Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) RF Conducted Spurious Emissions Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, non-hopping with transmitting frequency at Channel 0 (2.402GHz) (*lower ch*).
2. The start and stop frequencies of the spectrum analyser were set to 30MHz and 10GHz.
3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
4. The steps 2 to 3 were repeated with frequency span was set from 10GHz to 25GHz.
5. The steps 2 to 4 were repeated with the transmitting frequency was set to Channel 39 (2.441GHz) (*mid ch*) and Channel 78 (2.480GHz) (*upper ch*) respectively.



RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Test Setup

47 CFR FCC Part 15.247(d) RF Conducted Spurious Emissions Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	27 – 32	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

All spurious signals found were below the specified limit. Please refer to the attached plots.

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	33 – 38	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

All spurious signals found were below the specified limit. Please refer to the attached plots.


Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	39 – 44	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

All spurious signals found were below the specified limit. Please refer to the attached plots.




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - BDR 1Mbps



Plot 27 – Channel 0 (lower ch)




Plot 28 – Channel 0 (lower ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - BDR 1Mbps



Plot 29 – Channel 39 (mid ch)




Plot 30 – Channel 39 (mid ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - BDR 1Mbps



Plot 31 - Channel 78 (upper ch)




Plot 32 - Channel 78 (upper ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 2Mbps



Plot 33 – Channel 0 (lower ch)




Plot 34 – Channel 0 (lower ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 2Mbps



Plot 35 – Channel 39 (mid ch)




Plot 36 – Channel 39 (mid ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 2Mbps




Plot 37 - Channel 78 (upper ch)




Plot 38 - Channel 78 (upper ch)

RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 3Mbps



Plot 39 – Channel 0 (lower ch)




Plot 40 – Channel 0 (lower ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 3Mbps



Plot 41 – Channel 39 (mid ch)




Plot 42 – Channel 39 (mid ch)




RF CONDUCTED SPURIOUS EMISSIONS TEST

RF Conducted Spurious Emissions Plots - EDR 3Mbps



Plot 43 - Channel 78 (upper ch)



Plot 44 - Channel 78 (upper ch)



BAND EDGE COMPLIANCE (CONDUCTED) TEST

47 CFR FCC Part 15.247(d) Band Edge Compliance (Conducted) Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

47 CFR FCC Part 15.247(d) Band Edge Compliance (Conducted) Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(d) Band Edge Compliance (Conducted) Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) Band Edge Compliance (Conducted) Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with frequency hopping sequence on.
2. The frequency span of the spectrum analyser was set to wide enough to capture the lower band edge of the transmission band, 2.400GHz and any spurious emissions at the band edge.
3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
4. The steps 2 to 3 were repeated with the frequency span of the spectrum analyser was set to wide enough to capture the upper band edge frequency of the transmission band, 2.4835GHz and the any spurious emissions at the band-edge.



BAND EDGE COMPLIANCE (CONDUCTED) TEST

Band Edge Compliance (Conducted) Test Setup

47 CFR FCC Part 15.247(d) Band Edge Compliance (Conducted) Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	45 – 46	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

No significant signal was found and they were below the specified limit.

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	47 – 48	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

No significant signal was found and they were below the specified limit.


Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	49 – 50	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

No significant signal was found and they were below the specified limit.




BAND EDGE COMPLIANCE (CONDUCTED) TEST

Band Edge Compliance (Conducted) Plots - BDR 1Mbps



Plot 45 – Lower Band Edge at 2.4000GHz




Plot 46 – Upper Band Edge at 2.4835GHz




BAND EDGE COMPLIANCE (CONDUCTED) TEST

Band Edge Compliance (Conducted) Plots - EDR 2Mbps



Plot 47 – Lower Band Edge at 2.4000GHz




Plot 48 – Upper Band Edge at 2.4835GHz




BAND EDGE COMPLIANCE (CONDUCTED) TEST

Band Edge Compliance (Conducted) Plots - EDR 3Mbps



Plot 49 – Lower Band Edge at 2.4000GHz



Plot 50 – Upper Band Edge at 2.4835GHz



BAND EDGE COMPLIANCE (RADIATED) TEST

47 CFR FCC Part 15.247(d) Band Edge Compliance (Radiated) Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power. In addition, radiated emissions which fall in the restricted bands shall comply to the radiated emission limits specified in 15.209.

47 CFR FCC Part 15.247(d) Band Edge Compliance (Radiated) Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Rohde & Schwarz EMI Test Receiver (20Hz – 26.5GHz)	ESMI	848926/007 849182/003	24 Oct 2014
Eletro-Metrics Double Ridged Antenna (Horn) Antenna (1-18GHz)	EM-6961	6525	12 Apr 2014
Toyo MicroWave Preamplifier (1GHz - 8GHz)	TPA0108-40	0636	09 Jun 2014

47 CFR FCC Part 15.247(d) Band Edge Compliance (Radiated) Test Setup

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz to show compliance of spurious at band edges are at least 20dB below the carriers. For restricted band spurious at band edges, peak and average measurement plots were taken using the following setting:
 - a. Peak Plot:
RBW = VBW = 1MHz
 - b. Average Plot
RBW = 1MHz, VBW = 10Hz
4. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) Band Edge Compliance (Radiated) Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with frequency hopping sequence on.
2. The frequency span of the spectrum analyser was set to wide enough to capture the lower band edge of the transmission band, 2.400GHz and any spurious emissions at the band edge.
3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
4. The steps 2 to 3 were repeated with the frequency span of the spectrum analyser was set to wide enough to capture the upper band edge frequency of the transmission band, 2.4835GHz and the any spurious emissions at the band-edge.



BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Test Setup

47 CFR FCC Part 15.247(d) Band Edge Compliance (Radiated) Results

Test Input Power	230V 50Hz	Temperature	26°C
Attached Plots	51 – 56	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Kyaw Soe Hein

No significant signal was found and they were below the specified limit.

Test Input Power	230V 50Hz	Temperature	26°C
Attached Plots	57 – 62	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Kyaw Soe Hein


No significant signal was found and they were below the specified limit.

Test Input Power	230V 50Hz	Temperature	26°C
Attached Plots	63 - 68	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Kyaw Soe Hein


No significant signal was found and they were below the specified limit.

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - BDR 1Mbps




Plot 51 – Lower Band Edge at 2.4000GHz




Plot 52 – Upper Band Edge at 2.4835GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - BDR 1Mbps




Plot 53 – Peak Plot at Lower Band Edge at 2.4000GHz




Plot 54 – Average Plot at Lower Band Edge at 2.4000GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - BDR 1Mbps




Plot 55 – Peak Plot at Upper Band Edge at 2.4835GHz




Plot 56 – Average Plot at Upper Band Edge at 2.4835GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - EDR 2Mbps




Plot 57 – Lower Band Edge at 2.4000GHz




Plot 58 – Upper Band Edge at 2.4835GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - EDR 2Mbps




Plot 59 – Peak Plot at Lower Band Edge at 2.4000GHz




Plot 60 – Average Plot at Lower Band Edge at 2.4000GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - EDR 2Mbps




Plot 61 – Peak Plot at Upper Band Edge at 2.4835GHz




Plot 62 – Average Plot at Upper Band Edge at 2.4835GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - EDR 3Mbps




Plot 63 – Lower Band Edge at 2.4000GHz




Plot 64 – Upper Band Edge at 2.4835GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - EDR 3Mbps




Plot 65 – Peak Plot at Lower Band Edge at 2.4000GHz




Plot 66 – Average Plot at Lower Band Edge at 2.4000GHz

BAND EDGE COMPLIANCE (RADIATED) TEST

Band Edge Compliance (Radiated) Plots (Restricted Band) - EDR 3Mbps



Plot 67 – Peak Plot at Upper Band Edge at 2.4835GHz



Plot 68 – Average Plot at Upper Band Edge at 2.4835GHz



PEAK POWER SPECTRAL DENSITY TEST

47 CFR FCC Part 15.247(e) Peak Power Spectral Density Limits

The EUT shows compliance to the requirements of this section, which states the peak power spectral density conducted from the intentional radiator (EUT) to the antenna shall not be greater than 8dBm (6.3mW) in any 3kHz band during any time interval of continuous transmission.

47 CFR FCC Part 15.247(e) Peak Power Spectral Density Test Instrumentation

Instrument	Model	S/No	Cal Due Date
Agilent Spectrum Analyzer	E7405A	MY45106084	01 Aug 2014

47 CFR FCC Part 15.247(e) Peak Power Spectral Density Test Setup


1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum via a low-loss coaxial cable.
4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 3kHz and 10kHz.
5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(e) Peak Power Spectral Density Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, non-hopping with transmitting frequency at Channel 0 (2.402GHz) (*lower ch*).
2. The sweep time of the spectrum analyser was set to the value of the ratio of the frequency span divided by the RBW.
3. The peak power density of the transmitting frequency was detected and recorded.
4. The step 3 was repeated with the transmitting frequency was set to Channel 39 (2.441GHz) (*mid ch*) and Channel 78 (2.480GHz) (*upper ch*) respectively.



PEAK POWER SPECTRAL DENSITY TEST





PEAK POWER SPECTRAL DENSITY TEST

47 CFR FCC Part 15.247(e) Peak Power Spectral Density Results

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	69 – 71	Relative Humidity	60%
Data Rate	BDR 1Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)
0 (lower ch)	2.402	0.143	6.3
39 (mid ch)	2.441	0.142	6.3
78 (upper ch)	2.480	0.141	6.3

Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	72 – 74	Relative Humidity	60%
Data Rate	EDR 2Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)
0 (lower ch)	2.402	0.036	6.3
39 (mid ch)	2.441	0.036	6.3
78 (upper ch)	2.480	0.036	6.3


Test Input Power	120V 60Hz	Temperature	26°C
Attached Plots	75 – 77	Relative Humidity	60%
Data Rate	EDR 3Mbps	Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)
0 (lower ch)	2.402	0.035	6.3
39 (mid ch)	2.441	0.035	6.3
78 (upper ch)	2.480	0.034	6.3




PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - BDR 1Mbps



Plot 69 – Channel 0 (lower ch)




Plot 70 – Channel 39 (mid ch)



PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - BDR 1Mbps




Plot 71 - Channel 78 (upper ch)






PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - EDR 2Mbps



Plot 72 – Channel 0 (lower ch)




Plot 73 – Channel 39 (mid ch)



PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - EDR 2Mbps




Plot 74 – Channel 78 (upper ch)




PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - EDR 3Mbps



Plot 75 – Channel 0 (lower ch)




Plot 76 – Channel 39 (mid ch)



PEAK POWER SPECTRAL DENSITY TEST

Peak Power Spectral Density Plots - EDR 3Mbps



Plot 77 - Channel 78 (upper ch)





MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

47 CFR FCC Part 1.1310 Maximum Permissible Exposure (MPE) Limits

The EUT shows compliance to the requirements of this section, which states the MPE limits for general population / uncontrolled exposure are as shown below:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (min)
0.3 - 1.34	614	1.63	100 ^{Note 2}	30
1.34 - 30	824 / f	2.19 / f	180 / f ² Note 2	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f / 1500	30
1500 - 100000	-	-	1.0	30
Notes				
1.	f = frequency in MHz			
2.	Plane wave equivalent power density			

47 CFR FCC Part 1.1310 Maximum Permissible Exposure Computation

The power density at 20cm distance was computed from the following formula:

$$S = (30GP) / (377d^2)$$

where

- S = Power density in W/m²
- P = 0.0016W (maximum peak measured from Maximum Peak Power)
- d = Test distance at 0.2m
- G = Numerical isotropic gain, 1.59 (2.0dBi)

Substituting the relevant parameters into the formula:

$$S = [(30GP) / 377d^2]$$

$$= 0.0050 \text{ W/m}^2$$

$$= 0.0005 \text{ mW/cm}^2$$

∴ The power density of the EUT at 20cm distance is 0.005mW/cm² based on the above computation and found to be lower than the power density limit of 1.0mW/cm².



Please note that this Report is issued under the following terms :

1. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
2. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
3. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
5. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

July 2011

