

Panasonic Corporation of North America

RF TEST REPORT

Report Type:

FCC Part 15.407 RF report

Model:

EYFNH1WC, EYFNH1WP

REPORT NUMBER:

2412B2138SHA-002

ISSUE DATE:

March 21, 2025

DOCUMENT CONTROL NUMBER:

TTRF15.407_V1 © 2018 Intertek



APPLICANT: Panasonic Corporation of North America
Two Riverfront Plaza, NEWARK NJ 07102

MANUFACTURER: Panasonic Corporation
1006, Oaza Kadoma, Kadoma City, Osaka 571-8501, Japan

Factory: Panasonic Electric Works Electrical Construction Materials Mie Co., Ltd.
1668, Fujikata, Tsu city, Mie 514-8555, Japan

FCC ID: ACJ-EYFNH

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2021): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:

REVIEWED BY:



Project Engineer
Damon Ding



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Contents

REVISION HISTORY..... 5

MEASUREMENT RESULT SUMMARY 6

1 GENERAL INFORMATION 7

1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) 7

1.2 TECHNICAL SPECIFICATION 8

1.3 ANTENNA INFORMATION..... 8

1.4 DESCRIPTION OF TEST FACILITY 9

2 TEST SPECIFICATIONS..... 10

2.1 STANDARDS OR SPECIFICATION 10

2.2 MODE OF OPERATION DURING THE TEST..... 10

2.3 TEST SOFTWARE LIST 13

2.4 TEST PERIPHERALS LIST 13

2.5 TEST ENVIRONMENT CONDITION:..... 13

2.6 INSTRUMENT LIST 14

2.7 MEASUREMENT UNCERTAINTY 15

3 26 DB BANDWIDTH & 99% OCCUPIED BANDWIDTH 16

3.1 LIMIT 16

3.2 MEASUREMENT PROCEDURE 16

3.3 TEST CONFIGURATION 17

3.4 THE RESULTS OF 26 DB BANDWIDTH & 99% OCCUPIED BANDWIDTH..... 17

4 MINIMUM 6DB BANDWIDTH..... 18

4.1 LIMIT 18

4.2 MEASUREMENT PROCEDURE 18

4.3 TEST CONFIGURATION 18

4.4 THE RESULTS OF MINIMUM 6DB BANDWIDTH 18

5 MAXIMUM CONDUCTED OUTPUT POWER 19

5.1 LIMIT 19

5.2 MEASUREMENT PROCEDURE 20

5.3 TEST CONFIGURATION 20

5.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER..... 20

6 POWER SPECTRUM DENSITY 21

6.1 LIMIT 21

6.2 MEASUREMENT PROCEDURE 22

6.3 TEST CONFIGURATION 23

6.4 TEST RESULTS OF POWER SPECTRUM DENSITY 23

7 RADIATED EMISSIONS 24

7.1 LIMIT 24

7.2 MEASUREMENT PROCEDURE 25

7.3 TEST CONFIGURATION 26

7.4 TEST RESULTS OF RADIATED EMISSIONS 28

8 POWER LINE CONDUCTED EMISSION..... 32

TEST REPORT

| | | |
|-----------|--|-----------|
| 8.1 | LIMIT | 32 |
| 8.2 | TEST CONFIGURATION | 32 |
| 8.3 | MEASUREMENT PROCEDURE | 33 |
| 8.4 | TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... | 34 |
| 9 | FREQUENCY STABILITY..... | 35 |
| 9.1 | LIMIT | 35 |
| 9.2 | TEST RESULT..... | 35 |
| 10 | ANTENNA REQUIREMENT..... | 36 |

Revision History

| Report No. | Version | Description | Issued Date |
|------------------|---------|-------------------------|----------------|
| 2412B2138SHA-002 | Rev. 01 | Initial issue of report | March 21, 2025 |
| | | | |
| | | | |

Measurement result summary

| TEST ITEM | FCC REFERENCE | RESULT |
|--|-------------------------------|--------|
| 26 dB Bandwidth & 99% Occupied Bandwidth | 15.407(a) | Tested |
| Minimum 6dB Bandwidth | 15.407(e) | NA |
| Maximum Conducted Output Power | 15.407(a) | Pass |
| Power spectral density | 15.407(a) | Pass |
| Radiated emission | 15.407(b) 15.205 15.209 | Pass |
| Power line conducted emission | 15.407(b) 15.207 | NA |
| Frequency Stability | 15.407(g) | Pass |
| Antenna requirement | 15.203 | Pass |

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

| | |
|----------------------------|--|
| Product name: | Impact wrench |
| Type/Model: | EYFNH1WC, EYFNH1WP |
| Description of EUT: | The EUT is Impact wrench with WLAN function, There are two models. The difference between the two models is the shape of the tool's tip. We tested all of models and put the worst test data into this report. |
| Rating: | Battery Pack:18V,5.0Ah,90Wh |
| EUT type: | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing |
| Software Version: | / |
| Hardware Version: | / |
| Sample Identification No.: | 0241221-12 |
| Sample received date: | January 30, 2025 |
| Date of test: | January 30, 2025~ March 21, 2025 |

1.2 Technical Specification

| | |
|---------------------|--|
| Frequency Range: | 5180 ~ 5240MHz |
| Support Standards: | 802.11a, 802.11n(HT20) |
| Type of Modulation: | OFDM |
| Channel Number: | For 5180 ~ 5240MHz band: Channel 36 - 48 |

1.3 Antenna information

| Antenna information: | | | |
|----------------------|--------------|----------|------|
| No. | Antenna Type | Gain | Note |
| 1 | PCB Antenna | -0.97dBi | |
| | | | |
| Note: | | | |

1.4 Frequency List:

FCC

| 802.11a/n(HT20) | | | | | |
|-----------------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 36 | 5180MHz | 40 | 5200MHz | 44 | 5220MHz |
| 48 | 5240MHz | | | | |

TEST REPORT**1.5 Description of Test Facility**

| | |
|-------------------|--|
| Name: | Intertek Testing Services (Shanghai FTZ) Co., Ltd. |
| Address: | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200 |
| Telefax: | 86 21 54262353 |

| | |
|--|--|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab Registration No. CNAS L21189 |
| | FCC Accredited Lab Designation Number: CN0175 |
| | IC Registration Lab CAB identifier.: CN0014 |
| | VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252) |
| | A2LA Accreditation Lab Certificate Number: 3309.02 |

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2023)

ANSI C63.10 (2020)

KDB 558074 (v05r02)

2.2 Mode of operation during the test

While testing transmitting mode of EUT, the continuously transmission was applied by following software.

| Software name | Manufacturer | Version | Supplied by |
|---------------|--------------|---------|-------------|
| Teraterm | - | 4.106 | applicant |

The lowest, middle and highest channel for the following modes were tested as representatives.

| Frequency Band (MHz) | Mode | Lowest (MHz) | Middle (MHz) | Highest (MHz) |
|----------------------|---------------|--------------|--------------|---------------|
| 5180 - 5240 | 802.11a | 5180 | 5200 | 5240 |
| | 802.11n(HT20) | 5180 | 5200 | 5240 |

TEST REPORT

| Power Setting parameter | | | | |
|-------------------------|----------------|--------|--------|---------|
| Mode | Channel | | | |
| | Frequency Band | Lowest | Middle | Highest |
| 802.11a | 5180-5240MHz | 4 | 4 | 4 |
| 802.11n(HT20) | | 4 | 4 | 4 |

TEST REPORT**Data rate and Power setting:**

The pre-scan for the conducted power with all data rates in each modulation and band was used, and the worst case was found and used in all test cases. After this pre-scan, we choose the following table of the data rate as the worst case.

| Frequency Band (MHz) | Mode | Worst case data rate |
|----------------------|---------------|----------------------|
| 5180 - 5240 | 802.11a | 6Mbps |
| | 802.11n(HT20) | MCS0 |

TEST REPORT

2.3 Test software list

| Test Items | Software | Manufacturer | Version |
|--------------------|----------|--------------|---------|
| Conducted emission | ESxS-K1 | R&S | V2.1.0 |
| Radiated emission | ES-K1 | R&S | V1.71 |

2.4 Test peripherals list

| Item No. | Name | Band and Model | Description |
|----------|-----------------|----------------|-------------------------|
| 1 | Laptop computer | DELL 5480 | - |
| 2 | RF cable | / | 0.2m length; 0.5dB loss |

2.5 Test environment condition:

| Test items | Temperature | Humidity |
|--|-------------|----------|
| 26 dB Bandwidth & 99% Occupied Bandwidth | 25°C | 50% RH |
| Minimum 6dB Bandwidth | | |
| Maximum Conducted Output Power | | |
| Power spectral density | | |
| Radiated Emissions in restricted frequency bands | 24°C | 50%RH |
| Power line conducted emission | 25°C | 49%RH |

2.6 Instrument list

| Conducted Emission/Disturbance Power/Tri-loop Test/CDN method | | | | | |
|---|-----------------------------|-------------------|------------------------|--------------|------------|
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Test Receiver | R&S | ESCS 30 | EC 2107 | 2025-07-15 |
| <input checked="" type="checkbox"/> | A.M.N. | R&S | ESH2-Z5 | EC 3119 | 2025-11-30 |
| <input type="checkbox"/> | A.M.N. | R&S | ENV 216 | EC 3393 | 2025-07-04 |
| <input type="checkbox"/> | A.M.N. | R&S | ENV4200 | EC 3558 | 2025-06-10 |
| Radiated Emission | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Test Receiver | R&S | ESIB 26 | EC 3045 | 2025-10-19 |
| <input checked="" type="checkbox"/> | Bilog Antenna | TESEQ | CBL 6112D | EC 6411 | 2025-08-06 |
| <input checked="" type="checkbox"/> | TRILOG broadband Antenna | Schwarzbeck | VULB9168 | EC6402 | 2026-01-17 |
| <input checked="" type="checkbox"/> | Pre-amplifier | R&S | AFS42-00101800-25-S-42 | EC5262 | 2025-06-09 |
| <input checked="" type="checkbox"/> | Pre-amplifier | tonscend | tap01018050 | EC 6432-1 | 2025-12-26 |
| <input checked="" type="checkbox"/> | Horn antenna | tonscend | bha9120d | EC 6432-2 | 2025-01-09 |
| <input checked="" type="checkbox"/> | Horn antenna | ETS | 3117 | EC 4792-1 | 2025-08-28 |
| <input checked="" type="checkbox"/> | Horn antenna | ETS | 3116C | EC 5955 | 2025-06-17 |
| <input checked="" type="checkbox"/> | Horn antenna | TOYO | HAP18-26W | EC 4792-3 | 2025-07-08 |
| <input type="checkbox"/> | Active loop antenna | Schwarzbeck | FMZB1519 | EC 5345 | 2025-04-24 |
| RF test | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | PXA Signal Analyzer | Keysight | N9030A | EC 5338 | 2026-03-05 |
| <input type="checkbox"/> | Power sensor | Agilent | U2021XA | EC 5338-1 | 2026-03-05 |
| <input type="checkbox"/> | Vector Signal Generator | Agilent | N5182B | EC 5175 | 2026-03-05 |
| <input type="checkbox"/> | Spectrum analyzer | R&S | CMW500 | EC5944 | 2025-12-22 |
| <input type="checkbox"/> | MXG Analog Signal Generator | Agilent | N5181A | EC 5338-2 | 2026-03-05 |
| <input type="checkbox"/> | Mobile Test System | Litepoint | lqxel | EC 5176 | 2026-01-08 |
| <input type="checkbox"/> | Test Receiver | R&S | ESCI 7 | EC 4501 | 2025-09-12 |
| Tet Site | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Shielded room | Zhongyu | - | EC 2838 | 2026-01-14 |
| <input type="checkbox"/> | Shielded room | Zhongyu | - | EC 2839 | 2026-01-14 |
| <input checked="" type="checkbox"/> | Semi-anechoic chamber | Albatross project | - | EC 3048 | 2025-07-31 |
| <input type="checkbox"/> | Fully-anechoic chamber | Albatross project | - | EC 3047 | 2025-07-31 |
| Additional instrument | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 3783 | 2026-02-28 |

TEST REPORT

| | | | | | |
|-------------------------------------|-------------------|--------|-----------------|---------|------------|
| <input type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 2122 | 2026-03-11 |
| <input checked="" type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 5198 | 2026-01-18 |
| <input checked="" type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 3326 | 2026-03-28 |
| <input type="checkbox"/> | Pressure meter | YM3 | Shanghai Mengde | EC 3320 | 2025-07-01 |

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Test item | Measurement uncertainty |
|---|-------------------------|
| Maximum peak output power | $\pm 0.74\text{dB}$ |
| Radiated Emissions in restricted frequency bands below 1GHz | $\pm 4.90\text{dB}$ |
| Radiated Emissions in restricted frequency bands above 1GHz | $\pm 5.02\text{dB}$ |
| Emission outside the frequency band | $\pm 2.89\text{dB}$ |
| Power line conducted emission | $\pm 3.19\text{dB}$ |

TEST REPORT**3 26 dB Bandwidth & 99% Occupied Bandwidth****Test result: Tested****3.1 Limit**

None

3.2 Measurement Procedure

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

26 dB Bandwidth


- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

99% Occupied Bandwidth

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

3.3 Test Configuration



3.4 The results of 26 dB Bandwidth & 99% Occupied Bandwidth

Please refer to Appendix A1, A2.

TEST REPORT

4 Minimum 6dB Bandwidth

Test result: NA

4.1 Limit

For systems using digital modulation techniques that may operate in the 5725 - 5850 MHz band, the minimum 6 dB bandwidth shall be at least 500 kHz.


4.2 Measurement Procedure

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

4.3 Test Configuration



4.4 The results of Minimum 6dB Bandwidth

Please refer to Appendix A1, A2.

5 Maximum conducted output power

Test result: Pass

5.1 Limit

For an outdoor access point operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W provided the maximum antenna gain does not exceed 6dBi.

The maximum e.i.r.p. at any elevation angle above 30 degrees from the horizon must not exceed 125mW (21 dBm).

For an indoor access point operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6dBi.

For fixed point-to-point access points operating in the band 5.15-5.25GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W.

For client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. (FCC Limit)

For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or 11dBm + 10logB, where B is the 26dB emission bandwidth in megahertz. (FCC limit)

For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1W. (FCC limit)

For Frequency Band 5150-5250 MHz, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log10B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. (IC limit)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 99% emission bandwidth in megahertz. (IC limit)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log10B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. (IC limit)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. (IC limit)

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


TEST REPORT

5.2 Measurement Procedure

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW ≥ 3 MHz.
- (iv) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle < 98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.”
- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

5.3 Test Configuration



5.4 Test Results of Maximum conducted output power

Please refer to Appendix C.

6 Power spectrum density

Test result: Pass

6.1 Limit

For an outdoor access point operating in the band 5.15-5.25GHz, the maximum power spectral density shall not exceed 17dBm in any 1 megahertz band.

For an indoor access point operating in the band 5.15-5.25GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

For client devices in the 5.15-5.25GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (FCC limit)

For the 5.25-5.35 GHz and 5.47-5.725GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (FCC limit)

For the band 5.725-5.85GHz, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. (FCC limit)

For the 5.15-5.25GHz band, the e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band. (IC limit)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. (IC limit)

For the 5.725-5.85GHz band, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. (IC limit)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the less of original and original + (6 - antenna gain - beamforming gain).


6.2 Measurement Procedure

The EUT was tested according to test procedure of “KDB789033 D02 General UNII Test Procedures New Rules”

1. Create an average power spectrum for the EUT operating mode being tested by following the instructions in II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power....” (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
2. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
3. Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) If Method SA-2 or SA-2 Alternative was used, add $10 \log (1/x)$, where x is the duty cycle, to the peak of the spectrum.
 - b) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
4. The result is the Maximum PSD over 1 MHz reference bandwidth.
5. For devices operating in the bands 5.15 5.25 GHz, 5.25 5.35 GHz, and 5.47 5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in Section 15.407(a)(5). For devices operating in the band 5.725 5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 - a) Set $RBW \geq 1/T$, where T is defined in II.B.I.a).
 - b) Set $VBW \geq 3 RBW$.
 - c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 - d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 - e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for steps 5.c) and 5.d) above, since $RBW=100 \text{ KHZ}$ is available on nearly all spectrum analyzers.

6.3 Test Configuration



6.4 Test Results of Power spectrum density

Please refer to Appendix D.

TEST REPORT

7 Radiated Emissions

Test result: Pass

7.1 Limit

The radiated emissions which fall in the restricted bands, and the radiated emissions below 1GHz, must comply with the radiated emission limits specified showed as below:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

The radiated emissions which fall outside the restrict bands, should comply with the EIRP limit as below:

For transmitters operating in the 5.15 - 5.25 / 5.25 - 5.35 / 5.47 - 5.725GHz band:

| Frequency (MHz) | EIRP Limit (dBm) | Equivalent Field Strength (3m) (dBμV/m) |
|-----------------|------------------|---|
| <5150 | -27 | 68.20 |
| >5350 | | |
| <5470 | | |
| >5725 | | |

For transmitters operating in the 5.725 - 5.85GHz band:

| Frequency (MHz) | EIRP Limit (dBm/MHz) | Equivalent Field Strength (3m) (dBμV/m) |
|-----------------|----------------------|---|
| <5650 | -27 | 68.20 |
| 5650 ~ 5700 | -27 ~ 10 | 68.20 ~ 105.20 |
| 5700 ~ 5720 | 10 ~ 15.6 | 105.20 ~ 110.80 |
| 5720 ~ 5725 | 15.6 ~ 27 | 110.80 ~ 122.20 |
| 5850 ~ 5855 | 27 ~ 15.6 | 122.20 ~ 110.80 |
| 5855 ~ 5875 | 15.6 ~ 10 | 110.80 ~ 105.20 |
| 5875 ~ 5925 | 10 ~ -27 | 105.20 ~ 68.20 |
| >5925 | -27 | 68.20 |

TEST REPORT

7.2 Measurement Procedure

For Radiated emission below 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to peak or quasi-peak detect function and specified bandwidth with maximum hold mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to peak or quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


Note:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for peak or quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz at frequency above 1GHz for peak detection above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 3 x RBW (Duty cycle $\geq 98\%$) for average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.


TEST REPORT

7.3 Test Configuration

For Radiated emission below 30MHz:




For Radiated emission 30MHz to 1GHz:



TEST REPORT



For Radiated emission above 1GHz:



TEST REPORT

7.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



TEST REPORT

Test data below 1GHz

| Antenna | Frequency (MHz) | Limit (dBuV/m) | Level (dBuV/m) | Margin (dB) | Detector |
|---------|-----------------|----------------|----------------|-------------|----------|
| H | 191.343MHz | 43.5 | 35.9 | 7.6 | PK |
| | 269.098MHz | 46.0 | 36.7 | 9.3 | PK |
| | 337.134MHz | 46.0 | 39.4 | 6.6 | PK |
| | 409.058MHz | 46.0 | 35.7 | 10.3 | PK |
| | 494.589MHz | 46.0 | 35.0 | 11.0 | PK |
| | 869.760MHz | 46.0 | 37.1 | 8.9 | PK |
| V | 35.832MHz | 40.0 | 21.2 | 18.8 | PK |
| | 45.551MHz | 40.0 | 27.5 | 12.5 | PK |
| | 53.327MHz | 40.0 | 21.8 | 18.2 | PK |
| | 350.742MHz | 46.0 | 28.1 | 17.9 | PK |
| | 731.744MHz | 46.0 | 30.5 | 15.5 | PK |
| | 869.760MHz | 46.0 | 35.4 | 10.6 | PK |

TEST REPORT

Test result above 1GHz:

The emission was conducted from 1GHz to 40GHz

802.11a

| Channel | Polarity | Frequency (MHz) | Corrected Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---------|----------|-----------------|----------------------------|----------------|-------------|----------|
| L | V | 5180.00 | 57.26 | 74.00 | 16.74 | PK |
| | V | 5180.00 | 44.35 | 54.00 | 9.65 | AV |
| | H | 10360.00 | 53.1 | 74.00 | 20.9 | PK |
| | H | 15540.00 | 54.66 | 74.00 | 19.34 | PK |
| | V | 10360.00 | 55.66 | 74.00 | 18.34 | PK |
| | V | 15540.00 | 44.32 | 74.00 | 29.68 | PK |
| M | H | 10400.00 | 44.56 | 74.00 | 29.44 | PK |
| | H | 15600.00 | 47.52 | 74.00 | 26.48 | PK |
| | V | 10400.00 | 47.63 | 74.00 | 26.37 | PK |
| | V | 15600.00 | 49.54 | 74.00 | 24.46 | PK |
| H | V | 5240.00 | 54.33 | 74.00 | 19.67 | PK |
| | V | 5240.00 | 52.34 | 54.00 | 1.66 | AV |
| | H | 10480.00 | 44.32 | 74.00 | 29.68 | PK |
| | H | 15720.00 | 47.36 | 74.00 | 26.64 | PK |
| | V | 10480.00 | 49.67 | 74.00 | 24.33 | PK |
| | V | 15720.00 | 52.36 | 74.00 | 21.64 | PK |

802.11n20

| Channel | Polarity | Frequency (MHz) | Corrected Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---------|----------|-----------------|----------------------------|----------------|-------------|----------|
| L | V | 5180.00 | 58.33 | 74.00 | 15.67 | PK |
| | V | 5180.00 | 48.35 | 54.00 | 5.65 | AV |
| | V | 10360.00 | 49.65 | 74.00 | 24.35 | PK |
| | V | 15540.00 | 47.63 | 74.00 | 26.37 | PK |
| M | V | 10440.00 | 48.47 | 74.00 | 25.53 | PK |
| | V | 15660.00 | 49.36 | 74.00 | 24.64 | PK |
| H | V | 5240.00 | 51.36 | 74.00 | 22.64 | PK |
| | V | 5240.00 | 52.78 | 54.00 | 1.22 | AV |
| | V | 10480.00 | 58.36 | 74.00 | 15.64 | PK |
| | V | 15720.00 | 59.36 | 74.00 | 14.64 | PK |

TEST REPORT

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;
Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

8 Power line conducted emission


Test result: NA

8.1 Limit

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|------------------------|------------|
| | QP | AV |
| 0.15-0.5 | 66 to 56* | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT**8.4 Test Results of Power line conducted emission**

L Line

N Line

Test Data:

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta = Level - Limit

4. If the PK Level is lower than AV limit, the AV test can be elided.

*Example: Assuming LISN Factor = 10.00dB, Cable Loss = 2.00dB,
Original Receiver Reading = 10.00dBuV, Limit = 66.00dBuV.*

Then Factor = 10.00 + 2.00 = 12.00dB;

Level = 10dBuV + 12.00dB = 22.00dBuV;

Delta = 22.00dBuV - 66.00dBuV = -44.00dB.

9 Frequency Stability

Test result: Pass

9.1 Limit

The frequency stability shall be sufficient to ensure that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 Test Result

Frequency Error - Temperature Variation

| Supply Voltage DC (V) | Temperature (°C) | Frequency Deviation (ppm) |
|--------------------------|---------------------|---------------------------|
| | | Channel (5180MHz) |
| 3.3 | -20 | -4 |
| | -10 | -3 |
| | 0 | -2 |
| | 10 | 0 |
| | 20 | 0 |
| | 30 | 4 |
| | 40 | 4 |
| | 50 | 5 |

Frequency Error - Voltage Variation

| Supply Voltage DC (V) | Temperature (°C) | Frequency Deviation (ppm) |
|--------------------------|---------------------|---------------------------|
| | | Channel (5180MHz) |
| 2.97 | 20 | -4 |
| 3.3 | | -4 |
| 3.36 | | -4 |

TEST REPORT

10 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses a unique coupling to the intentional radiator, so it can comply with the provisions of this section.

***** END *****