

# RF TEST REPORT

**Applicant** Panasonic Corporation of  
North America

**FCC ID** ACJ-TNPA7911

**Product** Wireless module

**Brand** Panasonic

**Model** P24VS\_01

**Report No.** R2306A0670-R2V2

**Issue Date** October 13, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2022)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

---

*Prepared by: Xu Ying*

*Approved by: Xu Kai*

**TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## TABLE OF CONTENT

|      |                                                  |     |
|------|--------------------------------------------------|-----|
| 1    | Test Laboratory.....                             | 5   |
| 1.1  | Notes of the Test Report .....                   | 5   |
| 1.2. | Test facility .....                              | 5   |
| 1.3  | Testing Location.....                            | 5   |
| 2    | General Description of Equipment under Test..... | 6   |
| 2.1  | Applicant and Manufacturer Information.....      | 6   |
| 2.2  | General information.....                         | 6   |
| 3    | Applied Standards .....                          | 7   |
| 4    | Information about the FHSS characteristics ..... | 8   |
| 4.1  | Frequency Hopping System Requirement.....        | 8   |
| 4.2  | Pseudorandom Frequency Hopping Sequence.....     | 9   |
| 4.3  | Equal Hopping Frequency Use .....                | 10  |
| 4.4  | System Receiver Input Bandwidth .....            | 10  |
| 4.5  | Test Configuration .....                         | 11  |
| 5    | Test Case Results .....                          | 12  |
| 5.1  | Peak Power Output .....                          | 12  |
| 5.2  | 99% Bandwidth and 20dB Bandwidth .....           | 25  |
| 5.3  | Frequency Separation .....                       | 38  |
| 5.4  | Time of Occupancy (Dwell Time).....              | 51  |
| 5.5  | Band Edge Compliance .....                       | 72  |
| 5.6  | Number of hopping Frequency.....                 | 97  |
| 5.7  | Spurious RF Conducted Emissions.....             | 104 |
| 5.8  | Unwanted Emission .....                          | 124 |
| 5.9  | Conducted Emission .....                         | 145 |
| 6    | Main Test Instruments .....                      | 147 |
|      | ANNEX A: The EUT Appearance.....                 | 148 |
|      | ANNEX B: Test Setup Photos.....                  | 149 |

| Version                                                                                                                                                                                                                           | Revision Description                | Issue Date         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|--------------------|
| Rev.0                                                                                                                                                                                                                             | Initial issue of report.            | August 31, 2023    |
| Rev.1                                                                                                                                                                                                                             | Update information.                 | September 15, 2023 |
| Rev.2                                                                                                                                                                                                                             | Update information and description. | October 13, 2023   |
| Note: This revised report (Report No.: R2306A0670-R2V2) supersedes and replaces the previously issued report (Report No.: R2306A0670-R2V1). Please discard or destroy the previously issued report and dispose of it accordingly. |                                     |                    |

## Summary of Measurement Results

| Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Test Case                        | Clause in FCC rules        | Verdict |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|----------------------------|---------|
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Frequency Hopping System         | 15.247 (g), (h)            | PASS    |
| 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Peak Power Output                | 15.247(b)(1)               | PASS    |
| 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 99% Bandwidth and 20dB Bandwidth | 15.247(a)(1)<br>C63.10 6.9 | PASS    |
| 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Frequency Separation             | 15.247(a)(1)               | PASS    |
| 5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Time of Occupancy (Dwell Time)   | 15.247(a)(1)(iii)          | PASS    |
| 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Band Edge Compliance             | 15.247(d)                  | PASS    |
| 7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Number of Hopping Frequency      | 15.247(a)(1)(iii)          | PASS    |
| 8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Spurious RF Conducted Emissions  | 15.247(d)                  | PASS    |
| 9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Unwanted Emissions               | 15.247(d), 15.205, 15.209  | PASS    |
| 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Conducted Emissions              | 15.207                     | NA      |
| Date of Testing: July 6, 2023 ~ August 4, 2023<br>Date of Sample Received: June 12, 2023<br>Note: PASS: The EUT complies with the essential requirements in the standard.<br>FAIL: The EUT does not comply with the essential requirements in the standard.<br>All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. |                                  |                            |         |

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2. Test facility

### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

## 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2 General Description of Equipment under Test

### 2.1 Applicant and Manufacturer Information

|                             |                                                                        |
|-----------------------------|------------------------------------------------------------------------|
| <b>Applicant</b>            | Panasonic Corporation of North America                                 |
| <b>Applicant address</b>    | Two Riverfront Plaza, Newark, NJ 07102-5490, United States             |
| <b>Manufacturer</b>         | Panasonic Entertainment & Communication Co., Ltd.                      |
| <b>Manufacturer address</b> | 1-10-12 Yagumo-higashi-machi, Moriguchi City, Osaka<br>570-0021, Japan |

### 2.2 General information

| EUT Description                                                                                                                                                                                                                                                                           |                                                                                     |                         |       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------|-------|
| Model                                                                                                                                                                                                                                                                                     | P24VS_01                                                                            |                         |       |
| Lab internal SN                                                                                                                                                                                                                                                                           | R2306A0670/S02                                                                      |                         |       |
| Hardware Version                                                                                                                                                                                                                                                                          | 1                                                                                   |                         |       |
| Software Version                                                                                                                                                                                                                                                                          | 1                                                                                   |                         |       |
| Power Supply                                                                                                                                                                                                                                                                              | External power supply                                                               |                         |       |
| Antenna Type                                                                                                                                                                                                                                                                              | Internal Antenna / External Antenna                                                 |                         |       |
| Antenna Connector                                                                                                                                                                                                                                                                         | A permanently attached antenna (meet with the standard FCC Part 15.203 requirement) |                         |       |
| Antenna Gain                                                                                                                                                                                                                                                                              | Internal Antenna                                                                    | -8.10 dBi               |       |
|                                                                                                                                                                                                                                                                                           | External Antenna                                                                    | 0.60 dBi                |       |
| Test Mode(s)                                                                                                                                                                                                                                                                              | Basic Rate                                                                          | Enhanced Data Rate(EDR) |       |
| Modulation Type                                                                                                                                                                                                                                                                           | Frequency Hopping Spread Spectrum (FHSS)                                            |                         |       |
|                                                                                                                                                                                                                                                                                           | GFSK                                                                                | π/4 DQPSK               | 8DPSK |
| Packet Type<br>(Maximum Payload)                                                                                                                                                                                                                                                          | DH5                                                                                 | 2DH5                    | 3DH5  |
| Max. Output Power                                                                                                                                                                                                                                                                         | 10.75 dBm                                                                           |                         |       |
| Operating Frequency Range(s)                                                                                                                                                                                                                                                              | 2402-2480 MHz                                                                       |                         |       |
| Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.<br>2. The EUT is connected to 5V DC power supply. And EUT is connected a computer was used to configure the DUT using the tool QA Tool_Dbg to transmit all different modes |                                                                                     |                         |       |

### 3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**Test standards:**

**FCC CFR47 Part 15C (2022) Radio Frequency Devices**

**ANSI C63.10-2013**

**Reference standard:**

**KDB 558074 D01 15.247 Meas Guidance v05r02**

## 4 Information about the FHSS characteristics

### 4.1 Frequency Hopping System Requirement

Standard requirement:

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(g):

According to Bluetooth Core Specification, the Bluetooth system transmits the packets with the pseudorandom hopping frequency with a continuous data and short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Bluetooth Core Specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to Bluetooth Core Specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.


## 4.2 Pseudorandom Frequency Hopping Sequence

Frequency Hopping Systems. A spread spectrum system in which the carrier is modulated with the coded information in a conventional manner causing a conventional spreading of the RF energy about the frequency carrier. The frequency of the carrier is not fixed but changes at fixed intervals under the direction of a coded sequence. The wide RF bandwidth needed by such a system is not required by spreading of the RF energy about the carrier but rather to accommodate the range of frequencies to which the carrier frequency can hop. The test of a frequency hopping system is that the near term distribution of hops appears random, the long term distribution appears evenly distributed over the hop set, and sequential hops are randomly distributed in both direction and magnitude of change in the hop set.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its pioneer to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

The selection scheme chooses a segment of 32 hop frequencies spanning about 64 MHz and visits these hops in a pseudo-random order. Next, a different 32-hop segment is chosen, etc. In the page, master page response, slave page response, page scan, inquiry, inquiry response and inquiry scan hopping sequences, the same 32-hop segment is used all the time (the segment is selected by the address; different devices will have different paging segments).

When the basic channel hopping sequence is selected, the output constitutes a pseudo-random sequence that slides through the 79 hops. The principle is depicted in the figure below.



Hop selection scheme in CONNECTION state.

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45, etc.

Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 4.3 Equal Hopping Frequency Use

All Bluetooth units participating in the Pico net are time and hop-synchronized to the channel. Each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event.

### 4.4 System Receiver Input Bandwidth

Each channel bandwidth is 1MHz. The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 4.5 Test Configuration

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

**The test software is used WCN\_Combo\_Tool.**

| Test Cases                      | Test Modes    |
|---------------------------------|---------------|
| Peak Power Output -Conducted    | DH5/2DH5/3DH5 |
| Occupied Bandwidth (20dB)       | DH5/2DH5/3DH5 |
| Frequency Separation            | DH5/2DH5/3DH5 |
| Time of Occupancy (Dwell Time)  | DH5/2DH5/3DH5 |
| Band Edge Compliance            | DH5/2DH5/3DH5 |
| Number of Hopping Frequency     | DH5/2DH5/3DH5 |
| Spurious RF Conducted Emissions | DH5/2DH5/3DH5 |
| Unwanted Emission               | DH5/2DH5/3DH5 |
| Conducted Emission              | DH5/2DH5/3DH5 |

## 5 Test Case Results

### 5.1 Peak Power Output


#### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

#### Methods of Measurement

During the process of the testing, The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. The EUT is controlled by the Bluetooth test set to ensure max power transmission with proper modulation. The peak detector is used. RBW is set to 2 MHz; VBW is set to 6 MHz. These measurements have been tested at following channels: 0, 39, and 78.

#### Test Setup



#### Limits

Rule Part 15.247 (b) (1) specifies that " For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts."

| Peak Output Power | $\leq 125 \text{ mW (21dBm)}$ |
|-------------------|-------------------------------|
|-------------------|-------------------------------|

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U=0.44 \text{ dB}$ .


## Test Results

### Internal Antenna


| Power Index |           |
|-------------|-----------|
| Channel     | Bluetooth |
| CH0         | 7         |
| CH19        | 7         |
| CH39        | 7         |

| Channel | Frequency<br>(MHz) | Peak Output Power (dBm) |       |       | Limit<br>(dBm) | Conclusion |
|---------|--------------------|-------------------------|-------|-------|----------------|------------|
|         |                    | DH5                     | 2D H5 | 3DH5  |                |            |
| 0       | 2402               | 7.45                    | 9.88  | 10.21 | 30             | PASS       |
| 39      | 2441               | 7.04                    | 9.68  | 10.17 | 30             | PASS       |
| 78      | 2480               | 6.97                    | 9.41  | 9.99  | 30             | PASS       |


Power 1-DH5 2402MHz




Power 1-DH5 2441MHz




Power 1-DH5 2480MHz




Power 2-DH5 2402MHz




Power 2-DH5 2441MHz




Power 2-DH5 2480MHz




Power 3-DH5 2402MHz



Power 3-DH5 2441MHz



Power 3-DH5 2480MHz




**External Antenna**


| Power Index |           |
|-------------|-----------|
| Channel     | Bluetooth |
| CH0         | 7         |
| CH19        | 7         |
| CH39        | 7         |

| Channel | Frequency (MHz) | Peak Output Power (dBm) |       |       | Limit (dBm) | Conclusion |
|---------|-----------------|-------------------------|-------|-------|-------------|------------|
|         |                 | DH5                     | 2DH5  | 3DH5  |             |            |
| 0       | 2402            | 7.65                    | 10.03 | 10.43 | 30          | PASS       |
| 39      | 2441            | 7.44                    | 9.97  | 10.75 | 30          | PASS       |
| 78      | 2480            | 7.51                    | 10.10 | 10.54 | 30          | PASS       |


Power 1-DH5 2402MHz




Power 1-DH5 2441MHz




Power 1-DH5 2480MHz




Power 2-DH5 2402MHz




Power 2-DH5 2441MHz




Power 2-DH5 2480MHz




Power 3-DH5 2402MHz



Power 3-DH5 2441MHz



Power 3-DH5 2480MHz



## 5.2 99% Bandwidth and 20dB Bandwidth


### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

### Method of Measurement

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. The occupied bandwidth is measured using spectrum analyzer. RBW is set to 30kHz and VBW is set to 100kHz on spectrum analyzer. -20dB occupied bandwidths are recorded.

### Test Setup



### Limits

No specific occupied bandwidth requirements in part 15.247(a) (1).

### Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U=936$  Hz.

## Test Results


### Internal Antenna

| Test Mode |      | Channel | Frequency (MHz) | 99% bandwidth(MHz) | 20dB Bandwidth(MHz) |
|-----------|------|---------|-----------------|--------------------|---------------------|
| Bluetooth | DH5  | 0       | 2402            | 0.755              | 0.831               |
|           |      | 39      | 2441            | 0.759              | 0.806               |
|           |      | 78      | 2480            | 0.754              | 0.838               |
|           | 2DH5 | 0       | 2402            | 1.177              | 1.312               |
|           |      | 39      | 2441            | 1.186              | 1.334               |
|           |      | 78      | 2480            | 1.178              | 1.320               |
|           | 3DH5 | 0       | 2402            | 1.188              | 1.299               |
|           |      | 39      | 2441            | 1.176              | 1.311               |
|           |      | 78      | 2480            | 1.192              | 1.319               |


-20dB Bandwidth 1-DH5 2402MHz




-20dB Bandwidth 1-DH5 2441MHz




-20dB Bandwidth 1-DH5 2480MHz




-20dB Bandwidth 2-DH5 2402MHz




-20dB Bandwidth 2-DH5 2441MHz




-20dB Bandwidth 2-DH5 2480MHz




-20dB Bandwidth 3-DH5 2402MHz



-20dB Bandwidth 3-DH5 2441MHz




-20dB Bandwidth 3-DH5 2480MHz




## External Antenna

| Test Mode |      | Channel | Frequency (MHz) | 99% bandwidth(MHz) | 20dB Bandwidth(MHz) |
|-----------|------|---------|-----------------|--------------------|---------------------|
| BT        | DH5  | 0       | 2402            | 0.752              | 0.835               |
|           |      | 39      | 2441            | 0.750              | 0.814               |
|           |      | 78      | 2480            | 0.752              | 0.835               |
|           | 2DH5 | 0       | 2402            | 1.177              | 1.320               |
|           |      | 39      | 2441            | 1.184              | 1.318               |
|           |      | 78      | 2480            | 1.178              | 1.309               |
|           | 3DH5 | 0       | 2402            | 1.187              | 1.313               |
|           |      | 39      | 2441            | 1.192              | 1.315               |
|           |      | 78      | 2480            | 1.181              | 1.297               |


-20dB Bandwidth 1-DH5 2402MHz




-20dB Bandwidth 1-DH5 2441MHz




-20dB Bandwidth 1-DH5 2480MHz




-20dB Bandwidth 2-DH5 2402MHz




-20dB Bandwidth 2-DH5 2441MHz




-20dB Bandwidth 2-DH5 2480MHz




-20dB Bandwidth 3-DH5 2402MHz



-20dB Bandwidth 3-DH5 2441MHz



-20dB Bandwidth 3-DH5 2480MHz



### 5.3 Frequency Separation


#### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

#### Method of Measurement

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. RBW is set to 30 kHz and VBW is set to 100 kHz on spectrum analyzer. Set EUT on Hopping on mode.

#### Test setup



#### Limits

Rule Part 15.247(a)(1) specifies that “Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. ”

Note: The value of two-thirds of 20 dB bandwidth is always greater than 25 kHz.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U=936$  Hz.


## Test Results:

### Internal Antenna


| Test Mode | Carrier frequency (MHz) | Carrier frequency separation(MHz) | 20dB Bandwidth(MHz) | Limit (MHz) | Conclusion |
|-----------|-------------------------|-----------------------------------|---------------------|-------------|------------|
| DH5       | 2402                    | 1.000                             | 0.831               | 0.554       | PASS       |
|           | 2441                    | 0.970                             | 0.806               | 0.537       | PASS       |
|           | 2480                    | 1.030                             | 0.838               | 0.559       | PASS       |
| 2DH5      | 2402                    | 0.970                             | 1.312               | 0.875       | PASS       |
|           | 2441                    | 1.170                             | 1.334               | 0.889       | PASS       |
|           | 2480                    | 1.020                             | 1.320               | 0.880       | PASS       |
| 3DH5      | 2402                    | 1.060                             | 1.299               | 0.866       | PASS       |
|           | 2441                    | 0.980                             | 1.311               | 0.874       | PASS       |
|           | 2480                    | 0.990                             | 1.319               | 0.879       | PASS       |

Note: The limit is two-thirds of 20 dB bandwidth.


CFS 1-DH5 2402MHz




CFS 1-DH5 2441MHz




CFS 1-DH5 2480MHz




CFS 2-DH5 2402MHz




CFS 2-DH5 2441MHz




CFS 2-DH5 2480MHz




CFS 3-DH5 2402MHz



CFS 3-DH5 2441MHz



CFS 3-DH5 2480MHz




**External Antenna**


| Test Mode | Carrier frequency (MHz) | Carrier frequency separation(MHz) | 20dB Bandwidth(MHz) | Limit (MHz) | Conclusion |
|-----------|-------------------------|-----------------------------------|---------------------|-------------|------------|
| DH5       | 2402                    | 0.950                             | 0.835               | 0.557       | PASS       |
|           | 2441                    | 1.000                             | 0.814               | 0.543       | PASS       |
|           | 2480                    | 1.010                             | 0.835               | 0.557       | PASS       |
| 2DH5      | 2402                    | 0.940                             | 1.320               | 0.880       | PASS       |
|           | 2441                    | 0.990                             | 1.318               | 0.879       | PASS       |
|           | 2480                    | 1.190                             | 1.309               | 0.873       | PASS       |
| 3DH5      | 2402                    | 0.910                             | 1.313               | 0.875       | PASS       |
|           | 2441                    | 0.990                             | 1.315               | 0.877       | PASS       |
|           | 2480                    | 1.010                             | 1.297               | 0.865       | PASS       |

Note: The limit is two-thirds of 20 dB bandwidth.


CFS 1-DH5 2402MHz




CFS 1-DH5 2441MHz




CFS 1-DH5 2480MHz




CFS 2-DH5 2402MHz




CFS 2-DH5 2441MHz




CFS 2-DH5 2480MHz




CFS 3-DH5 2402MHz



CFS 3-DH5 2441MHz



CFS 3-DH5 2480MHz



## 5.4 Time of Occupancy (Dwell Time)

### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

### Methods of Measurement


The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. RBW is set to 1MHz and VBW is set to 1MHz on spectrum analyzer. The dwell time is calculated by:

Dwell time = Pulse Time \* Number of Pulses in 31.6 seconds:

In normal mode, The selected EUT Packet type uses a slot type of DH5 packet and a hopping rate of 1600(ch\*hop/s) for all channels. So the final hopping rate for all channel is  $1600/5=320(\text{ch*hop/s})$

In AFH mode, The selected EUT Packet type uses a slot type of DH5 packet and a hopping rate of 800(ch\*hop/s) for all channels. So the final hopping rate for all channel is  $800/5=160(\text{ch*hop/s})$

### Test Setup



### Limits

Rule Part15.247(a) specifies that " Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed."

| Dwell time | ≤ 400ms |
|------------|---------|
|------------|---------|

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ .

| Requirements | Uncertainty |                   |      |                   |      |                   |
|--------------|-------------|-------------------|------|-------------------|------|-------------------|
| Dwell Time   | DH5         | $U=0.70\text{ms}$ | 2DH5 | $U=0.70\text{ms}$ | 3DH5 | $U=0.70\text{ms}$ |


**Test Results:****Internal Antenna**

In normal mode:


| Test Mode | Frequency (MHz) | Number of Pulses in 31.6 seconds | Pulse Time (ms) | Dwell time (ms) | Limit (ms) | Conclusion |
|-----------|-----------------|----------------------------------|-----------------|-----------------|------------|------------|
| DH5       | 2402            | 118                              | 2.879           | 339.722         | 400        | PASS       |
|           | 2441            | 105                              | 2.877           | 302.085         | 400        | PASS       |
|           | 2480            | 98                               | 2.878           | 282.044         | 400        | PASS       |
| 2DH5      | 2402            | 126                              | 2.880           | 362.880         | 400        | PASS       |
|           | 2441            | 103                              | 2.880           | 296.640         | 400        | PASS       |
|           | 2480            | 109                              | 2.883           | 314.247         | 400        | PASS       |
| 3DH5      | 2402            | 111                              | 2.884           | 320.124         | 400        | PASS       |
|           | 2441            | 97                               | 2.884           | 279.748         | 400        | PASS       |
|           | 2480            | 100                              | 2.885           | 288.500         | 400        | PASS       |

Note: Dwell time = Pulse Time \* Number of Pulses in 31.6 seconds


Dwell 1-DH5 2402MHz One Burst




Dwell 1-DH5 2402MHz Accumulated




### Dwell 1-DH5 2441MHz One Burst




### Dwell 1-DH5 2441MHz Accumulated




### Dwell 1-DH5 2480MHz One Burst




### Dwell 1-DH5 2480MHz Accumulated




### Dwell 2-DH5 2402MHz One Burst




### Dwell 2-DH5 2402MHz Accumulated




### Dwell 2-DH5 2441MHz One Burst




### Dwell 2-DH5 2441MHz Accumulated




### Dwell 2-DH5 2480MHz One Burst




### Dwell 2-DH5 2480MHz Accumulated




### Dwell 3-DH5 2402MHz One Burst




### Dwell 3-DH5 2402MHz Accumulated




### Dwell 3-DH5 2441MHz One Burst




### Dwell 3-DH5 2441MHz Accumulated



## Dwell 3-DH5 2480MHz One Burst



## Dwell 3-DH5 2480MHz Accumulated




**External Antenna**


In normal mode:

| Test Mode                                                        | Frequency (MHz) | Number of Pulses in 31.6 seconds | Pulse Time (ms) | Dwell time (ms) | Limit (ms) | Conclusion |
|------------------------------------------------------------------|-----------------|----------------------------------|-----------------|-----------------|------------|------------|
| DH5                                                              | 2402            | 105                              | 2.879           | 302.295         | 400        | PASS       |
|                                                                  | 2441            | 100                              | 2.877           | 287.700         | 400        | PASS       |
|                                                                  | 2480            | 103                              | 2.879           | 296.537         | 400        | PASS       |
| 2DH5                                                             | 2402            | 105                              | 2.880           | 302.400         | 400        | PASS       |
|                                                                  | 2441            | 101                              | 2.880           | 290.880         | 400        | PASS       |
|                                                                  | 2480            | 115                              | 2.882           | 331.430         | 400        | PASS       |
| 3DH5                                                             | 2402            | 126                              | 2.885           | 363.510         | 400        | PASS       |
|                                                                  | 2441            | 104                              | 2.884           | 299.936         | 400        | PASS       |
|                                                                  | 2480            | 112                              | 2.885           | 323.120         | 400        | PASS       |
| Note: Dwell time = Pulse Time * Number of Pulses in 31.6 seconds |                 |                                  |                 |                 |            |            |


Dwell 1-DH5 2402MHz One Burst




Dwell 1-DH5 2402MHz Accumulated




### Dwell 1-DH5 2441MHz One Burst




### Dwell 1-DH5 2441MHz Accumulated




### Dwell 1-DH5 2480MHz One Burst




### Dwell 1-DH5 2480MHz Accumulated




### Dwell 2-DH5 2402MHz One Burst




### Dwell 2-DH5 2402MHz Accumulated




### Dwell 2-DH5 2441MHz One Burst




### Dwell 2-DH5 2441MHz Accumulated




### Dwell 2-DH5 2480MHz One Burst




### Dwell 2-DH5 2480MHz Accumulated




### Dwell 3-DH5 2402MHz One Burst




### Dwell 3-DH5 2402MHz Accumulated




### Dwell 3-DH5 2441MHz One Burst




### Dwell 3-DH5 2441MHz Accumulated



### Dwell 3-DH5 2480MHz One Burst



### Dwell 3-DH5 2480MHz Accumulated



## 5.5 Band Edge Compliance


### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

### Method of Measurement

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. The lowest and highest channels were measured. The peak detector is used. RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer. EUT test for Hopping On mode and Hopping Off mode.

### Test Setup



### Limits

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.”

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .


| Frequency | Uncertainty |
|-----------|-------------|
| 2GHz-3GHz | 1.407 dB    |

# Test Results


## Hopping On

### Internal Antenna


#### Band Edge(Hopping) 1-DH5 2402MHz Hopping Ref




#### Band Edge(Hopping) 1-DH5 2402MHz Hopping Emission




### Band Edge(Hopping) 1-DH5 2480MHz Hopping Ref




### Band Edge(Hopping) 1-DH5 2480MHz Hopping Emission




# Band Edge(Hopping) 2-DH5 2402MHz Hopping Ref




# Band Edge(Hopping) 2-DH5 2402MHz Hopping Emission




# Band Edge(Hopping) 2-DH5 2480MHz Hopping Ref




# Band Edge(Hopping) 2-DH5 2480MHz Hopping Emission




### Band Edge(Hopping) 3-DH5 2402MHz Hopping Ref




### Band Edge(Hopping) 3-DH5 2402MHz Hopping Emission



Band Edge(Hopping) 3-DH5 2480MHz Hopping Ref




Band Edge(Hopping) 3-DH5 2480MHz Hopping Emission




# External Antenna


## Band Edge(Hopping) 1-DH5 2402MHz Hopping Ref




## Band Edge(Hopping) 1-DH5 2402MHz Hopping Emission




# Band Edge(Hopping) 1-DH5 2480MHz Hopping Ref




# Band Edge(Hopping) 1-DH5 2480MHz Hopping Emission




# Band Edge(Hopping) 2-DH5 2402MHz Hopping Ref




# Band Edge(Hopping) 2-DH5 2402MHz Hopping Emission




Band Edge(Hopping) 2-DH5 2480MHz Hopping Ref




Band Edge(Hopping) 2-DH5 2480MHz Hopping Emission




### Band Edge(Hopping) 3-DH5 2402MHz Hopping Ref




### Band Edge(Hopping) 3-DH5 2402MHz Hopping Emission



### Band Edge(Hopping) 3-DH5 2480MHz Hopping Ref




### Band Edge(Hopping) 3-DH5 2480MHz Hopping Emission




Hopping Off  
Internal Antenna


Band Edge 1-DH5 2402MHz No-Hopping Ref




Band Edge 1-DH5 2402MHz No-Hopping Emission




### Band Edge 1-DH5 2480MHz No-Hopping Ref




### Band Edge 1-DH5 2480MHz No-Hopping Emission




### Band Edge 2-DH5 2402MHz No-Hopping Ref




### Band Edge 2-DH5 2402MHz No-Hopping Emission




### Band Edge 2-DH5 2480MHz No-Hopping Ref




### Band Edge 2-DH5 2480MHz No-Hopping Emission




Band Edge 3-DH5 2402MHz No-Hopping Ref




Band Edge 3-DH5 2402MHz No-Hopping Emission



### Band Edge 3-DH5 2480MHz No-Hopping Ref




### Band Edge 3-DH5 2480MHz No-Hopping Emission




External Antenna


Band Edge 1-DH5 2402MHz No-Hopping Ref




Band Edge 1-DH5 2402MHz No-Hopping Emission




### Band Edge 1-DH5 2480MHz No-Hopping Ref




### Band Edge 1-DH5 2480MHz No-Hopping Emission




### Band Edge 2-DH5 2402MHz No-Hopping Ref




### Band Edge 2-DH5 2402MHz No-Hopping Emission




### Band Edge 2-DH5 2480MHz No-Hopping Ref




### Band Edge 2-DH5 2480MHz No-Hopping Emission




### Band Edge 3-DH5 2402MHz No-Hopping Ref




### Band Edge 3-DH5 2402MHz No-Hopping Emission



### Band Edge 3-DH5 2480MHz No-Hopping Ref



### Band Edge 3-DH5 2480MHz No-Hopping Emission



## 5.6 Number of hopping Frequency


### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 20°C ~ 25°C | 45% ~ 50%         |

### Method of Measurement

The EUT was connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. RBW is set to 100kHz and VBW is set to 300kHz on spectrum analyzer. Set EUT on Hopping on mode.

### Test setup



### Limits


Rule Part 15.247(a) (1) (iii) specifies that" Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels."

| Limits | ≥ 15 channels |
|--------|---------------|
|--------|---------------|


**Test Results:**
**Internal Antenna**

| Test Mode |      | Number of hopping channels | conclusion |
|-----------|------|----------------------------|------------|
| Bluetooth | DH5  | 79                         | PASS       |
|           | 2DH5 | 79                         | PASS       |
|           | 3DH5 | 79                         | PASS       |

### Hopping No. 1-DH5 2402MHz



### Hopping No. 2-DH5 2402MHz



Hopping No. 3-DH5 2402MHz

