





# RADIO TEST REPORT

## Test Report No. 15659798H-R1

Customer	Panasonic Automotive Systems Co., Ltd.
Description of EUT	CAR DISPLAY AUDIO
Model Number of EUT	AN2402
FCC ID	ACJ932AN2402
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	April 8, 2025
Remarks	-

<b>Representative Test Engineer</b>	<b>Approved By</b>
	
Shousei Hamaguchi Engineer	Takumi Shimada Engineer
	 
	CERTIFICATE 5107.02
<input type="checkbox"/> The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.	
<input checked="" type="checkbox"/> There is no testing item of "Non-accreditation".	

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 24.0

## ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.  
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

## REVISION HISTORY

### Original Test Report No. 15659798H

This report is a revised version of 15659798H. 15659798H is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15659798H	March 18, 2025	-
1	15659798H-R1	April 8, 2025	<b><u>General Specification in clause 2.2</u></b> - Change the item name from "Rating" to "Nominal" <b><u>Radio Specification in clause 2.2</u></b> - Change antenna gain value for WLAN 5 GHz: 5 dBi -> 3 dBi

**Reference: Abbreviations (Including words undescribed in this report)**

A2LA	The American Association for Laboratory Accreditation	IEC	International Electrotechnical Commission
AC	Alternating Current	IEEE	Institute of Electrical and Electronics Engineers
AFH	Adaptive Frequency Hopping	IF	Intermediate Frequency
AM	Amplitude Modulation	ILAC	International Laboratory Accreditation Conference
Amp, AMP	Amplifier	ISED	Innovation, Science and Economic Development Canada
ANSI	American National Standards Institute	ISO	International Organization for Standardization
Ant, ANT	Antenna	JAB	Japan Accreditation Board
AP	Access Point	LAN	Local Area Network
ASK	Amplitude Shift Keying	LIMS	Laboratory Information Management System
Atten., ATT	Attenuator	MCS	Modulation and Coding Scheme
AV	Average	MRA	Mutual Recognition Arrangement
BPSK	Binary Phase-Shift Keying	N/A	Not Applicable
BR	Bluetooth Basic Rate	NIST	National Institute of Standards and Technology
BT	Bluetooth	NS	No signal detect.
BT LE	Bluetooth Low Energy	NSA	Normalized Site Attenuation
BW	BandWidth	NVLAP	National Voluntary Laboratory Accreditation Program
Cal Int	Calibration Interval	OBW	Occupied Band Width
CCK	Complementary Code Keying	OFDM	Orthogonal Frequency Division Multiplexing
Ch., CH	Channel	OFDMA	Orthogonal Frequency Division Multiple Access
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PP	Preamble Puncturing
DSSS	Direct Sequence Spread Spectrum	PRBS	Pseudo-Random Bit Sequence
EDR	Enhanced Data Rate	PSD	Power Spectral Density
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QAM	Quadrature Amplitude Modulation
EMC	ElectroMagnetic Compatibility	QP	Quasi-Peak
EMI	ElectroMagnetic Interference	QPSK	Quadri-Phase Shift Keying
EN	European Norm	RBW	Resolution Band Width
ERP, e.r.p.	Effective Radiated Power	RDS	Radio Data System
EU	European Union	RE	Radio Equipment
EUT	Equipment Under Test	RF	Radio Frequency
Fac.	Factor	RMS	Root Mean Square
FCC	Federal Communications Commission	RSS	Radio Standards Specifications
FHSS	Frequency Hopping Spread Spectrum	Rx	Receiving
FM	Frequency Modulation	SA, S/A	Spectrum Analyzer
Freq.	Frequency	SG	Signal Generator
FSK	Frequency Shift Keying	SVSWR	Site-Voltage Standing Wave Ratio
GFSK	Gaussian Frequency-Shift Keying	TR	Test Receiver
GNSS	Global Navigation Satellite System	Tx	Transmitting
GPS	Global Positioning System	VBW	Video BandWidth
Hori.	Horizontal	Vert.	Vertical
ICES	Interference-Causing Equipment Standard	WLAN	Wireless LAN

---

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer Information</b> .....	<b>5</b>
<b>SECTION 2: Equipment Under Test (EUT)</b> .....	<b>5</b>
<b>SECTION 3: Test Specification, Procedures &amp; Results</b> .....	<b>7</b>
<b>SECTION 4: Operation of EUT during testing</b> .....	<b>10</b>
<b>SECTION 5: Radiated Spurious Emission</b> .....	<b>13</b>
<b>SECTION 6: Antenna Terminal Conducted Tests</b> .....	<b>15</b>
<b>APPENDIX 1: Test data</b> .....	<b>16</b>
20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation .....	16
Number of Hopping Frequency.....	20
Dwell time .....	22
Maximum Peak Output Power .....	25
Average Output Power.....	26
Radiated Spurious Emission.....	28
Conducted Spurious Emission.....	41
Conducted Emission Band Edge compliance .....	47
<b>APPENDIX 2: Test Instruments</b> .....	<b>49</b>
<b>APPENDIX 3: Photographs of test setup</b> .....	<b>50</b>
Radiated Spurious Emission.....	50
Antenna Terminal Conducted Tests .....	51

## **SECTION 1: Customer Information**

Company Name	Panasonic Automotive Systems Co., Ltd. *1)
Address	4261, Ikonobe-cho, Tsuzuki-ku, Yokohama-shi, Kanagawa-ken 224-8520, Japan
Telephone Number	+81-80-3444-7148
Contact Person	Taichi Haraoka

\*1) The Grantee name in the FCC application is "Panasonic Corporation of North America".

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

## **SECTION 2: Equipment Under Test (EUT)**

### **2.1 Identification of EUT**

Description	CAR DISPLAY AUDIO
Model Number	AN2402
Serial Number	Refer to SECTION 4.2
Condition	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	February 7, 2025
Test Date	February 12 to 23, 2025

### **2.2 Product Description**

#### **General Specification**

Nominal	DC 13.2 V
Operating temperature	-30 deg. C to 60 deg. C

#### **Radio Specification**

This report contains data provided by the customer which can impact the validity of results. UL Japan, Inc. is only responsible for the validity of results after the integration of the data provided by the customer. The data provided by the customer is marked "a)" in the table below.

#### **Bluetooth (BR / EDR)**

Equipment Type	Transceiver
Frequency of Operation	2402 MHz to 2480 MHz
Type of Modulation	FHSS (GFSK, $\pi/4$ DQPSK, 8 DPSK)
Antenna Gain <sup>a)</sup>	5 dBi

#### **WLAN (IEEE802.11a/11n-20/11ac-20/11n-40/11ac-40/11ac-80)**

Equipment Type	Transceiver	
Frequency of Operation	20 MHz Band	5745 MHz to 5805 MHz
	40 MHz Band	5755 MHz to 5795 MHz
	80 MHz Band	5775 MHz
Type of Modulation	OFDM	
Antenna Gain <sup>a)</sup>	3 dBi	

**AM / FM**

Equipment Type	Receiver
Frequency of Operation	AM: 530 kHz to 1710 kHz FM: 87.9 MHz to 107.9 MHz
Type of Modulation	AM FM

**GNSS**

Equipment Type	Receiver
Frequency of Operation	See table below.

**Supported GNSS and GNSS signals**

GNSS	RNSS Frequency Band / Frequency [MHz]		
	1559 to 1610	1215 to 1300	1164 to 1215
BDS	<input type="checkbox"/> B1I 1561.098	-	-
	<input type="checkbox"/> B1C 1561.098 (IGSO)		
	<input type="checkbox"/> B1C 1561.098 (MEO)		
Galileo	<input checked="" type="checkbox"/> E1 1575.42	<input type="checkbox"/> E6 1278.75	<input type="checkbox"/> E5a 1176.45 <input type="checkbox"/> E5b 1207.14
	<input type="checkbox"/> G1 1598.0625 - 1605.375	<input type="checkbox"/> G2 1242.9375 - 1248.625	-
GPS	<input checked="" type="checkbox"/> L1 C/A 1575.42	<input type="checkbox"/> L2C 1227.6	<input type="checkbox"/> L5 1176.45
	<input type="checkbox"/> L1C 1575.42		
SBAS	<input type="checkbox"/> L1 1575.42	-	<input type="checkbox"/> L5 1176.45

Supported GNSS signal

Not supported GNSS signal

## SECTION 3: Test Specification, Procedures & Results

### 3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

\* Also the EUT complies with FCC Part 15 Subpart B.

### 3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	-	N/A	*1)
Carrier Frequency Separation	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (b)	See data.	Complied	Conducted
20dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (a)		Complied	Conducted
Number of Hopping Frequency	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Dwell time	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section15.247(b)(1) ISED: RSS-247 5.4 (b)		Complied	Conducted
Spurious Emission & Band Edge Compliance	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	12.8 dB 31.9 MHz Vertical, QP	Complied	Conducted/ Radiated (above 30 MHz) *1)
Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593. * In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.  *1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line. *2) Radiated test was selected over 30 MHz based on section 15.247(d).					

#### **FCC Part 15.31 (e)**

This EUT provides the stable voltage constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

### 3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement. Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

#### Conducted emission

Item	Frequency range	Unit	Calculated Uncertainty (+/-)
AMN (LISN)	0.15 MHz to 30 MHz	dB	3.3

#### Radiated emission

Measurement distance	Frequency range	Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz	dB	3.3
10 m		dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	5.0
		Vertical	5.0
	200 MHz to 1000 MHz	Horizontal	5.2
		Vertical	6.2
10 m	30 MHz to 200 MHz	Horizontal	5.5
		Vertical	5.4
	200 MHz to 1000 MHz	Horizontal	5.5
		Vertical	5.5
3 m	1 GHz to 6 GHz	dB	5.1
	6 GHz to 18 GHz	dB	5.4
1 m	10 GHz to 18 GHz	dB	5.4
	18 GHz to 26.5 GHz	dB	5.3
	26.5 GHz to 40 GHz	dB	4.8
0.5 m	26.5 GHz to 40 GHz	dB	5.0

#### Antenna Terminal Conducted

Item	Unit	Calculated Uncertainty (+/-)
Antenna terminated conducted emission / Power density / Burst power	dB	3.50
Adjacent channel power (ACP)	dB	2.32
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02
Power measurement (Power meter < 8 GHz)	dB	1.43
Power measurement (Call box < 6 GHz)	dB	1.89
Frequency readout (Frequency counter)	ppm	0.67
Frequency readout (Spectrum analyzer frequency readout function)	ppm	2.13
Temperature (constant temperature bath)	deg. C	0.69
Humidity (constant temperature bath)	%RH	2.98
Modulation characteristics	%	6.93
Frequency for mobile	ppm	0.08
Contention-based protocol	dB	2.97

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

### 3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

## SECTION 4: Operation of EUT during testing

### 4.1 Operating Mode(s)

Mode	Remarks*
Bluetooth (BT)	BR / EDR, Payload: PRBS9
<p>*EUT has the power settings by the software as follows;            Power Setting: 10 dBm            Software: MCU Version: V01            (Date: September 18, 2024, Storage location: EUT memory)</p> <p>*This setting of software is the worst case.            Any conditions under the normal use do not exceed the condition of setting.            In addition, end users cannot change the settings of the output power of the product.</p>	

#### Details of Operating Mode(s)

Test Item	Mode	Hopping	Tested Frequency
Radiated Spurious Emission (Below 1 GHz)	Tx 3DH5 *1)	Off	2402 MHz
Radiated Spurious Emission (Above 1 GHz), Conducted Spurious Emission	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Carrier Frequency Separation	Tx DH5 Tx 3DH5	On	2402 MHz 2441 MHz 2480 MHz
20dB Bandwidth	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Number of Hopping Frequency	Tx DH5 Tx 3DH5	On	-
Dwell time	Tx DH1, DH3, DH5 Tx 3DH1, 3DH3, 3DH5	On	-
Maximum Peak Output Power	Tx DH5 Tx 2DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Band Edge Compliance (Conducted)	Tx DH5 Tx 3DH5	On ----- Off	2402 MHz 2480 MHz
99% Occupied Bandwidth	Tx DH5 Tx 3DH5	On ----- Off	2402 MHz 2441 MHz 2480 MHz

\*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test)

\*2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.


\*It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all the test items based on Bluetooth Core specification.

\*1) Spurious emissions for frequencies below 1 GHz was limited to the channel that had the highest power during the antenna terminal test, as preliminary testing indicated that changing the operating frequency had no significant impact on the emissions in those frequency bands.

#### Simultaneous transmission

Test Item	Mode *1)
Radiated Spurious Emission	Tx, Hopping Off, 3DH5 2480 MHz + 11ac-40 5755 MHz
<p>*1) The test was conducted on representative mode, the worst mode at Spurious emission test (above 1 GHz) for BT and the mode had the highest power at Antenna terminal conducted test for WLAN 5 GHz band.</p>	

4.2 Configuration and Peripherals



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

**Description of EUT and Support Equipment**

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	CAR DISPLAY AUDIO	AN2402	NASLDA-A3S002	Panasonic Automotive Systems Co., Ltd.	EUT, For RE*
			NASLDA-A3S003		EUT, For AT*
B	SW BOX	ALL IN 1 SW BOX Ver.6	RS-23_No.057	Panasonic Automotive Systems Co., Ltd.	-
C	ST Switch Board	STRG-SW 5-LEVEL	RS-23-027	Panasonic Automotive Systems Co., Ltd.	-
D	Rear Camera	GP-KD7601RA	25M200106	Panasonic	-
E	Microphone	28336 7AA2A	28336 FD 7AA2A AX	Hosiden Corporation	-
F	USB HUB	284H3 7JA1A	244010078A	MinebeaMitsumi Inc.	-
G	FM Antenna Dummy	FAKRA FM 1 signal Dummy	RS-F017	Panasonic Automotive Systems Co., Ltd.	-
H	GNSS Antenna	25975 5EF0A	R16-A450	MinebeaMitsumi Inc.	-
I	2Ω Dummy Resistor Jig	-	RS-24_No.005	Panasonic Automotive Systems Co., Ltd.	-
J	USB Memory	RUF3-K16GB	P10416	Buffalo Inc.	-
K	iPhone 8	MQ7A2J/A	-	Apple	-

**List of Cables Used**

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	Signal Cable	2.5	Unshielded	Unshielded	-
2	Signal Cable	2.2	Unshielded	Unshielded	-
3	Microphone Cable	2.0	Unshielded	Unshielded	-
4	USB Cable	2.0	Shielded	Shielded	-
5	DC Cable	4.0	Unshielded	Unshielded	-
6	FM/AM Cable	2.0	Shielded	Shielded	-
7	GNSS Antenna Cable	2.7	Shielded	Shielded	-
8	Audio Cable	2.3	Shielded	Shielded	-
9	DC Cable	3.7	Unshielded	Unshielded	-
10	DC Cable	1.5	Unshielded	Unshielded	-
11	USB Cable	1.0	Shielded	Shielded	-

\*RE: Radiated Spurious Emission, AT: Antenna Terminal Conducted Tests

## **SECTION 5: Radiated Spurious Emission**

### **Test Procedure**

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn


In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

### **20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).**

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz

Figure 2: Test Setup


Below 1 GHz



\* : Center of turn table

Test Distance: 3 m

1 GHz to 10 GHz



r : Radius of an outer periphery of EUT  
 \* : Center of turn table

[1 GHz to 6 GHz]

Distance Factor:  $20 \times \log (3.9 \text{ m}^* / 3.0 \text{ m}) = 2.28 \text{ dB}$   
 \*(Test Distance + SVSWR Volume / 2) - r = 3.9 m


Test Distance: 3 m  
 SVSWR Volume: 2 m  
 (SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
 r: 0.1 m

[6 GHz to 10 GHz]

Distance Factor:  $20 \times \log (4.9 \text{ m}^* / 3.0 \text{ m}) = 4.27 \text{ dB}$   
 \*(Test Distance + SVSWR Volume / 2) - r = 4.9 m

Test Distance: 4.3 m  
 SVSWR Volume: 1.4 m  
 (SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
 r: 0.1 m

10 GHz to 26.5 GHz



\* : Center of turn table

Distance Factor:  $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$   
 \*Test Distance: 1 m

The test was made on EUT at the normal use position.

Test results are rounded off and limit are rounded down, so some differences might be observed.

Measurement Range : 30 MHz to 26.5 GHz  
 Test Data : APPENDIX  
 Test Result : Pass

## SECTION 6: Antenna Terminal Conducted Tests

### Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
20dB Bandwidth	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30 MHz	200 kHz	620 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100 kHz, 1 MHz	300 kHz, 3 MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3) *4)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				
	30 MHz to 25 GHz	100 kHz	300 kHz				
Conducted Spurious Emission Band Edge compliance	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

\*1) Peak hold was applied as Worst-case measurement.

\*2) Reference data

\*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart. (9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 10 kHz).

\*4) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to  $45.5 - 51.5 = -6.0$  dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

Test results are rounded off and limit are rounded down, so some differences might be observed. The equipment and cables were not used for factor 0 dB of the data sheets.

**Test Data** : APPENDIX  
**Test Result** : Pass

## APPENDIX 1: Test data

### 20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation


Test place	Ise EMC Lab. No.6 Measurement Room	
Date	February 12, 2025	February 13, 2025
Temperature / Humidity	23 deg. C / 39 % RH	20 deg. C / 39 % RH
Engineer	Shousei Hamaguchi	Shousei Hamaguchi
Mode	Tx, Hopping Off, Tx, Hopping On	

Mode	Freq. [MHz]	20 dB Bandwidth [MHz]	99 % Occupied Bandwidth [kHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	1.026	892.816	1.000	>= 0.684
DH5	2441.0	1.030	891.951	1.000	>= 0.687
DH5	2480.0	1.036	<b>897.145</b>	1.000	>= 0.691
DH5	Hopping On	-	78628.900	-	-
3DH5	2402.0	1.292	<b>1172.044</b>	1.000	>= 0.861
3DH5	2441.0	1.287	1167.281	1.000	>= 0.858
3DH5	2480.0	1.295	1168.909	1.000	>= 0.863
3DH5	Hopping On	-	78715.700	-	-


Limit: Two-thirds of 20 dB Bandwidth or 25 kHz (whichever is greater).

No limit applies to 20 dB Bandwidth.


**20dB Bandwidth and 99% Occupied Bandwidth**



**20dB Bandwidth and 99% Occupied Bandwidth**



### Carrier Frequency Separation




### Number of Hopping Frequency

Test place Ise EMC Lab. No.6 Measurement Room  
Date February 13, 2025  
Temperature / Humidity 20 deg. C / 39 % RH  
Engineer Shousei Hamaguchi  
Mode Tx, Hopping On

Mode	Number of channel [channels]	Limit [channels]
DH5	79	>= 15
3DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

**Number of Hopping Frequency**



## Dwell time

Test place	Ise EMC Lab. No.6 Measurement Room
Date	February 13, 2025
Temperature / Humidity	20 deg. C / 39 % RH
Engineer	Shousei Hamaguchi
Mode	Tx, Hopping On

Mode	Number of transmission in a 31.6 (79 Hopping x0.4) / 12.8 (32 Hopping x0.4) second period	Length of transmission [ms]	Result [ms]	Limit [ms]
DH1	27.0 times / 5 s x 31.6 s = 171 times	0.387	66	400
DH3	23.4 times / 5 s x 31.6 s = 148 times	1.647	244	400
DH5	17.2 times / 5 s x 31.6 s = 109 times	2.897	316	400
3DH1	29.8 times / 5 s x 31.6 s = 189 times	0.394	74	400
3DH3	25.8 times / 5 s x 31.6 s = 164 times	1.649	270	400
3DH5	15.6 times / 5 s x 31.6 s = 99 times	2.903	287	400

Sample Calculation

Result = Number of transmission x Length of transmission

\*Average data of 5 tests.(except Inquiry)


Mode	Sampling [times]					Average [times]
	1	2	3	4	5	
DH1	27	26	28	28	26	27
DH3	23	23	24	23	24	23.4
DH5	17	20	17	16	16	17.2
3DH1	28	29	32	31	29	29.8
3DH3	26	26	26	26	25	25.8
3DH5	16	15	16	15	16	15.6

Sample Calculation


Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in  $N \times 0.4$  s, where N is the number of channels being used in the hopping sequence ( $20 \leq N \leq 79$ ), is always less than 0.4 s regardless of packet size. This is confirmed in the test report for  $N = 79$ .

**Dwell time**



**Dwell time**



## Maximum Peak Output Power

Test place                   Ise EMC Lab. No.6 Measurement Room  
Date                           February 12, 2025  
Temperature / Humidity   23 deg. C / 39 % RH  
Engineer                    Shousei Hamaguchi  
Mode                         Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Conducted Power					e.i.r.p. for RSS-247					
					Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
					[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
DH5	2402.0	-3.05	1.44	0.00	<b>-1.61</b>	<b>0.69</b>	20.96	125	22.57	5.00	<b>3.39</b>	<b>2.18</b>	36.02	4000	32.63
DH5	2441.0	-3.83	1.45	0.00	-2.38	0.58	20.96	125	23.34	5.00	2.62	1.83	36.02	4000	33.40
DH5	2480.0	-4.11	1.46	0.00	-2.65	0.54	20.96	125	23.61	5.00	2.35	1.72	36.02	4000	33.67
2DH5	2402.0	-3.35	1.44	0.00	<b>-1.91</b>	<b>0.64</b>	20.96	125	22.87	5.00	<b>3.09</b>	<b>2.04</b>	36.02	4000	32.93
2DH5	2441.0	-4.08	1.45	0.00	-2.63	0.55	20.96	125	23.59	5.00	2.37	1.72	36.02	4000	33.65
2DH5	2480.0	-4.41	1.46	0.00	-2.95	0.51	20.96	125	23.91	5.00	2.05	1.60	36.02	4000	33.97
3DH5	2402.0	-3.03	1.44	0.00	<b>-1.59</b>	<b>0.69</b>	20.96	125	22.55	5.00	<b>3.41</b>	<b>2.19</b>	36.02	4000	32.61
3DH5	2441.0	-3.80	1.45	0.00	-2.35	0.58	20.96	125	23.31	5.00	2.65	1.84	36.02	4000	33.37
3DH5	2480.0	-4.15	1.46	0.00	-2.69	0.54	20.96	125	23.65	5.00	2.31	1.70	36.02	4000	33.71

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

Test was not performed at AFH mode, because the decrease of number of channel (min: 20 ch) at AFH mode does not influence on the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20 dB BW without 2/3 relaxation, 125 mW power limit was applied to it.

**Average Output Power**  
**(Reference data for RF Exposure)**

Test place	Ise EMC Lab. No.6 Measurement Room
Date	February 12, 2025
Temperature / Humidity	23 deg. C / 39 % RH
Engineer	Shousei Hamaguchi
Mode	Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
					[dBm]	[mW]		[dBm]	[mW]
DH5	2402.0	-4.57	1.44	0.00	<b>-3.13</b>	<b>0.49</b>	1.13	<b>-2.00</b>	<b>0.63</b>
DH5	2441.0	-5.35	1.45	0.00	-3.90	0.41	1.13	-2.77	0.53
DH5	2480.0	-5.66	1.46	0.00	-4.20	0.38	1.13	-3.07	0.49
2DH5	2402.0	-7.38	1.44	0.00	<b>-5.94</b>	<b>0.25</b>	1.12	<b>-4.82</b>	<b>0.33</b>
2DH5	2441.0	-8.15	1.45	0.00	-6.70	0.21	1.12	-5.58	0.28
2DH5	2480.0	-8.41	1.46	0.00	-6.95	0.20	1.12	-5.83	0.26
3DH5	2402.0	-7.36	1.44	0.00	<b>-5.92</b>	<b>0.26</b>	1.12	<b>-4.80</b>	<b>0.33</b>
3DH5	2441.0	-8.14	1.45	0.00	-6.69	0.21	1.12	-5.57	0.28
3DH5	2480.0	-8.42	1.46	0.00	-6.96	0.20	1.12	-5.84	0.26

Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss


Result (Burst power average) = Time average + Duty factor

\*The equipment and cables were not used for factor 0 dB of the data sheets.


**Burst Rate Confirmation**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 12, 2025  
 Temperature / Humidity 23 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off


**DH5**



**2DH5**



**3DH5**



## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2390.0	43.7	32.4	27.8	5.6	32.0	1.1	45.1	34.9	73.9	53.9	28.8	19.0	*1)
Hori.	4804.0	41.4	31.1	31.5	7.1	31.0	-	48.9	38.7	73.9	53.9	25.0	15.2	Floor noise
Hori.	7206.0	42.3	33.9	35.3	9.3	32.1	-	54.9	46.4	73.9	53.9	19.1	7.5	Floor noise
Hori.	9608.0	41.0	32.9	35.8	10.2	32.5	-	54.6	46.4	73.9	53.9	19.3	7.5	Floor noise
Vert.	2390.0	43.1	33.4	27.8	5.6	32.0	1.1	44.5	35.9	73.9	53.9	29.4	18.1	*1)
Vert.	4804.0	41.1	31.2	31.5	7.1	31.0	-	48.7	38.7	73.9	53.9	25.2	15.2	Floor noise
Vert.	7206.0	42.2	33.8	35.3	9.3	32.1	-	54.8	46.3	73.9	53.9	19.2	7.6	Floor noise
Vert.	9608.0	40.9	32.8	35.8	10.2	32.5	-	54.5	46.3	73.9	53.9	19.4	7.6	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP detector was used up to 1GHz.  
 \*1) Not Out of Band emission(Leakage Power)

### 20dBc Data Sheet



Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	94.1	27.7	5.6	31.9	95.5	-	-	Carrier
Hori.	2400.0	38.5	27.8	5.6	31.9	39.9	75.5	35.6	
Vert.	2402.0	89.6	27.7	5.6	31.9	90.9	-	-	Carrier
Vert.	2400.0	37.0	27.8	5.6	31.9	38.3	70.9	32.6	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Distance factor:  
 1 GHz - 6 GHz      20log (3.9 m / 3.0 m) = 2.28 dB  
 6 GHz - 10 GHz    20log (4.9 m / 3.0 m) = 4.27 dB  
 10 GHz - 26.5 GHz   20log (1.0 m / 3.0 m) = -9.5 dB

\*These results have sufficient margin without taking account Duty cycle correction factor.

## Radiated Spurious Emission (Reference Plot for band-edge)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.4
Date	February 19, 2025
Temperature / Humidity	24 deg. C / 39 % RH
Engineer	Takafumi Noguchi
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge and authorized band edge were shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Mode	Tx, Hopping Off, DH5 2441 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	4882.0	41.6	31.0	31.6	7.1	31.0	-	49.3	38.7	73.9	53.9	24.7	15.2	Floor noise
Hori.	7323.0	42.2	33.4	35.4	9.3	32.2	-	54.7	45.9	73.9	53.9	19.2	8.0	Floor noise
Hori.	9764.0	42.3	33.2	35.9	10.3	32.6	-	55.9	46.8	73.9	53.9	18.0	7.1	Floor noise
Vert.	4882.0	41.3	31.1	31.6	7.1	31.0	-	49.0	38.8	73.9	53.9	24.9	15.1	Floor noise
Vert.	7323.0	42.1	33.3	35.4	9.3	32.2	-	54.6	45.8	73.9	53.9	19.3	8.1	Floor noise
Vert.	9764.0	42.2	33.1	35.9	10.3	32.6	-	55.8	46.7	73.9	53.9	18.1	7.2	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

\*QP detector was used up to 1GHz.

Distance factor:	1 GHz - 6 GHz	20log (3.9 m / 3.0 m) = 2.28 dB
	6 GHz - 10 GHz	20log (4.9 m / 3.0 m) = 4.27 dB
	10 GHz - 26.5 GHz	20log (1.0 m / 3.0 m) = -9.5 dB

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2483.5	43.7	30.3	27.7	5.6	31.9	1.1	45.1	32.9	73.9	53.9	28.8	21.0	*1)
Hori.	4960.0	41.8	31.1	31.7	7.1	30.9	-	49.7	39.0	73.9	53.9	24.2	14.9	Floor noise
Hori.	7440.0	42.3	34.2	35.4	9.3	32.2	-	54.8	46.7	73.9	53.9	19.1	7.2	Floor noise
Hori.	9920.0	41.8	33.4	36.1	10.4	32.7	-	55.6	47.3	73.9	53.9	18.3	6.7	Floor noise
Vert.	2483.5	43.3	32.5	27.7	5.6	31.9	1.1	44.7	35.0	73.9	53.9	29.2	18.9	*1)
Vert.	4960.0	41.2	31.1	31.7	7.1	30.9	-	49.1	39.0	73.9	53.9	24.8	14.9	Floor noise
Vert.	7440.0	42.2	34.1	35.4	9.3	32.2	-	54.7	46.6	73.9	53.9	19.2	7.3	Floor noise
Vert.	9920.0	41.7	33.3	36.1	10.4	32.7	-	55.5	47.2	73.9	53.9	18.4	6.7	Floor noise



Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP detector was used up to 1GHz.  
 \*1) Not Out of Band emission(Leakage Power)

Distance factor:      1 GHz - 6 GHz              20log (3.9 m / 3.0 m) = 2.28 dB  
                                  6 GHz - 10 GHz            20log (4.9 m / 3.0 m) = 4.27 dB  
                                  10 GHz - 26.5 GHz        20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission  
(Reference Plot for band-edge)**

Test place  
Semi Anechoic Chamber  
Date  
Temperature / Humidity  
Engineer  
Mode

Ise EMC Lab.  
No.4  
February 19, 2025  
24 deg. C / 39 % RH  
Takafumi Noguchi  
(1 GHz to 6 GHz)  
Tx, Hopping Off, DH5 2480 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge was shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)

Semi Anechoic Chamber	No.4
Date	February 23, 2025
Temperature / Humidity	20 deg. C / 38 % RH
Engineer	Takafumi Noguchi (Below 1 GHz)

Mode Tx, Hopping Off, 3DH5 2402 MHz

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	33.0	21.6	-	17.5	6.9	32.1	-	13.9	-	40.0	-	26.2	-	
Hori.	72.6	37.7	-	6.4	7.4	32.1	-	19.4	-	40.0	-	20.6	-	
Hori.	99.0	29.1	-	10.1	7.7	32.1	-	14.8	-	43.5	-	28.7	-	
Hori.	168.6	29.8	-	15.7	8.3	32.0	-	21.8	-	43.5	-	21.7	-	
Hori.	330.0	32.9	-	14.7	9.6	32.1	-	25.1	-	46.0	-	20.9	-	
Hori.	924.0	28.5	-	22.1	12.3	31.0	-	31.9	-	46.0	-	14.1	-	
Hori.	2390.0	42.6	32.5	27.8	5.6	32.0	1.1	43.9	34.9	73.9	53.9	30.0	19.0	*1)
Hori.	4804.0	41.6	31.2	31.5	7.1	31.0	-	49.1	38.7	73.9	53.9	24.8	15.2	Floor noise
Hori.	7206.0	42.4	34.0	35.3	9.3	32.1	-	55.0	46.5	73.9	53.9	19.0	7.4	Floor noise
Hori.	9608.0	41.1	33.0	35.8	10.2	32.5	-	54.7	46.5	73.9	53.9	19.2	7.4	Floor noise
Vert.	31.9	33.7	-	18.0	6.8	32.1	-	26.4	-	40.0	-	13.6	-	
Vert.	33.0	31.1	-	17.5	6.9	32.1	-	23.4	-	40.0	-	16.7	-	
Vert.	72.6	35.7	-	6.4	7.4	32.1	-	17.4	-	40.0	-	22.6	-	
Vert.	99.0	28.9	-	10.1	7.7	32.1	-	14.6	-	43.5	-	28.9	-	
Vert.	150.0	27.9	-	15.0	8.1	32.0	-	19.0	-	43.5	-	24.5	-	
Vert.	330.0	29.7	-	14.7	9.6	32.1	-	21.9	-	46.0	-	24.1	-	
Vert.	924.0	27.9	-	22.1	12.3	31.0	-	31.3	-	46.0	-	14.7	-	
Vert.	2390.0	43.3	32.4	27.8	5.6	32.0	1.1	44.6	34.9	73.9	53.9	29.3	19.0	*1)
Vert.	4804.0	41.5	31.2	31.5	7.1	31.0	-	49.0	38.8	73.9	53.9	24.9	15.2	Floor noise
Vert.	7206.0	42.3	33.9	35.3	9.3	32.1	-	54.9	46.4	73.9	53.9	19.1	7.5	Floor noise
Vert.	9608.0	41.0	32.9	35.8	10.2	32.5	-	54.6	46.4	73.9	53.9	19.3	7.5	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP detector was used up to 1GHz.  
 \*1) Not Out of Band emission(Leakage Power)

### 20dBc Data Sheet



Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	92.8	27.7	5.6	31.9	94.1	-	-	Carrier
Hori.	2400.0	39.6	27.8	5.6	31.9	40.9	74.1	33.2	
Vert.	2402.0	88.2	27.7	5.6	31.9	89.6	-	-	Carrier
Vert.	2400.0	37.6	27.8	5.6	31.9	39.0	69.6	30.6	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor:  
 1 GHz - 6 GHz      20log (3.9 m / 3.0 m) = 2.28 dB  
 6 GHz - 10 GHz    20log (4.9 m / 3.0 m) = 4.27 dB  
 10 GHz - 26.5 GHz    20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission  
 (Reference Plot for band-edge)**

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.4
Date	February 19, 2025
Temperature / Humidity	24 deg. C / 39 % RH
Engineer	Takafumi Noguchi
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
 Final result of restricted band edge and authorized band edge were shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Mode	Tx, Hopping Off, 3DH5 2441 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	4882.0	41.7	31.0	31.6	7.1	31.0	-	49.4	38.7	73.9	53.9	24.5	15.2	Floor noise
Hori.	7323.0	42.3	33.5	35.4	9.3	32.2	-	54.8	46.0	73.9	53.9	19.1	7.9	Floor noise
Hori.	9764.0	42.4	33.2	35.9	10.3	32.6	-	56.0	46.8	73.9	53.9	17.9	7.1	Floor noise
Vert.	4882.0	41.7	31.0	31.6	7.1	31.0	-	49.4	38.7	73.9	53.9	24.5	15.2	Floor noise
Vert.	7323.0	42.2	33.4	35.4	9.3	32.2	-	54.7	45.9	73.9	53.9	19.2	8.0	Floor noise
Vert.	9764.0	42.3	33.2	35.9	10.3	32.6	-	55.9	46.8	73.9	53.9	18.0	7.1	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

\*QP detector was used up to 1GHz.

Distance factor:	1 GHz - 6 GHz	20log (3.9 m / 3.0 m) = 2.28 dB
	6 GHz - 10 GHz	20log (4.9 m / 3.0 m) = 4.27 dB
	10 GHz - 26.5 GHz	20log (1.0 m / 3.0 m) = -9.5 dB

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2483.5	43.7	33.6	27.7	5.6	31.9	1.1	45.1	36.1	73.9	53.9	28.8	17.8	*1)
Hori.	4960.0	41.7	31.5	31.7	7.1	30.9	-	49.6	39.4	73.9	53.9	24.3	14.5	Floor noise
Hori.	7440.0	42.4	34.3	35.4	9.3	32.2	-	54.9	46.8	73.9	53.9	19.0	7.1	Floor noise
Hori.	9920.0	41.9	33.5	36.1	10.4	32.7	-	55.7	47.4	73.9	53.9	18.2	6.6	Floor noise
Vert.	2483.5	43.2	33.3	27.7	5.6	31.9	1.1	44.6	35.9	73.9	53.9	29.3	18.0	*1)
Vert.	4960.0	41.1	31.1	31.7	7.1	30.9	-	49.0	39.0	73.9	53.9	24.9	14.9	Floor noise
Vert.	7440.0	42.3	34.2	35.4	9.3	32.2	-	54.8	46.7	73.9	53.9	19.1	7.2	Floor noise
Vert.	9920.0	41.8	33.4	36.1	10.4	32.7	-	55.6	47.3	73.9	53.9	18.3	6.7	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

\*QP detector was used up to 1GHz.



\*1) Not Out of Band emission(Leakage Power)

Distance factor:	1 GHz - 6 GHz	20log (3.9 m / 3.0 m) = 2.28 dB
	6 GHz - 10 GHz	20log (4.9 m / 3.0 m) = 4.27 dB
	10 GHz - 26.5 GHz	20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission  
 (Reference Plot for band-edge)**

Test place  
 Semi Anechoic Chamber  
 Date  
 Temperature / Humidity  
 Engineer  
 Mode

Ise EMC Lab.  
 No.4  
 February 19, 2025  
 24 deg. C / 39 % RH  
 Takafumi Noguchi  
 (1 GHz to 6 GHz)  
 Tx, Hopping Off, 3DH5 2480 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
 Final result of restricted band edge was shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 20, 2025	February 23, 2025
Temperature / Humidity	23 deg. C / 42 % RH	20 deg. C / 35 % RH	20 deg. C / 38 % RH
Engineer	Tomoya Sone (1 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)	Takafumi Noguchi (Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz + 11ac-40 5755 MHz		

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	33.0	22.3	-	17.5	6.9	32.1	-	14.6	-	40.0	-	25.5	-	
Hori.	72.6	38.3	-	6.4	7.4	32.1	-	20.0	-	40.0	-	20.0	-	
Hori.	99.0	29.2	-	10.1	7.7	32.1	-	14.9	-	43.5	-	28.6	-	
Hori.	168.6	29.6	-	15.7	8.3	32.0	-	21.6	-	43.5	-	21.9	-	
Hori.	330.0	32.7	-	14.7	9.6	32.1	-	24.9	-	46.0	-	21.1	-	
Hori.	924.0	28.5	-	22.1	12.3	31.0	-	31.9	-	46.0	-	14.1	-	
Hori.	2483.5	42.3	31.3	27.7	5.6	31.9	1.1	43.7	33.8	73.9	53.9	30.2	20.1	*1)
Hori.	4960.0	40.2	30.1	31.7	8.0	30.9	-	49.0	38.9	73.9	53.9	25.0	15.0	Floor noise
Hori.	7440.0	42.2	34.1	35.4	9.3	32.2	-	54.7	46.6	73.9	53.9	19.2	7.3	Floor noise
Hori.	9920.0	41.7	33.3	36.1	10.4	32.7	-	55.5	47.2	73.9	53.9	18.4	6.7	Floor noise
Vert.	31.9	34.5	-	18.0	6.8	32.1	-	27.2	-	40.0	-	12.8	-	
Vert.	33.0	31.6	-	17.5	6.9	32.1	-	23.9	-	40.0	-	16.2	-	
Vert.	72.6	36.2	-	6.4	7.4	32.1	-	17.9	-	40.0	-	22.1	-	
Vert.	99.0	28.9	-	10.1	7.7	32.1	-	14.6	-	43.5	-	28.9	-	
Vert.	150.0	27.5	-	15.0	8.1	32.0	-	18.6	-	43.5	-	24.9	-	
Vert.	330.0	29.4	-	14.7	9.6	32.1	-	21.6	-	46.0	-	24.4	-	
Vert.	924.0	27.9	-	22.1	12.3	31.0	-	31.3	-	46.0	-	14.7	-	
Vert.	2483.5	41.7	31.3	27.7	5.6	31.9	1.1	43.1	33.9	73.9	53.9	30.8	20.0	*1)
Vert.	4960.0	40.3	30.2	31.7	8.0	30.9	-	49.1	39.0	73.9	53.9	24.9	14.9	Floor noise
Vert.	7440.0	42.1	34.0	35.4	9.3	32.2	-	54.6	46.5	73.9	53.9	19.3	7.4	Floor noise
Vert.	9920.0	41.6	33.2	36.1	10.4	32.7	-	55.4	47.1	73.9	53.9	18.5	6.8	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

\*QP detector was used up to 1GHz.

\*1) Not Out of Band emission(Leakage Power)



Distance factor:      1 GHz - 6 GHz            20log (3.9 m / 3.0 m) = 2.28 dB  
                               6 GHz - 10 GHz            20log (4.9 m / 3.0 m) = 4.27 dB  
                               10 GHz - 26.5 GHz        20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission  
 (Reference Plot for band-edge)**

Test place  
 Semi Anechoic Chamber  
 Date  
 Temperature / Humidity  
 Engineer

Ise EMC Lab.  
 No.4  
 February 19, 2025  
 23 deg. C / 42 % RH  
 Tomoya Sone  
 (1 GHz to 18 GHz)  
 Tx, Hopping Off, 3DH5 2480 MHz + 11ac-40 5755 MHz



Mode



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
 Final result of restricted band edge was shown in tabular data.

**Radiated Spurious Emission**  
**(Plot data, Worst case mode for Maximum Peak Output Power)**

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.4	No.4	No.4
Date	February 19, 2025	February 19, 2025	February 20, 2025
Temperature / Humidity	24 deg. C / 39 % RH	23 deg. C / 42 % RH	20 deg. C / 35 % RH
Engineer	Takafumi Noguchi (1 GHz to 6 GHz)	Tomoya Sone (6 GHz to 18 GHz)	Tetsuro Yoshida (Above 18 GHz)
Semi Anechoic Chamber	No.4		
Date	February 23, 2025		
Temperature / Humidity	20 deg. C / 38 % RH		
Engineer	Takafumi Noguchi (Below 1 GHz)		
Mode	Tx, Hopping Off, 3DH5 2402 MHz		





\*These plots data contain sufficient number to show the trend of characteristic features for EUT.

**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, DH5



**2402 MHz**



**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, DH5



**2441 MHz**



**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, DH5



**2480 MHz**



**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, 3DH5



**2402 MHz**



**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, 3DH5



**2441 MHz**



**Conducted Spurious Emission**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx, Hopping Off, 3DH5


**2480 MHz**




**Conducted Emission Band Edge compliance**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx DH5

**Hopping On**




**Hopping Off**




**Conducted Emission Band Edge compliance**

Test place Ise EMC Lab. No.6 Measurement Room  
 Date February 13, 2025  
 Temperature / Humidity 20 deg. C / 39 % RH  
 Engineer Shousei Hamaguchi  
 Mode Tx 3DH5

**Hopping On**



**Hopping Off**



## APPENDIX 2: Test Instruments

### Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	141244	Attenuator(10dB)	Weinschel - API Technologies Corp	WA8-10-34	A198	02/04/2025	12
AT	141327	Coaxial Cable	UL-ISE	-	-	02/19/2025	12
AT	141414	Microwave Cable	Junkosha	MWX221	1207S407	07/06/2024	12
AT	141419	Attenuator	Weinschel Associates	WA56-10	56100305	05/22/2024	12
AT	141558	Digital Tester(TRUE RMS MULTIMETER)	Fluke Corporation	115	17930030	05/17/2024	12
AT	141809	Power Meter	Anritsu Corporation	ML2495A	825002	05/22/2024	12
AT	141830	Power sensor	Anritsu Corporation	MA2411B	738285	05/22/2024	12
AT	141900	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46185823	11/13/2024	12
AT	244712	Thermo-Hygrometer	HIOKI E. E. CORPORATION	LR5001	231202106	01/19/2025	12
RE	141267	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-192	09/18/2024	12
RE	141296	High Pass Filter 3.5-18.0GHz	UL-ISE	HPF SELECTOR	002	09/11/2024	12
RE	141397	Coaxial Cable	UL-ISE EMC	-	-	11/29/2024	12
RE	141425	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	VHA 91031302	08/23/2024	12
RE	141506	Horn Antenna 15-40GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9170	BBHA9170307	08/07/2024	12
RE	141508	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	557	05/17/2024	12
RE	141545	DIGITAL HiTESTER	HIOKI E. E. CORPORATION	3805	51201148	02/01/2024	12
RE	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	00650	10/30/2024	12
RE	141583	Pre Amplifier	SONOMA INSTRUMENT	310	260833	04/04/2024	12
RE	141899	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY46180655	05/09/2024	12
RE	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	05/17/2024	12
RE	142011	AC4_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	12/13/2023	24
RE	142017	AC4_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/14/2023	24
RE	142230	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	220646	Attenuator	Huber+Suhner	6806 N-50-1	-	03/12/2024	12
RE	234602	Microwave Cable	Huber+Suhner	SF126E/11PC35/11	537063/126E / 537074/126E	03/08/2024	12
RE	238713	Double Ridge Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA 9120 C	688	09/02/2024	12
RE	244710	Thermo-Hygrometer	HIOKI E. E. CORPORATION	LR5001	231202104	01/19/2025	12

\*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

AT: Antenna Terminal Conducted test

RE: Radiated Emission