## RF Exposure / SAR Statement

No.: 27FE0246HO-A

Applicant : Panasonic Corporation of North America

Type of Equipment: Bluetooth module Model No. : C5ZZZ0000035 FCC ID : ACJ932C5ZZZ035

Panasonic Corporation of North America declares that Model: C5ZZZ0000035 complies with FCC radiation exposure requirement specified in the FCC Rules 2.1093(for portable)/2.1091 (for mobile).

The "C5ZZZ0000035" has 1.21 mW of conducted Peak Output power and 1.71 mW of EIRP. This kind of equipment is below 60/frequency[GHz] mW(TCB Exclusion List) so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

## **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "C5ZZZ0000035" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm^2 uncontrolled exposure limit. The Friis formula used was:

 $S = (P * G) / (4* \pi * r^2)$ 

Where

P = 1.21 mW (Maximum peak output power)

G = 1.41 Numerical Antenna gain; equal 1.50 dBi

r = 20.0 cm

For: C5ZZZ0000035 S =  $0.00034 \text{ mW/cm}^2$ 

UL Japan, Inc.

**Head Office EMC Lab.** 

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124