

DISPLAY MONITOR DIVISION  
AVC COMPANY  
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.

1998.5.26  
REV-000

ENGINEERING SPECIFICATIONS (TENTATIVE)

**TY-LD65A ( for 21" ) USB HUB UNIT**

<FEATURES> (1) SELF POWERED HUB UNIT  
(2) ON THE PEDESTAL FOR 21" MONITOR  
(3) UPSTREAM : 1 PORT  
DOWNSTREAM : 4 PORTS

- [1] STANDARD : USB Spec. Rev. 1.0 compliant
- [2] INPUT SIGNAL : USB Signal Low speed / High speed
- [3] CONNECTOR : Upstream Receptacle series type A x 1  
Downstream Receptacle series type B x 4  
Power In 3-Pin Inlet ( CEE22 )  
Power Out 3-Pin Connector ( CEE22 )
- [4] POWER : Input voltage 90~132, 198~264Vac ( Auto-switching )  
Consumption 13 W ( max. )
- [5] OPERATING CONDITION : Temperature 0~40°C  
Humidity 5~90% ( Non-condensation )
- [6] DIMENSION : 300(W) x 56(H) x 300(D) mm
- [7] WEIGHT : 1.0 kg ( typ. ) ( Net )
- [8] SAFETY/REGULATIONS : UL, CSA, TUV/GS, NORDIC, FCC-B, IC-B, CISPR-B,  
CE

DISPLAY MONITOR DIVISION  
AVC COMPANY  
MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.

1998.5.26  
REV-000

ENGINEERING SPECIFICATIONS (TENTATIVE)

**TY-LD64A ( for 17" ) USB HUB UNIT**

<FEATURES> (1) SELF POWERED HUB UNIT  
(2) ON THE PEDESTAL FOR 17" MONITOR  
(3) UPSTREAM : 1 PORT  
DOWNSTREAM : 4 PORTS

- [1] STANDARD : USB Spec. Rev. 1.0 compliant
- [2] INPUT SIGNAL : USB Signal Low speed / High speed
- [3] CONNECTOR : Upstream Receptacle series type A x 1  
Downstream Receptacle series type B x 4  
Power In 3-Pin Inlet ( CEE22 )  
Power Out 3-Pin Connector ( CEE22 )
- [4] POWER : Input voltage 90~132, 198~264Vac ( Auto-switching )  
Consumption 13 W ( max. )
- [5] OPERATING CONDITION : Temperature 0~40°C  
Humidity 5~90% ( Non-condensation )
- [6] DIMENSION : 287(W) x 46(H) x 255(D) mm
- [7] WEIGHT : 1.0 kg ( typ. ) ( Net )
- [8] SAFETY/REGULATIONS : UL, CSA, TUV/GS, NORDIC, FCC-B, IC-B, CISPR-B,  
CE