



Test report no. : 224784-1

Item tested : KX-TG4221

Type of equipment : UPCS Base

FCC ID : ACJ96NKX-TG4221

Client : Panasonic System Networks Co., Ltd.

FCC Part 15, subpart D

Isochronous UPCS Device
1920 - 1930 MHz

Industry Canada RSS-213, Issue 2

2 GHz Licence-exempt Personal
Communications Service Devices
(LE-PCS)

2 January 2013

Authorized by :

Roy Uggerud
Technical Verificator

CONTENTS

1	GENERAL INFORMATION	3
1.1	Testhouse Info	3
1.2	Client Information	3
1.3	Responsible Manufacturer (if other than client)	3
2	TEST INFORMATION	4
2.1	Tested Item	4
2.2	Description of Tested Device	4
2.3	Exposure Evaluation	4
2.4	Test Environment	5
2.5	Test Period	5
2.6	Test Engineer(s)	5
2.7	Test Equipment	5
2.8	Other Comments	5
3	TEST REPORT SUMMARY	6
3.1	General	6
3.2	Test Summary	7
4	TEST RESULTS	8
4.1	Power Line Conducted Emissions	8
4.2	Coordination with fixed microwave	14
4.3	Digital Modulation Techniques	14
4.4	Labeling Requirements	14
4.5	Antenna Requirement	15
4.6	Channel Frequencies	15
4.7	Automatic Discontinuation of Transmission	16
4.8	Peak Power Output	17
4.9	Emission Bandwidth <i>B</i>	22
4.10	Power Spectral Density	25
4.11	In-Band Unwanted Emissions, Conducted	28
4.12	Out-of-band Emissions, Conducted	30
4.13	Carrier Frequency Stability	35
4.14	Frame Repetition Stability	36
4.15	Frame Period and Jitter	36
4.16	Monitoring Threshold, Least Interfered Channel	38
4.17	Threshold Monitoring Bandwidth	40
4.18	Reaction Time and Monitoring Interval	41
4.19	Time and Spectrum Window Access Procedure	43
4.20	Acknowledgements and Transmission Duration	47
4.21	Dual Access Criteria Check	48
4.22	Alternative Monitoring Interval	49
5	TEST SETUPS	50
5.1	Frequency Measurements	50
5.2	Timing Measurements	50
5.3	Conducted Emission Test	50
5.4	Power Line Conducted Emissions Test	50
5.5	Monitoring Tests	51
6	TEST EQUIPMENT USED	52

1 GENERAL INFORMATION

1.1 Testhouse Info

Name : Nemko AS
Address : Nemko Kjeller
Instituttveien 6
N-2007 Kjeller, NORWAY
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail: comlab@nemko.com
FCC test firm registration # : 994405
IC OATS registration # : 2040D-1
Total Number of Pages: 52

1.2 Client Information

Name : Panasonic System Networks Co., Ltd.
Address : 1-62, 4-chome Minoshima, Hakata-ku, Fukuoka, 812-8531, Japan
Telephone : +81-92-477-1405

Contact:

Name : Mr. Hirai Keisuke
Telephone : +81-92-477-1405
E-mail : hirai.keisuke@jp.panasonic.com

1.3 Responsible Manufacturer (if other than client)

Same as client.

2 Test Information

2.1 Tested Item

Name :	Panasonic
Model name :	KX-TG4221
FCC ID :	ACJ96NKX-TG4221
Industry Canada ID :	216A-KXTG4221
Serial number :	/
Hardware identity and/or version:	PNLB2154xx
Software identity and/or version :	SW401
Tested to IC Radio Standard (RSS) :	RSS-213 Issue 2, RSS-GEN Issue 3
Test Site IC Reg. Number :	IC 2040D-1
Frequency Range :	1921.536 – 1928.448 MHz
Number of Channels :	5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Type of Modulation :	Digital (Gaussian Frequency Shift Keying)
Conducted Output Power :	110 mW (Peak)
Antenna Connector :	None
Number of Antennas :	2
Antenna Diversity Supported :	Yes
Power Supply :	AC Adaptors: PNLV226 (UC) and PNLV226 (FW)

2.2 Description of Tested Device

The EUT is a DECT Base Station and is a responding device as described in ANSI C63.17 and is designed to operate together with a DECT portable part (i.e. a handset), which is the initiating device.

2.3 Exposure Evaluation

The EUT is designed to be fixed to a wall etc. and the user manual contains text that it shall be mounted with a separation distance of at least 20cm from any persons. For the purposes of exposure evaluation this EUT is a mobile or fixed device. MPE Calculation at 20cm satisfying FCC requirements is submitted as a separate document.

The EUT is exempted from RF Exposure Evaluation to Industry Canada requirements since the output power complies with the power levels of section 2.5.2 of RSS-102 Issue 4.

2.4 Test Environment

Temperature:	19.1 – 23.3 °C
Relative humidity:	20.1 – 43.9 %
Normal test voltage:	120 V AC

The values are the limit registered during the test period.

2.5 Test Period

Item received date:	2012-11-02
Test period :	from 2012-12-04 to 2012-12-20

2.6 Test Engineer(s)

Frode Sveinsen / Tore Løvlien

2.7 Test Equipment

See list of test equipment in clause 6.

2.8 Other Comments

The Monitoring and Time and Spectrum Window Access tests were performed with Test Set-Up 6 (Ref. clause 5). A clock signal from the companion device was used to synchronize the Pulse Pattern Generator and the Spectrum Analyzer to the start of the DECT time window. The EUT was limited by administrative commands to operate on only two frequency carriers. For the tests where the EUT was required to operate on only one frequency carrier, one carrier was blocked by applying a CW interfering signal from RF Generator 3. The Pulse Pattern Generator was used to apply time synchronized interference to time windows where this was required.

Since the EUT was programmed to operate on only two RF carriers, it was only necessary with two RF generators for the monitoring tests, however a third generator was applied for the tests that required specific time slots to be blocked.

This EUT supports Least Interfered Channel procedure (LIC), the Monitoring and Time and Spectrum Window Access tests were conducted as specified for EUTs that support LIC procedure.

All tests except Antenna Gain and Power-Line Conducted Emissions were performed in conducted mode with a temporary antenna connector.

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Panasonic
Model No.: KX-TG4221

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2 / RSS-GEN Issue 3.

All tests were conducted in accordance with ANSI C63.4-2009 and ANSI C63.17-2006. Antenna Gain tests were made in a 3m fully-anechoic chamber.

A description of the test facility is on file with the FCC and Industry Canada.

- | | |
|---|---|
| <input checked="" type="checkbox"/> New Submission | <input checked="" type="checkbox"/> Production Unit |
| <input type="checkbox"/> Class II Permissive Change | <input type="checkbox"/> Pre-production Unit |
| PUB Equipment Code | <input type="checkbox"/> Family Listing |

THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".



TEST REPORT NO: 224784-1

TESTED BY : Frode Sveinsen
Frode Sveinsen, Chief Engineer

DATE: 21 December 2012

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Coordination with fixed microwave	15.307(b)	N/A	Complies
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	3 RSS-GEN 5.2	Complies
Antenna Requirement	15.317, 15.203	RSS-GEN 7.1.2	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	6.3 RSS-GEN 7.2.2	Complies
Emission Bandwidth	15.323(a)	6.4	Complies
In-band emissions	15.323(d)	6.7.2	Complies
Out-of-band emissions	15.323(d)	6.7.1	Complies
Output Power and Antenna Gain	15.319(c)(e), 15.31(e)	6.5 and 4.1(e)	Complies
Power Spectral Density	15.319(d)	4.3.2.1	Complies
Automatic discontinuation of transmission	15.319(f)	4.3.4(a)	Complies
Carrier frequency stability	15.323(f)	6.2	Complies
Frame repetition stability	15.323(e)	4.3.4(c)	Complies
Frame period and jitter	15.323(e)	4.3.4(c)	Complies
Monitoring threshold, Least interfered channel	15.323(c)(2);(5); (9)	4.3.4(b)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	4.3.4(b)	Complies
Threshold monitoring bandwidth	15.323(c)(7)	4.3.4(b)	Complies
Reaction time and monitoring interval	15.323(c)(1);(5); (7)	4.3.4(b)	Complies
Access criteria test interval	15.323(c)(4);(6)	4.3.4(b)	Complies
Access Criteria functional test	15.323(c)(4);(6)	4.3.4(b)	Complies
Acknowledgements	15.323(c)(4)	4.3.4(b)	Complies
Transmission duration	15.323(c)(3)	4.3.4(b)	N/A ¹
Dual access criteria	15.323(c)(10)	4.3.4(b)	N/A ¹
Alterative monitoring interval	15.323(c)(10);(11)	4.3.4(b)	N/A ²
Spurious Emissions (Radiated)	15.319(g) 15.109(a) 15.209(a)	4.3.3 RSS-GEN 7.2.3	N/A ³

¹ Only applies for EUT that can be initiating device

² The client declares that the tested equipment does not implement this provision

³ Not required if the Conducted Out-of-Band Emissions test is Passed

4 TEST RESULTS

4.1 Power Line Conducted Emissions

Para. No.: 15.207 (a)

Test Performed By: Tore Løvlien	Date of Test: 3-Dec-2012
---------------------------------	--------------------------

Measurement procedure: ANSI C63.4-2009 using 50 µH/50 ohms LISN.

Test Results: Complies

Measurement Data: See attached graph, (Peak detector).

Highest measured value (L1 and N):

PNLV226(UC), Off-Hook Mode:

Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.360000	36.50	10.20	58.70	22.20	QP	N	Pass
1.850000	30.90	10.20	56.00	25.10	QP	N	Pass
2.560000	32.30	10.30	56.00	23.70	QP	N	Pass
3.220000	32.50	10.30	56.00	23.50	QP	N	Pass
3.705000	32.20	10.30	56.00	23.80	QP	N	Pass
0.165000	17.90	10.10	55.20	37.30	AV	N	Pass
0.215000	17.40	10.10	53.00	35.60	AV	N	Pass
0.330000	17.30	10.20	49.50	32.20	AV	N	Pass
0.360000	24.20	10.20	48.70	24.50	AV	N	Pass
0.500000	17.00	10.20	46.00	29.00	AV	N	Pass
0.725000	17.00	10.20	46.00	29.00	AV	N	Pass
0.950000	15.50	10.20	46.00	30.50	AV	N	Pass
0.980000	16.00	10.20	46.00	30.00	AV	N	Pass
1.475000	18.10	10.20	46.00	27.90	AV	N	Pass
1.850000	18.70	10.20	46.00	27.30	AV	N	Pass
2.560000	20.20	10.30	46.00	25.80	AV	N	Pass
3.220000	20.40	10.30	46.00	25.60	AV	N	Pass
3.705000	19.80	10.30	46.00	26.20	AV	N	Pass
4.840000	17.10	10.40	46.00	28.90	AV	N	Pass
6.180000	13.80	10.50	50.00	36.20	AV	N	Pass

PNLV226(UC), Charger Mode:


Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.160000	42.00	10.10	65.50	23.50	QP	N	Pass
0.210000	36.80	10.10	63.20	26.40	QP	N	Pass
0.325000	40.30	10.20	59.60	19.30	QP	N	Pass
0.335000	38.90	10.20	59.30	20.40	QP	N	Pass
0.385000	37.30	10.20	58.20	20.90	QP	N	Pass
0.560000	31.70	10.20	56.00	24.30	QP	N	Pass
0.720000	34.40	10.20	56.00	21.60	QP	N	Pass
0.940000	32.60	10.20	56.00	23.40	QP	N	Pass
1.165000	35.40	10.20	56.00	20.60	QP	N	Pass
1.555000	35.10	10.20	56.00	20.90	QP	N	Pass
1.970000	35.70	10.20	56.00	20.30	QP	N	Pass
2.750000	36.80	10.30	56.00	19.20	QP	N	Pass
3.570000	37.00	10.30	56.00	19.00	QP	N	Pass
3.995000	36.50	10.40	56.00	19.50	QP	N	Pass
4.885000	34.00	10.40	56.00	22.00	QP	N	Pass
0.160000	22.30	10.10	55.50	33.20	AV	N	Pass
0.210000	18.80	10.10	53.20	34.40	AV	N	Pass
0.325000	25.90	10.20	49.60	23.70	AV	N	Pass
0.335000	24.60	10.20	49.30	24.70	AV	N	Pass
0.385000	24.00	10.20	48.20	24.20	AV	N	Pass
0.560000	19.60	10.20	46.00	26.40	AV	N	Pass
0.720000	19.70	10.20	46.00	26.30	AV	N	Pass
0.940000	19.00	10.20	46.00	27.00	AV	N	Pass
1.165000	22.10	10.20	46.00	23.90	AV	N	Pass
1.555000	21.80	10.20	46.00	24.20	AV	N	Pass
1.970000	22.50	10.20	46.00	23.50	AV	N	Pass
2.750000	24.00	10.30	46.00	22.00	AV	N	Pass
3.570000	24.00	10.30	46.00	22.00	AV	N	Pass
3.995000	23.10	10.40	46.00	22.90	AV	N	Pass
4.885000	20.90	10.40	46.00	25.10	AV	N	Pass
6.145000	17.80	10.50	50.00	32.20	AV	N	Pass
8.160000	14.40	10.60	50.00	35.60	AV	L1	Pass
8.435000	14.00	10.60	50.00	36.00	AV	L1	Pass
8.625000	13.80	10.60	50.00	36.20	AV	L1	Pass
17.120000	13.60	10.90	50.00	36.40	AV	N	Pass

PNLV226(FW), Off-Hook Mode:


Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
4.040000	28.00	10.40	56.00	28.00	QP	N	Pass
0.420000	28.00	10.20	47.40	19.40	AV	L1	Pass
0.435000	22.10	10.20	47.20	25.10	AV	L1	Pass
0.735000	13.70	10.20	46.00	32.30	AV	N	Pass
0.790000	12.70	10.20	46.00	33.30	AV	N	Pass
1.235000	12.90	10.20	46.00	33.10	AV	N	Pass
1.485000	13.40	10.20	46.00	32.60	AV	N	Pass
1.705000	13.60	10.20	46.00	32.40	AV	N	Pass
2.640000	15.80	10.30	46.00	30.20	AV	N	Pass
3.520000	18.60	10.30	46.00	27.40	AV	L1	Pass
4.040000	18.00	10.40	46.00	28.00	AV	N	Pass
4.825000	19.30	10.40	46.00	26.70	AV	L1	Pass
6.210000	16.70	10.50	50.00	33.30	AV	L1	Pass

PNLV226(FW), Charger Mode:


Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.150000	28.00	10.10	66.00	38.00	QP	N	Pass
0.185000	24.10	10.10	64.30	40.20	QP	N	Pass
0.205000	25.70	10.10	63.40	37.70	QP	N	Pass
0.215000	23.90	10.10	63.00	39.10	QP	N	Pass
0.245000	25.60	10.10	61.90	36.30	QP	N	Pass
0.275000	25.00	10.10	61.00	36.00	QP	N	Pass
0.330000	30.20	10.20	59.50	29.30	QP	N	Pass
0.410000	35.00	10.20	57.60	22.60	QP	N	Pass
0.455000	31.50	10.20	56.80	25.30	QP	N	Pass
0.480000	16.20	10.20	56.30	40.10	QP	N	Pass
0.520000	24.00	10.20	56.00	32.00	QP	N	Pass
0.565000	24.40	10.20	56.00	31.60	QP	N	Pass
0.955000	32.00	10.20	56.00	24.00	QP	N	Pass
1.690000	33.00	10.20	56.00	23.00	QP	N	Pass
1.725000	33.20	10.20	56.00	22.80	QP	N	Pass
1.735000	32.60	10.20	56.00	23.40	QP	N	Pass
1.870000	30.50	10.20	56.00	25.50	QP	N	Pass
1.965000	31.80	10.20	56.00	24.20	QP	N	Pass
2.280000	32.60	10.30	56.00	23.40	QP	N	Pass
9.185000	23.70	10.60	60.00	36.30	QP	N	Pass
0.150000	15.10	10.10	56.00	40.90	AV	N	Pass
0.185000	14.40	10.10	54.30	39.90	AV	N	Pass
0.205000	15.60	10.10	53.40	37.80	AV	N	Pass
0.215000	15.40	10.10	53.00	37.60	AV	N	Pass
0.245000	15.50	10.10	51.90	36.40	AV	N	Pass
0.275000	14.20	10.10	51.00	36.80	AV	N	Pass
0.330000	17.30	10.20	49.50	32.20	AV	N	Pass
0.410000	26.60	10.20	47.60	21.00	AV	N	Pass
0.455000	20.30	10.20	46.80	26.50	AV	N	Pass
0.480000	7.40	10.20	46.30	38.90	AV	N	Pass
0.520000	12.30	10.20	46.00	33.70	AV	N	Pass
0.565000	14.00	10.20	46.00	32.00	AV	N	Pass
0.955000	17.00	10.20	46.00	29.00	AV	N	Pass
1.690000	16.80	10.20	46.00	29.20	AV	N	Pass
1.725000	16.30	10.20	46.00	29.70	AV	N	Pass
1.735000	16.50	10.20	46.00	29.50	AV	N	Pass
1.870000	16.60	10.20	46.00	29.40	AV	N	Pass
1.965000	16.20	10.20	46.00	29.80	AV	N	Pass
2.280000	19.60	10.30	46.00	26.40	AV	N	Pass
9.185000	13.80	10.60	50.00	36.20	AV	N	Pass




PNLV226(UC), Off-Hook Mode (Plot shows worst case of Phase L1 and N)



PNLV226(UC), Charger Mode (Plot shows worst case of Phase L1 and N)



PNLV226(FW), Off-Hook Mode (Plot shows worst case of Phase L1 and N)



PNLV226(FW), Charger Mode (Plot shows worst case of Phase L1 and N)

4.2 Coordination with fixed microwave

The affidavit from UTAM, Inc. is included in the documentation supplied by the applicant:

Yes

No

Requirement, FCC 15.307 (b):

Each application for certification of equipment operating under the provisions of this Subpart must be accompanied by an affidavit from UTAM, Inc. certifying that the applicant is a participating member of UTAM, Inc. In the event a grantee fails to fulfill the obligations attendant to participation in UTAM, Inc., the Commission may invoke administrative sanctions as necessary to preclude continued marketing and installation of devices covered by the grant of certification, including but not limited to revoking certification.

4.3 Digital Modulation Techniques

The EUT uses Multi Carrier / Time Division Multiple Access / Time Division Duplex and Digital GFSK modulation. For further details see the operational description provided by the applicant.

Requirement, FCC 15.319(b):

All transmissions must use only digital modulation techniques.

4.4 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirements FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

4.5 Antenna Requirement

Does the EUT have detachable antenna(s)? Yes No

If detachable, is the antenna connector(s) non-standard? Yes No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

Requirement: FCC 15.203, 15.204, 15.317.

4.6 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.303 (d), (g)

Within 1920 -1930 MHz band for isochronous devices.

4.7 Automatic Discontinuation of Transmission

Does the EUT transmit Control and Signaling Information?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
TYPE OF EUT :	<input type="checkbox"/> INITIATING DEVICE	<input checked="" type="checkbox"/> RESPONDING DEVICE

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	A	Pass
2	Switch Off EUT	N/A	Pass
3	Hook-On by EUT	N/A	Pass
4	Power Removed from Companion Device	B	Pass
5	Switch Off Companion Device	B	Pass
6	Hook-On by Companion Device	B	Pass

- A - Connection breakdown, Cease of all transmissions
- B - Connection breakdown, EUT transmits control and signaling information
- C - Connection breakdown, Companion Device transmits control and signaling information
- N/A - Not Applicable (EUT does not have On/Off switch and cannot perform Hook-On)

Requirements, FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

4.8 Peak Power Output

Test Method:

ANSI C63.17, clause 6.1.2.

Test Results: Complies

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Maximum Radiated Output Power (dBm)	Maximum Antenna Gain (dBi)
4	1921.536	20.4	18.7	-1.7
2	1924.992	20.3	18.9	-1.4
0	1928.448	20.2	19.0	-1.2

Substitution:

Frequency MHz	Measured value dBm	Subst. Gen. (incl. corr.) dBm	Attenuator and Cable dB	Gain Subst. Antenna dB	Result dBm
1921.536	17.8	24.4	-14.0	8.3	18.7
1924.992	17.8	24.6	-14.0	8.3	18.9
1928.448	17.9	24.7	-14.0	8.3	19.0

Result = Subst.Gen. + Attenuator + Cable + Antenna Gain

For this test it was also checked that input voltage variation of 85 and 115% of nominal value did not have any effect on the measured output power, neither radiated nor conducted.

Limit:

Conducted: $100 \mu\text{W} \times \text{SQRT}(B)$ where B is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e): 21.8 dBm (152 mW)

RSS-213, Issue 2: 20.6 dBm (115 mW)


The antenna gain is below 3 dBi, no reduction in transmit power is necessary.

Requirements, FCC 15.319(c)(e), RSS-213, Issue 2

Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.


The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Conducted Peak Output Power




Date: 4.DEC.2012 10:32:49

Lower Channel



Date: 4.DEC.2012 10:30:15


Upper Channel



Date: 4. DEC. 2012 10:32:06


Middle Channel

Radiated Peak Output Power




Date: 11.DEC.2012 13:37:22

Lower Channel (Max Position: Ant 2, HP)



Date: 11.DEC.2012 13:35:32

Upper Channel (Max Position: Ant 2, HP)



Date: 11.DEC.2012 13:32:57

Middle Channel (Max Position: Ant 2, HP)

4.9 Emission Bandwidth *B*

Test Method:

ANSI C63.17, clause 6.1.3.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	26 dB Bandwidth <i>B</i> (kHz)
4	1921.536	2330.2
0	1928.448	2322.7

Channel No.	Frequency (MHz)	99% Bandwidth (kHz)
2	1924.992	1322.4

Channel No.	Frequency (MHz)	6 dB Bandwidth (kHz)
4	1921.536	N/A
0	1928.448	N/A

Channel No.	Frequency (MHz)	12 dB Bandwidth (kHz)
4	1921.536	N/A
0	1928.448	N/A


Requirements, FCC 15.323(a)

The 26 dB Bandwidth *B* shall be larger than 50 kHz and less than 2.5 MHz.

Requirements, RSS-213 Issue 2, clause 6.4


The 99% Bandwidth shall be larger than 50 kHz and less than 2.5 MHz.

No requirements for 6 and 12 dB Bandwidth, these values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).




Date: 4. DEC. 2012 10:26:58

Emission Bandwidth B, Lower Channel



Date: 4. DEC. 2012 10:28:29

Emission Bandwidth B, Upper Channel



Date: 4. DEC. 2012 10:16:29

99% Bandwidth, Middle Channel

4.10 Power Spectral Density

Test Method:

ANSI C63.17, clause 6.1.5.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm)
4	1921.536	2.8
0	1928.448	2.8


Averaged over 1000 sweeps.

Requirements, FCC 15.319(d)

The Power Spectral Density shall be less than 3 mW (4.77 dBm) when averaged over at least 100 sweeps.


Power Spectral Density

Lower Channel:



Date: 4. DEC. 2012 10:36:38


Overview



Date: 4. DEC. 2012 10:43:44


Averaged, 1000 Sweeps

Upper Channel:



Date: 4. DEC. 2012 10:39:58

Overview



Date: 4. DEC. 2012 10:41:29

Averaged, 1000 Sweeps

4.11 In-Band Unwanted Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.1.

Test Results: Complies

Measurement Data:


See plots.

Requirements, FCC 15.323(d):

$B < f \leq 2B$: at least 30 dB below max. permitted peak power

$2B < f \leq 3B$: at least 50 dB below max. permitted peak power


$3B < f \leq$ UPCS Band Edge : at least 60 dB below max. permitted peak power



Date: 4.DEC.2012 11:04:50


Middle Channel

In-Band Unwanted Emissions, Conducted



Date: 4.DEC.2012 11:12:22

Lower Channel



Date: 4.DEC.2012 11:20:08

Upper Channel

4.12 Out-of-band Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.2.

Test Results: Complies

Measurement Data:


See plots.

Requirements, FCC 15.323(d):

$f \leq 1.25\text{MHz}$ outside UPCS band :	$\leq -9.5\text{dBm}$
$1.25\text{MHz} \leq f \leq 2.5\text{MHz}$ outside UPCS band :	$\leq -29.5 \text{ dBm}$
$f \geq 2.5\text{MHz}$ outside UPCS band :	$\leq -39.5 \text{ dBm}$


Out-of-Band Emissions, Conducted

Lower Channel, AC Adaptor PNLV226 (UC):



Date: 4.DEC.2012 12:02:53


Lower Channel, AC Adaptor PNLV226 (FW):




Date: 13.DEC.2012 13:21:04

Out-of-Band Emissions, Conducted

Lower Channel:




Date: 4.DEC.2012 12:02:24




Date: 4.DEC.2012 12:01:21

Out-of-Band Emissions, Conducted

Upper Channel:




Date: 4.DEC.2012 12:04:18




Date: 4.DEC.2012 12:05:18

Out-of-Band Emissions, Conducted

Upper Channel:



Date: 4. DEC. 2012 12:05:58



Date: 4. DEC. 2012 12:06:42

4.13 Carrier Frequency Stability

Test Method:

ANSI C63.17, clause 6.2.1.

Test Results: Complies

Measurement Data:

The Frequency Stability is measured with the CMD60. The CMD60 was logged by a computer programmed to get new readings as fast as possible (about 3 readings per second) over the noted time period or number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier Frequency (MHz)	Max. Diff. (kHz)	Min. Diff. (kHz)	Max. Dev. (ppm)	Limit
1924.997762	6.983	4.593	0.6	±10 ppm

Deviation (ppm) is calculated from 3000 readings.

Frequency Stability over Power Supply Voltage at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
V _{nom}	1924.980298	0	0	±10 ppm
85% of V _{nom}	1924.980448	0.2	0.1	
115% of V _{nom}	1924.980597	0.3	0.2	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10⁶

This test does not apply for EUT that is powered from batteries.

Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
T = +20 °C	1924.980298	0	0	±10 ppm
T = -20 °C	1924.985310	5.0	2.6	
T = +50 °C	1924.974881	-5.4	-2.8	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10⁶

4.14 Frame Repetition Stability

Test Method:

ANSI C63.17, clause 6.2.2.

Test Results: Complies

Measurement Data:

The envelope of the RF signal from the EUT is detected with a Crystal Detector and the mean and standard deviation of the frame repetition frequency is then gated over 100 frames and measured with a Frequency Domain Analyzer. The frame repetition stability is 3 times the standard deviation.

Carrier Frequency (MHz)	Mean (Hz)	Standard Deviation (Hz)	Frame Repetition Stability (ppm)
1924.992	99.999971	0.034	0.102

Limit:

Frame Repetition Stability	±10 ppm (TDMA)
----------------------------	----------------

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.2

4.15 Frame Period and Jitter

Test Method:

ANSI C63.17, clause 6.2.3.

Test Results: Complies

Measurement Data:

Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (µs)	3xStandard Deviation of Jitter (µs)
1924.992	10.000	-0.053	-0.022

Max Jitter = (1/ (Frame period + Pk-Pk/2)) - (1/Frame Period), when Pk-Pk and Frame Period are in Hz


3xSt.Dev.Jitter = 3x (1/(Frame Period + St.Dev) – 1/St.Dev) x 10⁶

Limit:

Frame Period	20 or 10 ms
Max Jitter	25 µs
3 times St.Dev of Jitter	12.5 µs

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.3


(hp) Freq A t1k
 acquiring data



Mean 99.9999709273 MHz 1/Mean 10.000ms
 Pk-Pk 16.04 μHz Std Dev 3.3908 μHz

Frame Repetition Stability, Gated over 100 Frames

(hp) Freq A rem t1k
 acquiring data



Mean 99.9999671572 MHz 1/Mean 10.000ms
 Pk-Pk 1.0646 mHz Std Dev 72.2526 μHz

Frame Period and Jitter

4.16 Monitoring Threshold, Least Interfered Channel

Monitoring Threshold Limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT} \quad (\text{dBm})$$

Upper Threshold:

$$T_U = 15 \log B - 184 + 50 - P_{EUT} \quad (\text{dBm})$$

B is measured Emission Bandwidth in Hz
 P_{EUT} is measured Transmitter Power in dBm

Calculated values:

	FCC 15.323	RSS-213, Issue 2
Lower Threshold	-78.8 dBm	-82.5 dBm
Upper Threshold	N/A	-62.5 dBm

The Lower Threshold is applicable for systems which have defined less than 40 duplex system access channels. The Upper Threshold is applicable for systems with more than 40 duplex system access channels and that implements the Least Interfered Channel Procedure (LIC).

Measurement Procedure:

The Upper or Lower Threshold is found by the procedure defined in ANSI C63.17 clause 7.3.1 or 7.3.2.

Least Interfered Channel Procedure NOT used:	
Lower Threshold	N/A dBm
Least Interfered Channel Procedure:	
Upper Threshold	-61.5 dBm

Least Interfered Channel (LIC) Procedure Test, FCC 15.323(b), (c)(2) and (c)(5)


ANSI C63.17 clause 7.3.3 ref.	Observation	Verdict
b) f_1 $T_L + 13$ dB, f_2 at $T_L + 6$ dB	Transmission always on f_2	Pass
c) f_1 $T_L + 6$ dB, f_2 at $T_L + 13$ dB	Transmission always on f_1	Pass
d) f_1 $T_L + 7$ dB, f_2 at T_L	Transmission always on f_2	Pass
e) f_1 T_L , f_2 at $T_L + 7$ dB	Transmission always on f_1	Pass

Selected Channel Confirmation, FCC 15.323(c)(1) and (5)

ANSI C63.17 clause 7.3.4	Observation	Verdict
b) Shall not transmit on f_1	EUT transmits on f_2	Pass
d) Shall not transmit on f_2	EUT transmits on f_1	Pass

Limits:

	FCC 15.323	RSS-213, Issue 2
Lower Threshold + 6 dB margin	-72.8 dBm	-76.5 dBm
Upper Threshold + 6 dB margin	N/A	-56.5 dBm



Date: 18.DEC.2012 14:13:43

7.3.4 Selected Channel Confirmation, Connection 0.975s After Interferer Removed

4.17 Threshold Monitoring Bandwidth

This test is only required if a dedicated monitoring receiver is used. However, if the test is not carried out the manufacturer shall declare and provide proper evidence that the monitoring is made through the radio receiver used for communication.

Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if **either** the Simple Compliance Test or the More Detailed test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

Test Results:

Test performed	Observation	Verdict
Simple Compliance test, at $\pm 30\%$ of B	No transmissions	Pass
More Detailed Test, at -6 dB points	N/A	N/A
More Detailed Test, at -12 dB points	N/A	N/A

The more detailed test must be pass at both the -6 and -12 dB points if the Simple Compliance test fails.

Comment: The Simple Compliance Test was performed with the level at $T_U + U_M + 10$ dB to check that the EUT did not transmit at all.

The tested EUT uses the same receiver for monitoring and communication, this test is therefore not required. However the test has been performed nonetheless and the test is passed.

Limits, FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.

4.18 Reaction Time and Monitoring Interval

Measurement Procedure

ANSI C63.17, clause 7.5

Test results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on a single carrier frequency.

Time-synchronized pulsed interference was then applied on the carrier at pulsed levels $T_U + U_M$ to check that the EUT does not transmit at all. The level was raised 6 dB for part d) with 35 μ s pulses.

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.


Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 μ s and $50 \cdot \text{SQRT}(1.25/B)$	No connection	Pass
d) > largest of 35 μ s and $35 \cdot \text{SQRT}(1.25/B)$, and with interference level raised 6 dB	No connection	Pass

Comment: Since B is larger than 1.25 MHz the test was performed with pulse lengths of 50 μ s and 35 μ s. It was checked that it was not possible to set up a connection with pulses present. It was also checked that the EUT stopped transmission of control bearer if the pulses were moved so that they blocked the control bearer.

Limits, FCC 15.323(c)(1), (5) and (7)


The maximum reaction time must be less than $50 \cdot \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be $35 \cdot \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds but shall not be required to be less than 35 microseconds.



Date: 18.DEC.2012 14:31:12

50 µs Pulses



Date: 18.DEC.2012 14:29:47

35 µs Pulses

4.19 Time and Spectrum Window Access Procedure

This requirement is only for EUTs which transmit unacknowledged control and signaling information.

Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time-slot	EUT transmits on the interference free time-slot	Pass
b) The EUT must terminate or pause in its repetitive transmission of the control and signalling channel on the open channel to repeat the access criteria not less frequently than every 30 s	Transmission paused every 1.28 s	Pass

If FCC 15.323(c)(6) option, **If Random Waiting Interval is NOT implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to an interference-free slot when interference is introduced on the time slot in use	EUT changes to the interference-free time-slot, and stays there	Pass

If FCC 15.323(c)(6) option, **Only if Random Waiting Interval is implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	N/A

Comment: The tested EUT does not support the Random Waiting Interval option.

Limits:


FCC 15.323(c)(4):

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

FCC 15.323(c)(6):

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available


Access Criteria Check




Date: 18.DEC.2012 14:47:21

8.1.1a) EUT Transmits on Unblocked Slot

Access Criteria Check




Date: 18.DEC.2012 15:08:44




Date: 18.DEC.2012 15:07:43

8.1.1b) Access Criteria check Interval

Access Criteria Check



Date: 18.DEC.2012 15:04:53



Date: 18.DEC.2012 15:05:27

8.1.1b) Access Criteria Functional Test, Before and After

4.20 Acknowledgements and Transmission Duration

Measurement Procedure:

Acknowledgements: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test **Initial transmission without acknowledgements** the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test **Transmission time after loss of acknowledgements** is performed by cutting-off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

Test Results:

Acknowledgements

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgements	Not applicable for EUT that transmits control and signaling information	N/A
c) Transmission time after loss of acknowledgements	10 sec	Pass

Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	Only for initiating device that controls which time slot is used	N/A

Comment: /

Limits, FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

4.21 Dual Access Criteria Check

Measurement Procedure:

EUTs that does not implement the Upper Threshold: ANSI C63.17, clause 8.3.1

EUTs that implement the Upper Threshold: ANSI C63.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

Test Results:

EUTs that Implements the Upper Threshold:

Test ref. to ANSI C63.17 clause 8.3.2	Observation	Verdict
b) EUT is restricted to a single carrier f_i for TDMA systems. The Test is Pass if EUT can transmit	N/A	N/A
c) d) Transmission on interference-free receive time/spectrum window	N/A	N/A
e) f) Transmission on interference-free transmit time/spectrum window	N/A	N/A
g) Transmission not possible on any time/spectrum window	N/A	N/A

Comment: This test is only applicable for EUT that can be initiating device.

Limits, FCC 15.323(c)(10)

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

4.22 Alternative Monitoring Interval

Test procedure described in ANSI C63.17 clause 8.4.

This test is required if the EUT implements the provisions of FCC 15.323(c)(11).

Test result:

Not Tested. The tested EUT does not implement this provision. See manufacturers' declaration.

5 Test Setups

5.1 Frequency Measurements




Test equipment included: 5, 9, 28

Test Set-up 1

This setup is used for measuring Carrier frequency stability at normal and extreme temperatures.

5.2 Timing Measurements




Test equipment included: 5, 7, 9, 28

Test Set-up 2

This setup is used for measuring Frame repetition stability, Frame period and Jitter.

5.3 Conducted Emission Test




Test equipment included: 1, 2, 9, 26

Test Set-up 3

This setup is used for all conducted emission tests.


5.4 Power Line Conducted Emissions Test



Test equipment: 8, 17, 18, 22, 27

Test Set-Up 5

5.5 Monitoring Tests



Test equipment: 1, 2, 3, 4, 6, 9, 10, 11, 12, 13, 14, 15, 19, 23, 24, 25, 26

Test Set-Up 6

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generators to the EUT is measured with a power meter before the testing is started.

The CLK100 is used to synchronize the Pulse-/ Pattern generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the CLK100 signal will come from the Companion Device.

The sync signal to the Spectrum Analyzer is the CLK100 signal that is regenerated in the Pulse-/ Pattern Generator, this is used to synchronize the Spectrum Analyzer to the DECT frame when in zero span. The Pulse-/ Pattern Generator is used for tests that require time synchronized pulses or blocking of specific time slots.

6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSW26	Spectrum Analyzer	Rohde & Schwarz	LR 1504	2012.06	2013.06
2	SME03	Signal generator	Rohde & Schwarz	LR 1238	2011.04.11	2013.04.11
3	SMIQ03B	Signal generator	Rohde & Schwarz	LR 1516	Cal b4 use	
4	SMP22	Signal generator	Rohde & Schwarz	LR 1287	Cal b4 use	
5	53310A	Modulation Domain Analyzer	Hewlett Packard	LR 1483	2011.12.13	2013.12.13
6	81104A	Pulse-/ Pattern Generator	Agilent	LR 1502	2013.04.26	2013.04.26
7	8470B	Crystal Detector	Hewlett Packard	LR 1207	N/A	
8	ESHS10	Measuring Receiver	Rohde & Schwarz	N- 3528	2012.06	2013.06
9	4768-10	Attenuator	Narda	LR1356	Cal b4 use	
10	745-69	Step Attenuator	Narda	LR 1442	2011.10.19	2013.10.19
11	WE 1506A	Power Splitter	Weinchel	LR 244	Cal b4 use	
12	WE 1506A	Power Splitter	Weinchel	LR 245	Cal b4 use	
13	H-9	Hybrid	Anzac	LR 86	Cal b4 use	
14	H-9	Hybrid	Anzac	LR 257	Cal b4 use	
15	S212DS	RF Switch	Narda	LR 1244	N/A	
16	3115	Double Ridged Horn Antenna	EMCO	LR 1226	N/A	
17	ESH3-Z5	Two Line V-Network	Rohde & Schwarz	LR 1076	2011.11.03	2013.11.03
18	80S	Signal Generator	Powertron	LT 502	Cal b4 use	
19	6812B	AC Power Source	Agilent	LR 1515	2012.05.08	2013.05.08
20	FSU26	Spectrum Analyzer	Rohde & Schwarz	LR 1504	2011.11.03	2013.11.03
21	JS4	Pre-Amplifier	Miteq	LR 1552	2012.09.10	2013.09.10
22	Model 87 V	Multimeter	Fluke	N-4669	2012.09.05	2013.09.05
23	87H35-1	Circulator	Racal-MESL	s.no.: 140	N/A	
24	87H35-1	Circulator	Racal-MESL	s.no.: 141	N/A	
25	87H35-1	Circulator	Racal-MESL	s.no.: 142	N/A	
26	U2000A	USB Power Sensor	Agilent	LR 1523	2011.03.26	2013.03.26
27	ESH3-Z2	Pulse Limiter	Rohde & Schwarz	LR 285	2012.04.24	2014.04.24
28	CMD60	DECT Tester	Rohde & Schwarz	LR 1335	Cal b4 use	
29	Model 7200	Signal generator	Gigatronics	LR 1188	2012.10.31	2014.10.31
30	3115	Double Ridged Horn Antenna	EMCO	LR 1330	2010.08.05	2013.08.05