



Test report no. : 174870-2

Item tested : KX-TG6671

Type of equipment : UPCS Base Station

FCC ID : ACJ96NKX-TG6671

Client : Panasonic System Networks Co., Ltd.

FCC Part 15, subpart D

Isosynchronous UPCS Device
1920 - 1930 MHz

Industry Canada RSS-213, Issue 2

2 GHz Licence-exempt Personal
Communications Service Devices
(LE-PCS)

5 May 2011

Authorized by : 

G. Suhantakumar
Technical Vericator



CONTENTS

1	GENERAL INFORMATION	3
1.1	Testhouse Info	3
1.2	Client Information	3
1.3	Responsible Manufacturer (if other than client)	3
2	TEST INFORMATION	4
2.1	Tested Item	4
2.2	Description of Tested Device	4
2.3	Exposure Evaluation	4
2.4	Test Environment	5
2.5	Test Period	5
2.6	Test Engineer(s)	5
2.7	Test Equipment	5
2.8	Other Comments	5
3	TEST REPORT SUMMARY	6
3.1	General	6
3.2	Test Summary	7
4	TEST RESULTS	8
4.1	Power Line Conducted Emissions	8
4.2	Coordination with fixed microwave	13
4.3	Digital Modulation Techniques	13
4.4	Labeling Requirements	13
4.5	Antenna Requirement	14
4.6	Channel Frequencies	14
4.7	Peak Power Output	15
4.8	Spurious Emissions (Radiated)	18
5	TEST SETUPS	24
5.1	Radiated Emissions Test, Semi-Anechoic Chamber	24
5.2	Power Line Conducted Emissions Test	24
6	TEST EQUIPMENT USED	25

1 GENERAL INFORMATION

1.1 Testhouse Info

Name : Nemko AS
Address : Nemko Kjeller
 Instituttveien 6
 N-2007 Kjeller, NORWAY
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail: comlab@nemko.com
FCC test firm registration # : 994405
IC OATS registration # : 2040D-1
Total Number of Pages: 25

1.2 Client Information

Name : Panasonic System Networks Co., Ltd.
Address : 1-62, 4-Chome, Minoshima, Hakata-ku, Fukuoka 812-8531 Japan
Telephone : +81-92-477-1405
Fax : +81-92-477-1487

Contact:

Name : Mr. Junji Sumi
Telephone : +81 92 477 1405
E-mail : sumi.junji@jp.panasonic.com

1.3 Responsible Manufacturer (if other than client)

Name : /
Address : /

2 Test Information

2.1 Tested Item

Name :	Panasonic
Model name :	KX-TG6671
FCC ID :	ACJ96NKX-TG6671
Industry Canada ID :	216A-KXTG6671
Serial number :	/
Hardware identity and/or version:	/
Software identity and/or version :	/
Tested to IC Radio Standard (RSS) :	RSS-213 Issue 2, RSS-GEN Issue 3
Test Site IC Reg. Number :	IC 2040D-1
Frequency Range :	1921.536 – 1928.448 MHz
Number of Channels :	5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Type of Modulation :	Digital (Gaussian Frequency Shift Keying)
Peak Output Power :	98 mW (Conducted)
Antenna Connector :	None (Integral antennas)
Number of Antennas :	2
Antenna Diversity Supported :	Yes
Power Supply :	AC Adaptors: PNLV226(FW) and PNLV226(UC)

2.2 Description of Tested Device

The tested equipment is a DECT base which complies with ETSI EN 300 175. The frequencies have been reprogrammed, the output power reduced and the software updated to comply with the FCC requirements to an Isochronous UPCS device after FCC Part 15D.

The EUT is an responding device as described in ANSI C63.17 and is designed to operate together with a DECT portable part (i.e. a handset), which is then the initiating device.

2.3 Exposure Evaluation

The EUT is designed to be fixed to a wall etc. and the user manual contains text that it shall be mounted with a separation distance of at least 20cm from any persons. For the purposes of exposure evaluation this EUT is a mobile or fixed device. MPE Calculation at 20cm satisfying FCC requirements is submitted as a separate document.

The EUT is exempted from RF Exposure Evaluation to Industry Canada SAR requirements since the output power is below the limit in RSS-102 Issue 4, clause 2.5.2 for General Public Use.

2.4 Test Environment

Temperature:	21.2 – 23.8 °C
Relative humidity:	25.1 – 36.5 %
Normal test voltage:	120 V AC

The values are the limit registered during the test period.

2.5 Test Period

Item received date:	2011-04-26
Test period :	from 2011-04-28 to 2011-05-04

2.6 Test Engineer(s)

Frode Sveinsen / Tore Løvlien

2.7 Test Equipment

See list of test equipment in clause 6.

2.8 Other Comments

This test report covers only radiated tests. All other tests are covered by Nemko test report no. 137945-3.

The UPCS Base Station uses the same radio part as the previously certified model KX-TG6531 (FCC ID: ACJ96NKX-TG6531). The only differences are the antennas and changes to the PCB other than the RF part.

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Panasonic
Model No.: KX-TG6671
Serial No.: /

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2 / RSS-GEN Issue 3.

All tests were conducted in accordance with ANSI C63.4-2009 and ANSI C63.17-2006. Antenna Gain tests were made in a 3m fully-anechoic chamber.

A description of the test facility is on file with the FCC and Industry Canada.

- | | |
|---|---|
| <input checked="" type="checkbox"/> New Submission | <input checked="" type="checkbox"/> Production Unit |
| <input type="checkbox"/> Class II Permissive Change | <input type="checkbox"/> Pre-production Unit |
| PUB Equipment Code | <input type="checkbox"/> Family Listing |

THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".



TEST REPORT NO: 174870-2

TESTED BY : Frode Sveinsen
Frode Sveinsen, Chief Engineer

DATE: 4 May 2011

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Coordination with fixed microwave	15.307(b)	N/A	Complies
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	RSS-GEN 5.2	Complies
Antenna Requirement	15.317, 15.203	4.1(e)	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	6.3 RSS-GEN 7.2.2	Complies
Peak transmit Power	15.319(c)(e), 15.31(e)	6.5	Complies
Spurious Emissions (Radiated)	15.319(g) 15.109(a) 15.209(a)	4.3.3 RSS-GEN 7.2.3	Complies

4 TEST RESULTS

4.1 Power Line Conducted Emissions

Para. No.: 15.207 (a)

Test Performed By: Tore Løvlien	Date of Test: 28 Apr 2011
---------------------------------	---------------------------

Measurement procedure: ANSI C63.4-2009 using 50 μ H/50 ohms LISN.

Test Results: Complies

Measurement Data: See attached graph, (Peak detector).

Highest measured value (L1 and N):

AC Adaptor PNLV226(UC):

Hook-On, Charge Mode:

Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.345000	49.40	10.20	59.10	9.70	QP	N	Pass
1.920000	41.50	10.20	56.00	14.50	QP	N	Pass
3.450000	42.60	10.30	56.00	13.40	QP	N	Pass
3.615000	42.50	10.30	56.00	13.50	QP	N	Pass
0.170000	28.30	10.10	55.00	26.70	AV	N	Pass
0.345000	38.00	10.20	49.10	11.10	AV	N	Pass
0.675000	28.50	10.20	46.00	17.50	AV	N	Pass
1.235000	30.90	10.20	46.00	15.10	AV	N	Pass
1.920000	31.10	10.20	46.00	14.90	AV	N	Pass
3.450000	32.30	10.30	46.00	13.70	AV	N	Pass
3.615000	32.00	10.30	46.00	14.00	AV	N	Pass
6.190000	24.80	10.50	50.00	25.20	AV	L1	Pass

Hook-Off:

Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.345000	50.10	10.20	59.10	9.00	QP	N	Pass
1.180000	40.30	10.20	56.00	15.70	QP	N	Pass
1.665000	42.00	10.30	56.00	14.00	QP	N	Pass
3.140000	44.30	10.30	56.00	11.70	QP	N	Pass
3.895000	43.00	10.40	56.00	13.00	QP	N	Pass
0.180000	28.30	10.10	54.50	26.20	AV	N	Pass
0.345000	39.70	10.20	49.10	9.40	AV	N	Pass
0.665000	29.60	10.20	46.00	16.40	AV	N	Pass
1.180000	29.90	10.20	46.00	16.10	AV	N	Pass
1.665000	31.20	10.30	46.00	14.80	AV	N	Pass
3.140000	33.60	10.30	46.00	12.40	AV	N	Pass
3.895000	32.30	10.40	46.00	13.70	AV	N	Pass
6.485000	25.30	10.50	50.00	24.70	AV	L1	Pass


AC Adaptor PNLV226(FW):

Hook-On, Charge Mode:


Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.365000	44.90	10.20	58.60	13.70	QP	N	Pass
0.720000	44.50	10.20	56.00	11.50	QP	N	Pass
1.025000	46.50	10.20	56.00	9.50	QP	N	Pass
1.420000	45.90	10.20	56.00	10.10	QP	N	Pass
2.295000	42.40	10.30	56.00	13.60	QP	N	Pass
0.245000	24.50	10.10	51.90	27.40	AV	L1	Pass
0.365000	28.90	10.20	48.60	19.70	AV	N	Pass
0.720000	29.40	10.20	46.00	16.60	AV	N	Pass
1.025000	31.50	10.20	46.00	14.50	AV	N	Pass
1.420000	31.30	10.20	46.00	14.70	AV	N	Pass
2.295000	30.10	10.30	46.00	15.90	AV	N	Pass
3.900000	29.20	10.40	46.00	16.80	AV	L1	Pass

Hook-Off:


Frequency [MHz]	Level [dBuV]	Af [dB]	Limit [dBuV]	Margin [dB]	Det	Position	Verdict [Pass/Fail]
0.355000	48.10	10.20	58.80	10.70	QP	N	Pass
0.505000	40.20	10.20	56.00	15.80	QP	N	Pass
1.245000	46.90	10.20	56.00	9.10	QP	N	Pass
1.330000	47.10	10.20	56.00	8.90	QP	N	Pass
2.240000	43.60	10.30	56.00	12.40	QP	N	Pass
3.615000	39.90	10.30	56.00	16.10	QP	N	Pass
0.175000	24.80	10.10	54.70	29.90	AV	N	Pass
0.355000	31.90	10.20	48.80	16.90	AV	N	Pass
0.505000	24.70	10.20	46.00	21.30	AV	N	Pass
1.245000	31.50	10.20	46.00	14.50	AV	N	Pass
1.330000	33.00	10.20	46.00	13.00	AV	N	Pass
2.240000	30.90	10.30	46.00	15.10	AV	N	Pass
3.615000	29.60	10.30	46.00	16.40	AV	N	Pass




Hook-On, Charge Mode, Phase L1 and N, AC Adaptor PNLV226(UC)



Hook-Off, Phase L1 and N, AC Adaptor PNLV226(UC)



Hook-On, Charge Mode, Phase L1 and N, AC Adaptor PNLV226(FW)



Hook-Off, Phase L1 and N, AC Adaptor PNLV226(FW)

4.2 Coordination with fixed microwave

The affidavit from UTAM, Inc. is included in the documentation supplied by the applicant:

Yes

No

Requirement, FCC 15.307 (b):

Each application for certification of equipment operating under the provisions of this Subpart must be accompanied by an affidavit from UTAM, Inc. certifying that the applicant is a participating member of UTAM, Inc. In the event a grantee fails to fulfill the obligations attendant to participation in UTAM, Inc., the Commission may invoke administrative sanctions as necessary to preclude continued marketing and installation of devices covered by the grant of certification, including but not limited to revoking certification.

4.3 Digital Modulation Techniques

The tested equipment is based on DECT technology described in the ETSI standard EN 300175, the only difference is that the channel allocation is modified to operate in the 1920-1930 MHz band.

The EUT used Multi Carrier / Time Division Multiple Access / Time Division Duplex and Digital GFSK modulation.

For further details see the operational description provided by the applicant.

Requirement, FCC 15.319(b):

All transmissions must use only digital modulation techniques.

4.4 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirements FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

4.5 Antenna Requirement

Does the EUT have detachable antenna(s)?

Yes No

If detachable, is the antenna connector(s) non-standard?

Yes No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

Requirement: FCC 15.203, 15.204, 15.317.

4.6 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.303 (d), (g)

Within 1920 -1930 MHz band for isochronous devices.

4.7 Peak Power Output

Test Method:

ANSI C63.17, clause 6.1.2.

Test Results: Complies

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Maximum Radiated Output Power (dBm)	Maximum Antenna Gain (dBi)
4	1921.536	19.9	19.6	-0.3
2	1924.992	19.9	20.0	+0.1
0	1928.448	19.9	19.8	-0.1

Substitution:

Frequency MHz	Measured value dBm	Subst. Gen. (incl. corr.) dBm	Attenuator and Cable dB	Gain Subst. Antenna dB	Result dBm
1921.536	19.6	25.2	-13.9	8.3	19.6
1924.992	19.9	25.6	-13.9	8.3	20.0
1928.448	20.0	25.4	-13.9	8.3	19.8

Result = Subst.Gen. + Attenuator + Cable + Antenna Gain

Conducted values are from Nemko report no. 137945-3.

Limit:

Conducted: $100 \mu\text{W} \times \text{SQRT}(B)$ where B is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e): 21.85 dBm (153 mW)

RSS-213, Issue 2: 20.55 dBm (114 mW)


The antenna gain is below 3 dBi, no reduction in transmit power is necessary.

Requirements, FCC 15.319(c)(e), RSS-213, Issue 2

Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.


The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Radiated Peak Output Power




Date: 4.MAY.2011 14:57:24

Lower Channel (Max: Ant 1, VP)



Date: 4.MAY.2011 14:53:59

Upper Channel (Max: Ant 1, VP)



Date: 4.MAY.2011 14:37:06

Middle Channel (Max: Ant 1, VP)

4.8 Spurious Emissions (Radiated)

Measurement Procedure:

FCC 15.209

Test Results:

Radiated Emissions 10 kHz - 30 MHz.

Detector: Peak

Measuring distance: 10m.

See plots.

Radiated Emissions 30 - 1000 MHz.

Detector: Quasi Peak

Measuring distance: 3m

The EUT were rotated 360 degrees and the antenna height varied between 1 and 4 m on all found frequencies.

AC Adaptor PNLV226(UC):

Frequency MHz	Dist. corr. Factor dB	Field strength @3m QP Det., dB μ V/m	Limit dB μ V/m	Margin dB
32.96	0	24.6	40	15.4
50.36	0	15.0	40	25.0
165.52	0	11.0	43.5	32.5


AC Adaptor PNLV226(FW):

Frequency MHz	Dist. corr. Factor dB	Field strength @3m QP Det., dB μ V/m	Limit dB μ V/m	Margin dB
30.56	0	15.8	40	24.2
33.60	0	17.5	40	22.5

See plots.


Limits:

Spurious Frequency MHz	Field Strength dB μ V/m @3m
30-88	40
88-216	43.5
216-960	46
Above 960	54




Date: 29.APR.2011 16:34:13

Spurious Emissions 10 kHz – 30 MHz, Peak Det., Adaptor PNLV226(FW)




Date: 29.APR.2011 16:23:06

Spurious Emissions 10 kHz – 30 MHz, Peak Det., Adaptor PNLV226(UC)




Date: 29.APR.2011 14:36:00

Spurious Emissions 30 – 200 MHz, Peak Det., VP, Adaptor PNLV226(FW)




Date: 29.APR.2011 14:31:32

Spurious Emissions 30 – 200 MHz, Peak Det., HP Adaptor PNLV226(FW)




Date: 29.APR.2011 14:13:05

Spurious Emissions 30 – 200 MHz, Peak Det., VP, Adaptor PNLV226(UC)




Date: 29.APR.2011 14:06:10

Spurious Emissions 30 – 200 MHz, Peak Det., HP Adaptor PNLV226(UC)




Date: 29.APR.2011 14:58:57

Spurious Emissions 200 - 1000 MHz, Peak Det., VP Adaptor PNLV226(FW)




Date: 29.APR.2011 15:20:22

Spurious Emissions 200 - 1000 MHz, Peak Det., HP Adaptor PNLV226(FW)



Date: 29.APR.2011 15:39:51

Spurious Emissions 200 - 1000 MHz, Peak Det., VP Adaptor PNLV226(UC)




Date: 29.APR.2011 16:02:33

Spurious Emissions 200 - 1000 MHz, Peak Det., HP Adaptor PNLV226(UC)

5 Test Setups

5.1 Radiated Emissions Test, Semi-Anechoic Chamber




Test equipment: 7, 10, 11, 12

Test Set-Up 4

This test setup is used for all radiated emissions tests. For frequencies below 30 MHz the measuring distance is 10 m, for all other frequencies it is 3m or 1m. Emissions above 1 GHz were measured with a Spectrum Analyzer and Horn Antenna and with the preamplifier after the antenna. For measurements above 18 GHz the test receiver is moved inside the anechoic chamber and located next to the antenna to minimize the cable loss.

5.2 Power Line Conducted Emissions Test



Test equipment: 2, 4, 5, 6

Test Set-Up 5

6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSU26	Spectrum Analyzer	Rohde & Schwarz	LR 1504	2010.09.28	2012.09.28
2	ESHS10	Measuring Receiver	Rohde & Schwarz	N-3528	2011-03	2012-03
3	6810.17B	Attenuator	Suhner	LR1212	2010.09.15	2012.09.15
4	ESH3-Z5	Two Line V-Network	Rohde & Schwarz	LR 1076	2009.10.22	2011.10.22
5	80S	Signal Generator	Powertron	LT 502	Cal b4 use	
6	ESH3-Z2	Pulse Limiter	Rohde & Schwarz	LR 1074	2010.03.03	2012.03.03
7	6812B	AC Power Source	Agilent	LR 1515	2011.04.13	2012.04.13
8	JS3	Pre-Amplifier	Miteq	LR 1552	2010.08.04	2011.08.04
9	U2000A	USB Power Sensor	Agilent	LR 1523	2011.03.26	2012.03.26
10	ESCI	Measuring Receiver	Rohde & Schwarz	N-4259	2010.11.03	2011.11.03
11	HK116	Biconical Antenna	Rohde & Schwarz	LR 1260	2010.05.12	2013.05.12
12	HL223	Log Period Antenna	Rohde & Schwarz	LR 1261	2010.05.12	2013.05.12
13	3115	Horn Antenna	EMCO	LR 1330	2010.08.05	2013.08.05