

FCC Part 15D – Compliance Information

EUT AND PRODUCT INFORMATION

Type of Equipment	UPCS (DECT 6.0)
Applicant Name	Panasonic System Networks Co., Ltd.
Address	1-62, 4-chome, Minoshima, Hakata-ku, Fukuoka, 812-8531, Japan
Contact	Michihito Miyazaki
Telephone	+81-50-3380-2671
Email	miyazaki.michihito@jp.panasonic.com
Grantee Code	ACJ
IC Company Number	216A
Brand Name	Panasonic
Model Number	KX-TGP600 (Base), KX-TPA60 (Handset)

	FP	PP	Repeater
EUT Type/System	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
FCC ID	ACJ96NKX-TGP600	ACJ96NKX-TPA60	
Industry Canada ID	216A-KXTGP600	216A-KXTPA60	
Model name	KX-TGP600	KX-TPA60	
HW Version	PNLB2350ZAxx	PNLB2348ZAxx	
SW Version	SW00.010	SW0.50	
Maximum Antenna Gain	2dBi	1.5dBi	
Can the EUT be Initiating Device	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> YES
Does the EUT transmit signaling channels	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> YES	<input type="checkbox"/> YES
Max number of slots in use simultaneously	10 slot	1 slot	
Test standard:	<input checked="" type="checkbox"/> FCC part 15D	<input checked="" type="checkbox"/> RSS-213, Issue 2 / RSS-GEN, Issue 3	
Frequency Band	1921.536 – 1928.448 MHz		
Number of RF Channels	5		
Frame Period	10 ms		
Max. Burst length	723us / duplex channel		
Min. Burst Length	106us / signaling channel		
Minimum Number of System Channels	60 (12 duplex channels per RF carrier)		
Supported DECT Slot Types	<input checked="" type="checkbox"/> Full Slot	<input checked="" type="checkbox"/> Long Slot	
Operating Mode	<input type="checkbox"/> Simplex	<input checked="" type="checkbox"/> Duplex	

FCC Part 15D – Compliance Information

ANTENNAS				
Base (FP)	Antenna	Type	Internal	External
	1	$\lambda / 4$ monopole Antenna	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	2	$\lambda / 4$ monopole Antenna	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	3		<input type="checkbox"/>	<input type="checkbox"/>
	4		<input type="checkbox"/>	<input type="checkbox"/>
Does RX and TX use the same antenna(s)?			<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Handset (PP)	Antenna	Type	Internal	External
	1	$\lambda / 4$ PIFA Antenna	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	2		<input type="checkbox"/>	<input type="checkbox"/>
Does RX and TX use the same antenna(s)?			<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No

ANTENNA DIVERSITY			
	Antenna	Diversity Supported	
		TX	RX
Base (FP)	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	3	<input type="checkbox"/>	<input type="checkbox"/>
	4	<input type="checkbox"/>	<input type="checkbox"/>
Handset (PP)	1	<input type="checkbox"/>	<input type="checkbox"/>
	2	<input type="checkbox"/>	<input type="checkbox"/>

VOLTAGE AND TEMPERATURE RANGES			
VOLTAGES	FP	PP	Repeater
Nominal Voltage	120V AC	DC 2.6V	
Cut-Off Voltage (if applicable)		2.35V	
POWER SOURCE	Type	Manufacturer	
Base or Repeater	PQLV219 (AC Adaptor for Base)	Panasonic	
Handset (PP) (charger)	PNLV226 (AC Adaptor for charger)	Panasonic	
Data Connections	<input type="checkbox"/> PSTN <input checked="" type="checkbox"/> Others (please specify)LAN(RJ-45)		


FCC Part 15D – Compliance Information

ANCILLARY EQUIPMENT	
Description	Charger cradle
Type	PNLC1061ZA (Charger for KX-TPA60)
Manufacturer	Panasonic

HOST DEVICE	
Description	
Type	
Manufacturer	

ADDITIONAL INFORMATION

FCC Part 15D – Compliance Information

MANUFACTURERS DECLARATIONS		
FCC part 15.323 (c)(5)		
The applicant declares that the system in this application has more than 40 duplex system access channels defined, and that the system is operating in Least Interfered Channel (LIC) mode in accordance with this section.		
Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
FCC part 15.323 (c)(5)		
No device or group of co-operating devices located within 1m of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.		
Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
FCC part 15.323 (c)(10)		
The applicant hereby declares that the system in this application does use the criteria of (c)(10) of this section.		
Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
FCC part 15.323 (c)(11)		
The applicant hereby declares that system in this application does not use the criteria of (c)(11) of this section.		
Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
FCC part 15.323 (c)(12)		
The provisions of (c)(10) or (c)(11) of this section shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.		
Applicant Agrees	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
FCC part 15.307 (b)		
The Applicant is a participating member of UTAM, Inc. and will provide an affidavit from UTAM, Inc. certifying this.		
Confirmed By Applicant	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
ADDITIONAL REMARKS:		
>		
DECLARED BY:		
May 13, 2014	Michihito Miyazaki	
Date	Name (print)	Signature

FCC Part 15D – Compliance Information

About this document

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15D. The form must be completed by the applicant and submitted to Nemko before testing is started.

Preparation of Equipment for Testing

Note (a): Number of samples for testing

The following samples are needed for FCC 15D testing:

RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is needed for these tests even if the equipment has more than one antenna.

Monitoring Tests:

One sample with 50 ohm antenna connectors fitted to all antennas (preferably SMA female). Additionally we need a companion device that will work together with the EUT, the companion device must also have antenna connectors on all antennas.

Radiated Tests:

One sample with integral antennas. This sample will be used to measure Antenna Gain, Part 15B and Power-Line Conducted tests.

Note (b): Monitoring Tests

Monitoring tests are performed by establishing a connection from the handset (or the initiating device) to the base station (or the responding device). Most tests are performed by establishing connections from the initiating device to the responding device and observing which channel and/or timeslot is used.

For monitoring tests we need a EUT and a Companion device that both have antenna connectors on all antennas (preferably SMA female, again). Additionally, we need access to the CLK100 signal on the Base Station, this is necessary because some of the tests require that the interferers are synced to the DECT frame.

Note (c): Connection to an external power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with batteries.

Note (d): Burst Mode

Most RF tests are performed with the EUT in force transmit mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

Note (e): Test-Mode (Loopback Mode)

Some FCC test may also be performed in Loopback Mode with a CMD60 or similar DECT tester. If loopback mode is implemented in the EUT, the method for setting the equipment in Loopback should be submitted to Nemko together with the test samples before start of testing.