Test report no. : 210879-2

Item tested : VL-CM851A

Type of equipment : UPCS Wireless Door Camera

FCC ID : ACJ96NVL-CM851A

Client : Panasonic Corporation of North America

FCC Part 15, subpart D
Isochronous UPCS Device
1920 - 1930 MHz

Industry Canada RSS-213, Issue 2
2 GHz Licence-exempt Personal
Communications Service Devices
(LE-PCS)

12 July 2012

Authorized by : .....
G. Suhanthakumar
Technical Verificator

www.nemko.com

CONTENTS

1 GENERAL INFORMATION 3
1.1 Testhouse Info 3
1.2 Client Information 3
1.3 Responsible Manufacturer (if other than client) 3

2 TEST INFORMATION 4
2.1 Tested Item 4
2.2 Description of Tested Device 4
2.3 Exposure Evaluation 4
2.4 Test Environment 5
2.5 Test Period 5
2.6 Test Engineer(s) 5
2.7 Test Equipment 5
2.8 Other Comments 5

3 TEST REPORT SUMMARY 6
3.1 General 6
3.2 Test Summary 7

4 TEST RESULTS 8
4.1 Coordination with fixed microwave 8
4.2 Digital Modulation Techniques 8
4.3 Labeling Requirements 8
4.4 Antenna Requirement 9
4.5 Channel Frequencies 9
4.6 Automatic Discontinuation of Transmission 10
4.7 Peak Power Output 11
4.8 Emission Bandwidth *B* 16
4.9 Power Spectral Density 19
4.10 In-Band Unwanted Emissions, Conducted 22
4.11 Out-of-band Emissions, Conducted 24
4.12 Carrier Frequency Stability 28
4.13 Frame Repetition Stability 29
4.14 Frame Period and Jitter 29
4.15 Monitoring Threshold, Least Interfered Channel 31
4.16 Threshold Monitoring Bandwidth 33
4.17 Reaction Time and Monitoring Interval 34
4.18 Time and Spectrum Window Access Procedure 36
4.19 Acknowledgements and Transmission Duration 37
4.20 Dual Access Criteria Check 40
4.21 Alternative Monitoring Interval 44

5 TEST SETUPS 45
5.1 Frequency Measurements 45
5.2 Timing Measurements 45
5.3 Conducted Emission Test 45
5.4 Power Line Conducted Emissions Test 45
5.5 Monitoring Tests 46
5.6 Radiated Emissions Test, Fully Anechoic Chamber 47

6 TEST EQUIPMENT USED 48

1 GENERAL INFORMATION

1.1 Testhouse Info

Name :	Nemko AS
Address :	Nemko Kjeller Instituttveien 6 N-2007 Kjeller, NORWAY
Telephone :	+47 64 84 57 00
Fax :	+47 64 84 57 05
E-mail:	comlab@nemko.com
FCC test firm registration # :	994405
IC OATS registration # :	2040D-1
Total Number of Pages:	48

1.2 Client Information

Name :	Panasonic Corporation of North America
Address :	One Panasonic Way, Secaucus, 07094, NJ, USA

Contact:

Name :	Mr. Richard Mullen
Telephone :	201-348-7758
E-mail :	Richard.Mullen@us.panasonic.com

1.3 Responsible Manufacturer (if other than client)

Same as client.

2 Test Information

2.1 Tested Item

Name :	Panasonic
Model name :	VL-CM851A
FCC ID :	ACJ96NVL-CM851A
Industry Canada ID :	216A-VLCM851A
Serial number :	/
Hardware identity and/or version:	PNLB1993xx
Software identity and/or version :	Ver.006
Tested to IC Radio Standard (RSS) :	RSS-213 Issue 2, RSS-GEN Issue 3
Test Site IC Reg. Number :	IC 2040D-1
Frequency Range :	1921.536 – 1928.448 MHz
Number of Channels :	5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Type of Modulation :	Digital (Gaussian Frequency Shift Keying)
Conducted Output Power :	93 mW (Peak)
Antenna Connector :	None
Number of Antennas :	1
Antenna Diversity Supported :	No
Power Supply :	Primary Batteries (4xAAA cells)
Maximum Duty Cycle :	6/25 = 24%

2.2 Description of Tested Device

The EUT is a DECT Wireless Door Camera and is an initiating device as described in ANSI C63.17 and is designed to operate together with a DECT fixed part (i.e. a base station), which is the responding device.

2.3 Exposure Evaluation

The EUT is designed to be fixed to the top of a door and the user manual contains text that it shall be mounted with a separation distance of at least 20cm from any persons. For the purposes of exposure evaluation this EUT is a fixed device. MPE Calculation at 20cm satisfying FCC requirements is submitted as a separate document.

The EUT is exempted from RF Exposure Evaluation to Industry Canada requirements since the output power complies with the power levels of section 2.5.2 of RSS-102 Issue 4.

2.4 Test Environment

Temperature:	21 – 23 °C
Relative humidity:	38 – 45 %
Normal test voltage:	3.0 V DC (Primary Batteries)

The values are the limit registered during the test period.

2.5 Test Period

Item received date: 2012-06-05

Test period : from 2012-06-15 to 2012-07-03

2.6 Test Engineer(s)

Frode Sveinsen

2.7 Test Equipment

See list of test equipment in clause 6.

2.8 Other Comments

The Monitoring and Time and Spectrum Window Access tests were performed with Test Set-Up 6 (Ref. clause 5). A clock signal from the companion device was used to synchronize the Pulse Pattern Generator and the Spectrum Analyzer to the start of the DECT time window. The EUT was limited by administrative commands to operate on only two frequency carriers. For the tests where the EUT was required to operate on only one frequency carrier, one carrier was blocked by applying a CW interfering signal from RF Generator 3. The Pulse Pattern Generator was used to apply time synchronized interference to time windows where this was required.

Since the EUT was programmed to operate on only two RF carriers, it was only necessary with two RF generators for the monitoring tests, however a third generator was applied for the tests that required specific time slots to be blocked.

The tested EUT supports both normal DECT slot length and DECT Long slot. Long slot is effectively two normal DECT slots that is bonded together to allow a higher data rate for video with bit rate higher than 32kbps.

This EUT supports Least Interfered Channel procedure (LIC) when full slot is used, the Monitoring and Time and Spectrum Window Access tests were conducted as specified for EUTs that support LIC procedure.

All tests except Antenna Gain and Power-Line Conducted Emissions were performed in conducted mode with a temporary antenna connector.

3 TEST REPORT SUMMARY

3.1 General

Manufacturer: Panasonic

Model No.: VL-CM851A

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2 / RSS-GEN Issue 3.

All tests were conducted is accordance with ANSI C63.4-2009 and ANSI C63.17-2006. Antenna Gain tests were made in a 3m fully-anechoic chamber.

A description of the test facility is on file with the FCC and Industry Canada.

☒ New Submission ☒ Production Unit

☐ Class II Permissive Change ☐ Pre-production Unit

PUB Equipment Code ☐ Family Listing

THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

TEST REPORT NO: 210879-2

TESTED BY : _____ **DATE: 6 July 2012**

Frode Sveinsen, Chief Engineer

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.

3.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Coordination with fixed microwave	15.307(b)	N/A	Complies
Digital Modulation Techniques	15.319(b)	6.1	Complies
Labeling requirements	15.19(a)(3)	3 RSS-GEN 5.2	Complies
Antenna Requirement	15.317, 15.203	RSS-GEN 7.1.2	Complies
Power Line Conducted Emission	15.107(a) 15.207(a)	6.3 RSS-GEN 7.2.2	N/A[1]
Emission Bandwidth	15.323(a)	6.4	Complies
In-band emissions	15.323(d)	6.7.2	Complies
Out-of-band emissions	15.323(d)	6.7.1	Complies
Output Power and Antenna Gain	15.319(c)(e), 15.31(e)	6.5 and 4.1(e)	Complies
Power Spectral Density	15.319(d)	4.3.2.1	Complies
Automatic discontinuation of transmission	15.319(f)	4.3.4(a)	Complies
Carrier frequency stability	15.323(f)	6.2	Complies
Frame repetition stability	15.323(e)	4.3.4(c)	Complies
Frame period and jitter	15.323(e)	4.3.4(c)	Complies
Monitoring threshold, Least interfered channel	15.323(c)(2);(5); (9)	4.3.4(b)	Complies
Monitoring of intended transmit window and maximum reaction time	15.323(c)(1)	4.3.4(b)	Complies
Threshold monitoring bandwidth	15.323(c)(7)	4.3.4(b)	Complies
Reaction time and monitoring interval	15.323(c)(1);(5); (7)	4.3.4(b)	Complies
Access criteria test interval	15.323(c)(4);(6)	4.3.4(b)	N/A[2]
Access Criteria functional test	15.323(c)(4);(6)	4.3.4(b)	N/A[2]
Acknowledgements	15.323(c)(4)	4.3.4(b)	Complies
Transmission duration	15.323(c)(3)	4.3.4(b)	Complies
Dual access criteria	15.323(c)(10)	4.3.4(b)	Complies
Alterative monitoring interval	15.323(c)(10);(11)	4.3.4(b)	N/A[3]
Spurious Emissions (Radiated)	15.319(g) 15.109(a) 15.209(a)	4.3.3 RSS-GEN 7.2.3	N/A[4]

[1] The EUT operates from batteries only

[2] Only applies for EUT that can be initiating device

[3] The client declares that the tested equipment does not implement this provision

[4] Not required if the Conducted Out-of-Band Emissions test is Passed

4 TEST RESULTS

4.1 Coordination with fixed microwave

The affidavit from UTAM, Inc. is included in the documentation supplied by the applicant:

☒ Yes ☐ No

Requirement, FCC 15.307 (b):

Each application for certification of equipment operating under the provisions of this Subpart must be accompanied by an affidavit from UTAM, Inc. certifying that the applicant is a participating member of UTAM, Inc. In the event a grantee fails to fulfill the obligations attendant to participation in UTAM, Inc., the Commission may invoke administrative sanctions as necessary to preclude continued marketing and installation of devices covered by the grant of certification, including but not limited to revoking certification.

4.2 Digital Modulation Techniques

The EUT uses Multi Carrier / Time Division Multiple Access / Time Division Duplex and Digital GFSK modulation. For further details see the operational description provided by the applicant.

Requirement, FCC 15.319(b):

All transmissions must use only digital modulation techniques.

4.3 Labeling Requirements

See separate documents showing the label design and the placement of the label on the EUT.

Requirements FCC 15.19

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

4.4 Antenna Requirement

Does the EUT have detachable antenna(s)? ☐ Yes ☒ No

If detachable, is the antenna connector(s) non-standard? ☐ Yes ☐ No

The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

Requirement: FCC 15.203, 15.204, 15.317.

4.5 Channel Frequencies

UPCS CHANNEL	FREQUENCY (MHz)
Upper Band Edge	1930.000
0 (Highest)	1928.448
1	1926.720
2	1924.992
3	1923.264
4 (Lowest)	1921.536
Lower Band Edge	1920.000

Requirement: FCC 15.303 (d), (g)

Within 1920 -1930 MHz band for isochronous devices.

4.6 Automatic Discontinuation of Transmission

Does the EUT transmit Control and Signaling Information?		☐ **YES** ☒ **NO**
TYPE OF EUT :	☒ **INITIATING DEVICE**	☐ **RESPONDING DEVICE**

The following tests simulate the reaction of the EUT in case of either absence of information to transmit or operational failure after a connection with the companion device is established.

Number	Test	EUT Reaction	Verdict
1	Power removed from EUT	C	**Pass**
2	Switch Off EUT	C	**Pass**
3	Hook-On by EUT	N/A	**Pass**
4	Power Removed from Companion Device	A	**Pass**
5	Switch Off Companion Device	N/A	**Pass**
6	Hook-On by Companion Device	C	**Pass**

A - Connection breakdown, Cease of all transmissions
B - Connection breakdown, EUT transmits control and signaling information
C - Connection breakdown, Companion Device transmits control and signaling information
N/A - Not Applicable (Companion Device does not have On/Off switch and EUT cannot perform Hook-On)

Requirements, FCC 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

4.7 Peak Power Output

Test Method:

ANSI C63.17, clause 6.1.2.

Test Results: Complies

Measurement Data:

Maximum Conducted Output Power

Channel No.	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Maximum Radiated Output Power (dBm)	Maximum Antenna Gain (dBi)
4	1921.536	19.6	19.8	0.2
2	1924.992	19.7	21.4	1.7
0	1928.448	19.6	20.2	0.6

Substitution:

Frequency MHz	Measured value dBm	Subst. Gen. (incl. corr.) dBm	Attenuator and Cable dB	Gain Subst. Antenna dB	Result dBm
1921.536	18.9	25.5	-14.0	8.3	19.8
1924.992	20.3	27.1	-14.0	8.3	21.4
1928.448	19.1	25.9	-14.0	8.3	20.2

Result = Subst.Gen. + Attenuator + Cable + Antenna Gain

Limit:

Conducted: 100 µW x SQRT(*B*) where *B* is the measured Emission Bandwidth in Hz

FCC 15.319(c)(e): 20.79 dBm (120.0 mW)

RSS-213, Issue 2: 20.47 dBm (111.4 mW)

The antenna gain is below 3 dBi, no reduction in transmit power is necessary.

Requirements, FCC 15.319(c)(e), RSS-213, Issue 2

Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in Hertz.

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

Conducted Peak Output Power



Date: 15.JUN.2012 15:15:33

Lower Channel



Date: 15.JUN.2012 15:16:49

Upper Channel



Date: 15.JUN.2012 15:16:16

Middle Channel

Radiated Peak Output Power



Date: 28.JUN.2012 11:15:56

Lower Channel (Max: EUT V, HP)



Date: 28.JUN.2012 11:14:18

Upper Channel (Max: EUT V, HP)



Date: 28.JUN.2012 11:08:05

Middle Channel (Max: EUT V, HP)

4.8 Emission Bandwidth *B*

Test Method:

ANSI C63.17, clause 6.1.3.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	26 dB Bandwidth *B* (kHz)
4	1921.536	1470.0
0	1928.448	1440.0

Channel No.	Frequency (MHz)	99% Bandwidth (kHz)
2	1924.992	1240.0

Channel No.	Frequency (MHz)	6 dB Bandwidth (kHz)
4	1921.536	N/A
0	1928.448	N/A
Channel No.	**Frequency (MHz)**	**12 dB Bandwidth (kHz)**
4	1921.536	N/A
0	1928.448	N/A

Requirements, FCC 15.323(a)

The 26 dB Bandwidth *B* shall be larger than 50 kHz and less than 2.5 MHz.

Requirements, RSS-213 Issue 2, clause 6.4

The 99% Bandwidth shall be larger than 50 kHz and less than 2.5 MHz.

No requirements for 6 and 12 dB Bandwidth, these values are only used for testing Monitoring Bandwidth if the Simple Compliance test fails (ANSI C63.17, clause 7.4).



Emission Bandwidth *B*, Lower Channel



Emission Bandwidth *B*, Upper Channel



99% Bandwidth, Middle Channel

4.9 Power Spectral Density

Test Method:

ANSI C63.17, clause 6.1.5.

Test Results: Complies

Measurement Data:

Channel No.	Frequency (MHz)	Power Spectral Density (dBm)
4	1921.536	3.4
0	1928.448	3.7

Averaged over 1000 sweeps.

Requirements, FCC 15.319(d)

The Power Spectral Density shall be less than 3 mW (4.77 dBm) when averaged over at least 100 sweeps.

Power Spectral Density

Lower Channel:



Date: 15.JUN.2012 14:13:05

Overview



Date: 15.JUN.2012 14:14:42

Averaged, 1000 Sweeps

Upper Channel:



Date: 15.JUN.2012 14:16:17

Overview



Date: 15.JUN.2012 14:17:31

Averaged, 1000 Sweeps

4.10 In-Band Unwanted Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.1.

Test Results: Complies

Measurement Data:

See plots.

Requirements, FCC 15.323(d):

$B < f \leq 2B$: at least 30 dB below max. permitted peak power
$2B < f \leq 3B$: at least 50 dB below max. permitted peak power
$3B < f \leq$ UPCS Band Edge : at least 60 dB below max. permitted peak power



Middle Channel

In-Band Unwanted Emissions, Conducted



Date: 15.JUN.2012 14:24:16

Lower Channel



Date: 15.JUN.2012 14:22:24

Upper Channel

4.11 Out-of-band Emissions, Conducted

Test Method:

ANSI C63.17, clause 6.1.6.2.

Test Results: Complies

Measurement Data:

See plots.

Requirements, FCC 15.323(d):

$f \leq$ 1.25MHz outside UPCS band :	≤ -9.5dBm
1.25MHz ≤ $f \leq$ 2.5MHz outside UPCS band :	≤ -29.5 dBm
$f \geq$ 2.5MHz outside UPCS band :	≤ -39.5 dBm

Out-of-Band Emissions, Conducted

Lower Channel:



Date: 21.JUN.2012 11:31:34

Out-of-Band Emissions, Conducted

Lower Channel:



Date: 21.JUN.2012 11:30:57



Date: 21.JUN.2012 11:30:28

Out-of-Band Emissions, Conducted

Upper Channel:



Date: 21.JUN.2012 11:36:43



Date: 21.JUN.2012 11:38:20

Out-of-Band Emissions, Conducted

Upper Channel:



Date: 21.JUN.2012 11:39:12



Date: 21.JUN.2012 11:41:31

4.12 Carrier Frequency Stability

Test Method:

ANSI C63.17, clause 6.2.1.

Test Results: Complies

Measurement Data:

The Frequency Stability is measured with the RTX2011. The RTX2011 was logged by a computer programmed to get new readings as fast as possible (about 3 readings per second) over the noted time period or number of readings. The peak-to-peak difference was recorded and the mean value and deviation in ppm was calculated.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

Carrier Frequency Stability over Time at Nominal Temperature

Average Mean Carrier Frequency (MHz)	Max. Diff. (kHz)	Min. Diff. (kHz)	Max. Dev. (ppm)	Limit
1924.981441	-7.5	-11.9	-0.7	±10 ppm

Deviation ppm = ((Diff. - Mean Diff) / Mean Carrier Freq.) x 10^6

Deviation (ppm) is calculated from 3000 readings.

Frequency Stability over Power Supply Voltage at Nominal Temperature

Voltage	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
V_{nom}	/	/	/	±10 ppm
85% of V_{nom}	/	/	/	
115% of V_{nom}	/	/	/	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10^6

This test does not apply for EUT that is powered from batteries.

Frequency Stability over Temperature

Temperature	Measured Carrier Frequency (MHz)	Difference (kHz)	Deviation (ppm)	Limit
T = +20 ℃	1924.980503	0	0	±10 ppm
T = -20 ℃	1924.978654	-1.8	-1.0	
T = +50 ℃	1924.974124	-6.4	-3.3	

Deviation ppm = ((Mean – Measured Frequency) / Mean) x 10^6

4.13 Frame Repetition Stability

Test Method:

ANSI C63.17, clause 6.2.2.

Test Results: Complies

Measurement Data:

The envelope of the RF signal from the EUT is detected with a Crystal Detector and the mean and standard deviation of the frame repetition frequency is then gated over 100 frames and measured with a Frequency Domain Analyzer. The frame repetition stability is 3 times the standard deviation.

Carrier Frequency (MHz)	Mean (Hz)	Standard Deviation (Hz)	Frame Repetition Stability (ppm)
1924.992	99.9997	0.008	0.023

Limit:

Frame Repetition Stability	±10 ppm (TDMA)

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.2

4.14 Frame Period and Jitter

Test Method:

ANSI C63.17, clause 6.2.3.

Test Results: Complies

Measurement Data:

Carrier Frequency (MHz)	Frame Period (ms)	Max Jitter (µs)	3xStandard Deviation of Jitter (µs)
1924.992	10.000	-0.026	-0.017

Max Jitter = (1/ (Frame period + Pk-Pk/2)) - (1/Frame Period), when Pk-Pk and Frame Period are in Hz

3xSt.Dev.Jitter = 3x (1/(Frame Period + St.Dev) – 1/St.Dev) x 10^6

Limit:

Frame Period	20 or 10 ms
Max Jitter	25 µs
3 times St.Dev of Jitter	12.5 µs

Ref. FCC 15.323(e), ANSI C63.17, clause 6.2.3



Frame Repetition Stability, Gated over 100 Frames



Frame Period and Jitter

4.15 Monitoring Threshold, Least Interfered Channel

Monitoring Threshold Limits:

Lower Threshold:

$$T_L = 15 \log B - 184 + 30 - P_{EUT} \quad \text{(dBm)}$$

Upper Threshold:

$$T_U = 15 \log B - 184 + 50 - P_{EUT} \quad \text{(dBm)}$$

B is measured Emission Bandwidth in Hz
P_{EUT} is measured Transmitter Power in dBm

Calculated values:

	FCC 15.323	**RSS-213, Issue 2**
Lower Threshold	-81.3 dBm	-82.3 dBm
Upper Threshold	-61.3 dBm	-62.3 dBm

The Upper Threshold is applicable for systems with more than 40 duplex system access channels and that implements the Least Interfered Channel Procedure (LIC).

Measurement Procedure:

The Upper or Lower Threshold is found by the procedure defined in ANSI C63.17 clause 7.3.1 or 7.3.2.

Least Interfered Channel Procedure NOT used:	
Lower Threshold	N/A dBm
Least Interfered Channel Procedure:	
Upper Threshold	-60.8 dBm

Least Interfered Channel (LIC) Procedure Test, FCC 15.323(b), (c)(2) and (c)(5)

ANSI C63.17 clause 7.3.3 ref.	**Observation**	**Verdict**
b) f_1 T_L + 13 dB, f_2 at T_L + 6 dB	Transmission always on f_2	**Pass**
c) f_1 T_L + 6 dB, f_2 at T_L + 13 dB	Transmission always on f_1	**Pass**
d) f_1 T_L + 7 dB, f_2 at T_L	Transmission always on f_2	**Pass**
e) f_1 T_L, f_2 at T_L + 7 dB	Transmission always on f_1	**Pass**

Selected Channel Confirmation, FCC 15.323(c)(1) and (5)

ANSI C63.17 clause 7.3.4	Observation	Verdict
b) Shall **not** transmit on f_1	EUT transmits on f_2	**Pass**
d) Shall **not** transmit on f_2	EUT transmits on f_1	**Pass**

Limits:

	FCC 15.323	RSS-213, Issue 2
Lower Threshold + 6 dB margin	-75.3 dBm	-76.3 dBm
Upper Threshold + 6 dB margin	-55.3 dBm	-56.3 dBm



7.3.4 Selected Channel Confirmation, Connection 4.0s After Interferer Removed

4.16 Threshold Monitoring Bandwidth

This test is only required if a dedicated monitoring receiver is used. However, if the test is not carried out the manufacturer shall declare and provide proper evidence that the monitoring is made through the radio receiver used for communication.

Measurement Procedure:

Simple Compliance Test, ANSI C63.17, clause 7.4.1

More Detailed Test, ANSI C63.17, clause 7.4.2

The test is passed if **either** the Simple Compliance Test or the More Detailed test is passed.

During this test the spectrum analyzer is observed visually to see if the EUT transmits or not.

Test Results:

Test performed	Observation	Verdict
Simple Compliance test, at ±30% of *B*	No transmissions	**Pass**
More Detailed Test, at -6 dB points	N/A	**N/A**
More Detailed Test, at -12 dB points	N/A	**N/A**

The more detailed test must be pass at both the -6 and -12 dB points if the Simple Compliance test fails.

Comment: The Simple Compliance Test was performed with the level at $T_U + U_M + 10$ dB to check that the EUT did not transmit at all.

The tested EUT uses the same receiver for monitoring and communication, this test is therefore not required. However the test has been performed nonetheless and the test is passed.

Limits, FCC 15.323(c)(7):

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission.

4.17 Reaction Time and Monitoring Interval

Measurement Procedure

ANSI C63.17, clause 7.5

Test results:

By administrative commands and out-of-operating region interference, the EUT is restricted to operate on a single carrier frequency.

Time-synchronized pulsed interference was then applied on the carrier at pulsed levels $T_U + U_M$ to check that the EUT does not transmit at all. The level was raised 6 dB for part d) with 35 µs pulses.

The pulses are synchronized with the EUT timeslots and applied centered within all timeslots.

Pulse Width, ref. to ANSI C63.17 clause 7.5	Observation	Verdict
c) > largest of 50 µs and 50*SQRT(1.25/*B*)	No transmissions	**Pass**
d) > largest of 35 µs and 35*SQRT(1.25/*B*), and with interference level raised 6 dB	No transmissions	**Pass**

Comment: Since *B* is larger than 1.25 MHz the test was performed with pulse lengths of 50 µs and 35 µs.

Limits, FCC 15.323(c)(1), (5) and (7)

The maximum reaction time must be less than 50xSQRT (1.25/emission bandwidth in MHz) microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be 35xSQRT (1.25/emission bandwidth in MHz) microseconds but shall not be required to be less than 35 microseconds.



Date: 3.JUL.2012 15:18:35

50 µs Pulses



Date: 3.JUL.2012 15:16:54

35 µs Pulses

4.18 Time and Spectrum Window Access Procedure

This requirement is only for EUTs which transmit unacknowledged control and signaling information.

Measurement Procedure:

Timing for EUTs using control and signaling channel type transmissions: ANSI C63.17, clause 8.1

Test results:

Access Criteria, ref. to ANSI C63.17 clause 8.1.1	Observation	Verdict
b) Check that the EUT transmits on the interference free time-slot	N/A	**N/A**
b) The EUT must terminate or pause in its repetitive transmission of the control and signalling channel on the open channel to repeat the access criteria not less frequently than every 30 s	N/A	**N/A**

If FCC 15.323(c)(6) option, **If Random Waiting Interval is NOT implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.2	Observation	Verdict
b) Check that the EUT changes to an interference-free slot when interference is introduced on the time slot in use	N/A	**N/A**

If FCC 15.323(c)(6) option, **Only if Random Waiting Interval is implemented**

Access Criteria, ref. to ANSI C63.17 clause 8.1.3	Observation	Verdict
b-d) Check that the EUT uses random waiting interval before continuing transmission on an interfered time slot	N/A	**N/A**

Comment: The tested EUT does not transmit unacknowledged control and signaling information.

Limits:

FCC 15.323(c)(4):

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

FCC 15.323(c)(6):

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same windows after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

4.19 Acknowledgements and Transmission Duration

Measurement Procedure:

Acknowledgements: ANSI C63.17, clause 8.2.1

Transmission Duration: ANSI C63.17, clause 8.2.2

During the test **Initial transmission without acknowledgements** the signal from the EUT to the companion device is blocked by circulators in addition to the tunable attenuator.

The test **Transmission time after loss of acknowledgements** is performed by cutting-off the signal from the companion device by a RF switch and measuring the time until the EUT stops transmitting.

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

Test Results:

Acknowledgements

Test ref. to ANSI C63.17 clause 8.2.1	Observation	Verdict
a) Initial transmission without acknowledgements	0.22 sec	**Pass**
c) Transmission time after loss of acknowledgements	10 sec	**Pass**

Transmission Duration

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	182 sec*	**Pass**

*Maximum transmission duration with user input is 182 sec.

Comment: /

Limits, FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease.

Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.



Date: 3.JUL.2012 16:47:56

8.2.1a) Initial Transmission Without Acknowledgements



Date: 3.JUL.2012 16:57:30

8.2.1c) Transmission Time After Loss of Acknowledgements



Date: 3.JUL.2012 17:05:06

8.2.2b) Transmission Duration (with user input)

4.20 Dual Access Criteria Check

Measurement Procedure:

EUTs that does not implement the Upper Threshold: ANSI C63.17, clause 8.3.1

EUTs that implement the Upper Threshold: ANSI C63.17, clause 8.3.2

This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

Test Results:

EUTs that Implements the Upper Threshold:

Test ref. to ANSI C63.17 clause 8.3.2	**Observation**	**Verdict**
b) EUT is restricted to a single carrier f_1 for TDMA systems. The Test is Pass if EUT can transmit	EUT can transmit	**Pass**
c) d) Transmission on interference-free **receive** time/spectrum window	EUT transmits on interference free **receive** slot	**Pass**
e) f) Transmission on interference-free **transmit** time/spectrum window	EUT transmits on interference free **transmit** slot	**Pass**
g) Transmission not possible on any time/spectrum window	No connection possible	**Pass**

Comment: See plots.

Limits, FCC 15.323(c)(10)

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.



Date: 3.JUL.2012 16:29:10

8.3.2c) EUT Transmits on Interference Free RECEIVE Slot, BEFORE



Date: 3.JUL.2012 16:28:48

8.3.2c) EUT Transmits on Interference Free RECEIVE Slot, AFTER



Date: 3.JUL.2012 16:29:40

8.3.2e) EUT Transmits on Interference Free TRANSMIT Slot, BEFORE



Date: 3.JUL.2012 16:30:09

8.3.2e) EUT Transmits on Interference Free TRANSMIT Slot, AFTER



Date: 3.JUL.2012 16:31:57

8.3.2g) No Connection

4.21 Alternative Monitoring Interval

Test procedure described in ANSI C63.17 clause 8.4.

This test is required if the EUT implements the provisions of FCC 15.323(c)(11).

Test result:

Not Tested. The tested EUT does not implement this provision. See manufacturers' declaration.

5 Test Setups

5.1 Frequency Measurements

Test equipment included: 5, 9, 28

Test Set-up 1

This setup is used for measuring Carrier frequency stability at normal and extreme temperatures.

The EUT was in loopback-mode and was controlled with the RTX2011 for this test. The modulation pattern was set to 01010101…

5.2 Timing Measurements



Test equipment included: 5, 7, 9, 28

Test Set-up 2

This setup is used for measuring Frame repetition stability, Frame period and Jitter.

5.3 Conducted Emission Test



Test equipment included: 1, 2, 9, 26

Test Set-up 3

This setup is used for all conducted emission tests.

5.4 Power Line Conducted Emissions Test



Test equipment: 8, 17, 18, 22, 27

Test Set-Up 5

5.5 Monitoring Tests



Test equipment: 1, 2, 3, 4, 6, 9, 10, 11, 12, 13, 14, 15, 19, 23, 24, 25, 26

Test Set-Up 6

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generators to the EUT is measured with a power meter before the testing is started.

The CLK100 is used to synchronize the Pulse-/ Pattern generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the CLK100 signal will come form the Companion Device.

The sync signal to the Spectrum Analyzer is the CLK100 signal that is regenerated in the Pulse-/ Pattern Generator, this is used to synchronize the Spectrum Analyzer to the DECT frame when in zero span. The Pulse-/ Pattern Generator is used for tests that require time synchronized pulses or blocking of specific time slots.

5.6 Radiated Emissions Test, Fully Anechoic Chamber



Test equipment: 9, 16, 19, 20, 21, 29, 30

Test Set-Up 7

This test setup is used for measuring radiated output power. The measurements are performed in a 3m Fully Anechoic Chamber with a Spectrum Analyzer and Horn Antenna, a preamplifier may be used after the antenna. The measuring distance is 3m.

6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSU26	Spectrum Analyzer	Rohde & Schwarz	LR 1504	2011.11.03	2013.11.03
2	SME03	Signal generator	Rohde & Schwarz	LR 1238	2011.04.11	2013.04.11
3	SMIQ03B	Signal generator	Rohde & Schwarz	LR 1516	Cal b4 use	
4	SMP22	Signal generator	Rohde & Schwarz	LR 1287	Cal b4 use	
5	53310A	Modulation Domain Analyzer	Hewlett Packard	LR 1483	2011.12.13	2013.12.13
6	81104A	Pulse-/ Pattern Generator	Agilent	LR 1502	2013.04.26	2013.04.26
7	8470B	Crystal Detector	Hewlett Packard	LR 1207	N/A	
8	ESCS30	Measuring Receiver	Rohde & Schwarz	N- 3924	2011.12.15	2012.12.15
9	6810.17B	Attenuator	Suhner	LR1212	2010.09.15	2012.09.15
10	745-69	Step Attenuator	Narda	LR 1442	2011.10.19	2013.10.19
11	WE 1506A	Power Splitter	Weinchel	LR 244	Cal b4 use	
12	WE 1506A	Power Splitter	Weinchel	LR 245	Cal b4 use	
13	H-9	Hybrid	Anzac	LR 86	Cal b4 use	
14	H-9	Hybrid	Anzac	LR 257	Cal b4 use	
15	S212DS	RF Switch	Narda	LR 1244	N/A	
16	3115	Double Ridged Horn Antenna	EMCO	LR 1226	N/A	
17	ESH3-Z5	Two Line V-Network	Rohde & Schwarz	LR 1076	2011.11.03	2013.11.03
18	80S	Signal Generator	Powertron	LT 502	Cal b4 use	
19	6812B	AC Power Source	Agilent	LR 1515	2012.05.08	2013.05.08
20	FSP30	Spectrum Analyzer	Rohde & Schwarz	LR 1551	2011.04.04	2013.04.04
21	JS4	Pre-Amplifier	Miteq	LR 1552	2011.09.28	2012.09.28
22	Model 87 V	Multimeter	Fluke	LR 1600	2010.12.15	2012.12.15
23	87H35-1	Circulator	Racal-MESL	s.no.: 140	N/A	
24	87H35-1	Circulator	Racal-MESL	s.no.: 141	N/A	
25	87H35-1	Circulator	Racal-MESL	s.no.: 142	N/A	
26	U2000A	USB Power Sensor	Agilent	LR 1523	2011.03.26	2013.03.26
27	ESH3-Z2	Pulse Limiter	Rohde & Schwarz	LR 285	2010.10.08	2013.10.08
28	RTX2011	DECT Tester	RTX Telecom	LR 1587	2011-08	2012-08
29	Model 7200	Signal generator	Gigatronics	LR 1188	2010.11.02	2012.11.02
30	3115	Double Ridged Horn Antenna	EMCO	LR 1330	2010.08.05	2013.08.05