

Report No. 296983-1

# **Test Report**

Product UPCS Transceiver in Wireless Handheld Microphone

Name and address of the

applicant

Panasonic Corporation of North America

Name and address of the

manufacturer

Panasonic System Networks Co., Ltd. 1-62, 4-chome, Minoshima, Hakata-ku

Fukuoka 812-8531, Japan

Model K-SHH14

Rating 3.7V DC (Secondary Battery)

Trademark Panasonic

Serial number

Additional information DECT 6.0

Tested according to FCC Part 15, subpart D

Isochronous UPCS Device, 1920 – 1930 MHz

**Industry Canada RSS 213, Issue 3** 

2 GHz License-exempt Personal Communications Service Devices (LE-PCS)

Order number 296983

**Tested in period** 2015.12.07 to 2015.12.08

**Issue date** 2015.12.08

Name and address of the testing laboratory

Nemko

FCC No: 994405 IC OATS: 2040D-1


Instituttveien 6 Kjeller, Norway

TEL: +47 22 96 03 30 FAX: +47 22 96 05 50

Prepared by [Frode Sveinsen]

Approved by [G.Suhanthakumar]

This report shall not be reproduced except in full without the written approval of Nemko. Opinions and interpretations expressed within this report are not part of the current accreditation. This report was originally distributed electronically with digital signatures. For more information contact Nemko.





# **CONTENTS**

1	INFORMATION	3
1.1	Tested Item	3
1.2	Description of Tested Device	3
1.3	Exposure Evaluation	Error! Bookmark not defined.
1.4	Test Environment	4
1.5	Test Engineer(s)	4
1.6	Test Equipment	4
1.7	Other Comments	4
2	TEST REPORT SUMMARY	5
2.1	General	5
2.2	Test Summary	
3	TEST RESULTS	5
3.1	Acknowledgements and Transmission Duration	
4	TEST SETUPS	9
4.1	Monitoring Tests	9
5	TEST EQUIPMENT USED	10



# 1 INFORMATION

## 1.1 Tested Item

Name :	Panasonic
Model name :	K-SHH14
FCC ID:	ACJ9TAK-SHH14
Industry Canada ID :	N/A
Serial number :	/
Hardware identity and/or version:	ES2
Software identity and/or version :	V0.02R02(PP_US)
Tested to IC Radio Standard (RSS):	RSS-213 Issue 3, RSS-GEN Issue 4
Test Site IC Reg. Number :	IC 2040D-1
Frequency Range :	1921.536 – 1928.448 MHz
Number of Channels :	5 RF Channels, 5x12 = 60 TDMA Duplex Channels
Type of Modulation :	Digital (Gaussian Frequency Shift Keying)
Conducted Output Power :	6.9 mW (Burst Power)
Antenna Connector :	None
Number of Antennas :	1
Antenna Diversity Supported :	No
Power Supply :	Secondary Battery (3.7V Li-Ion)
Interface :	None

# 1.2 Description of Tested Device

The EUT is a DECT Handheld Microphone (Portable Part) and is an initiating device as described in ANSI C63.17 and is designed to operate together with a DECT Receiver (Fixed Part), which is the responding device.

The EUT has already been certified, this report is an update to verify a change in the access protocol. The only change is that maximum transmit time on same frequency and time window has been changed to 7.5 hours.



TEST REPORT FCC part 15D Report no.: 296983-1

FCC ID: ACJ9TAK-SHH14

#### 1.3 Test Environment

Temperature:  $20.5 - 21.9 \,^{\circ}\text{C}$ 

Relative humidity: 32 – 42 %

Normal test voltage: 3.7 V DC (Secondary Battery)

All tests were performed with a fully charged battery.

The values are the limit registered during the test period.

# 1.4 Test Engineer(s)

Frode Sveinsen

# 1.5 Test Equipment

See list of test equipment in clause 6.

#### 1.6 Other Comments

The Monitoring and Time and Spectrum Window Access tests were performed with Test Set-Up 6 (Ref. clause 5). A clock signal from the companion device was used to synchronize the Pulse Pattern Generator and the Spectrum Analyzer to the start of the DECT time window. The EUT was limited by administrative commands to operate on only two frequency carriers. For the tests where the EUT was required to operate on only one frequency carrier, one carrier was blocked by applying a CW interfering signal from RF Generator 3.

Since the EUT was programmed to operate on only two RF carriers, it was only necessary with two RF generators for the monitoring tests, however a third generator was applied for the tests that required specific time slots to be blocked.

The test was performed in conducted mode with a temporary antenna connector.



2 TEST REPORT SUMMARY

#### 2.1 General

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15D for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 3 / RSS-GEN Issue 4 / RSP-100 Issue 10.

All tests were conducted is accordance with ANSI C63.4-2014 and ANSI C63.17-2013.

A description of the test facility is on file with the FCC and Industry Canada.

, , , , , , , , , , , , , , , , , , , ,	
☐ New Submission	
⊠ Class II Permissive Change	☐ Pre-production Unit
PUF Equipment Code	☐ Family Listing

# 2.2 Test Summary

Name of test	FCC CFR 47 Paragraph #	IC RSS-213 Paragraph #	Verdict
Transmission duration	15.323(c)(3)	4.3.4(b)	Complies



## THIS TEST REPORT APPLIES ONLY TO THE ITEM(S) AND CONFIGURATIONS TESTED.

Deviations from, additions to, or exclusions from the test specifications are described in "Summary of Test Data".

Nemko Group authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any reproduction of parts of this report requires approval in writing from Nemko Group.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Group accepts no responsibility for damages suffered by any third party as a result of decisions made or actions based on this report.



TEST REPORT FCC part 15D Report no.: 296983-1

FCC ID: ACJ9TAK-SHH14

# 3 TEST RESULTS

# 3.1 Acknowledgements and Transmission Duration

#### **Measurement Procedure:**

Transmission Duration: ANSI C63.17, clause 8.2.2

The **Transmission Duration** test is performed by monitoring the slot in use and measuring the time until the EUT changes to a different slot.

#### **Test Results:**

#### **Transmission Duration**

Test ref. to ANSI C63.17 clause 8.2.2	Observation	Verdict
b) Transmission duration on same time and frequency window	7:29:59 hours	Pass

Comment: The EUT stops transmitting after 7 hours 29 minutes and 59 seconds.

## Limits, FCC 15.323(c)(3) and (4)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.





**TEST REPORT** 



# 4 Measurement Uncertainty

Measurement Uncertainty Values			
Test Item		Uncertainty	
Output Power		±0.5 dB	
Power Spectral Density		±0.5 dB	
Out of Band Emissions, Conducted (RBW < 100 kHz)	ted (RBW < 100 kHz) < 3.6 GHz		
	> 3.6 GHz	±0.9 dB	
Spurious Emissions, Radiated	< 1 GHz	±2.5 dB	
	> 1 GHz	±2.2 dB	
Emission Bandwidth		±4 %	
Power Line Conducted Emissions		+2.9 / -4.1 dB	
Spectrum Mask Measurements	Frequency	±5 %	
	Amplitude	±1.0 dB	
Frequency Error		±0.6 ppm	
Timing and Jitter Measurements		±2.0 ns	
Frame Timing Measurements		±1.4 ppm	
Receiver Blocking Levels		±1.0 dB	
Temperature Uncertainty		±1 °C	

All uncertainty values are expanded standard uncertainty to give a confidence level of 95%, based on coverage factor k=2



**Revision history** 


Version	Date	Comment	Sign
1.0	2015.12.08	Version for TCB review	FS





#### 5 **Test Setups**

#### 5.1 **Monitoring Tests**



Test equipment: 1, 2, 3, 4, 6, 9, 10, 11, 12, 13, 14, 15, 19, 23, 24, 25, 26

### Test Set-Up 6

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests. The path loss from the signal generators to the EUT is measured with a power meter before the testing is started.

The CLK100 is used to synchronize the Pulse-/ Pattern generator to the start of the DECT frame, this signal always comes from the base station. If the EUT is a DECT Portable Part (i.e. a handset) the CLK100 signal will come form the Companion Device.

The sync signal to the Spectrum Analyzer is the CLK100 signal that is regenerated in the Pulse-/ Pattern Generator, this is used to synchronize the Spectrum Analyzer to the DECT frame when in zero span. The Pulse-/ Pattern Generator is used for tests that require time synchronized pulses or blocking of specific time slots.



6 Test Equipment Used

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Testhouse.

No.	Model number	Description	Manufacturer	Ref. no.	Cal. date	Cal. Due
1	FSP30	Spectrum Analyzer	Rohde & Schwarz	LR 1551	2015.04.27	2017.04.27
2	SME03	Signal generator	Rohde & Schwarz	LR 1238	2015.05	2017.05
3	SMIQ03B	Signal generator	Rohde & Schwarz	LR 1516	2015.05	2017.05
4	SMHU52	Signal generator	Rohde & Schwarz	LR 1240	Cal b4 use	
6	81104A	Pulse-/ Pattern Generator	Agilent	LR 1502	2015.05	2016.05
9	6810.17A	Attenuator	Suhner	LR 1187	Cal b4 use	
10	745-69	Step Attenuator	Narda	LR 1442	N/A	
11	WE 1506A	Power Splitter	Weinchel	LR 244	Cal b4 use	
12	WE 1506A	Power Splitter	Weinchel	LR 245	Cal b4 use	
13	H-9	Hybrid	Anzac	LR 86	Cal b4 use	
14	H-9	Hybrid	Anzac	LR 257	Cal b4 use	
18	6812B	AC Power Source	Agilent	LR 1515	Cal b4 use	
19	Model 87 V	Multimeter	Fluke	N-4672	2015.10	2016.10
23	NRP-Z81	Wideband Power Sensor	Rohde & Schwarz	LR 1644	2015.11.03	2016.11.03