




# PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.

TEL (410) 290-6652 · FAX (410) 290-6654

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 24 & 22 Certification

Matsushita Electric Industrial Co., Ltd.  
1006 Oaza Kadoma, Kadoma  
Osaka, 571 JAPAN

Dates of Tests: February 13, 2004  
Test Report S/N: 22/24.240603347.ACJ  
Test Site: PCTEST Lab, Columbia MD  
Project No.: ITPD-04-F030A

FCC ID

**ACJ9TGCF-29A**

APPLICANT

**Matsushita Electric Industrial Co., Ltd.**

Classification: Licensed Portable Transmitter Worn on Body (PCT)  
FCC Rule Part(s): §24(E), §22H; §2  
EUT Type: Panasonic Toughbook w/ Intel WLAN Module FCC ID: PD9W3M3B2200BG  
and Sierra Wireless CDMA OEM Radio FCC ID: N7NSB555  
Model: CF-29mk2  
Tx Frequency Range: 824.70 – 848.31MHz (CDMA) / 1851.25MHz – 1908.75MHz (PCS CDMA)  
Rx Frequency Range: 869.70 – 893.31MHz (CDMA) / 1931.25MHz – 1988.75MHz (PCS CDMA)  
Max. RF Output Power: 0.231 W ERP CDMA (23.633 dBm) / 0.352 W EIRP PCS CDMA (25.451 dBm)  
Emission Designator(s): 1M25F9W (CDMA)  
Test Device Serial No. Identical Prototype [S/N: 3JKSA00051]  
Installed Options:  WLAN  Bluetooth  CDMA Radio Module  Other

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. This device is approved as a mobile device with respect to RF Exposure compliance (see antenna height photo), however, SAR data is included to demonstrate compliance at a 1.5 cm spacing or closer.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian  
Vice President Engineering





PCTEST PT. 22/24 REPORT	PCTEST	FCC MEASUREMENT REPORT	Panasonic	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 1 of 25


## TABLE OF CONTENTS

---

ATTACHMENT A: COVER LETTER(S)	
ATTACHMENT B: ATTESTATION STATEMENT(S)	
ATTACHMENT C: TEST REPORT	
1.1 SCOPE	3
2.1 INTRODUCTION	4
3.1 INSERTS	5
4.1 DESCRIPTION OF TESTS	6-9
5.1 EFFECTIVE RADIATED POWER OUTPUT	10
6.1 EQUIVALENT ISOTROPIC RADIATED POWER	11
7.1 RADIATED MEASUREMENTS	12-17
8.1 FREQUENCY STABILITY	18-21
9.1 PLOTS OF EMISSIONS	22
10.1 LIST OF TEST EQUIPMENT	23
11.1 SAMPLE CALCULATIONS	24
12.1 CONCLUSION	25
ATTACHMENT D: SIERRA WIRELESS & C.C.S. TEST REPORT FCC ID: N7NSB555	
ATTACHMENT E: FCC ID LABEL / LOCATION	
ATTACHMENT F: TEST SETUP PHOTOGRAPHS	
ATTACHMENT G: EXTERNAL PHOTOGRAPHS	
ATTACHMENT H: INTERNAL PHOTOGRAPHS	
ATTACHMENT I: BLOCK DIAGRAM(S)	
ATTACHMENT J: SCHEMATIC DIAGRAM(S)	
ATTACHMENT K: OPERATIONAL / CIRCUIT DESCRIPTION	
ATTACHMENT L: PARTS LIST/TUNE UP PROCEDURE	
ATTACHMENT M: USER'S MANUAL	
ATTACHMENT N: MPE/ SAR MEASUREMENT REPORT	

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A Page 2 of 25

# MEASUREMENT REPORT





## 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

## §2.1033 General Information


<b>Applicant Name:</b>	<b>Matsushita Electric Industrial Co., Ltd.</b>
<b>Address:</b>	<b>1006 Oaza Kadoma, Kadoma Oaza, 571 JAPAN</b>

- **FCC ID:** ACJ9TGCF-29A
- **Quantity:** Quantity production is planned
- **Emission Designators:** 1M25F9W (CDMA)
- **Tx Freq. Range:** 824.70 – 848.31 MHz (CDMA)  
1851.25 – 1908.75 MHz (PCS CDMA)
- **Rx Freq. Range:** 869.70 – 893.31 MHz (CDMA)  
1931.25 – 1988.75 MHz (PCS CDMA)
- **Max. Power Rating:** 0.231 W ERP CDMA (23.633 dBm)  
0.352 W EIRP PCS CDMA (25.451 dBm)
- **FCC Classification(s):** Licensed Portable Transmitter Worn on Body (PCT)
- **Equipment (EUT) Type:** Panasonic Toughbook w/ Intel WLAN Module FCC ID: PD9WM3B2200BG  
and Sierra Wireless CDMA OEM Radio FCC ID: N7NSB555
- **Modulation(s):** CDMA
- **Frequency Tolerance:** ± 0.00025% (2.5 ppm)
- **FCC Rule Part(s):** § 24(E), §22H
- **Dates of Tests:** February 13, 2004

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 3 of 25

- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22/24.240603347.ACJ
- Project No.: ITPD-04-F030A

## 2.1 INTRODUCTION



These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Open Area Test Site






Figure 2. Diagram of 3-meter outdoor test range

### Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

PCTEST PT. 22/24 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 4 of 25

### 3.1 INSERTS

---

#### Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

#### Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

#### Operating Instructions

The instruction manual is shown in Attachment M.

#### Parts List & Tune-Up Procedure (Confidential)



The parts list & tune-up procedure is shown in Attachment L.

#### Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

#### Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppression Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.


PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A	Page 5 of 25

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

### 4.2 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### 4.3 Cellular - Base Frequency Blocks




**BLOCK 1: 869 – 880 MHz (A\* Low + A)**

**BLOCK 3: 890 – 891.5 MHz (A\* High)**

**BLOCK 2: 880 – 890 MHz (B)**

**BLOCK 4: 891.5 – 894 MHz (B\*)**

### 4.4 Cellular - Mobile Frequency Blocks





**BLOCK 1: 824 – 835 MHz (A\* Low + A)**

**BLOCK 3: 845 – 846.5 MHz (A\* High)**


**BLOCK 2: 835 – 845 MHz (B)**

**BLOCK 4: 846.5 – 849 MHz (B\*)**

PCTEST PT. 22/24 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 6 of 25

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

### 4.5 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

### 4.6 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)


BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

PCTEST PT. 22/24 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
Page 7 of 25			

## 4.1 DESCRIPTION OF TESTS (CONTINUED)

---

### 4.7 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to at least the 10<sup>th</sup> harmonic. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provide 50% modulation.



At the input terminals of the spectrum analyzer, an isolator (RF circulator with one port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

### 4.8 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

### 4.9 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. The spectrum is scanned from the lowest frequency generated in the equipment up to at least the 10<sup>th</sup> harmonic.

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 8 of 25

## 5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:



- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025$  ( $\pm 2.5$  ppm) of the center frequency.*

### Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at -30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

**NOTE: The EUT is tested down to the battery endpoint.**

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b> 	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN
	FCC ID: ACJ9TGCF -29A	Page 9 of 25

# 5.1 Test Data

## 5.3 Effective Radiated Power Output

### A. POWER: High (CDMA Mode)



Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.70	-18.000	V	0.212	23.273	Standard
835.89	-17.800	V	0.231	23.633	Standard
848.31	-18.500	V	0.203	23.083	Standard

Note: Standard batteries are the only options for this phone

#### NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b> 	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN
	FCC ID: ACJ9TGCF-29A	Page 10 of 25

# 6.1 Test Data

## 6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

Radiated measurements at 3 meters

Supply Voltage: 3.7 VDC

Modulation: PCS CDMA



FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Battery
1851.25	-17.900	V	180	25.181	0.330	Standard
1880.00	-17.800	V	180	25.451	0.352	Standard
1908.75	-18.100	V	180	25.321	0.341	Standard

Note: Standard batteries are the only options for this phone

**NOTES:**

Equivalent Isotropic Radiated Power Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b> 	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN
	FCC ID: ACJ9TGCF-29A	Page 11 of 25

# 7.1 Test Data (Continued)

## 7.2 CELLULAR CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013 (Low)  
 MEASURED OUTPUT POWER: 23.633 dBm = 0.231 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.64 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-49.08	6.10	-42.98	V	66.6
2474.10	-48.28	6.70	-41.58	V	65.2
3298.80	-52.98	6.80	-46.18	V	69.8
4123.50	-64.68	6.50	-58.18	V	81.8
4948.20	-84.38	7.00	-77.38	V	101.0

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/FIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 12 of 25

# 7.1 Test Data (Continued)

## 7.3 CELLULAR CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 835.89 MHz  
 CHANNEL: 0363 (Mid)  
 MEASURED OUTPUT POWER: 23.633 dBm = 0.231 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.63 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1671.78	-48.08	6.10	-41.98	V	65.6
2507.67	-47.68	6.70	-40.98	V	64.6
3343.56	-51.28	6.80	-44.48	V	68.1
4179.45	-65.78	6.50	-59.28	V	82.9
5015.34	-83.78	7.00	-76.78	V	100.4

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
 according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 13 of 25

# 7.1 Test Data (Continued)

## 7.4 CELLULAR CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 0777 (High)  
 MEASURED OUTPUT POWER: 23.633 dBm = 0.231 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  36.63 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-50.18	6.10	-44.08	V	67.7
2544.93	-47.28	6.70	-40.58	V	64.2
3393.24	-53.08	6.80	-46.28	V	69.9
4241.55	-66.98	6.50	-60.48	V	84.1
5089.86	-83.98	7.00	-76.98	V	100.6

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 14 of 25

# 7.1 Test Data (Continued)

## 7.5 PCS CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 0025 (Low)  
 MEASURED OUTPUT POWER: 25.451 dBm = 0.352 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  38.46 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-42.53	8.70	-33.83	V	59.3
5553.75	-53.23	9.70	-43.53	V	69.0
7405.00	-52.63	9.90	-42.73	V	68.2
9256.25	-74.43	11.40	-63.03	V	88.5
11107.50	-77.33	12.10	-65.23	V	90.7

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 15 of 25

# 7.1 Test Data (Continued)

## 7.6 PCS CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation



OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 0600 (Mid)  
 MEASURED OUTPUT POWER: 25.451 dBm = 0.352 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  38.46 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-41.53	8.70	-32.83	V	58.3
5640.00	-50.83	9.70	-41.13	V	66.6
7520.00	-50.83	9.90	-40.93	V	66.4
9400.00	-72.53	11.40	-61.13	V	86.6
11280.00	-73.13	12.10	-61.03	V	86.5

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT		FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A	Page 16 of 25

# 7.1 Test Data (Continued)

## 7.7 PCS CDMA Radiated Measurements

### Field Strength of SPURIOUS Radiation


OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175 (High)  
 MEASURED OUTPUT POWER: 25.451 dBm = 0.352 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  38.46 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-41.93	8.70	-33.23	V	58.7
5726.25	-51.03	9.70	-41.33	V	66.8
7635.00	-51.43	9.90	-41.53	V	67.0
9543.75	-70.93	11.40	-59.53	V	85.0
11452.50	-76.93	12.10	-64.83	V	90.3

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/FIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A peak detector is used, with RBW = 1MHz, VBW = 10 Hz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST PT. 22/24 REPORT	 FCC MEASUREMENT REPORT 	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN
	FCC ID: ACJ9TGCF-29A	Page 17 of 25

## 8.1 Test Data

### 8.2 FREQUENCY STABILITY (CDMA)

OPERATING FREQUENCY: 835,890,002 Hz

CHANNEL: 363


REFERENCE VOLTAGE: 3.7 VDC



DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)	
100 %	3.70	+ 20 (Ref)	835,890,002	0.000000	
100 %		- 30	835,889,910	0.000011	
100 %		- 20	835,889,918	0.000010	
100 %		- 10	835,889,918	0.000010	
100 %		0	835,889,927	0.000009	
100 %		+ 10	835,889,952	0.000006	
100 %		+ 20	835,890,002	0.000000	
100 %		+ 25	835,889,985	0.000002	
100 %		+ 30	835,889,969	0.000004	
100 %		+ 40	835,890,077	-0.000009	
100 %		+ 50	835,890,069	-0.000008	
100 %		+ 60	835,890,086	-0.000010	
85 %		3.17	+ 20	835,890,002	0.000000
115 %		4.26	+ 20	835,890,002	0.000000
BATT. ENDPOINT	2.91	+ 20	835,890,002	0.000000	

## 8.1 Test Data (Continued)

### 8.3 FREQUENCY STABILITY (CDMA)



PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
Page 19 of 25			

## 8.1 Test Data (Continued)


### 8.4 FREQUENCY STABILITY (PCS CDMA)

OPERATING FREQUENCY: 1,880,000,004 Hz  
 CHANNEL: 600  
 REFERENCE VOLTAGE: 3.7 VAC  
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,880,000,004	0.000000
100 %		- 30	1,879,999,816	0.000010
100 %		- 20	1,879,999,797	0.000011
100 %		- 10	1,879,999,816	0.000010
100 %		0	1,879,999,910	0.000005
100 %		+ 10	1,879,999,948	0.000003
100 %		+ 20	1,880,000,004	0.000000
100 %		+ 25	1,879,999,966	0.000002
100 %		+ 30	1,879,999,891	0.000006
100 %		+ 40	1,880,000,173	-0.000009
100 %		+ 50	1,880,000,173	-0.000009
100 %		+ 60	1,880,000,192	-0.000010
85 %		3.17	+ 20	1,880,000,004
115 %	4.26	+ 20	1,880,000,004	0.000000
BATT. ENDPOINT	2.91	+ 20	1,880,000,004	0.000000

## 8.1 Test Data (Continued)

### 8.5 FREQUENCY STABILITY (PCS CDMA)





PCTEST PT. 22/24 REPORT	<b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF-29A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 21 of 25

## 9.1 PLOT(S) OF EMISSIONS

---



(SEE Sierra Wireless Inc. and CCS Test Report FCC ID: N7NSB555 Attachment S)

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>			Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A	Page 22 of 25

## 10.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	8566B (100Hz-22GHz) HP	08/15/04	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/04	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/04	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/04	894215/012
Alltech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/04	0792-032
Alltech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/04	0805-03334
Alltech/Eaton Receiver	NM17/27A (0.1-32MHz)	09/17/04	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/04	2043A00301
Alltech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/04	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5SIG4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30uW-3W)		2237A02084
Harmonic/Flicker	Test System HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455 Eaton 94455-1 Singer 94455-10 Compliance Design		1295, 1332, 0355
Log-Spiral Antenna (3)	Alltech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Alltech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB	Gain HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Alltech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holiday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

\* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b> 	Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN
	FCC ID: ACJ9TGCF-29A	Page 23 of 25

## 11.1 SAMPLE CALCULATIONS

---

### A. Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info



W = Combination (Audio/Data)

(Measured at the 99.75% power bandwidth)

### B. Spurious Radiated Emission - PCS Band

**Example: Channel 25 PCS Mode 2<sup>nd</sup> Harmonic (3702.50 MHz)**



The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>		Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A
Page 24 of 25			

## 12.1 CONCLUSION

---

The data collected shows that the **Panasonic Toughbook w/ Intel WLAN Module and Sierra Wireless CDMA OEM Radio Module** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

PCTEST PT. 22/24 REPORT	 <b>FCC MEASUREMENT REPORT</b>			Reviewed By: Quality Manager
Test Report S/N: 22/24.240603347.ACJ	Test Dates: FEB. 13, 2004	EUT Type: Panasonic Toughbook w/ Sierra OEM Radio & WLAN	FCC ID: ACJ9TGCF -29A	Page 25 of 25