

< CF-30 Series Addendum >

FCC RF Exposure Warning:

- This equipment is provided with external antenna connector(s) for connection to optional Car Mounter or Port Replicator for mobile external mounted antenna(s). External antenna(s) must be professionally installed and cannot exceed recommended maximum antenna gain as described in individual provided supplement instructions for wireless transmitters. The Car Mounter is provided with Radiall/Larsen WLAN whip antenna, type NMO5E2400BKTNC with 5dBi antenna gain. The maximum allowable antenna gain for the external WWAN base whip antenna for the cellular band and PCS band is shown in below table. Also, user must maintain minimum 20 cm spacing between external antenna(s) and all person's body (excluding extremities of hands, wrist and feet) during wireless modes of operation.

	Frequency Band	Max Antenna Gain
MPE for Standalone	824.7~848.31 MHz	0.1 dBi
MPE for Standalone	1851.25~1908.75 MHz	0.1 dBi
MPE for Standalone	2412 ~ 2462 MHz	0.94 dBi (802.11b)
MPE for Standalone	5180 ~ 5320 MHz	0.17 dBi (802.11a – UNII)
MPE for Standalone	5745 ~ 5825 MHz	0.17 dBi (802.11a)
MPE for Car Mount	824.7~848.31 MHz	1.43 dBi
MPE for Car Mount	1851.25~1908.75	3.53 dBi
MPE for Car Mount	2412 ~ 2462 MHz	5.0 dBi