



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
http://www.pctestlab.com



## CERTIFICATE OF COMPLIANCE FCC PART 15.247 Certification

**Applicant Name:**  
Panasonic Corporation of North America  
One Panasonic Way, 4B-8  
Secaucus, NJ 07094  
United States

**Date of Testing:**  
April 5 - 6, 2007  
**Test Site/Location:**  
PCTEST Lab, Columbia, MD, USA  
**Test Report Serial No.:**  
0702280137.ACJ

<b>FCC ID:</b>	<b>ACJ9TGCF-743</b>
<b>APPLICANT:</b>	<b>Panasonic Corporation of North America</b>

**Model(s):** CF-74  
**EUT Type:** Toughbook Model: CF-74  
**Max. RF Output Power:** 23.933 mW (13.79 dBm) Conducted (a)  
 19.142 mW (12.82 dBm) Conducted (g)  
**Frequency Range:** 2412 - 2462 MHz (DSSS/OFDM)  
 5745 – 5825 MHz (OFDM)  
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15.247  
**Test Device Serial No.:** N/A

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



*Grant Conditions: Listed output power is conducted.*

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*



Randy Ortanez  
President






<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 1 of 36	

# TABLE OF CONTENTS

---


FCC PART 15.247 MEASUREMENT REPORT.....	3
1.0 INTRODUCTION.....	4
1.1 EVALUATION PROCEDURE.....	4
1.2 SCOPE.....	4
1.3 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION .....	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
2.3 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TEST .....	6
3.1 CONDUCTED EMISSIONS.....	6
3.2 RADIATED EMISSIONS .....	7
4.0 ANTENNA REQUIREMENTS.....	8
5.0 TEST EQUIPMENT CALIBRATION DATA.....	9
6.0 TEST RESULTS .....	10
6.1 SUMMARY .....	10
6.2 6DB BANDWIDTH MEASUREMENT – 802.11G .....	11
6.3 6DB BANDWIDTH MEASUREMENT – 802.11A (5.8GHZ).....	13
6.4 OUTPUT POWER MEASUREMENT – 802.11G.....	15
6.5 OUTPUT POWER MEASUREMENT – 802.11A (5.8GHZ).....	17
6.6 POWER SPECTRAL DENSITY (802.11A/G).....	18
6.7 OUT OF BAND EMISSIONS AT THE BAND EDGE .....	22
6.8 RADIATED MEASUREMENTS.....	24
6.9 RADIATED RESTRICTED BAND MEASUREMENTS .....	31
6.10 LINE-CONDUCTED TEST DATA.....	32
7.0 CONCLUSION .....	36

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 2 of 36	



# MEASUREMENT REPORT

## FCC Part 15.247



### § 2.1033 General Information

**APPLICANT:** Panasonic Corporation of North America

**APPLICANT ADDRESS:** One Panasonic Way, 4B-8  
Secaucus, NJ 07094

**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.

**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA

**FCC RULE PART(S):** Part 15.247

**MODEL NAME:** CF-74

**FCC ID:** ACJ9TGCF-743

**Test Device Serial No.:** N/A       Production     Pre-Production     Engineering


**FCC CLASSIFICATION:** Digital Transmission System (DTS)

**DATE(S) OF TEST:** April 5 - 6, 2007

**TEST REPORT S/N:** 0702280137.ACJ

### Test Facility / Accreditations

Measurements were performed at **PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.**



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC Engineering registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

<b>FCC ID:</b> ACJ9TGCF-743	<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 3 of 36

# 1.0 INTRODUCTION

## 1.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2003) and FCC procedure dated March 23, 2005 entitled "Measurements of Digital Transmission Systems Operating Under Section 15.247" were used in the measurement of **Panasonic Toughbook Model: CF-74 FCC ID: ACJ9TGCF-743.**

Deviation from measurement procedure.....None


## 1.2 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

## 1.3 PCTEST Test Location

The map at the right shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.



**Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area**

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 4 of 36

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Panasonic Toughbook Model: CF-74 FCC ID: ACJ9TGCF-743**.

The EUT consisted of the following component(s):

Manufacturer / Model	FCC ID	Description
Panasonic / Model: CF-74	ACJ9TGCF-743	Toughbook Model: CF-74
Intel / Model: WM4965AG	PD94965AG	Wireless LAN module
Taiyo Yuden / Model: EYSF1CSMX	N/A	Bluetooth module
Sierra Wireless / Model: MC5725	N7N-MC5725	CDMA/EvDO module

**Table 2-1. EUT Equipment Description**

**Note:** This report contains data pertaining only to the 802.11a and 802.11g frequency bands.

### 2.2 EMI Suppression Device(s)/Modifications



No EMI suppression device(s) were added and/or no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 5 of 36	

## 3.0 DESCRIPTION OF TEST


### 3.1 Conducted Emissions




**Figure 3-1. Shielded Enclosure Line-Conducted Test Facility**



**Figure 3-2. Line Conducted Emission Test Set-Up**



**Figure 3-3. Wooden Table & Bonded LISNs**




**Figure 3-4. LISN Schematic Diagram**

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see Figure 3-1). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see Figure 3-2). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (see Figure 3-3). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (see Figure 3-4). All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.


The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in the test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 6 of 36


### 3.2 Radiated Emissions




**Figure 3-5. 3-Meter Test Site**



**Figure 3-6. Dimensions of Outdoor Test Site**



**Figure 3-7. Turntable and System Setup**



**Figure 3-8. Normalized Site Attenuation Curves (H&V)**

Preliminary measurements were made indoors at 1-meter using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, and turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using a bi-conical antenna and from 200 to 1000 MHz using a log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antennas (see Figure 3-5). The test equipment was placed on a wooden and plastic bench situated on a 1.5m x 2m area adjacent to the measurement area (see Figure 3-6). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 100kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. Above 1GHz the detector function was set to average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3-7). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in test setup photographs. Each EME reported was calibrated using the Agilent E8257D (250kHz – 20GHz) PSG Signal Generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3-8.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 7 of 36

## 4.0 ANTENNA REQUIREMENTS

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Toughbook Model: CF-74 are **permanently attached**.
- There are provisions for connection to an external antenna. Please refer to Panasonic’s application cover letter for details.



**Conclusion:**

The **Panasonic Toughbook Model: CF-74 FCC ID: ACJ9TGCF-743** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
-	:	157	5785
-	:	-	:
-	:	-	:
-	:	-	:
-	:	-	:
149	5745	165	5825

**Table 4-1. Frequency/ Channel Operations**


<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 8 of 36

## 5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Agilent	E4404B/E4407B ESA Spectrum Analyzer	04/20/06	Annual	04/20/07	US39210313
Agilent	N4010A Wireless Connectivity Test Set	06/11/06	Annual	06/11/07	GB46170464
EMCO	Model 3115 (1-18GHz) Horn Antenna	08/24/06	Biennial	08/23/08	9203-2178
EMCO	Model 3115 (1-18GHz) Horn Antenna	08/25/06	Biennial	08/24/08	9704-5182
Rohde & Schwarz	NRVS Power Meter	06/01/05	Biennial	06/01/07	835360/079
Rohde & Schwarz	NRV-Z53 Power Sensor	06/01/05	Biennial	06/01/07	846076/007
Agilent	HP 8566B (100Hz-22GHz)	12/21/06	Annual	12/21/07	3638A08713
Agilent	HP 8591A (9kHz-1.8GHz)	09/20/06	Annual	09/20/07	3144A02458
Agilent	E4448A (3Hz-50GHz)	09/22/06	Annual	09/22/07	US42510244
Gigatronics	80701A (0.05-18GHz) Power Sensor	08/04/06	Annual	08/04/07	1835299
Ailtech/Eaton	NM 37/57A (30MHz-1GHz)	06/07/06	Annual	06/07/07	0805-03334
Agilent	HP 85650A Quasi-Peak Adapter	12/21/06	Annual	12/21/07	2043A00301
Agilent	HP 8449B (1-26.5GHz) Pre-Amplifier	12/12/06	Annual	12/12/07	3008A00985
Agilent	HP 11713A Attenuation/Switch Driver	12/12/06	Annual	12/12/07	N/A
Agilent	HP 85685A (20Hz-2GHz) Preselector	12/12/06	Annual	12/12/07	N/A
Agilent	HP 8566B Opt. 462 Impulse Bandwidth	12/12/06	Annual	12/12/07	3701A22204
EMCO	3115 (1-18GHz) Horn Antenna	08/25/05	Biennial	08/25/07	9205-3874
Compliance Design	A100 Roberts Dipoles	08/31/05	Biennial	08/31/07	5118
EMCO	Dipole Pair	09/21/06	Biennial	09/20/08	23951
SOLAR	8012-50 LISN (2)	11/18/05	Biennial	11/18/07	0313233, 0310234
-	No.165 (30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166 (1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167 (100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A

**Table 5-1. Annual Test Equipment Calibration Schedule**

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>	<b>Panasonic</b>	<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 9 of 36



## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Panasonic Corporation of North America  
 FCC ID: ACJ9TGCF-743  
 FCC Classification: Digital Transmission System (DTS)  
 Data Rate(s) Tested: 1Mbps, 2Mbps, 5.5Mbps, 11Mbps (g)  
6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps (a/g)

FCC Part Section(s)	RSS 210 Section	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (TX)</b>						
15.247(a)(2)	RSS-210 [A8.2 (1)]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2, Section 6.3
15.247(b)(3)	RSS-210 [A8.4 (4)]	Transmitter Output Power	< 1 Watt		PASS	Sections 6.4, 6.5
15.247(e)	RSS-210 [A8.2 (2)]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.6
15.247(d)	RSS-210 [A8.5]	Band Edge / Out-of-Band Emissions	Conducted < 20dBc		PASS	Section 6.7, Intel Test Report
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Radiated < 20dBc. Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)	RADIATED	PASS	Sections 6.8, 6.9
15.207	RSS-Gen [7.2.2 ]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.10
<b>RECEIVER MODE (RX) / DIGITAL EMISSIONS</b>						
15.107	RSS-Gen [7.2.2 ]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Part 15B Test Report
15.109	RSS-Gen [7.2.3.2]	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.209 limits or < RSS-210 table 3 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Part 15B Test Report
<b>RF EXPOSURE</b>						
2.1091 / 2.1093	RSS-102	MPE Test	1.0 mW/cm <sup>2</sup> (MPE Limit)	MPE	PASS	MPE Report

**Table 6-1. Summary of Test Results**

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74	Page 10 of 36	

## 6.2 6dB Bandwidth Measurement – 802.11g

### §15.247(a)(2); RSS-210(A8.2 (1))

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The minimum permissible 6dB bandwidth is 500 kHz.**

Frequency [MHz]	Channel No.	802.11 Mode	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2412	1	g	16.40	0.500	Pass
2437	6	g	16.42	0.500	Pass
2462	11	g	16.40	0.500	Pass

Table 6-2. Conducted Bandwidth Measurements






Figure 6-1. Test Instrument & Measurement Setup




Plot 6-1. 6dB Bandwidth Plot (802.11g – Ch. 1)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 11 of 36



Plot 6-2. 6dB Bandwidth Plot (802.11g – Ch. 6)



Plot 6-3. 6dB Bandwidth Plot (802.11g – Ch. 11)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 12 of 36

### 6.3 6dB Bandwidth Measurement – 802.11a (5.8GHz) §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies. **The minimum permissible 6dB bandwidth is 500 kHz.**

Frequency [MHz]	Channel No.	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
5745	149	16.42	0.500	Pass
5785	157	16.42	0.500	Pass
5825	165	16.40	0.500	Pass

Table 6-3. Conducted Bandwidth Measurements






Figure 6-2. Test Instrument & Measurement Setup




Plot 6-4. 6dB Bandwidth Plot (802.11a – Ch. 149)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 13 of 36



Plot 6-5. 6dB Bandwidth Plot (802.11a – Ch. 157)



Plot 6-6. 6dB Bandwidth Plot (802.11a – Ch. 165)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 14 of 36



## 6.4 Output Power Measurement – 802.11g

**§15.247(b)(3); RSS-210(A8.4 (4))**

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power is 1 Watt.**


Freq [MHz]	Channel	Data Rate [Mbps]	Modulation	Main Ant. Measured Power [dBm]	Aux Ant. Measured Power [dBm]
2412	1	1	CCK	12.53	12.17
		2	CCK	<b>12.82</b>	11.93
		5.5	CCK	12.57	11.68
		11	CCK	12.78	11.82
		6	OFDM	12.55	12.48
		9	OFDM	11.95	11.91
		12	OFDM	11.85	11.78
		18	OFDM	11.52	11.45
		24	OFDM	11.65	11.69
		36	OFDM	10.62	10.52
		48	OFDM	10.70	10.58
		54	OFDM	9.97	9.83
2437	6	1	CCK	12.72	12.18
		2	CCK	12.64	11.91
		5.5	CCK	12.41	11.73
		11	CCK	12.06	11.91
		6	OFDM	12.54	12.47
		9	OFDM	12.40	12.27
		12	OFDM	12.24	12.28
		18	OFDM	11.98	12.03
		24	OFDM	11.66	11.69
		36	OFDM	11.17	11.15
		48	OFDM	10.72	10.58
		54	OFDM	9.41	9.34

**Table 6-4. Conducted Output Power Measurements**



FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 15 of 36

Freq [MHz]	Channel	Data Rate [Mbps]	Modulation	Main Ant. Measured Power [dBm]	Aux Ant. Measured Power [dBm]
2462	11	1	CCK	12.02	12.25
		2	CCK	12.61	12.03
		5.5	CCK	12.36	11.98
		11	CCK	12.03	11.95
		6	OFDM	12.34	12.28
		9	OFDM	12.14	12.04
		12	OFDM	12.06	11.99
		18	OFDM	11.72	11.63
		24	OFDM	11.32	11.28
		36	OFDM	10.80	10.63
		48	OFDM	10.36	10.25
		54	OFDM	9.68	9.63

**Table 6 5. Conducted Output Power Measurements (Cont'd)**



**Figure 6-3. Test Instrument & Measurement Setup**

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 16 of 36	

## 6.5 Output Power Measurement – 802.11a (5.8GHz)

§15.247(b)(3); RSS-210(A8.4 (4))

A transmitter antenna terminal of EUT is connected to the input of a RF power sensor. Measurement is made while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible conducted output power is 1 Watt.**

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]	Aux Ant. Measured Power [dBm]
5745	149	6	13.79	13.71
		9	13.45	13.42
		12	13.23	13.27
		18	12.89	12.81
		24	12.58	12.46
		36	12.05	12.03
		48	9.85	9.67
		54	8.19	8.08
		5785	157	6
9	13.14			13.09
12	13.02			12.87
18	12.77			12.59
24	12.47			12.35
36	11.97			11.78
48	9.75			9.63
54	7.64			7.61

Table 6-5. Conducted Output Power Measurements

Freq [MHz]	Channel	Data Rate [Mbps]	Main Ant. Measured Power [dBm]	Aux Ant. Measured Power [dBm]
5825	165	6	12.65	12.49
		9	12.55	12.51
		12	12.33	12.29
		18	12.06	11.96
		24	12.09	12.01
		36	11.19	11.24
		48	9.45	9.46
		54	7.37	7.24






Figure 6-4. Test Instrument & Measurement Setup

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74	Page 17 of 36	

## 6.6 Power Spectral Density (802.11a/g) §15.247(e); RSS-210(A8.2 (2))

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies. **The maximum permissible power spectral density is 8 dBm in any 3 kHz band.**

Frequency [MHz]	Channel No.	802.11 Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2412	1	g	-10.930	8.0	-18.9
2437	6	g	-12.020	8.0	-20.0
2462	11	g	-11.160	8.0	-19.2
5745	149	a	-10.380	8.0	-18.4
5785	157	a	-9.660	8.0	-17.7
5825	165	a	-9.700	8.0	-17.7

Table 6-6. Conducted Power Density Measurements








Figure 6-5. Test Instrument & Measurement Setup

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74	Page 18 of 36	




Plot 6-7. Power Spectral Density Plot (802.11g – Ch. 1)




Plot 6-8. Power Spectral Density Plot (802.11g – Ch. 6)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 19 of 36




Plot 6-9. Power Spectral Density Plot (802.11g – Ch. 11)




Plot 6-10. Power Spectral Density Plot (802.11a – Ch. 149)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 20 of 36



Plot 6-11. Power Spectral Density Plot (802.11a – Ch. 157)




Plot 6-12. Power Spectral Density Plot (802.11a – Ch. 165)


FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 21 of 36

## 6.7 Out of Band Emissions at the Band Edge

### §15.247(d); RSS-210(A8.5)




Plot 6-13. Band Edge Plot (802.11g– Ch. 1)




Plot 6-14. Band Edge Plot (802.11g – Ch. 11)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 22 of 36



Plot 6-15. Band Edge Plot (802.11a – Ch. 149)



Plot 6-16. Band Edge Plot (802.11a – Ch. 165)

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 23 of 36



## 6.8 Radiated Measurements

§15.247(d) / §15.205 & §15.209

The EUT was tested from 9kHz to the tenth harmonic of the fundamental frequency of the transmitter. Below 1GHz a CISPR quasi peak detector was used. Above 1 GHz average measurements were taken, using RBW= 1MHz, VBW= 10Hz, and linearly polarized horn antennas. In addition, peak measurements (RBW= 1MHz, VBW= 1MHz) were taken to ensure that the peak levels are not more than 20dB above the average limit. No harmonics/spurs peak emissions are more than 20dB above the average limit. Special attention is taken for the EUT's harmonic and spurious radiated emissions in the restricted bands of operations, as defined in Section 15.205.

Frequency	Field Strength [ $\mu$ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

**Table 6-7. Radiated Limits**

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74	Page 24 of 36	



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11g  
 Transfer Rate: 2 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2412MHz  
 Channel: 01

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 4824.00	-107.68	38.8	V	38.13	80.63	-15.87
7236.00	-112.65	42.4	V	36.76	68.87	-29.84
9648.00	-135.00	45.2	V	17.20	7.24	-49.40
* 12060.00	-135.00	46.6	V	18.63	8.54	-35.37

**Table 6-8. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 25 of 36



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11g  
 Transfer Rate: 2 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2437MHz  
 Channel: 06

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 4874.00	-109.08	38.95	V	36.87	69.74	-17.13
* 7311.00	-108.60	42.67	V	41.07	113.11	-12.93
9748.00	-135.00	45.36	V	17.36	7.38	-48.21
* 12185.00	-135.00	46.68	V	18.68	8.59	-35.32

**Table 6-9. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 26 of 36



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11g  
 Transfer Rate: 2 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 2462MHz  
 Channel: 11

Frequency [MHz]	Level [dBm]	AFCL [dB]	Po. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 4924.00	-107.95	39.19	V	38.24	81.66	-15.76
* 7386.00	-104.17	43.01	V	45.84	195.88	-8.16
9848.00	-135.00	45.67	V	17.67	7.65	-51.16
* 12310.00	-135.00	46.61	V	18.61	8.52	-35.39

**Table 6-10. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74	Page 27 of 36	



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11a  
 Transfer Rate: 6 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5745MHz  
 Channel: 149

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 11490.00	-104.40	40.6	V	43.2	144.5	-10.78
17235.00	-105.83	45.8	V	47.0	223.1	-12.13
* 22980.00	-135.00	49.6	V	21.6	12.0	-32.38
28725.00	-135.00	52.1	V	24.1	16.0	-35.00

**Table 6-11. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 28 of 36



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11a  
 Transfer Rate: 6 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5785MHz  
 Channel: 157

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 11570.00	-107.88	40.5	V	39.6	95.7	-14.36
17355.00	-105.96	47.3	V	48.3	261.2	-6.51
23140.00	-135.00	50.1	V	22.1	12.7	-32.80
28925.00	-135.00	52.5	V	24.5	16.8	-30.35

**Table 6-12. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 29 of 36



**Radiated Measurements (Cont'd)**  
**§15.247(d) / §15.205 & §15.209; RSS-210(A8.5)**

Mode: 802.11a  
 Transfer Rate: 6 Mbps  
 Distance of Measurements: 3 Meters  
 Operating Frequency: 5825MHz  
 Channel: 165

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dBμV/m]	Field Strength [μV/m]	Margin [dB]
* 11650.00	-109.45	40.6	V	38.2	80.8	-15.83
17475.00	-105.13	45.9	V	47.8	244.6	-8.23
23300.00	-135.00	49.4	V	21.4	11.7	-34.61
29125.00	-135.00	53.4	V	25.4	18.5	-30.65

**Table 6-13. Radiated Measurements @ 3 meters**

**NOTES:**

- All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table 6-7.  
(Note: \* = Restricted Band measured frequency)
- All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
- Average Measurements > 1GHz using RBW = 1MHz VBW = 10Hz
- The peak emissions above 1GHz are not more than 20dB above the average limit.
- The antenna is manipulated through typical positions, polarity and length during the tests.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
- < - 135 dBm are below the analyzer floor level.
- Above 1GHz, the limit is 500 μV/m (54dBμ/m) at 3 meters radiated.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 30 of 36



## 6.9 Radiated Restricted Band Measurements

§15.205 / §15.209; RSS-210(A8.5)

- Special attention is paid to the EUT's harmonic and spurious radiated emissions in the restricted bands of operations.

Mode: 802.11g

Transfer Rate: 2 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 2462MHz

Channel: 11

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol. [H/V]	Field Strength [dB $\mu$ V/m]	Field Strength [ $\mu$ V/m]	Margin [dB]
2483.53	-103.7	31.80	V	35.07	56.69	-18.91
2485.69	-104.5	31.80	V	34.27	51.70	-19.71
2488.17	-104.4	31.80	V	34.37	52.30	-19.61
2490.03	-105.2	31.80	V	33.57	47.70	-20.41
2491.28	-105.3	31.80	V	33.47	47.15	-20.51
2493.72	-106.4	31.80	V	32.37	41.54	-21.61

**Table 6-14. Radiated Restricted Band Measurements at 3-meters**

**NOTES:**

- The antenna is manipulated through typical positions, polarity and length during the testing.
- The EUT is supplied with the minimal AC voltage or/and a new/fully re-charged battery.
- The spectrum is measured from 9 kHz up to the 10th harmonic and the worst-case emissions are reported.
- Above 1 GHz the limit is 500 $\mu$ V/m.
- < -135 dBm is below the analyzer measurement floor level.
- The data in the table are Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
- The peak emissions above 1 GHz are not more than 20 dB above the average limit.


FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 31 of 36

**6.10 Line-Conducted Test Data**  
**§15.207; RSS-Gen(7.2.2)**

# PCTEST Engineering Laboratory Inc.

Company : Panasonic Corporation  
 Model Number : CF-74  
 FCC ID Code : ACJ9TGCF-743  
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz  
 Tested Date : 04/05/2007  
 Note : Tested with WLAN a ON





Ver.1.1 ©PCTEST 2006.08

**Plot 6-17. Line Conducted Plot with 802.11a**

**Notes:**

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 32 of 36



**Line-Conducted Test Data (Cont'd)**  
**§15.207; RSS-Gen(7.2.2)**

Nb.	Line	Frequency [MHz]	Factor [dB]	QP [dBμV]	Limit [dBμV]	Margin [dB]	Average [dBμV]	Limit [dBμV]	Margin [dB]
1	A	12.903	7.77	49.11	60.00	-10.89	35.12	50.00	-14.88
2	A	14.006	7.83	49.17	60.00	-10.83	36.09	50.00	-13.91
3	A	14.974	7.87	49.86	60.00	-10.14	35.58	50.00	-14.42
4	A	15.101	7.88	49.16	60.00	-10.84	36.56	50.00	-13.44
5	A	15.333	7.89	47.70	60.00	-12.30	36.39	50.00	-13.61
6	A	16.185	7.93	49.23	60.00	-10.77	35.42	50.00	-14.58
7	A	16.194	7.93	49.04	60.00	-10.96	36.35	50.00	-13.65
8	A	17.165	7.97	48.74	60.00	-11.26	37.06	50.00	-12.94
9	A	17.403	7.98	48.36	60.00	-11.64	35.98	50.00	-14.02
10	A	17.525	7.99	48.12	60.00	-11.88	36.52	50.00	-13.48
11	B	0.738	7.37	44.41	56.00	-11.59	33.86	46.00	-12.14
12	B	2.862	7.44	42.63	56.00	-13.37	26.97	46.00	-19.03
13	B	13.882	7.82	47.46	60.00	-12.54	34.06	50.00	-15.94
14	B	14.972	7.87	47.96	60.00	-12.04	34.93	50.00	-15.07
15	B	15.219	7.89	47.29	60.00	-12.71	35.34	50.00	-14.66
16	B	16.071	7.93	47.90	60.00	-12.10	34.20	50.00	-15.80
17	B	21.800	8.19	46.09	60.00	-13.91	35.24	50.00	-14.76
18	B	22.032	8.21	47.07	60.00	-12.93	35.92	50.00	-14.08
19	B	22.158	8.21	47.76	60.00	-12.24	36.46	50.00	-13.54
20	B	22.282	8.22	47.48	60.00	-12.52	36.85	50.00	-13.15

**Table 6-15. Line Conducted Data with 802.11a**

**Notes:**

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.


FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74	Page 33 of 36	

**Line-Conducted Test Data (Cont'd)**  
**§15.207; RSS-Gen(7.2.2)**

# PCTEST Engineering Laboratory Inc.

Company : Panasonic Corporation  
 Model Number : CF-74  
 FCC ID Code : ACJ9TGCF-743  
 Standard : FCC Part 15B class B

Power Source : AC120V/60Hz  
 Tested Date : 04/05/2007  
 Note : Tested with WLAN g ON



Ver.1.1 ©PCTEST 2006.08

**Plot 6-18. Line Conducted Plot with 802.11g**

**Notes:**

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 34 of 36

## Line-Conducted Test Data (Cont'd)



§15.207; RSS-Gen(7.2.2)

Nb.	Line	Frequency [MHz]	Factor [dB]	QP [dBμV]	Limit [dBμV]	Margin [dB]	Average [dBμV]	Limit [dBμV]	Margin [dB]
1	A	13.758	7.82	49.61	60.00	-10.39	35.96	50.00	-14.04
2	A	13.878	7.82	50.04	60.00	-9.96	35.74	50.00	-14.26
3	A	14.735	7.86	49.39	60.00	-10.61	36.19	50.00	-13.81
4	A	14.851	7.87	49.98	60.00	-10.02	36.73	50.00	-13.27
5	A	15.827	7.91	49.77	60.00	-10.23	36.33	50.00	-13.67
6	A	16.928	7.96	49.53	60.00	-10.47	36.66	50.00	-13.34
7	A	17.047	7.97	49.74	60.00	-10.26	36.49	50.00	-13.51
8	A	17.172	7.97	49.00	60.00	-11.00	36.33	50.00	-13.67
9	A	17.645	7.99	48.46	60.00	-11.54	35.87	50.00	-14.13
10	A	17.894	8.00	48.91	60.00	-11.09	36.15	50.00	-13.85
11	B	0.733	7.37	44.70	56.00	-11.30	34.14	46.00	-11.86
12	B	13.022	7.78	46.54	60.00	-13.46	33.53	50.00	-16.47
13	B	13.875	7.82	47.83	60.00	-12.17	33.98	50.00	-16.02
14	B	16.066	7.93	48.14	60.00	-11.86	34.32	50.00	-15.68
15	B	16.307	7.94	47.09	60.00	-12.91	34.22	50.00	-15.78
16	B	16.912	7.96	47.28	60.00	-12.72	35.14	50.00	-14.86
17	B	21.656	8.18	46.21	60.00	-13.79	34.56	50.00	-15.44
18	B	21.780	8.19	46.51	60.00	-13.49	35.05	50.00	-14.95
19	B	22.153	8.21	47.51	60.00	-12.49	35.39	50.00	-14.61
20	B	22.635	8.24	46.87	60.00	-13.13	35.66	50.00	-14.34

Table 6-16. Line Conducted Data with 802.11g

**Notes:**



1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Line A = Phase; Line B = Neutral
4. Traces shown in plot are made using a peak detector.
5. Deviations to the Specifications: None.

FCC ID: ACJ9TGCF-743		FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0702280137.ACJ	Test Dates: April 5 - 6, 2007	EUT Type: Toughbook Model: CF-74		Page 35 of 36



## 7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Panasonic Toughbook Model: CF-74** **FCC ID: ACJ9TGCF-743** is in compliance with Part 15C of the FCC Rules.

<b>FCC ID:</b> ACJ9TGCF-743		<b>FCC Pt. 15.247 WLAN 802.11a/g MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Reviewed by:</b> Quality Manager
<b>Test Report S/N:</b> 0702280137.ACJ	<b>Test Dates:</b> April 5 - 6, 2007	<b>EUT Type:</b> Toughbook Model: CF-74		Page 36 of 36