



**FCC CFR47 PART 15 SUBPART E
INDUSTRY CANADA RSS-210 ISSUE 8**

**CLASS II PERMISSIVE CHANGE
TEST REPORT**

FOR

802.11a/b/g/n 2x2 Radio Module inside PANASONIC TABLET PC CF-D1

MODEL NUMBER: WL11A

**FCC ID: ACJ9TGWL11A
IC: 216A-CFWL11A**

REPORT NUMBER: 11J13897-2

ISSUE DATE: JULY 05, 2011

Prepared for
**PANASONIC CORPORATION OF NORTH AMERICA
ONE PANASONIC WAY, 4B-8
SECAUCUS, NEW JERSEY 07094, U.S.A.**

Prepared by
**COMPLIANCE CERTIFICATION SERVICES (UL CCS)
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
--	07/5/11	Initial Issue	F. Ibrahim

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. SAMPLE CALCULATION	5
4.3. MEASUREMENT UNCERTAINTY	5
5. EQUIPMENT UNDER TEST	6
5.1. DESCRIPTION OF EUT	6
5.2. DESCRIPTION OF CLASS II PERMISSIVE CHANGE	6
5.3. MAXIMUM OUTPUT POWER	6
5.4. DESCRIPTION OF AVAILABLE ANTENNAS	6
5.5. SOFTWARE AND FIRMWARE	6
5.6. WORST-CASE CONFIGURATION AND MODE	7
5.7. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. RADIATED TEST RESULTS	11
7.1. LIMITS AND PROCEDURE	11
7.1. TRANSMITTER ABOVE 1 GHz (worst-case modes)	12
7.1.1. 5.2 GHz BAND	12
7.1.2. 5.3 GHz BAND	15
7.1.3. 5.6 GHz BAND	17
7.2. TRANSMITTER BELOW 1 GHz (worst-case modes)	21
8. SETUP PHOTOS	25

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: PANASONIC CORPORATION OF NORTH AMERICA
ONE PANASONIC WAY, 4B-8
SECAUCUS, NEW JERSEY 07094, U.S.A.

EUT DESCRIPTION: 802.11a/b/g/n 2x2 Radio Module inside PANASONIC TABLET PC
CF-C1

MODEL: WL11A

SERIAL NUMBER: 1CTSA00169

DATE TESTED: JYLY 01-05, 2011

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass
INDUSTRY CANADA RSS-210 Issue 8 Annex 9	Pass
INDUSTRY CANADA RSS-GEN Issue 3	Pass

Compliance Certification Services (UL CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL CCS By:

Tested By:



FRANK IBRAHIM
EMC SUPERVISOR
UL CCS

CHIN PANG
EMC ENGINEER
UL CCS

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, FCC 06-96, RSS-GEN Issue 3, and RSS-210 Issue 8.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an 802.11a/b/g/n that operates in both the 2.4GHz and 5 GHz bands.

The radio module is manufactured by Intel.

5.2. DESCRIPTION OF CLASS II PERMISSIVE CHANGE

The major change filed under this application is adding Portable Host (Representative model; CF-D1).

5.3. MAXIMUM OUTPUT POWER

Same power settings were used from original reports.

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIFA antenna, Main and Aux antenna with a maximum gain as:

**Intel Taylor Peak
Original**

2.4GHz	5150-5350	5470-5725	5725-5850
3.24	3.73	4.77	4.97

CF-D1

Main	2.69	2.41	2.07	2.07
Aux	1.82	4.39	4.48	2.47

5.5. SOFTWARE AND FIRMWARE

The test utility software used during testing was DRTU, version. 1.3.12.0263.

Driver software is V14.1.4.115.

5.6. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power. Radiated Emissions below 1 GHz was performed with EUT set to transmit at the channel with highest output power.

Worst-case data rates used per input from the client are as follows:

11a: 6Mbps
11n HT20: MCS0
11n HT40: MCS0

The EUT (tablet) was investigated in three orthogonal orientations X,Y,Z and it was determined that Y-axis orientation is the worst-case orientation; therefore, all testing in this report was conducted with EUT in worst case orientation.

Worst-case modes were selected for BE and Harmonics based on an investigation of the original reports, as shown in the summary table below:

Worst-case Modes to test					
5.2 GHz			5.3 GHz		
Low BE	High BE	Harmonics	Low BE	High BE	Harmonics
11n 20M Chain A+B Channel 36 (5180MHz) Pwr AV=12.4, 12.5 dBm Margin= -1.1 dB	No need to test	11n 20M Chain A+B Channel 40 (5200MHz) Pwr AV=16.5 dBm AV Margin= -6.3 dB Freq= 11000.3 MHz	No need to test	11n 20M Chain A+B Channel 64 (5320MHz) Pwr AV=13.2, 13.1 dBm Margin= -5.4 dB	No need to test
5.6 GHz					
Low BE	High BE	Harmonics			
11n 40M Chain A+B Channel 102 (5510MHz) Pwr AV=12.6, 12.4 dBm Margin= -4.6 dB	11n 20M Chain A+B Channel 140 (5700MHz) Pwr AV=13.4, 13.6 dBm Margin= -16.5 dB	11a 20M Chain B Channel 100 (5500MHz) Pwr AV=16.1, 16 dBm AV Margin= -9.7 dB Freq= 7500.1 MHz			

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	PANASONIC	CF-D1	1CTSA00169	DoC
AC Adapter	PANASONIC	CF-AA5713Am1	5713AM110Z12951A	DoC


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	AC	Un-Sheilded	2M	N/A
2	DC	1	DC	Un-Sheilded	1M	N/A

TEST SETUP

The EUT is installed in a host laptop computer during the tests. Test software exercised the radio card. A laptop computer was used to configure the EUT to continuously transmit at a specified output power or continuously receive on the channel specified in the test data. For transmit modes the worst case was evaluated.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	Asset	Cal Date	Cal Due
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	07-12-10	07-12-11
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01-27-11	01-27-12
Antenna, Horn, 18 GHz	EMCO	3115	C00783	06-29-10	06-30-12
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	04-07-11	04-07-12
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	01-07-10	04-11-12
Peak Power Meter	Agilent / HP	E4416A	C00963	12-04-09	04-11-12
Preamplifier, 40 GHz	Miteq	NSP4000-SP2	C00990	07-15-10	07-15-11
Antenna, Horn, 40 GHz	ARA	MWH-2640/B	C00981	06-14-11	06-14-12
Reject Filter, 5.47-5.725 GHz	Micro-Tronics	BRC13191	N02678	CNR	CNR
Reject Filter, 5.15-5.35 GHz	Micro-Tronics	BRC13190	N02679	CNR	CNR

7. RADIATED TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.



The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



7.1. TRANSMITTER ABOVE 1 GHz (worst-case modes)

7.1.1. 5.2 GHz BAND

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



HARMONICS AND SPURIOUS EMISSIONS

High Frequency Measurement

Compliance Certification Services, Fremont 5m Chamber

Test Engr: Chin Pang
Date: 06-29-11
Project #: 11j13897
Company: Panasonic
Test Target: FCC 15.407
Mode Oper: TX, HT20, 5.2GHz Band

f	Measurement Frequency	Amp	Preamp Gain	Average Field Strength Limit
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Peak Field Strength Limit
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Margin vs. Average Limit
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Margin vs. Peak Limit
CL	Cable Loss	HPF	High Pass Filter	



f GHz	Dist (m)	Read dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Corr. dBuV/m	Limit dBuV/m	Margin dB	Ant. Pol. V/H	Det. P/A/QP	Notes
Low Ch, 5200MHZ													
15.600	3.0	37.1	38.7	11.4	-32.3	0.0	0.0	54.9	74.0	-19.1	H	P	
15.600	3.0	25.3	38.7	11.4	-32.3	0.0	0.0	43.1	54.0	-10.9	H	A	
15.600	3.0	35.9	38.7	11.4	-32.3	0.0	0.0	53.7	74.0	-20.3	V	P	
15.600	3.0	23.7	38.7	11.4	-32.3	0.0	0.0	41.5	54.0	-12.5	V	A	

Rev. 4.1.2.7



Note: No other emissions were detected above the system noise floor.

7.1.2. 5.3 GHz BAND



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)




7.1.3. 5.6 GHz BAND




RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



AUTHORIZED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



AUTHORIZED BANDEDGE (HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS

High Frequency Measurement													
Compliance Certification Services, Fremont 5m Chamber													
Test Engr:		Chin Pang											
Date:		06-29-11											
Project #:		11j13897											
Company:		Panasonic											
Test Target:		FCC 15.407											
Mode Oper:		TX, 5.6GHz Band, a mode CF-D1											
f	Measurement Frequency	Amp	Preamp Gain		Average Field Strength Limit								
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters		Peak Field Strength Limit								
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m		Margin vs. Average Limit								
AF	Antenna Factor	Peak	Calculated Peak Field Strength		Margin vs. Peak Limit								
CL	Cable Loss	HPF	High Pass Filter										
f GHz	Dist (m)	Read dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fitr dB	Corr. dBuV/m	Limit dBuV/m	Margin dB	Ant. Pol V/H	Det. P/A/QP	Notes
Low Ch, 5500MHz													
11.000	3.0	40.2	37.7	9.2	-33.8	0.0	0.0	53.4	74.0	-20.6	H	P	
11.000	3.0	28.3	37.7	9.2	-33.8	0.0	0.0	41.5	54.0	-12.5	H	A	
11.000	3.0	43.2	37.7	9.2	-33.8	0.0	0.0	56.3	74.0	-17.7	V	P	
11.000	3.0	31.2	37.7	9.2	-33.8	0.0	0.0	44.4	54.0	-9.6	V	A	
Rev. 4.1.2.7													
Note: No other emissions were detected above the system noise floor.													


7.2. TRANSMITTER BELOW 1 GHz (worst-case modes)

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)





SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



VERTICAL DATA

Panasonic									
Model: CF-D1									
Range 1 30 - 1000MHz									
Test Freq	Meter Res	Detector	Chamber	ET10	Below	T130	Bil	dBuV/m	CFR 47 Pa
76.9105	49.01	PK	1.2	-29.4	7.8	28.61	40	-11.39	200 Horz
84.2766	50.82	PK	1.3	-29.4	7.5	30.22	40	-9.78	200 Horz
96.295	47.17	PK	1.4	-29.3	9.1	28.37	43.5	-15.13	200 Horz
150.5715	47.63	PK	1.7	-29.1	12.5	32.73	43.5	-10.77	200 Horz
257.3801	49.86	PK	2.2	-28.7	12	35.36	46	-10.64	100 Horz
306.229	51.65	PK	2.4	-28.6	13.4	38.85	46	-7.15	100 Horz
700.1219	44.32	PK	3.7	-29.3	19.2	37.92	46	-8.08	100 Horz
336.0811	52.51	PK	2.5	-28.7	13.9	40.21	46	-5.79	100 Horz
Range 2 30 - 1000MHz									
Test Freq	Meter Res	Detector	Chamber	ET10	Below	T130	Bil	dBuV/m	CFR 47 Pa
38.1415	42.96	PK	0.9	-29.5	15.5	29.86	40	-10.14	108 Vert
77.1043	53.9	PK	1.2	-29.4	7.8	33.5	40	-6.5	108 Vert
55.5875	48.55	PK	1.1	-29.4	7.9	28.15	40	-11.85	200 Vert
250.014	47.05	PK	2.2	-28.7	11.8	32.35	46	-13.65	108 Vert
337.0504	51.22	PK	2.6	-28.7	13.9	39.02	46	-6.98	200 Vert
700.1219	41.56	PK	3.7	-29.3	19.2	35.16	46	-10.84	108 Vert