



FCC SAR TEST REPORT

FCC ID : ACJFZA3A20A
Equipment : Radio module
Brand Name : Panasonic
Model Name : WW18A
Marketing Name : WW18A
Applicant : Panasonic Corporation of North America
Two Riverfront Plaza, 9th Floor, Newark, NJ 07102-5490
Manufacturer : Panasonic Mobile Communications Co., Ltd.
600 Saedo-cho, Tsuzuki-ku, Yokohama City 224-8539,
Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was installed into Tablet Computer (Brand Name Panasonic, Model Name: FZ-A3) during test.

The product was received on Nov. 25, 2019 and testing was started from Dec. 13, 2019 and completed on Dec. 18, 2019. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	7
4. Proximity Sensor Triggering Test.....	9
5. RF Exposure Limits.....	14
5.1 Uncontrolled Environment.....	14
5.2 Controlled Environment.....	14
6. Specific Absorption Rate (SAR).....	15
6.1 Introduction	15
6.2 SAR Definition.....	15
7. System Description and Setup	16
7.1 E-Field Probe	17
7.2 Data Acquisition Electronics (DAE)	17
7.3 Phantom.....	18
7.4 Device Holder.....	19
8. Measurement Procedures	20
8.1 Spatial Peak SAR Evaluation.....	20
8.2 Power Reference Measurement.....	21
8.3 Area Scan	21
8.4 Zoom Scan.....	22
8.5 Volume Scan Procedures.....	22
8.6 Power Drift Monitoring.....	22
9. Test Equipment List.....	23
10. System Verification	24
10.1 Tissue Simulating Liquids.....	24
10.2 Tissue Verification	25
10.3 System Performance Check Results.....	26
11. RF Exposure Positions	26
11.1 SAR Testing for Tablet	26
12. Conducted RF Output Power (Unit: dBm).....	27
13. Antenna Location	78
14. SAR Test Results	80
14.1 Body SAR	81
14.2 Repeated SAR Measurement	85
15. Simultaneous Transmission Analysis.....	86
15.1 Body Exposure Conditions	87
15.2 SPLSR Evaluation and Analysis.....	89
16. Uncertainty Assessment	103
17. References.....	103
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA992410-02A	01	Initial issue of report	Jan. 10, 2020
FA992410-02A	02	Update FCC ID, section 1, 15.1 and 15.2	Jan. 16, 2020
FA992410-02A	03	Update section 3.1	Jan. 22, 2020

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Panasonic Corporation of North America, Radio module, WW18A, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
		Body	
		1g SAR (W/kg)	
Licensed	WCDMA II	1.12	1.56
	WCDMA IV	1.03	
	WCDMA V	1.02	
	LTE Band 2	1.03	
	LTE Band 7	1.18	
	LTE Band 12	1.20	
	LTE Band 13	1.04	
	LTE Band 14	1.18	
	LTE Band 5 / 26	1.07	
	LTE Band 41	1.18	
	LTE Band 4 / 66	1.11	
DTS	2.4GHz WLAN	0.91	1.41
NII	5GHz WLAN	1.23	1.56
DSS	Bluetooth	0.31	1.56
Date of Testing:		2019/12/13 ~ 2019/12/18	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Radio module
Brand Name	Panasonic
Model Name	WW18A
Marketing Name	WW18A
FCC ID	ACJFZA3A20A
S/N	75eec4ed
Wireless Technology and Frequency Range	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz LTE Band 14: 790.5 MHz ~ 795.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz
Mode	RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM
Remark: 1. The WLAN / Bluetooth module is also integrated into this host, WLAN /Bluetooth power and WLAN SAR testing results which can be referred to Sporton SAR Test Report, Report No.: FA992410-01 (FCC ID: ACJFZA3A). 2. RF exposure chose Battery 1 as the main test, Battery 2 with Scanner and Battery 2 with USB were spot checked the worst case of Battery 1. 3. The device support hand strap accessory, user still can place on human body even the device attached this hand strap, in this report the device was direct connect the phantom at 0mm to consider body SAR testing and it is worst case. So the extremity SAR consideration was not necessary when the device attach hand strap.	

Host Information	
Equipment Name	Tablet Computer
Brand Name	Panasonic
Model Name	FZ-A3
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	WLAN: 802.11a/b/g/n/ac HT20 / HT40 / VHT20 / VHT40 / VHT80 Bluetooth BR/EDR/LE NFC:ASK
EUT Stage	Production Unit



Accessories Information				
Battery 1	Brand Name	Panasonic	Model Name	FZ-VZSUT10U
Battery 2	Brand Name	Panasonic	Model Name	FZ-VZSUT11U
Gadget 1 (USB)	Brand Name	Panasonic	Model Name	N/A
Gadget 2 (Scanner)	Brand Name	Panasonic	Model Name	N/A
Shoulder Strap	Brand Name	Panasonic	Model Name	CF-VNS331U

3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05												
FCC ID			ACJFZA3A20A									
Equipment Name			Radio module									
Operating Frequency Range of each LTE transmission band			LTE Band 2: 1850.7 MHz ~ 1909.3 MHz									
			LTE Band 4: 1710.7 MHz ~ 1754.3 MHz									
			LTE Band 5: 824.7 MHz ~ 848.3 MHz									
			LTE Band 7: 2502.5 MHz ~ 2567.5 MHz									
			LTE Band 12: 699.7 MHz ~ 715.3 MHz									
			LTE Band 13: 779.5 MHz ~ 784.5 MHz									
			LTE Band 14: 790.5 MHz ~ 795.5 MHz									
			LTE Band 26: 814.7 MHz ~ 848.3 MHz									
			LTE Band 41: 2498.5 MHz ~ 2687.5 MHz									
Channel Bandwidth			LTE Band 66: 1710.7 MHz ~ 1779.3 MHz									
			LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 13: 5MHz, 10MHz									
			LTE Band 14: 5MHz, 10MHz									
			LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz									
uplink modulations used			QPSK / 16QAM / 64QAM									
LTE Voice / Data requirements			Data only									
LTE MPR permanently built-in by design			Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3									
			Modulation		Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	
					1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz		
			QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1		
			16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1		
			16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2		
			64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2		
			64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3		
			256 QAM	≥ 1						≤ 5		
LTE A-MPR			In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)									
Spectrum plots for RB configuration			A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.									
Power reduction applied to satisfy SAR compliance			1. Yes, Proximity Sensor.									
Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745




LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 14												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Channel #		Channel #		Freq.(MHz)					
L	23305		790.5		23330		793					
M	23330		793									
H	23355		795.5									
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5		
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5		
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5		
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	39675	2498.5	39700	2501	39725	2503.5	39750		2506			
L	40148	2545.8	40160	2547	40173	2548.3	40185		2549.5			
M	40620	2593	40620	2593	40620	2593	40620		2593			
H	41093	2640.3	41080	2639	41068	2637.8	41055		2636.5			
H	41565	2687.5	41540	2685	41515	2682.5	41490		2680			
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

4. Proximity Sensor Triggering Test

<Proximity Sensor Triggering Distance (KDB 616217 D04 section 6.2)>:

Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed. The details are illustrated in the exhibit “P-Sensor operational description”, and the shortest triggering distances were reported and used for SAR assessment.

In the preliminary triggering distance testing, the tissue-equivalent medium for different frequency bands were used for verification; no other frequency bands tissue-equivalent medium was found to result in shortest triggering distance than that for 1900MHz, and the tissue-equivalent medium for 1900MHz was used for formal proximity sensor triggering testing.



Proximity Sensor Trigger Distance (mm)		
Position	Bottom Face	Edge 1
Minimum	21	22

<Proximity Sensor Triggering Coverage (KDB 616217 D04 section 6.3)>:

If a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. For p-sensor coverage testing, the device is moved and “along the direction of maximum antenna and sensor offset”.


Illustrated in the internal photo exhibit, although the sensor is spatially offset, there is no trigger condition where the antenna is next to the user but the sensor is laterally further away, therefore proximity sensor coverage testing is not required.

This procedure is not required because antenna and sensor are collocated and the peak SAR location is overlapping with the sensor.

<Tablet Tilt angle influences to proximity sensor triggering (KDB 616217 D04 section 6.4)>:

The influence of table tilt angles to proximity sensor triggering was determined by positioning each tablet edge that contains a transmitting antenna, perpendicular to the flat phantom, at 13 mm separation.

Rotating the tablet around the edge next to the phantom in $\leq 10^\circ$ increments until the tablet is $\pm 45^\circ$ from the vertical position at 0° , and the maximum output power remains in the reduced mode.



The Sensor Trigger Distance (mm)	
Position	Edge 1
Minimum	23

Proximity sensor power reduction



Exposure Position / wireless mode	Bottom Face ⁽¹⁾	Edge 1 ⁽¹⁾	Edge 2	Edge 3	Edge 4
WCDMA Band II	8 dB	8 dB	0 dB	0 dB	0 dB
WCDMA Band IV	7.4 dB	7.4 dB	0 dB	0 dB	0 dB
WCDMA Band V	3 dB	3 dB	0 dB	0 dB	0 dB
LTE Band 2	8 dB	8 dB	0 dB	0 dB	0 dB
LTE Band 4	7.4 dB	7.4 dB	0 dB	0 dB	0 dB
LTE Band 5	3 dB	3 dB	0 dB	0 dB	0 dB
LTE Band 7	3 dB	3 dB	0 dB	0 dB	0 dB
LTE Band 12	0.5 dB	0.5 dB	0 dB	0 dB	0 dB
LTE Band 13	3.5 dB	3.5 dB	0 dB	0 dB	0 dB
LTE Band 14	3 dB	3 dB	0 dB	0 dB	0 dB
LTE Band 26	3 dB	3 dB	0 dB	0 dB	0 dB
LTE Band 41	1.5 dB	1.5 dB	0 dB	0 dB	0 dB
LTE Band 66	7.4 dB	7.4 dB	0 dB	0 dB	0 dB



Remark:

- ⁽¹⁾: Reduced maximum limit applied by activation of proximity sensor.
- Power reduction is not applicable for WLAN and Bluetooth.
- Tests were performed in accordance with KDB 616217 D04 section 6.1, 6.2, 6.3, 6.4 and 6.5 and compliant results are shown and described in exhibit "P-Sensor operational description"
- For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed:
 - Bottom Face: [20 mm](#)
 - Edge1: [22 mm](#)

Power Measurement during Sensor Trigger distance testing

Band/Mode	Measured power reduction (dBm)		Reduction Levels
	w/o power back-off	w/ power back-off	(dB)
WCDMA Band II	23.97	15.93	8.04
WCDMA Band IV	23.97	16.59	7.38
WCDMA Band V	23.75	21.00	2.75
LTE Band 2	24.00	15.99	8.01
LTE Band 4	23.99	16.58	7.41
LTE Band 5	23.39	20.60	2.79
LTE Band 7	22.49	19.63	2.86
LTE Band 12	23.53	23.05	0.48
LTE Band 13	23.25	20.14	3.11
LTE Band 14	23.40	20.65	2.75
LTE Band 26	23.48	20.79	2.69
LTE Band 41	22.76	21.37	1.39
LTE Band 66	23.97	16.57	7.40





5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

7.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

7.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

7.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

7.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1107	Mar. 08, 2019	Mar. 07, 2020
SPEAG	835MHz System Validation Kit	D835V2	4d167	Nov. 25, 2019	Nov. 24, 2020
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Mar. 07, 2019	Mar. 06, 2020
SPEAG	1900MHz System Validation Kit	D1900V2	5d185	Mar. 07, 2019	Mar. 06, 2020
SPEAG	2600MHz System Validation Kit	D2600V2	1078	Mar. 06, 2019	Mar. 05, 2020
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 17, 2019	Sep. 16, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 25, 2019	Sep. 24, 2020
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2019	Nov. 11, 2020
RCPTWN	Thermometer	HTC-1	TM560-2	Nov. 12, 2019	Nov. 11, 2020
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 31, 2019	Oct. 30, 2020
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 27, 2019	May. 26, 2020
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Nov. 20, 2019	Nov. 19, 2020
Agilent	ENA Network Analyzer	E5071C	MY46104758	Sep. 06, 2019	Sep. 05, 2020
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 18, 2019	Sep. 17, 2020
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 10, 2019	Sep. 09, 2020
Anritsu	Power Meter	ML2495A	1036004	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Sensor	MA2411B	1027253	Aug. 08, 2019	Aug. 07, 2020
Anritsu	Power Meter	ML2495A	1419002	May. 29, 2019	May. 28, 2020
Anritsu	Power Sensor	MA2411B	1339124	May. 29, 2019	May. 28, 2020
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 27, 2019	Aug. 26, 2020
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 27, 2019	Jun. 26, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 16, 2019	Oct. 15, 2020
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 12, 2019	Aug. 11, 2020
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

10.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	22.2	0.891	40.360	0.89	41.90	0.11	-3.68	±5	2019/12/17
750	22.2	0.903	43.070	0.89	41.90	1.46	2.79	±5	2019/12/18
835	22.2	0.888	42.279	0.90	41.50	-1.33	1.88	±5	2019/12/16
1750	22.4	1.379	40.539	1.37	40.10	0.66	1.09	±5	2019/12/15
1900	22.4	1.457	39.126	1.40	40.00	4.07	-2.19	±5	2019/12/14
2600	22.5	2.022	38.794	1.96	39.00	3.16	-0.53	±5	2019/12/13

10.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2019/12/17	750	250	D750V3-1107	ES3DV3 - SN3270	DAE3 Sn577	2.28	8.32	9.12	9.62
2019/12/18	750	250	D750V3-1107	ES3DV3 - SN3270	DAE3 Sn577	2.15	8.32	8.6	3.37
2019/12/16	835	250	D835V2-4d167	ES3DV3 - SN3270	DAE3 Sn577	2.45	9.55	9.8	2.62
2019/12/15	1750	250	D1750V2-1112	ES3DV3 - SN3270	DAE3 Sn577	9.45	36.70	37.8	3.00
2019/12/14	1900	250	D1900V2-5d185	ES3DV3 - SN3270	DAE3 Sn577	10.30	39.40	41.2	4.57
2019/12/13	2600	250	D2600V2-1078	ES3DV3 - SN3270	DAE3 Sn577	14.20	57.60	56.8	-1.39




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

12. Conducted RF Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<Default Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	23.89	23.97	23.86	24.00	23.84	23.97	23.94	24.00	23.59	23.75	23.63	24.00
3GPP Rel 6	HSDPA Subtest-1	23.19	23.17	23.13	24.00	23.02	23.10	22.95	24.00	22.61	22.61	22.57	24.00
3GPP Rel 6	HSDPA Subtest-2	23.23	23.22	23.11	24.00	23.04	23.14	22.98	24.00	22.59	22.68	22.60	24.00
3GPP Rel 6	HSDPA Subtest-3	22.74	22.71	22.61	23.50	22.42	22.60	22.51	23.50	22.04	22.20	22.07	23.50
3GPP Rel 6	HSDPA Subtest-4	22.69	22.76	22.61	23.50	22.43	22.55	22.48	23.50	22.09	22.25	22.06	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	23.09	23.23	23.09	24.00	23.09	23.05	22.93	24.00	22.56	22.54	22.65	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	23.30	23.22	23.07	24.00	22.98	23.14	23.07	24.00	22.68	22.70	22.69	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.76	22.76	22.51	23.50	22.32	22.70	22.49	23.50	21.96	22.10	21.99	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.76	22.79	22.60	23.50	22.33	22.48	22.57	23.50	22.04	22.18	22.16	23.50
3GPP Rel 6	HSUPA Subtest-1	23.16	23.08	22.98	24.00	22.93	23.14	22.85	24.00	22.55	22.68	22.55	24.00
3GPP Rel 6	HSUPA Subtest-2	21.24	21.24	21.06	22.00	20.89	21.15	20.91	22.00	20.66	20.62	20.41	22.00
3GPP Rel 6	HSUPA Subtest-3	22.13	22.16	22.13	23.00	21.91	22.15	21.84	23.00	21.54	21.68	21.55	23.00
3GPP Rel 6	HSUPA Subtest-4	21.23	21.13	21.17	22.00	20.92	21.11	20.92	22.00	20.56	20.67	20.61	22.00
3GPP Rel 6	HSUPA Subtest-5	23.00	23.10	23.00	24.00	22.90	23.10	22.77	24.00	22.50	22.50	22.40	24.00


<Reduced Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	15.98	15.93	15.89	16.00	16.57	16.59	16.56	16.60	20.91	21.00	20.88	21.00
3GPP Rel 6	HSDPA Subtest-1	15.17	15.16	15.12	16.00	15.57	15.78	15.55	16.60	19.87	19.96	19.85	21.00
3GPP Rel 6	HSDPA Subtest-2	15.25	15.24	15.10	16.00	15.55	15.77	15.60	16.60	19.89	19.98	19.88	21.00
3GPP Rel 6	HSDPA Subtest-3	14.35	14.63	14.58	15.50	15.01	15.16	15.07	16.10	19.32	19.45	19.30	20.50
3GPP Rel 6	HSDPA Subtest-4	14.72	14.67	14.63	15.50	15.04	15.21	15.08	16.10	19.36	19.44	19.32	20.50
3GPP Rel 8	DC-HSDPA Subtest-1	15.17	15.25	15.02	16.00	15.63	15.79	15.65	16.60	19.89	19.86	19.92	21.00
3GPP Rel 8	DC-HSDPA Subtest-2	15.27	15.19	15.15	16.00	15.62	15.79	15.62	16.60	19.85	19.96	19.79	21.00
3GPP Rel 8	DC-HSDPA Subtest-3	14.31	14.69	14.59	15.50	15.07	15.24	14.98	16.10	19.32	19.42	19.23	20.50
3GPP Rel 8	DC-HSDPA Subtest-4	14.78	14.63	14.70	15.50	15.00	15.18	15.04	16.10	19.43	19.50	19.22	20.50
3GPP Rel 6	HSUPA Subtest-1	15.15	15.13	15.10	16.00	15.41	15.61	15.45	16.60	19.83	19.96	19.83	21.00
3GPP Rel 6	HSUPA Subtest-2	13.16	13.03	13.17	14.00	13.42	13.68	13.49	14.60	17.81	17.90	17.82	19.00
3GPP Rel 6	HSUPA Subtest-3	14.28	14.10	14.09	15.00	14.32	14.65	14.36	15.60	18.80	18.98	18.80	20.00
3GPP Rel 6	HSUPA Subtest-4	13.26	13.14	13.06	14.00	13.43	13.58	13.37	14.60	17.89	17.97	17.89	19.00
3GPP Rel 6	HSUPA Subtest-5	14.90	14.90	15.00	16.00	15.45	15.60	15.37	16.60	19.58	19.88	19.68	21.00


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B12 / B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 4 / 5 SAR test was covered by Band 66 / 26; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

<Default Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.60	23.73	24.00	24	0
20	QPSK	1	49	23.51	23.69	23.84		
20	QPSK	1	99	23.53	23.57	23.86		
20	QPSK	50	0	22.65	22.69	23.00	23	1
20	QPSK	50	24	22.62	22.64	22.91		
20	QPSK	50	50	22.55	22.66	22.89		
20	QPSK	100	0	22.57	22.76	22.90	23	1
20	16QAM	1	0	22.92	22.97	22.99		
20	16QAM	1	49	22.81	22.97	22.98		
20	16QAM	1	99	22.78	22.85	22.97	22	2
20	16QAM	50	0	21.67	21.67	21.92		
20	16QAM	50	24	21.60	21.73	21.93		
20	16QAM	50	50	21.53	21.70	21.92	22	2
20	16QAM	100	0	21.58	21.75	21.92		
20	64QAM	1	0	21.79	21.85	21.93		
20	64QAM	1	49	21.75	21.88	21.92	22	2
20	64QAM	1	99	21.65	21.76	21.94		
20	64QAM	50	0	20.67	20.71	21.00		
20	64QAM	50	24	20.64	20.73	20.91	21	3
20	64QAM	50	50	20.54	20.65	20.88		
20	64QAM	100	0	20.63	20.75	20.97		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.58	23.72	23.98	24	0
15	QPSK	1	37	23.47	23.65	23.78		
15	QPSK	1	74	23.44	23.56	23.82		
15	QPSK	36	0	22.59	22.59	22.97	23	1
15	QPSK	36	20	22.54	22.55	22.81		
15	QPSK	36	39	22.54	22.58	22.83		
15	QPSK	75	0	22.55	22.76	22.85	23	1
15	16QAM	1	0	22.92	22.95	22.99		
15	16QAM	1	37	22.81	22.90	22.89		
15	16QAM	1	74	22.72	22.81	22.88	22	2
15	16QAM	36	0	21.61	21.65	21.83		
15	16QAM	36	20	21.50	21.67	21.86		
15	16QAM	36	39	21.50	21.62	21.92	22	2
15	16QAM	75	0	21.53	21.67	21.87		
15	64QAM	1	0	21.79	21.83	21.93		
15	64QAM	1	37	21.75	21.86	21.91	22	2
15	64QAM	1	74	21.58	21.73	21.88		
15	64QAM	36	0	20.67	20.68	20.92		
15	64QAM	36	20	20.64	20.67	20.83	21	3
15	64QAM	36	39	20.46	20.56	20.86		
15	64QAM	75	0	20.63	20.68	20.87		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.58	23.71	23.99	24	0
10	QPSK	1	25	23.41	23.59	23.74		
10	QPSK	1	49	23.48	23.50	23.85		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	0	22.61	22.61	22.95	23	1
10	QPSK	25	12	22.56	22.58	22.85		
10	QPSK	25	25	22.53	22.61	22.89		
10	QPSK	50	0	22.57	22.72	22.85		
10	16QAM	1	0	22.82	22.89	22.99	23	1
10	16QAM	1	25	22.74	22.96	22.89		
10	16QAM	1	49	22.78	22.78	22.96		
10	16QAM	25	0	21.62	21.65	21.85	22	2
10	16QAM	25	12	21.51	21.72	21.90		
10	16QAM	25	25	21.49	21.70	21.89		
10	16QAM	50	0	21.48	21.67	21.86		
10	64QAM	1	0	21.77	21.78	21.93	22	2
10	64QAM	1	25	21.70	21.85	21.88		
10	64QAM	1	49	21.61	21.71	21.86		
10	64QAM	25	0	20.57	20.63	20.99	21	3
10	64QAM	25	12	20.64	20.72	20.91		
10	64QAM	25	25	20.47	20.61	20.79		
10	64QAM	50	0	20.59	20.70	20.95		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.56	23.68	23.98	24	0
5	QPSK	1	12	23.43	23.69	23.79		
5	QPSK	1	24	23.44	23.51	23.79		
5	QPSK	12	0	22.63	22.61	22.90	23	1
5	QPSK	12	7	22.55	22.54	22.83		
5	QPSK	12	13	22.48	22.61	22.85		
5	QPSK	25	0	22.49	22.67	22.89		
5	16QAM	1	0	22.92	22.97	22.99	23	1
5	16QAM	1	12	22.74	22.89	22.96		
5	16QAM	1	24	22.76	22.81	22.97		
5	16QAM	12	0	21.62	21.64	21.91	22	2
5	16QAM	12	7	21.57	21.68	21.85		
5	16QAM	12	13	21.43	21.70	21.90		
5	16QAM	25	0	21.58	21.69	21.85		
5	64QAM	1	0	21.74	21.82	21.84	22	2
5	64QAM	1	12	21.65	21.83	21.83		
5	64QAM	1	24	21.57	21.68	21.93		
5	64QAM	12	0	20.59	20.63	20.94	21	3
5	64QAM	12	7	20.64	20.71	20.85		
5	64QAM	12	13	20.45	20.57	20.84		
5	64QAM	25	0	20.62	20.68	20.97		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.53	23.64	23.91	24	0
3	QPSK	1	8	23.48	23.64	23.80		
3	QPSK	1	14	23.46	23.49	23.85		
3	QPSK	8	0	22.58	22.63	22.96	23	1
3	QPSK	8	4	22.57	22.56	22.83		
3	QPSK	8	7	22.48	22.66	22.80		
3	QPSK	15	0	22.55	22.67	22.81		
3	16QAM	1	0	22.83	22.87	22.92	23	1
3	16QAM	1	8	22.81	22.95	22.97		
3	16QAM	1	14	22.69	22.77	22.93		
3	16QAM	8	0	21.63	21.59	21.82	22	2
3	16QAM	8	4	21.57	21.67	21.92		
3	16QAM	8	7	21.43	21.62	21.86		



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	16QAM	15	0	21.56	21.72	21.87		
3	64QAM	1	0	21.76	21.85	21.91	22	2
3	64QAM	1	8	21.71	21.84	21.92		
3	64QAM	1	14	21.63	21.69	21.86		
3	64QAM	8	0	20.59	20.63	20.93	21	3
3	64QAM	8	4	20.63	20.73	20.87		
3	64QAM	8	7	20.44	20.57	20.80		
3	64QAM	15	0	20.54	20.66	20.88		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.49	23.55	23.64	24	0
1.4	QPSK	1	3	23.59	23.65	23.64		
1.4	QPSK	1	5	23.52	23.56	23.62		
1.4	QPSK	3	0	23.52	23.62	23.66		
1.4	QPSK	3	1	23.58	23.67	23.66		
1.4	QPSK	3	3	23.47	23.68	23.70		
1.4	QPSK	6	0	22.51	22.59	22.67	23	1
1.4	16QAM	1	0	22.73	22.92	22.88	23	1
1.4	16QAM	1	3	22.77	22.96	22.90		
1.4	16QAM	1	5	22.71	22.90	22.90		
1.4	16QAM	3	0	22.57	22.65	22.64		
1.4	16QAM	3	1	22.57	22.66	22.69		
1.4	16QAM	3	3	22.56	22.61	22.71		
1.4	16QAM	6	0	21.59	21.69	21.76	22	2
1.4	64QAM	1	0	21.73	21.69	21.84	22	2
1.4	64QAM	1	3	21.71	21.82	21.91		
1.4	64QAM	1	5	21.65	21.76	21.82		
1.4	64QAM	3	0	21.60	21.78	21.79		
1.4	64QAM	3	1	21.69	21.81	21.82		
1.4	64QAM	3	3	21.60	21.72	21.77		
1.4	64QAM	6	0	20.54	20.59	20.66	21	3



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	23.89	23.99	23.98		
20	QPSK	1	49	23.75	23.87	23.71	24	0
20	QPSK	1	99	23.78	23.87	23.67		
20	QPSK	50	0	22.87	23.00	22.97		
20	QPSK	50	24	22.86	22.96	22.83	23	1
20	QPSK	50	50	22.90	22.92	22.78		
20	QPSK	100	0	22.91	22.96	22.87		
20	16QAM	1	0	22.88	22.97	22.97	23	1
20	16QAM	1	49	22.75	22.87	22.83		
20	16QAM	1	99	22.75	22.89	22.95		
20	16QAM	50	0	21.87	21.94	22.00	22	2
20	16QAM	50	24	21.93	22.00	21.86		
20	16QAM	50	50	21.84	21.93	21.79		
20	16QAM	100	0	21.88	22.00	21.85	22	2
20	64QAM	1	0	21.98	22.00	21.97		
20	64QAM	1	49	21.97	21.99	21.86		
20	64QAM	1	99	21.94	21.95	21.87	21	3
20	64QAM	50	0	20.87	20.97	21.00		
20	64QAM	50	24	20.91	20.99	20.88		
20	64QAM	50	50	20.87	20.95	20.82	21	3
20	64QAM	100	0	20.91	20.93	20.82		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	23.82	23.98	23.94		
15	QPSK	1	37	23.68	23.86	23.70	24	0
15	QPSK	1	74	23.73	23.81	23.57		
15	QPSK	36	0	22.80	22.90	22.94	23	1
15	QPSK	36	20	22.83	22.95	22.80		
15	QPSK	36	39	22.86	22.89	22.75		
15	QPSK	75	0	22.90	22.94	22.85	23	1
15	16QAM	1	0	22.87	22.89	22.96		
15	16QAM	1	37	22.68	22.87	22.73		
15	16QAM	1	74	22.69	22.83	22.91	22	2
15	16QAM	36	0	21.78	21.90	21.91		
15	16QAM	36	20	21.90	21.91	21.85		
15	16QAM	36	39	21.74	21.93	21.79	22	2
15	16QAM	75	0	21.85	21.97	21.83		
15	64QAM	1	0	21.96	22.00	21.87		
15	64QAM	1	37	21.92	21.94	21.84	22	2
15	64QAM	1	74	21.93	21.88	21.80		
15	64QAM	36	0	20.84	20.91	20.99		
15	64QAM	36	20	20.90	20.92	20.81	21	3
15	64QAM	36	39	20.77	20.89	20.74		
15	64QAM	75	0	20.90	20.84	20.77		
Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	23.89	23.92	23.94		
10	QPSK	1	25	23.67	23.86	23.71	24	0
10	QPSK	1	49	23.73	23.78	23.59		
10	QPSK	25	0	22.77	22.95	22.90	23	1
10	QPSK	25	12	22.79	22.88	22.81		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	22.80	22.90	22.76		
10	QPSK	50	0	22.84	22.93	22.82		
10	16QAM	1	0	22.80	22.88	22.90		
10	16QAM	1	25	22.67	22.86	22.81	23	1
10	16QAM	1	49	22.69	22.87	22.89		
10	16QAM	25	0	21.80	21.93	21.92		
10	16QAM	25	12	21.92	21.91	21.85	22	2
10	16QAM	25	25	21.74	21.87	21.77		
10	16QAM	50	0	21.81	21.91	21.81		
10	64QAM	1	0	21.97	21.91	21.93	22	2
10	64QAM	1	25	21.89	21.98	21.81		
10	64QAM	1	49	21.87	21.85	21.85		
10	64QAM	25	0	20.77	20.92	20.91	21	3
10	64QAM	25	12	20.85	20.97	20.87		
10	64QAM	25	25	20.86	20.91	20.82		
10	64QAM	50	0	20.82	20.89	20.75		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	23.85	23.93	23.97	24	0
5	QPSK	1	12	23.74	23.87	23.65		
5	QPSK	1	24	23.72	23.79	23.58		
5	QPSK	12	0	22.85	22.96	22.92	23	1
5	QPSK	12	7	22.83	22.89	22.75		
5	QPSK	12	13	22.86	22.83	22.70		
5	QPSK	25	0	22.90	22.91	22.84	23	1
5	16QAM	1	0	22.85	22.87	22.96		
5	16QAM	1	12	22.70	22.80	22.73		
5	16QAM	1	24	22.71	22.81	22.94	22	2
5	16QAM	12	0	21.80	21.94	21.97		
5	16QAM	12	7	21.85	21.94	21.82		
5	16QAM	12	13	21.78	21.88	21.72	22	2
5	16QAM	25	0	21.85	21.90	21.79		
5	64QAM	1	0	21.90	22.00	21.89		
5	64QAM	1	12	21.92	21.97	21.83	22	2
5	64QAM	1	24	21.86	21.86	21.81		
5	64QAM	12	0	20.86	20.92	21.00		
5	64QAM	12	7	20.84	20.99	20.88	21	3
5	64QAM	12	13	20.87	20.87	20.74		
5	64QAM	25	0	20.88	20.90	20.80		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	23.81	23.95	23.97	24	0
3	QPSK	1	8	23.68	23.82	23.65		
3	QPSK	1	14	23.68	23.79	23.66		
3	QPSK	8	0	22.85	22.99	22.92	23	1
3	QPSK	8	4	22.83	22.93	22.73		
3	QPSK	8	7	22.81	22.88	22.78		
3	QPSK	15	0	22.84	22.94	22.84	23	1
3	16QAM	1	0	22.82	22.88	22.93		
3	16QAM	1	8	22.74	22.85	22.75		
3	16QAM	1	14	22.70	22.83	22.87	22	2
3	16QAM	8	0	21.78	21.90	21.90		
3	16QAM	8	4	21.84	21.90	21.82		
3	16QAM	8	7	21.84	21.88	21.71	22	2
3	16QAM	15	0	21.79	21.95	21.78		
3	64QAM	1	0	21.94	21.98	21.87	22	2



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	64QAM	1	8	21.91	21.99	21.86	21	3
3	64QAM	1	14	21.94	21.87	21.81		
3	64QAM	8	0	20.80	20.91	20.98		
3	64QAM	8	4	20.90	20.96	20.82		
3	64QAM	8	7	20.84	20.92	20.74		
3	64QAM	15	0	20.87	20.90	20.74		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	23.60	23.77	23.59	24	0
1.4	QPSK	1	3	23.67	23.82	23.65		
1.4	QPSK	1	5	23.60	23.76	23.61		
1.4	QPSK	3	0	23.64	23.78	23.69		
1.4	QPSK	3	1	23.73	23.82	23.75		
1.4	QPSK	3	3	23.66	23.80	23.62		
1.4	QPSK	6	0	22.68	22.85	22.64	23	1
1.4	16QAM	1	0	22.88	22.88	22.83	23	1
1.4	16QAM	1	3	22.91	22.92	22.92		
1.4	16QAM	1	5	22.83	22.84	22.84		
1.4	16QAM	3	0	22.67	22.81	22.67		
1.4	16QAM	3	1	22.71	22.82	22.75		
1.4	16QAM	3	3	22.68	22.80	22.63		
1.4	16QAM	6	0	21.70	21.86	21.75	22	2
1.4	64QAM	1	0	21.81	21.96	21.78	22	2
1.4	64QAM	1	3	21.93	21.99	21.82		
1.4	64QAM	1	5	21.78	21.93	21.84		
1.4	64QAM	3	0	21.78	21.88	21.73		
1.4	64QAM	3	1	21.80	21.92	21.84		
1.4	64QAM	3	3	21.81	21.89	21.70		
1.4	64QAM	6	0	20.70	20.78	20.69	21	3



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	23.30	23.39	23.27	24	0
10	QPSK	1	25	23.21	23.37	23.19		
10	QPSK	1	49	23.17	23.22	23.16		
10	QPSK	25	0	22.24	22.43	22.26	23	1
10	QPSK	25	12	22.32	22.41	22.22		
10	QPSK	25	25	22.24	22.22	22.27		
10	QPSK	50	0	22.27	22.40	22.18	23	1
10	16QAM	1	0	22.56	22.66	22.55		
10	16QAM	1	25	22.53	22.60	22.38		
10	16QAM	1	49	22.51	22.46	22.42	22	2
10	16QAM	25	0	21.23	21.42	21.26		
10	16QAM	25	12	21.27	21.47	21.25		
10	16QAM	25	25	21.27	21.24	21.27	22	2
10	16QAM	50	0	21.30	21.40	21.19		
10	64QAM	1	0	21.39	21.59	21.52		
10	64QAM	1	25	21.45	21.59	21.40	22	2
10	64QAM	1	49	21.33	21.45	21.35		
10	64QAM	25	0	20.23	20.44	20.26		
10	64QAM	25	12	20.36	20.46	20.26	21	3
10	64QAM	25	25	20.25	20.27	20.29		
10	64QAM	50	0	20.31	20.40	20.23		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	23.28	23.38	23.20	24	0
5	QPSK	1	12	23.22	23.32	23.22		
5	QPSK	1	24	23.37	23.32	23.15		
5	QPSK	12	0	22.29	22.34	22.28	23	1
5	QPSK	12	7	22.29	22.36	22.28		
5	QPSK	12	13	22.36	22.37	22.21		
5	QPSK	25	0	22.27	22.30	22.26	23	1
5	16QAM	1	0	22.60	22.81	22.41		
5	16QAM	1	12	22.53	22.68	22.46		
5	16QAM	1	24	22.63	22.51	22.41	22	2
5	16QAM	12	0	21.32	21.41	21.29		
5	16QAM	12	7	21.29	21.42	21.27		
5	16QAM	12	13	21.34	21.36	21.23	22	2
5	16QAM	25	0	21.27	21.37	21.28		
5	64QAM	1	0	21.50	21.61	21.38		
5	64QAM	1	12	21.41	21.54	21.34	22	2
5	64QAM	1	24	21.51	21.57	21.31		
5	64QAM	12	0	20.33	20.37	20.31		
5	64QAM	12	7	20.36	20.41	20.30	21	3
5	64QAM	12	13	20.42	20.35	20.28		
5	64QAM	25	0	20.30	20.39	20.28		
Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	23.31	23.37	23.17	24	0
3	QPSK	1	8	23.29	23.36	23.29		
3	QPSK	1	14	23.25	23.34	23.25		
3	QPSK	8	0	22.27	22.36	22.22	23	1
3	QPSK	8	4	22.26	22.36	22.23		



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	QPSK	8	7	22.25	22.37	22.23		
3	QPSK	15	0	22.28	22.37	22.25		
3	16QAM	1	0	22.52	22.63	22.44		
3	16QAM	1	8	22.68	22.59	22.52	23	1
3	16QAM	1	14	22.49	22.60	22.51		
3	16QAM	8	0	21.26	21.36	21.23		
3	16QAM	8	4	21.27	21.38	21.21	22	2
3	16QAM	8	7	21.27	21.37	21.23		
3	16QAM	15	0	21.41	21.46	21.32		
3	64QAM	1	0	21.53	21.62	21.36	22	2
3	64QAM	1	8	21.60	21.57	21.44		
3	64QAM	1	14	21.43	21.57	21.38		
3	64QAM	8	0	20.31	20.40	20.26	21	3
3	64QAM	8	4	20.33	20.37	20.29		
3	64QAM	8	7	20.32	20.35	20.28		
3	64QAM	15	0	20.39	20.44	20.29		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	23.13	23.26	23.09	24	0
1.4	QPSK	1	3	23.18	23.31	23.16		
1.4	QPSK	1	5	23.16	23.23	23.13		
1.4	QPSK	3	0	23.21	23.31	23.15		
1.4	QPSK	3	1	23.29	23.33	23.21		
1.4	QPSK	3	3	23.23	23.29	23.12		
1.4	QPSK	6	0	22.21	22.26	22.12	23	1
1.4	16QAM	1	0	22.45	22.45	22.35	23	1
1.4	16QAM	1	3	22.49	22.53	22.40		
1.4	16QAM	1	5	22.33	22.65	22.43		
1.4	16QAM	3	0	22.21	22.34	22.21		
1.4	16QAM	3	1	22.23	22.38	22.18		
1.4	16QAM	3	3	22.20	22.27	22.11		
1.4	16QAM	6	0	21.25	21.34	21.24	22	2
1.4	64QAM	1	0	21.45	21.49	21.36	22	2
1.4	64QAM	1	3	21.46	21.55	21.44		
1.4	64QAM	1	5	21.36	21.47	21.40		
1.4	64QAM	3	0	21.37	21.42	21.26		
1.4	64QAM	3	1	21.37	21.50	21.34		
1.4	64QAM	3	3	21.33	21.44	21.29		
1.4	64QAM	6	0	20.21	20.25	20.12	21	3



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	22.49	22.48	22.32	23	0
20	QPSK	1	49	22.30	22.13	22.17		
20	QPSK	1	99	22.30	22.15	22.15		
20	QPSK	50	0	21.40	21.37	21.33	22	1
20	QPSK	50	24	21.36	21.19	21.28		
20	QPSK	50	50	21.30	21.17	21.18		
20	QPSK	100	0	21.40	21.32	21.26	22	1
20	16QAM	1	0	21.81	21.80	21.58		
20	16QAM	1	49	21.54	21.57	21.53		
20	16QAM	1	99	21.60	21.50	21.47	21	2
20	16QAM	50	0	20.47	20.44	20.36		
20	16QAM	50	24	20.38	20.24	20.28		
20	16QAM	50	50	20.28	20.19	20.21	21	2
20	16QAM	100	0	20.30	20.29	20.28		
20	64QAM	1	0	20.64	20.74	20.48		
20	64QAM	1	49	20.47	20.40	20.42	21	2
20	64QAM	1	99	20.55	20.36	20.39		
20	64QAM	50	0	19.47	19.43	19.35		
20	64QAM	50	24	19.39	19.24	19.32	20	3
20	64QAM	50	50	19.33	19.17	19.20		
20	64QAM	100	0	19.38	19.32	19.27		
Channel				20825	21100	21375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.46	22.44	22.35	23	0
15	QPSK	1	37	22.29	22.16	22.20		
15	QPSK	1	74	22.27	22.18	22.17		
15	QPSK	36	0	21.38	21.37	21.33	22	1
15	QPSK	36	20	21.39	21.21	21.29		
15	QPSK	36	39	21.32	21.13	21.22		
15	QPSK	75	0	21.35	21.17	21.24	22	1
15	16QAM	1	0	21.71	21.74	21.57		
15	16QAM	1	37	21.61	21.35	21.44		
15	16QAM	1	74	21.59	21.50	21.49	21	2
15	16QAM	36	0	20.45	20.42	20.29		
15	16QAM	36	20	20.41	20.22	20.29		
15	16QAM	36	39	20.33	20.14	20.24	21	2
15	16QAM	75	0	20.38	20.22	20.28		
15	64QAM	1	0	20.71	20.66	20.50		
15	64QAM	1	37	20.51	20.31	20.40	21	2
15	64QAM	1	74	20.43	20.35	20.38		
15	64QAM	36	0	19.45	19.40	19.36		
15	64QAM	36	20	19.39	19.26	19.30	20	3
15	64QAM	36	39	19.36	19.16	19.22		
15	64QAM	75	0	19.33	19.21	19.28		
Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	22.41	22.42	22.34	23	0
10	QPSK	1	25	22.35	22.16	22.25		
10	QPSK	1	49	22.31	22.10	22.22		
10	QPSK	25	0	21.40	21.26	21.32	22	1
10	QPSK	25	12	21.40	21.24	21.34		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	21.34	21.17	21.27		
10	QPSK	50	0	21.37	21.21	21.29		
10	16QAM	1	0	21.75	21.61	21.58		
10	16QAM	1	25	21.70	21.48	21.50	22	1
10	16QAM	1	49	21.56	21.41	21.57		
10	16QAM	25	0	20.43	20.24	20.34		
10	16QAM	25	12	20.39	20.26	20.30	21	2
10	16QAM	25	25	20.36	20.16	20.30		
10	16QAM	50	0	20.41	20.25	20.31		
10	64QAM	1	0	20.68	20.64	20.53	21	2
10	64QAM	1	25	20.52	20.47	20.55		
10	64QAM	1	49	20.55	20.28	20.44		
10	64QAM	25	0	19.45	19.29	19.34	20	3
10	64QAM	25	12	19.42	19.25	19.33		
10	64QAM	25	25	19.36	19.16	19.28		
10	64QAM	50	0	19.42	19.24	19.32		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.44	22.21	22.24	23	0
5	QPSK	1	12	22.43	22.16	22.21		
5	QPSK	1	24	22.38	22.12	22.23		
5	QPSK	12	0	21.47	21.22	21.29	22	1
5	QPSK	12	7	21.50	21.26	21.31		
5	QPSK	12	13	21.42	21.16	21.26		
5	QPSK	25	0	21.44	21.20	21.28		
5	16QAM	1	0	21.78	21.44	21.52	22	1
5	16QAM	1	12	21.79	21.52	21.59		
5	16QAM	1	24	21.67	21.34	21.43		
5	16QAM	12	0	20.40	20.26	20.34	21	2
5	16QAM	12	7	20.49	20.28	20.33		
5	16QAM	12	13	20.38	20.19	20.28		
5	16QAM	25	0	20.33	20.20	20.30		
5	64QAM	1	0	20.46	20.40	20.46	21	2
5	64QAM	1	12	20.54	20.46	20.40		
5	64QAM	1	24	20.49	20.28	20.41		
5	64QAM	12	0	19.43	19.25	19.37	20	3
5	64QAM	12	7	19.43	19.28	19.36		
5	64QAM	12	13	19.38	19.22	19.29		
5	64QAM	25	0	19.46	19.22	19.31		



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	24	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.33	23.53	23.51		
10	QPSK	1	25	23.35	23.41	23.42	23	1
10	QPSK	1	49	23.38	23.32	23.47		
10	QPSK	25	0	22.45	22.50	22.47		
10	QPSK	25	12	22.40	22.46	22.40	23	1
10	QPSK	25	25	22.39	22.37	22.32		
10	QPSK	50	0	22.41	22.42	22.33		
10	16QAM	1	0	22.62	22.63	22.72	23	1
10	16QAM	1	25	22.51	22.67	22.66		
10	16QAM	1	49	22.55	22.55	22.61		
10	16QAM	25	0	21.56	21.38	21.50	22	2
10	16QAM	25	12	21.49	21.50	21.42		
10	16QAM	25	25	21.36	21.41	21.40		
10	16QAM	50	0	21.43	21.46	21.44	22	2
10	64QAM	1	0	21.62	21.60	21.63		
10	64QAM	1	25	21.57	21.67	21.51		
10	64QAM	1	49	21.54	21.53	21.58	21	3
10	64QAM	25	0	20.50	20.41	20.47		
10	64QAM	25	12	20.46	20.49	20.43		
10	64QAM	25	25	20.38	20.44	20.32	21	3
10	64QAM	50	0	20.49	20.47	20.46		
Channel				23035	23095	23155	24	0
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.44	23.35	23.41		
5	QPSK	1	12	23.39	23.36	23.23	23	1
5	QPSK	1	24	23.32	23.31	23.35		
5	QPSK	12	0	22.45	22.42	22.42		
5	QPSK	12	7	22.47	22.47	22.40	23	1
5	QPSK	12	13	22.39	22.40	22.43		
5	QPSK	25	0	22.37	22.47	22.32		
5	16QAM	1	0	22.60	22.63	22.64	23	1
5	16QAM	1	12	22.54	22.56	22.51		
5	16QAM	1	24	22.48	22.52	22.46		
5	16QAM	12	0	21.51	21.46	21.40	22	2
5	16QAM	12	7	21.49	21.48	21.41		
5	16QAM	12	13	21.40	21.37	21.46		
5	16QAM	25	0	21.46	21.42	21.39	22	2
5	64QAM	1	0	21.55	21.58	21.58		
5	64QAM	1	12	21.59	21.65	21.47		
5	64QAM	1	24	21.43	21.49	21.50	21	3
5	64QAM	12	0	20.47	20.48	20.44		
5	64QAM	12	7	20.46	20.53	20.40		
5	64QAM	12	13	20.41	20.46	20.51	21	3
5	64QAM	25	0	20.39	20.45	20.39		
Channel				23025	23095	23165	24	0
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.44	23.31	23.36		
3	QPSK	1	8	23.51	23.46	23.42	23	1
3	QPSK	1	14	23.35	23.25	23.28		
3	QPSK	8	0	22.43	22.40	22.45		
3	QPSK	8	4	22.41	22.37	22.46	23	1



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	QPSK	8	7	22.44	22.41	22.41		
3	QPSK	15	0	22.36	22.40	22.28		
3	16QAM	1	0	22.53	22.60	22.46		
3	16QAM	1	8	22.60	22.70	22.65	23	1
3	16QAM	1	14	22.56	22.51	22.54		
3	16QAM	8	0	21.54	21.35	21.45		
3	16QAM	8	4	21.43	21.41	21.49	22	2
3	16QAM	8	7	21.50	21.39	21.50		
3	16QAM	15	0	21.44	21.52	21.41		
3	64QAM	1	0	21.68	21.47	21.46	22	2
3	64QAM	1	8	21.70	21.64	21.71		
3	64QAM	1	14	21.65	21.52	21.49		
3	64QAM	8	0	20.41	20.48	20.47	21	3
3	64QAM	8	4	20.41	20.46	20.47		
3	64QAM	8	7	20.47	20.49	20.45		
3	64QAM	15	0	20.45	20.51	20.36		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.22	23.29	23.35	24	0
1.4	QPSK	1	3	23.25	23.33	23.28		
1.4	QPSK	1	5	23.20	23.25	23.26		
1.4	QPSK	3	0	23.34	23.31	23.41		
1.4	QPSK	3	1	23.44	23.37	23.39		
1.4	QPSK	3	3	23.42	23.31	23.37		
1.4	QPSK	6	0	22.34	22.38	22.36	23	1
1.4	16QAM	1	0	22.45	22.49	22.52	23	1
1.4	16QAM	1	3	22.43	22.58	22.52		
1.4	16QAM	1	5	22.54	22.48	22.54		
1.4	16QAM	3	0	22.40	22.39	22.34		
1.4	16QAM	3	1	22.33	22.44	22.38		
1.4	16QAM	3	3	22.30	22.31	22.34		
1.4	16QAM	6	0	21.40	21.44	21.45	22	2
1.4	64QAM	1	0	21.54	21.52	21.64	22	2
1.4	64QAM	1	3	21.56	21.60	21.55		
1.4	64QAM	1	5	21.52	21.52	21.55		
1.4	64QAM	3	0	21.44	21.49	21.48		
1.4	64QAM	3	1	21.47	21.52	21.57		
1.4	64QAM	3	3	21.41	21.42	21.46		
1.4	64QAM	6	0	20.38	20.40	20.38	21	3

<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0		23.25		24	0
10	QPSK	1	25		23.16			
10	QPSK	1	49		23.05			
10	QPSK	25	0		22.30		23	1
10	QPSK	25	12		22.21			
10	QPSK	25	25		22.21			
10	QPSK	50	0		22.25		23	1
10	16QAM	1	0		22.55			
10	16QAM	1	25		22.54			
10	16QAM	1	49		22.41		22	2
10	16QAM	25	0		21.42			
10	16QAM	25	12		21.27			
10	16QAM	25	25		21.20		22	2
10	16QAM	50	0		21.28			
10	64QAM	1	0		21.45			
10	64QAM	1	25		21.38		22	2
10	64QAM	1	49		21.26			
10	64QAM	25	0		20.38			
10	64QAM	25	12		20.30		21	3
10	64QAM	25	25		20.21			
10	64QAM	50	0		20.26			
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	23.17	23.24	23.17	24	0
5	QPSK	1	12	23.24	23.12	23.18		
5	QPSK	1	24	23.22	23.13	23.10		
5	QPSK	12	0	22.25	22.36	22.17	23	1
5	QPSK	12	7	22.34	22.24	22.21		
5	QPSK	12	13	22.34	22.17	22.15		
5	QPSK	25	0	22.27	22.17	22.21	23	1
5	16QAM	1	0	22.52	22.59	22.47		
5	16QAM	1	12	22.51	22.49	22.38		
5	16QAM	1	24	22.55	22.37	22.40	22	2
5	16QAM	12	0	21.25	21.35	21.24		
5	16QAM	12	7	21.38	21.27	21.22		
5	16QAM	12	13	21.31	21.16	21.16	22	2
5	16QAM	25	0	21.34	21.22	21.21		
5	64QAM	1	0	21.43	21.53	21.44		
5	64QAM	1	12	21.46	21.38	21.38	22	2
5	64QAM	1	24	21.48	21.25	21.30		
5	64QAM	12	0	20.29	20.39	20.27		
5	64QAM	12	7	20.35	20.28	20.26	21	3
5	64QAM	12	13	20.32	20.26	20.20		
5	64QAM	25	0	20.30	20.26	20.21		

<LTE Band 14>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23330				
Frequency (MHz)				793				
10	QPSK	1	0		23.40		24	0
10	QPSK	1	25		23.29			
10	QPSK	1	49		23.26			
10	QPSK	25	0		22.34		23	1
10	QPSK	25	12		22.33			
10	QPSK	25	25		22.33			
10	QPSK	50	0		22.27		23	1
10	16QAM	1	0		22.50			
10	16QAM	1	25		22.46			
10	16QAM	1	49		22.42		22	2
10	16QAM	25	0		21.33			
10	16QAM	25	12		21.35			
10	16QAM	25	25		21.32		22	2
10	16QAM	50	0		21.31			
10	64QAM	1	0		21.51			
10	64QAM	1	25		21.45		22	2
10	64QAM	1	49		21.42			
10	64QAM	25	0		20.38			
10	64QAM	25	12		20.34		21	3
10	64QAM	25	25		20.37			
10	64QAM	50	0		20.35			
Channel				23305	23330	23355	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				790.5	793	795.5		
5	QPSK	1	0	23.39	23.28	23.27	24	0
5	QPSK	1	12	23.25	23.21	23.29		
5	QPSK	1	24	23.24	23.20	23.25		
5	QPSK	12	0	22.35	22.27	22.26	23	1
5	QPSK	12	7	22.31	22.30	22.34		
5	QPSK	12	13	22.27	22.19	22.30		
5	QPSK	25	0	22.30	22.27	22.32	23	1
5	16QAM	1	0	22.53	22.44	22.47		
5	16QAM	1	12	22.54	22.47	22.51		
5	16QAM	1	24	22.45	22.41	22.45	22	2
5	16QAM	12	0	21.36	21.29	21.25		
5	16QAM	12	7	21.36	21.32	21.36		
5	16QAM	12	13	21.27	21.21	21.30	22	2
5	16QAM	25	0	21.35	21.26	21.31		
5	64QAM	1	0	21.49	21.42	21.42		
5	64QAM	1	12	21.50	21.34	21.40	22	2
5	64QAM	1	24	21.41	21.41	21.40		
5	64QAM	12	0	20.38	20.32	20.29		
5	64QAM	12	7	20.39	20.31	20.40	21	3
5	64QAM	12	13	20.30	20.27	20.32		
5	64QAM	25	0	20.31	20.26	20.34		



<LTE Band 26>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26765	26865	26965	24	0
Frequency (MHz)				821.5	831.5	841.5		
15	QPSK	1	0	23.27	23.48	23.42		
15	QPSK	1	37	23.14	23.38	23.31	23	1
15	QPSK	1	74	23.19	23.31	23.19		
15	QPSK	36	0	22.23	22.53	22.39		
15	QPSK	36	20	22.22	22.48	22.38	23	1
15	QPSK	36	39	22.17	22.39	22.21		
15	QPSK	75	0	22.19	22.48	22.37		
15	16QAM	1	0	22.63	22.71	22.74	23	1
15	16QAM	1	37	22.43	22.69	22.55		
15	16QAM	1	74	22.45	22.53	22.44		
15	16QAM	36	0	21.27	21.46	21.45	22	2
15	16QAM	36	20	21.22	21.55	21.41		
15	16QAM	36	39	21.18	21.43	21.21		
15	16QAM	75	0	21.16	21.50	21.35	22	2
15	64QAM	1	0	21.53	21.63	21.69		
15	64QAM	1	37	21.36	21.71	21.61		
15	64QAM	1	74	21.41	21.59	21.39	21	3
15	64QAM	36	0	20.28	20.47	20.44		
15	64QAM	36	20	20.22	20.56	20.41		
15	64QAM	36	39	20.23	20.43	20.26	21	3
15	64QAM	75	0	20.19	20.49	20.35		
Channel				26740	26865	26990	24	0
Frequency (MHz)				819	831.5	844		
10	QPSK	1	0	23.35	23.47	23.36		
10	QPSK	1	25	23.25	23.44	23.14	23	1
10	QPSK	1	49	23.26	23.32	23.22		
10	QPSK	25	0	22.29	22.52	22.33		
10	QPSK	25	12	22.30	22.49	22.26	23	1
10	QPSK	25	25	22.21	22.42	22.18		
10	QPSK	50	0	22.26	22.47	22.31		
10	16QAM	1	0	22.50	22.67	22.57	23	1
10	16QAM	1	25	22.59	22.72	22.43		
10	16QAM	1	49	22.49	22.66	22.50		
10	16QAM	25	0	21.31	21.50	21.34	22	2
10	16QAM	25	12	21.28	21.47	21.24		
10	16QAM	25	25	21.23	21.42	21.19		
10	16QAM	50	0	21.29	21.47	21.29	22	2
10	64QAM	1	0	21.62	21.64	21.54		
10	64QAM	1	25	21.40	21.54	21.34		
10	64QAM	1	49	21.51	21.54	21.40	21	3
10	64QAM	25	0	20.33	20.50	20.36		
10	64QAM	25	12	20.31	20.50	20.30		
10	64QAM	25	25	20.23	20.40	20.20	21	3
10	64QAM	50	0	20.27	20.45	20.34		
Channel				26715	26865	27015	24	0
Frequency (MHz)				816.5	831.5	846.5		
5	QPSK	1	0	23.29	23.41	23.21		
5	QPSK	1	12	23.21	23.38	23.11	24	0
5	QPSK	1	24	23.19	23.36	23.19		
5	QPSK	12	0	22.29	22.43	22.18	23	1
5	QPSK	12	7	22.32	22.47	22.17		



FCC SAR TEST REPORT

Report No. : FA992410-02A

5	QPSK	12	13	22.25	22.41	22.24		
5	QPSK	25	0	22.27	22.43	22.17		
5	16QAM	1	0	22.58	22.65	22.41		
5	16QAM	1	12	22.50	22.66	22.45	23	1
5	16QAM	1	24	22.48	22.58	22.46		
5	16QAM	12	0	21.35	21.51	21.19		
5	16QAM	12	7	21.32	21.44	21.22	22	2
5	16QAM	12	13	21.31	21.47	21.25		
5	16QAM	25	0	21.29	21.48	21.17		
5	64QAM	1	0	21.53	21.61	21.33	22	2
5	64QAM	1	12	21.36	21.61	21.34		
5	64QAM	1	24	21.35	21.53	21.36		
5	64QAM	12	0	20.33	20.50	20.23	21	3
5	64QAM	12	7	20.34	20.49	20.25		
5	64QAM	12	13	20.26	20.48	20.30		
5	64QAM	25	0	20.29	20.47	20.15		
Channel				26705	26865	27025	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				815.5	831.5	847.5		
3	QPSK	1	0	23.28	23.39	23.15	24	0
3	QPSK	1	8	23.32	23.47	23.26		
3	QPSK	1	14	23.26	23.40	23.16		
3	QPSK	8	0	22.27	22.43	22.24	23	1
3	QPSK	8	4	22.28	22.41	22.25		
3	QPSK	8	7	22.27	22.41	22.22		
3	QPSK	15	0	22.28	22.45	22.16		
3	16QAM	1	0	22.56	22.64	22.45	23	1
3	16QAM	1	8	22.61	22.68	22.55		
3	16QAM	1	14	22.50	22.73	22.36		
3	16QAM	8	0	21.34	21.44	21.29	22	2
3	16QAM	8	4	21.29	21.46	21.30		
3	16QAM	8	7	21.29	21.48	21.30		
3	16QAM	15	0	21.40	21.54	21.23		
3	64QAM	1	0	21.48	21.60	21.35	22	2
3	64QAM	1	8	21.53	21.77	21.55		
3	64QAM	1	14	21.46	21.55	21.34		
3	64QAM	8	0	20.33	20.44	20.30	21	3
3	64QAM	8	4	20.31	20.47	20.26		
3	64QAM	8	7	20.34	20.48	20.29		
3	64QAM	15	0	20.36	20.45	20.23		
Channel				26697	26865	27033	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				814.7	831.5	848.3		
1.4	QPSK	1	0	23.16	23.36	23.16	24	0
1.4	QPSK	1	3	23.26	23.41	23.20		
1.4	QPSK	1	5	23.14	23.32	23.09		
1.4	QPSK	3	0	23.21	23.39	23.20		
1.4	QPSK	3	1	23.29	23.45	23.26		
1.4	QPSK	3	3	23.25	23.36	23.24		
1.4	QPSK	6	0	22.21	22.34	22.14	23	1
1.4	16QAM	1	0	22.38	22.61	22.48	23	1
1.4	16QAM	1	3	22.46	22.65	22.38		
1.4	16QAM	1	5	22.41	22.55	22.42		
1.4	16QAM	3	0	22.22	22.40	22.13		
1.4	16QAM	3	1	22.26	22.45	22.29		
1.4	16QAM	3	3	22.19	22.36	22.23		
1.4	16QAM	6	0	21.28	21.43	21.24	22	2
1.4	64QAM	1	0	21.36	21.58	21.36	22	2



FCC SAR TEST REPORT

Report No. : FA992410-02A

1.4	64QAM	1	3	21.38	21.55	21.41		
1.4	64QAM	1	5	21.27	21.48	21.42		
1.4	64QAM	3	0	21.34	21.47	21.33		
1.4	64QAM	3	1	21.37	21.53	21.32		
1.4	64QAM	3	3	21.33	21.49	21.31		
1.4	64QAM	6	0	20.18	20.37	20.21	21	3



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	23.84	23.97	23.93		
20	QPSK	1	49	23.63	23.72	23.82	24	0
20	QPSK	1	99	23.73	23.77	23.76		
20	QPSK	50	0	22.78	22.90	22.89		
20	QPSK	50	24	22.73	22.86	22.84	23	1
20	QPSK	50	50	22.75	22.81	22.84		
20	QPSK	100	0	22.71	22.89	22.86		
20	16QAM	1	0	22.96	23.00	22.99	23	1
20	16QAM	1	49	22.95	22.99	22.98		
20	16QAM	1	99	23.00	22.99	22.96		
20	16QAM	50	0	21.80	21.93	21.89	22	2
20	16QAM	50	24	21.75	21.90	21.90		
20	16QAM	50	50	21.80	21.82	21.83		
20	16QAM	100	0	21.71	21.86	21.92	22	2
20	64QAM	1	0	21.94	22.00	22.00		
20	64QAM	1	49	21.84	22.00	21.96		
20	64QAM	1	99	21.97	21.95	21.95	21	3
20	64QAM	50	0	20.77	20.96	20.87		
20	64QAM	50	24	20.74	20.86	20.89		
20	64QAM	50	50	20.79	20.83	20.81	21	3
20	64QAM	100	0	20.72	20.88	20.91		
Channel				132047	132322	132597	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	23.83	23.96	23.92		
15	QPSK	1	37	23.59	23.66	23.73	24	0
15	QPSK	1	74	23.72	23.76	23.69		
15	QPSK	36	0	22.74	22.81	22.88		
15	QPSK	36	20	22.65	22.79	22.77	23	1
15	QPSK	36	39	22.69	22.73	22.81		
15	QPSK	75	0	22.68	22.81	22.77		
15	16QAM	1	0	22.89	23.00	22.91	23	1
15	16QAM	1	37	22.92	22.97	22.88		
15	16QAM	1	74	22.96	22.96	22.91		
15	16QAM	36	0	21.76	21.93	21.80	22	2
15	16QAM	36	20	21.71	21.84	21.88		
15	16QAM	36	39	21.75	21.78	21.83		
15	16QAM	75	0	21.66	21.84	21.84	22	2
15	64QAM	1	0	21.85	21.99	21.93		
15	64QAM	1	37	21.82	21.95	21.86		
15	64QAM	1	74	21.93	21.88	21.88	21	3
15	64QAM	36	0	20.69	20.92	20.79		
15	64QAM	36	20	20.67	20.84	20.84		
15	64QAM	36	39	20.72	20.81	20.75	21	3
15	64QAM	75	0	20.66	20.81	20.86		
Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	23.74	23.95	23.89		
10	QPSK	1	25	23.61	23.70	23.76	24	0
10	QPSK	1	49	23.66	23.68	23.71		
10	QPSK	25	0	22.75	22.83	22.79		
10	QPSK	25	12	22.64	22.83	22.77	23	1



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	22.75	22.75	22.83		
10	QPSK	50	0	22.70	22.89	22.85		
10	16QAM	1	0	22.95	22.95	22.89		
10	16QAM	1	25	22.91	22.99	22.89	23	1
10	16QAM	1	49	22.97	22.95	22.88		
10	16QAM	25	0	21.80	21.83	21.79		
10	16QAM	25	12	21.69	21.81	21.86	22	2
10	16QAM	25	25	21.74	21.75	21.76		
10	16QAM	50	0	21.71	21.76	21.87		
10	64QAM	1	0	21.90	21.96	21.97	22	2
10	64QAM	1	25	21.84	21.91	21.94		
10	64QAM	1	49	21.88	21.85	21.89		
10	64QAM	25	0	20.77	20.86	20.82	21	3
10	64QAM	25	12	20.64	20.82	20.85		
10	64QAM	25	25	20.71	20.80	20.74		
10	64QAM	50	0	20.62	20.83	20.87		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	23.82	23.87	23.85	24	0
5	QPSK	1	12	23.60	23.68	23.75		
5	QPSK	1	24	23.68	23.69	23.68		
5	QPSK	12	0	22.75	22.81	22.80	23	1
5	QPSK	12	7	22.70	22.81	22.76		
5	QPSK	12	13	22.71	22.72	22.77		
5	QPSK	25	0	22.63	22.88	22.77	23	1
5	16QAM	1	0	22.92	22.99	22.89		
5	16QAM	1	12	22.88	22.93	22.96		
5	16QAM	1	24	22.97	22.90	22.89	22	2
5	16QAM	12	0	21.71	21.90	21.84		
5	16QAM	12	7	21.70	21.87	21.90		
5	16QAM	12	13	21.70	21.72	21.78	22	2
5	16QAM	25	0	21.68	21.85	21.91		
5	64QAM	1	0	21.92	22.00	21.98		
5	64QAM	1	12	21.75	22.00	21.96	22	2
5	64QAM	1	24	21.91	21.87	21.90		
5	64QAM	12	0	20.69	20.92	20.78		
5	64QAM	12	7	20.64	20.78	20.89	21	3
5	64QAM	12	13	20.79	20.77	20.81		
5	64QAM	25	0	20.72	20.87	20.87		
Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	23.82	23.93	23.92	24	0
3	QPSK	1	8	23.57	23.71	23.72		
3	QPSK	1	14	23.64	23.69	23.74		
3	QPSK	8	0	22.76	22.84	22.79	23	1
3	QPSK	8	4	22.63	22.77	22.80		
3	QPSK	8	7	22.74	22.74	22.75		
3	QPSK	15	0	22.61	22.83	22.83	23	1
3	16QAM	1	0	22.88	22.94	22.95		
3	16QAM	1	8	22.92	22.96	22.96		
3	16QAM	1	14	22.95	22.90	22.90	22	2
3	16QAM	8	0	21.73	21.93	21.80		
3	16QAM	8	4	21.74	21.84	21.86		
3	16QAM	8	7	21.73	21.82	21.79	22	2
3	16QAM	15	0	21.61	21.86	21.92		
3	64QAM	1	0	21.87	21.93	21.98	22	2



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	64QAM	1	8	21.82	21.93	21.90	21	3
3	64QAM	1	14	21.87	21.87	21.86		
3	64QAM	8	0	20.77	20.95	20.78		
3	64QAM	8	4	20.67	20.79	20.82		
3	64QAM	8	7	20.79	20.76	20.71		
3	64QAM	15	0	20.64	20.81	20.90		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	23.68	23.69	23.67	24	0
1.4	QPSK	1	3	23.71	23.76	23.72		
1.4	QPSK	1	5	23.65	23.68	23.64		
1.4	QPSK	3	0	23.70	23.73	23.72		
1.4	QPSK	3	1	23.75	23.78	23.78		
1.4	QPSK	3	3	23.70	23.73	23.71		
1.4	QPSK	6	0	22.71	22.70	22.71	23	1
1.4	16QAM	1	0	22.99	22.91	22.92	23	1
1.4	16QAM	1	3	22.94	22.95	22.93		
1.4	16QAM	1	5	22.90	22.86	22.90		
1.4	16QAM	3	0	22.75	22.72	22.69		
1.4	16QAM	3	1	22.77	22.75	22.72		
1.4	16QAM	3	3	22.70	22.75	22.68		
1.4	16QAM	6	0	21.73	21.80	21.74	22	2
1.4	64QAM	1	0	21.84	21.91	21.84	22	2
1.4	64QAM	1	3	21.85	21.95	21.97		
1.4	64QAM	1	5	21.84	21.83	21.82		
1.4	64QAM	3	0	21.85	21.84	21.85		
1.4	64QAM	3	1	21.90	21.90	21.83		
1.4	64QAM	3	3	21.82	21.81	21.85		
1.4	64QAM	6	0	20.69	20.71	20.66	21	3

<Reduced Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	15.69	15.68	15.99	16	0
20	QPSK	1	49	15.56	15.61	15.78		
20	QPSK	1	99	15.49	15.50	15.79		
20	QPSK	50	0	15.68	15.73	15.97	16	0
20	QPSK	50	24	15.64	15.62	15.88		
20	QPSK	50	50	15.64	15.66	15.89		
20	QPSK	100	0	15.65	15.67	15.92	16	0
20	16QAM	1	0	15.93	15.96	15.98		
20	16QAM	1	49	15.85	15.82	15.89		
20	16QAM	1	99	15.83	15.82	15.89	16	0
20	16QAM	50	0	15.76	15.67	15.96		
20	16QAM	50	24	15.65	15.73	15.90		
20	16QAM	50	50	15.60	15.68	15.86	16	0
20	16QAM	100	0	15.71	15.72	15.90		
20	64QAM	1	0	15.93	15.80	15.94		
20	64QAM	1	49	15.84	15.82	15.91	16	0
20	64QAM	1	99	15.74	15.73	15.93		
20	64QAM	50	0	15.75	15.71	15.92		
20	64QAM	50	24	15.69	15.74	15.94	16	0
20	64QAM	50	50	15.64	15.72	15.87		
20	64QAM	100	0	15.69	15.74	15.93		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	15.61	15.64	15.91	16	0
15	QPSK	1	37	15.48	15.51	15.74		
15	QPSK	1	74	15.40	15.44	15.73		
15	QPSK	36	0	15.58	15.68	15.89	16	0
15	QPSK	36	20	15.60	15.60	15.82		
15	QPSK	36	39	15.58	15.65	15.82		
15	QPSK	75	0	15.56	15.63	15.86	16	0
15	16QAM	1	0	15.92	15.91	15.96		
15	16QAM	1	37	15.78	15.73	15.86		
15	16QAM	1	74	15.76	15.76	15.81	16	0
15	16QAM	36	0	15.70	15.67	15.89		
15	16QAM	36	20	15.61	15.69	15.88		
15	16QAM	36	39	15.54	15.68	15.79	16	0
15	16QAM	75	0	15.67	15.69	15.87		
15	64QAM	1	0	15.88	15.71	15.94		
15	64QAM	1	37	15.78	15.81	15.84	16	0
15	64QAM	1	74	15.74	15.67	15.93		
15	64QAM	36	0	15.68	15.67	15.89		
15	64QAM	36	20	15.61	15.72	15.85	16	0
15	64QAM	36	39	15.58	15.68	15.79		
15	64QAM	75	0	15.64	15.67	15.85		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	15.67	15.65	15.94	16	0
10	QPSK	1	25	15.47	15.56	15.69		
10	QPSK	1	49	15.49	15.42	15.70		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	0	15.59	15.73	15.88	16	0
10	QPSK	25	12	15.64	15.60	15.87		
10	QPSK	25	25	15.57	15.65	15.87		
10	QPSK	50	0	15.57	15.60	15.83		
10	16QAM	1	0	15.85	15.89	15.93	16	0
10	16QAM	1	25	15.81	15.73	15.87		
10	16QAM	1	49	15.78	15.82	15.86		
10	16QAM	25	0	15.75	15.67	15.91	16	0
10	16QAM	25	12	15.58	15.72	15.82		
10	16QAM	25	25	15.55	15.62	15.79		
10	16QAM	50	0	15.67	15.63	15.87		
10	64QAM	1	0	15.91	15.74	15.93	16	0
10	64QAM	1	25	15.82	15.74	15.89		
10	64QAM	1	49	15.66	15.69	15.85		
10	64QAM	25	0	15.68	15.69	15.92	16	0
10	64QAM	25	12	15.67	15.67	15.86		
10	64QAM	25	25	15.57	15.64	15.81		
10	64QAM	50	0	15.59	15.66	15.93		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	15.67	15.58	15.89	16	0
5	QPSK	1	12	15.52	15.59	15.69		
5	QPSK	1	24	15.44	15.40	15.75		
5	QPSK	12	0	15.68	15.71	15.95	16	0
5	QPSK	12	7	15.55	15.53	15.83		
5	QPSK	12	13	15.63	15.58	15.79		
5	QPSK	25	0	15.55	15.67	15.82		
5	16QAM	1	0	15.89	15.92	15.90	16	0
5	16QAM	1	12	15.78	15.73	15.80		
5	16QAM	1	24	15.78	15.82	15.87		
5	16QAM	12	0	15.66	15.67	15.86	16	0
5	16QAM	12	7	15.60	15.63	15.84		
5	16QAM	12	13	15.54	15.59	15.83		
5	16QAM	25	0	15.66	15.65	15.90		
5	64QAM	1	0	15.89	15.80	15.89	16	0
5	64QAM	1	12	15.75	15.77	15.89		
5	64QAM	1	24	15.67	15.65	15.84		
5	64QAM	12	0	15.66	15.69	15.85	16	0
5	64QAM	12	7	15.67	15.73	15.89		
5	64QAM	12	13	15.64	15.66	15.80		
5	64QAM	25	0	15.67	15.69	15.84		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	15.66	15.65	15.98	16	0
3	QPSK	1	8	15.52	15.57	15.75		
3	QPSK	1	14	15.48	15.46	15.78		
3	QPSK	8	0	15.68	15.70	15.92	16	0
3	QPSK	8	4	15.58	15.55	15.84		
3	QPSK	8	7	15.57	15.60	15.81		
3	QPSK	15	0	15.60	15.61	15.87		
3	16QAM	1	0	15.89	15.94	15.92	16	0
3	16QAM	1	8	15.82	15.80	15.82		
3	16QAM	1	14	15.82	15.82	15.89		
3	16QAM	8	0	15.71	15.58	15.88	16	0
3	16QAM	8	4	15.65	15.73	15.82		
3	16QAM	8	7	15.56	15.60	15.77		



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	16QAM	15	0	15.61	15.71	15.82		
3	64QAM	1	0	15.93	15.76	15.91	16	0
3	64QAM	1	8	15.77	15.79	15.86		
3	64QAM	1	14	15.74	15.73	15.93		
3	64QAM	8	0	15.72	15.63	15.89	16	0
3	64QAM	8	4	15.61	15.66	15.87		
3	64QAM	8	7	15.61	15.66	15.80		
3	64QAM	15	0	15.67	15.67	15.90		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	15.67	15.64	15.95	16	0
1.4	QPSK	1	3	15.54	15.57	15.78		
1.4	QPSK	1	5	15.40	15.42	15.79		
1.4	QPSK	3	0	15.58	15.69	15.97		
1.4	QPSK	3	1	15.55	15.62	15.86		
1.4	QPSK	3	3	15.61	15.61	15.85		
1.4	QPSK	6	0	15.59	15.64	15.90	16	0
1.4	16QAM	1	0	15.92	15.95	15.90	16	0
1.4	16QAM	1	3	15.85	15.72	15.84		
1.4	16QAM	1	5	15.81	15.81	15.82		
1.4	16QAM	3	0	15.70	15.65	15.93		
1.4	16QAM	3	1	15.57	15.72	15.87		
1.4	16QAM	3	3	15.56	15.60	15.80		
1.4	16QAM	6	0	15.66	15.63	15.90	16	0
1.4	64QAM	1	0	15.84	15.72	15.86	16	0
1.4	64QAM	1	3	15.80	15.75	15.85		
1.4	64QAM	1	5	15.72	15.63	15.93		
1.4	64QAM	3	0	15.66	15.68	15.82		
1.4	64QAM	3	1	15.59	15.71	15.90		
1.4	64QAM	3	3	15.57	15.68	15.82		
1.4	64QAM	6	0	15.68	15.71	15.83	16	0



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	16.43	16.58	16.54	16.6	0
20	QPSK	1	49	16.34	16.40	16.28		
20	QPSK	1	99	16.32	16.42	16.27		
20	QPSK	50	0	16.38	16.45	16.35	16.6	0
20	QPSK	50	24	16.44	16.54	16.53		
20	QPSK	50	50	16.44	16.44	16.31		
20	QPSK	100	0	16.45	16.54	16.41	16.6	0
20	16QAM	1	0	16.57	16.56	16.56		
20	16QAM	1	49	16.56	16.51	16.56		
20	16QAM	1	99	16.51	16.57	16.52	16.6	0
20	16QAM	50	0	16.44	16.49	16.54		
20	16QAM	50	24	16.44	16.57	16.41		
20	16QAM	50	50	16.42	16.47	16.35	16.6	0
20	16QAM	100	0	16.48	16.56	16.44		
20	64QAM	1	0	16.53	16.56	16.52		
20	64QAM	1	49	16.52	16.55	16.50	16.6	0
20	64QAM	1	99	16.48	16.55	16.42		
20	64QAM	50	0	16.40	16.50	16.57		
20	64QAM	50	24	16.46	16.55	16.40	16.6	0
20	64QAM	50	50	16.44	16.48	16.34		
20	64QAM	100	0	16.42	16.55	16.42		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	16.35	16.50	16.46	16.6	0
15	QPSK	1	37	16.34	16.36	16.22		
15	QPSK	1	74	16.28	16.41	16.25		
15	QPSK	36	0	16.35	16.40	16.31	16.6	0
15	QPSK	36	20	16.41	16.51	16.45		
15	QPSK	36	39	16.36	16.41	16.23		
15	QPSK	75	0	16.37	16.48	16.33	16.6	0
15	16QAM	1	0	16.51	16.49	16.49		
15	16QAM	1	37	16.55	16.47	16.52		
15	16QAM	1	74	16.46	16.47	16.51	16.6	0
15	16QAM	36	0	16.41	16.49	16.46		
15	16QAM	36	20	16.44	16.51	16.41		
15	16QAM	36	39	16.32	16.47	16.26	16.6	0
15	16QAM	75	0	16.46	16.47	16.40		
15	64QAM	1	0	16.48	16.47	16.46		
15	64QAM	1	37	16.42	16.50	16.44	16.6	0
15	64QAM	1	74	16.43	16.47	16.32		
15	64QAM	36	0	16.34	16.45	16.52		
15	64QAM	36	20	16.40	16.54	16.32	16.6	0
15	64QAM	36	39	16.34	16.46	16.34		
15	64QAM	75	0	16.41	16.45	16.37		
Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	16.39	16.51	16.44	16.6	0
10	QPSK	1	25	16.26	16.35	16.23		
10	QPSK	1	49	16.31	16.33	16.20		
10	QPSK	25	0	16.34	16.43	16.31	16.6	0
10	QPSK	25	12	16.39	16.53	16.52		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	16.41	16.42	16.26		
10	QPSK	50	0	16.39	16.50	16.38		
10	16QAM	1	0	16.56	16.51	16.46		
10	16QAM	1	25	16.46	16.47	16.47	16.6	0
10	16QAM	1	49	16.44	16.54	16.48		
10	16QAM	25	0	16.40	16.41	16.46		
10	16QAM	25	12	16.42	16.56	16.34	16.6	0
10	16QAM	25	25	16.40	16.45	16.28		
10	16QAM	50	0	16.39	16.47	16.41		
10	64QAM	1	0	16.46	16.55	16.42	16.6	0
10	64QAM	1	25	16.46	16.53	16.43		
10	64QAM	1	49	16.41	16.52	16.34		
10	64QAM	25	0	16.36	16.40	16.48	16.6	0
10	64QAM	25	12	16.45	16.55	16.39		
10	64QAM	25	25	16.34	16.46	16.31		
10	64QAM	50	0	16.38	16.45	16.40		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	16.40	16.55	16.50	16.6	0
5	QPSK	1	12	16.32	16.36	16.23		
5	QPSK	1	24	16.24	16.36	16.22		
5	QPSK	12	0	16.32	16.43	16.28	16.6	0
5	QPSK	12	7	16.35	16.52	16.45		
5	QPSK	12	13	16.36	16.42	16.22		
5	QPSK	25	0	16.40	16.44	16.39	16.6	0
5	16QAM	1	0	16.57	16.53	16.47		
5	16QAM	1	12	16.46	16.50	16.55		
5	16QAM	1	24	16.43	16.51	16.51	16.6	0
5	16QAM	12	0	16.41	16.45	16.53		
5	16QAM	12	7	16.36	16.57	16.39		
5	16QAM	12	13	16.40	16.44	16.30	16.6	0
5	16QAM	25	0	16.48	16.56	16.41		
5	64QAM	1	0	16.52	16.46	16.50		
5	64QAM	1	12	16.46	16.47	16.46	16.6	0
5	64QAM	1	24	16.48	16.50	16.33		
5	64QAM	12	0	16.34	16.45	16.57		
5	64QAM	12	7	16.38	16.48	16.35	16.6	0
5	64QAM	12	13	16.44	16.43	16.29		
5	64QAM	25	0	16.39	16.45	16.39		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	16.43	16.57	16.51	16.6	0
3	QPSK	1	8	16.29	16.33	16.25		
3	QPSK	1	14	16.29	16.34	16.21		
3	QPSK	8	0	16.31	16.35	16.28	16.6	0
3	QPSK	8	4	16.36	16.52	16.45		
3	QPSK	8	7	16.40	16.37	16.27		
3	QPSK	15	0	16.40	16.52	16.40	16.6	0
3	16QAM	1	0	16.53	16.53	16.49		
3	16QAM	1	8	16.47	16.41	16.47		
3	16QAM	1	14	16.44	16.47	16.51	16.6	0
3	16QAM	8	0	16.39	16.44	16.46		
3	16QAM	8	4	16.44	16.53	16.34		
3	16QAM	8	7	16.39	16.40	16.31	16.6	0
3	16QAM	15	0	16.42	16.52	16.42		
3	64QAM	1	0	16.52	16.47	16.43	16.6	0



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	64QAM	1	8	16.42	16.49	16.46	16.6	0
3	64QAM	1	14	16.45	16.51	16.41		
3	64QAM	8	0	16.35	16.41	16.55		
3	64QAM	8	4	16.45	16.53	16.38		
3	64QAM	8	7	16.44	16.42	16.31		
3	64QAM	15	0	16.42	16.46	16.38		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	16.39	16.51	16.46	16.6	0
1.4	QPSK	1	3	16.33	16.33	16.21		
1.4	QPSK	1	5	16.25	16.37	16.17		
1.4	QPSK	3	0	16.33	16.42	16.34		
1.4	QPSK	3	1	16.37	16.47	16.49		
1.4	QPSK	3	3	16.39	16.38	16.22		
1.4	QPSK	6	0	16.44	16.47	16.34	16.6	0
1.4	16QAM	1	0	16.49	16.47	16.46	16.6	0
1.4	16QAM	1	3	16.48	16.51	16.49		
1.4	16QAM	1	5	16.46	16.50	16.46		
1.4	16QAM	3	0	16.37	16.45	16.48		
1.4	16QAM	3	1	16.39	16.54	16.41		
1.4	16QAM	3	3	16.33	16.41	16.31		
1.4	16QAM	6	0	16.40	16.54	16.37	16.6	0
1.4	64QAM	1	0	16.47	16.52	16.50	16.6	0
1.4	64QAM	1	3	16.44	16.50	16.47		
1.4	64QAM	1	5	16.42	16.55	16.38		
1.4	64QAM	3	0	16.39	16.40	16.49		
1.4	64QAM	3	1	16.43	16.49	16.31		
1.4	64QAM	3	3	16.36	16.48	16.29		
1.4	64QAM	6	0	16.38	16.51	16.32	16.6	0



<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	20.25	20.60	20.16	21	0
10	QPSK	1	25	20.29	20.28	20.12		
10	QPSK	1	49	20.23	20.14	20.12		
10	QPSK	25	0	20.25	20.37	20.18	21	0
10	QPSK	25	12	20.36	20.34	20.18		
10	QPSK	25	25	20.32	20.20	20.23		
10	QPSK	50	0	20.34	20.34	20.15	21	0
10	16QAM	1	0	20.56	20.55	20.47		
10	16QAM	1	25	20.26	20.58	20.42		
10	16QAM	1	49	20.53	20.51	20.56	21	0
10	16QAM	25	0	20.28	20.39	20.20		
10	16QAM	25	12	20.39	20.38	20.18		
10	16QAM	25	25	20.32	20.23	20.26	21	0
10	16QAM	50	0	20.35	20.38	20.18		
10	64QAM	1	0	20.46	20.44	20.32		
10	64QAM	1	25	20.47	20.53	20.28	21	0
10	64QAM	1	49	20.45	20.37	20.36		
10	64QAM	25	0	20.30	20.39	20.22		
10	64QAM	25	12	20.37	20.37	20.19	21	0
10	64QAM	25	25	20.34	20.24	20.21		
10	64QAM	50	0	20.36	20.38	20.18		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	20.20	20.19	20.08	21	0
5	QPSK	1	12	20.25	20.19	20.05		
5	QPSK	1	24	20.20	20.05	20.08		
5	QPSK	12	0	20.24	20.29	20.08	21	0
5	QPSK	12	7	20.32	20.30	20.13		
5	QPSK	12	13	20.25	20.17	20.22		
5	QPSK	25	0	20.27	20.31	20.11	21	0
5	16QAM	1	0	20.54	20.54	20.43		
5	16QAM	1	12	20.54	20.48	20.34		
5	16QAM	1	24	20.45	20.45	20.55	21	0
5	16QAM	12	0	20.25	20.38	20.14		
5	16QAM	12	7	20.30	20.31	20.16		
5	16QAM	12	13	20.22	20.20	20.18	21	0
5	16QAM	25	0	20.34	20.28	20.08		
5	64QAM	1	0	20.38	20.38	20.25		
5	64QAM	1	12	20.41	20.52	20.18	21	0
5	64QAM	1	24	20.44	20.37	20.31		
5	64QAM	12	0	20.27	20.39	20.21		
5	64QAM	12	7	20.36	20.32	20.14	21	0
5	64QAM	12	13	20.33	20.14	20.12		
5	64QAM	25	0	20.26	20.35	20.08		
Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	20.20	20.24	20.16	21	0
3	QPSK	1	8	20.27	20.19	20.06		
3	QPSK	1	14	20.23	20.11	20.09		
3	QPSK	8	0	20.16	20.33	20.11	21	0
3	QPSK	8	4	20.30	20.26	20.17		



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	QPSK	8	7	20.26	20.13	20.13		
3	QPSK	15	0	20.25	20.26	20.06		
3	16QAM	1	0	20.55	20.48	20.39		
3	16QAM	1	8	20.57	20.55	20.38	21	0
3	16QAM	1	14	20.48	20.43	20.55		
3	16QAM	8	0	20.24	20.34	20.12		
3	16QAM	8	4	20.33	20.34	20.10	21	0
3	16QAM	8	7	20.29	20.18	20.25		
3	16QAM	15	0	20.33	20.29	20.17		
3	64QAM	1	0	20.42	20.42	20.22	21	0
3	64QAM	1	8	20.41	20.52	20.24		
3	64QAM	1	14	20.39	20.30	20.31		
3	64QAM	8	0	20.25	20.33	20.14	21	0
3	64QAM	8	4	20.35	20.30	20.10		
3	64QAM	8	7	20.26	20.22	20.12		
3	64QAM	15	0	20.31	20.28	20.17		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	20.25	20.20	20.14	21	0
1.4	QPSK	1	3	20.22	20.18	20.04		
1.4	QPSK	1	5	20.14	20.10	20.11		
1.4	QPSK	3	0	20.24	20.35	20.14		
1.4	QPSK	3	1	20.33	20.31	20.13		
1.4	QPSK	3	3	20.23	20.14	20.22		
1.4	QPSK	6	0	20.28	20.24	20.05	21	0
1.4	16QAM	1	0	20.46	20.49	20.40	21	0
1.4	16QAM	1	3	20.59	20.49	20.40		
1.4	16QAM	1	5	20.52	20.42	20.49		
1.4	16QAM	3	0	20.25	20.33	20.15		
1.4	16QAM	3	1	20.32	20.28	20.18		
1.4	16QAM	3	3	20.28	20.13	20.17		
1.4	16QAM	6	0	20.26	20.37	20.09	21	0
1.4	64QAM	1	0	20.42	20.37	20.24	21	0
1.4	64QAM	1	3	20.41	20.51	20.21		
1.4	64QAM	1	5	20.40	20.33	20.35		
1.4	64QAM	3	0	20.28	20.35	20.19		
1.4	64QAM	3	1	20.30	20.28	20.14		
1.4	64QAM	3	3	20.30	20.20	20.19		
1.4	64QAM	6	0	20.34	20.30	20.17	21	0



<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	19.63	19.82	19.74	20	0
20	QPSK	1	49	19.31	19.20	19.47		
20	QPSK	1	99	19.38	19.39	19.49		
20	QPSK	50	0	19.41	19.41	19.59	20	0
20	QPSK	50	24	19.37	19.33	19.56		
20	QPSK	50	50	19.40	19.30	19.57		
20	QPSK	100	0	19.41	19.59	19.41		
20	16QAM	1	0	19.76	19.73	19.76	20	0
20	16QAM	1	49	19.57	19.56	19.78		
20	16QAM	1	99	19.67	19.67	19.65		
20	16QAM	50	0	19.43	19.39	19.58	20	0
20	16QAM	50	24	19.41	19.30	19.57		
20	16QAM	50	50	19.40	19.33	19.57		
20	16QAM	100	0	19.37	19.38	19.57		
20	64QAM	1	0	19.63	19.64	19.63	20	0
20	64QAM	1	49	19.50	19.46	19.64		
20	64QAM	1	99	19.61	19.62	19.72		
20	64QAM	50	0	19.42	19.39	19.58	20	0
20	64QAM	50	24	19.39	19.33	19.59		
20	64QAM	50	50	19.42	19.33	19.57		
20	64QAM	100	0	19.40	19.40	19.59		
Channel				20825	21100	21375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	19.30	19.37	19.45	20	0
15	QPSK	1	37	19.19	19.22	19.39		
15	QPSK	1	74	19.27	19.38	19.47		
15	QPSK	36	0	19.26	19.40	19.48	20	0
15	QPSK	36	20	19.30	19.33	19.47		
15	QPSK	36	39	19.28	19.26	19.45		
15	QPSK	75	0	19.31	19.28	19.45		
15	16QAM	1	0	19.60	19.68	19.76	20	0
15	16QAM	1	37	19.49	19.46	19.70		
15	16QAM	1	74	19.56	19.71	19.77		
15	16QAM	36	0	19.30	19.37	19.46	20	0
15	16QAM	36	20	19.31	19.31	19.50		
15	16QAM	36	39	19.27	19.28	19.47		
15	16QAM	75	0	19.27	19.29	19.46		
15	64QAM	1	0	19.50	19.56	19.67	20	0
15	64QAM	1	37	19.40	19.42	19.57		
15	64QAM	1	74	19.45	19.62	19.61		
15	64QAM	36	0	19.29	19.38	19.47	20	0
15	64QAM	36	20	19.30	19.32	19.48		
15	64QAM	36	39	19.29	19.32	19.47		
15	64QAM	75	0	19.26	19.25	19.44		
Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	19.27	19.30	19.46	20	0
10	QPSK	1	25	19.29	19.21	19.48		
10	QPSK	1	49	19.26	19.24	19.49		
10	QPSK	25	0	19.32	19.26	19.54	20	0
10	QPSK	25	12	19.31	19.27	19.52		



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	19.28	19.28	19.54		
10	QPSK	50	0	19.32	19.27	19.54		
10	16QAM	1	0	19.59	19.66	19.78		
10	16QAM	1	25	19.63	19.54	19.79	20	0
10	16QAM	1	49	19.60	19.56	19.77		
10	16QAM	25	0	19.32	19.24	19.52		
10	16QAM	25	12	19.32	19.27	19.52	20	0
10	16QAM	25	25	19.29	19.21	19.48		
10	16QAM	50	0	19.33	19.28	19.52		
10	64QAM	1	0	19.41	19.57	19.70	20	0
10	64QAM	1	25	19.51	19.46	19.70		
10	64QAM	1	49	19.46	19.35	19.64		
10	64QAM	25	0	19.32	19.26	19.55	20	0
10	64QAM	25	12	19.34	19.28	19.46		
10	64QAM	25	25	19.33	19.25	19.41		
10	64QAM	50	0	19.34	19.26	19.55		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	19.36	19.33	19.49	20	0
5	QPSK	1	12	19.28	19.12	19.43		
5	QPSK	1	24	19.37	19.30	19.56		
5	QPSK	12	0	19.41	19.36	19.49	20	0
5	QPSK	12	7	19.37	19.23	19.49		
5	QPSK	12	13	19.39	19.28	19.58		
5	QPSK	25	0	19.32	19.34	19.54	20	0
5	16QAM	1	0	19.71	19.66	19.69		
5	16QAM	1	12	19.53	19.55	19.68		
5	16QAM	1	24	19.63	19.57	19.80	20	0
5	16QAM	12	0	19.37	19.34	19.53		
5	16QAM	12	7	19.35	19.28	19.52		
5	16QAM	12	13	19.33	19.23	19.54	20	0
5	16QAM	25	0	19.34	19.28	19.52		
5	64QAM	1	0	19.61	19.58	19.60		
5	64QAM	1	12	19.42	19.36	19.64	20	0
5	64QAM	1	24	19.51	19.60	19.71		
5	64QAM	12	0	19.38	19.30	19.54		
5	64QAM	12	7	19.39	19.24	19.53	20	0
5	64QAM	12	13	19.33	19.32	19.57		
5	64QAM	25	0	19.32	19.31	19.52		



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	22.98	23.05	22.98	23.5	0
10	QPSK	1	25	22.93	22.88	22.94		
10	QPSK	1	49	22.92	22.97	22.97		
10	QPSK	25	0	22.51	22.54	22.49	23	0.5
10	QPSK	25	12	22.44	22.45	22.48		
10	QPSK	25	25	22.49	22.49	22.44		
10	QPSK	50	0	22.48	22.49	22.48	23	0.5
10	16QAM	1	0	22.60	22.62	22.70		
10	16QAM	1	25	22.64	22.71	22.68		
10	16QAM	1	49	22.74	22.69	22.71	22	1.5
10	16QAM	25	0	21.52	21.45	21.51		
10	16QAM	25	12	21.52	21.56	21.54		
10	16QAM	25	25	21.46	21.48	21.49	22	1.5
10	16QAM	50	0	21.51	21.50	21.50		
10	64QAM	1	0	21.70	21.59	21.65		
10	64QAM	1	25	21.56	21.69	21.64	22	1.5
10	64QAM	1	49	21.70	21.63	21.69		
10	64QAM	25	0	20.54	20.46	20.52		
10	64QAM	25	12	20.53	20.58	20.54	21.5	2
10	64QAM	25	25	20.49	20.51	20.53		
10	64QAM	50	0	20.52	20.53	20.49		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	22.94	22.90	22.95	23.5	0
5	QPSK	1	12	22.86	22.87	22.93		
5	QPSK	1	24	22.92	22.95	22.90		
5	QPSK	12	0	22.44	22.54	22.44	23	0.5
5	QPSK	12	7	22.38	22.44	22.44		
5	QPSK	12	13	22.43	22.46	22.34		
5	QPSK	25	0	22.39	22.43	22.39	23	0.5
5	16QAM	1	0	22.58	22.54	22.67		
5	16QAM	1	12	22.62	22.70	22.58		
5	16QAM	1	24	22.73	22.67	22.63	22	1.5
5	16QAM	12	0	21.48	21.42	21.41		
5	16QAM	12	7	21.50	21.53	21.45		
5	16QAM	12	13	21.39	21.46	21.42	22	1.5
5	16QAM	25	0	21.51	21.49	21.40		
5	64QAM	1	0	21.68	21.50	21.56		
5	64QAM	1	12	21.53	21.61	21.55	22	1.5
5	64QAM	1	24	21.68	21.62	21.68		
5	64QAM	12	0	20.52	20.40	20.49		
5	64QAM	12	7	20.53	20.50	20.52	21.5	2
5	64QAM	12	13	20.49	20.46	20.50		
5	64QAM	25	0	20.43	20.43	20.41		
Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	22.88	22.90	22.91	23.5	0
3	QPSK	1	8	22.90	22.83	22.84		
3	QPSK	1	14	22.91	22.93	22.92		
3	QPSK	8	0	22.42	22.54	22.39	23	0.5
3	QPSK	8	4	22.41	22.39	22.39		



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	QPSK	8	7	22.44	22.42	22.40		
3	QPSK	15	0	22.42	22.45	22.42		
3	16QAM	1	0	22.52	22.53	22.62		
3	16QAM	1	8	22.59	22.67	22.60	23	0.5
3	16QAM	1	14	22.71	22.62	22.67		
3	16QAM	8	0	21.45	21.38	21.48		
3	16QAM	8	4	21.42	21.56	21.48	22	1.5
3	16QAM	8	7	21.44	21.48	21.43		
3	16QAM	15	0	21.49	21.47	21.42		
3	64QAM	1	0	21.65	21.51	21.58	22	1.5
3	64QAM	1	8	21.49	21.65	21.60		
3	64QAM	1	14	21.63	21.62	21.67		
3	64QAM	8	0	20.45	20.46	20.43	21.5	2
3	64QAM	8	4	20.52	20.53	20.54		
3	64QAM	8	7	20.48	20.50	20.52		
3	64QAM	15	0	20.46	20.44	20.42		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	22.93	22.93	22.97	23.5	0
1.4	QPSK	1	3	22.91	22.86	22.89		
1.4	QPSK	1	5	22.86	22.89	22.89		
1.4	QPSK	3	0	22.46	22.44	22.46		
1.4	QPSK	3	1	22.36	22.45	22.42		
1.4	QPSK	3	3	22.49	22.43	22.34		
1.4	QPSK	6	0	22.38	22.47	22.48	23	0.5
1.4	16QAM	1	0	22.52	22.60	22.70	23	0.5
1.4	16QAM	1	3	22.63	22.71	22.66		
1.4	16QAM	1	5	22.71	22.61	22.64		
1.4	16QAM	3	0	21.44	21.37	21.51		
1.4	16QAM	3	1	21.48	21.46	21.52		
1.4	16QAM	3	3	21.37	21.47	21.47		
1.4	16QAM	6	0	21.42	21.50	21.44	22	1.5
1.4	64QAM	1	0	21.60	21.50	21.59	22	1.5
1.4	64QAM	1	3	21.54	21.65	21.59		
1.4	64QAM	1	5	21.63	21.63	21.68		
1.4	64QAM	3	0	20.51	20.46	20.52		
1.4	64QAM	3	1	20.43	20.55	20.50		
1.4	64QAM	3	3	20.39	20.43	20.44		
1.4	64QAM	6	0	20.45	20.51	20.42	21.5	2



<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0		20.14		20.5	0
10	QPSK	1	25		20.08			
10	QPSK	1	49		20.00			
10	QPSK	25	0		19.91		20.5	0
10	QPSK	25	12		19.82			
10	QPSK	25	25		19.84			
10	QPSK	50	0		19.84		20.5	0
10	16QAM	1	0		19.83			
10	16QAM	1	25		19.72			
10	16QAM	1	49		19.67		20.5	0
10	16QAM	25	0		19.97			
10	16QAM	25	12		19.86			
10	16QAM	25	25		19.76		20.5	0
10	16QAM	50	0		19.87			
10	64QAM	1	0		20.01			
10	64QAM	1	25		19.98		20.5	0
10	64QAM	1	49		19.86			
10	64QAM	25	0		19.94			
10	64QAM	25	12		19.85		20.5	0
10	64QAM	25	25		19.81			
10	64QAM	50	0		19.84			
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	20.03	20.11	20.01	20.5	0
5	QPSK	1	12	19.97	20.07	19.97		
5	QPSK	1	24	19.84	19.93	19.83		
5	QPSK	12	0	19.82	19.82	19.80	20.5	0
5	QPSK	12	7	19.72	19.80	19.66		
5	QPSK	12	13	19.72	19.78	19.65		
5	QPSK	25	0	19.71	19.74	19.68	20.5	0
5	16QAM	1	0	19.67	19.73	19.64		
5	16QAM	1	12	19.61	19.70	19.60		
5	16QAM	1	24	19.61	19.66	19.60	20.5	0
5	16QAM	12	0	19.88	19.96	19.83		
5	16QAM	12	7	19.72	19.79	19.69		
5	16QAM	12	13	19.58	19.67	19.49	20.5	0
5	16QAM	25	0	19.73	19.82	19.63		
5	64QAM	1	0	19.86	19.92	19.78		
5	64QAM	1	12	19.86	19.94	19.83	20.5	0
5	64QAM	1	24	19.75	19.76	19.73		
5	64QAM	12	0	19.93	19.93	19.91		
5	64QAM	12	7	19.76	19.81	19.74	20.5	0
5	64QAM	12	13	19.73	19.75	19.67		
5	64QAM	25	0	19.76	19.83	19.68		

<LTE Band 14>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23330				
Frequency (MHz)				793				
10	QPSK	1	0		20.65		21	0
10	QPSK	1	25		20.57			
10	QPSK	1	49		20.60			
10	QPSK	25	0		20.39		21	0
10	QPSK	25	12		20.40			
10	QPSK	25	25		20.45			
10	QPSK	50	0		20.33		21	0
10	16QAM	1	0		20.37			
10	16QAM	1	25		20.30			
10	16QAM	1	49		20.32		21	0
10	16QAM	25	0		20.39			
10	16QAM	25	12		20.41			
10	16QAM	25	25		20.41		21	0
10	16QAM	50	0		20.35			
10	64QAM	1	0		20.60		21	0
10	64QAM	1	25		20.49			
10	64QAM	1	49		20.50			
10	64QAM	25	0		20.42		21	0
10	64QAM	25	12		20.42			
10	64QAM	25	25		20.44			
10	64QAM	50	0		20.37			
Channel				23305	23330	23355	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				790.5	793	795.5		
5	QPSK	1	0	20.49	20.58	20.49	21	0
5	QPSK	1	12	20.48	20.50	20.42		
5	QPSK	1	24	20.51	20.56	20.43		
5	QPSK	12	0	20.31	20.38	20.21	21	0
5	QPSK	12	7	20.24	20.33	20.20		
5	QPSK	12	13	20.35	20.44	20.26		
5	QPSK	25	0	20.22	20.29	20.12	21	0
5	16QAM	1	0	20.21	20.27	20.11		
5	16QAM	1	12	20.26	20.27	20.26		
5	16QAM	1	24	20.28	20.29	20.27	21	0
5	16QAM	12	0	20.35	20.36	20.26		
5	16QAM	12	7	20.23	20.32	20.21		
5	16QAM	12	13	20.24	20.31	20.24	21	0
5	16QAM	25	0	20.29	20.34	20.22		
5	64QAM	1	0	20.50	20.53	20.46		
5	64QAM	1	12	20.41	20.49	20.39	21	0
5	64QAM	1	24	20.39	20.45	20.34		
5	64QAM	12	0	20.33	20.36	20.27		
5	64QAM	12	7	20.33	20.37	20.33	21	0
5	64QAM	12	13	20.33	20.38	20.28		
5	64QAM	25	0	20.34	20.37	20.27		



<LTE Band 26>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26765	26865	26965	21	0
Frequency (MHz)				821.5	831.5	841.5		
15	QPSK	1	0	20.27	20.79	20.44		
15	QPSK	1	37	20.16	20.47	20.35	21	0
15	QPSK	1	74	20.27	20.41	20.23		
15	QPSK	36	0	20.23	20.45	20.41		
15	QPSK	36	20	20.27	20.51	20.38	21	0
15	QPSK	36	39	20.28	20.45	20.24		
15	QPSK	75	0	20.23	20.50	20.39		
15	16QAM	1	0	20.64	20.65	20.73	21	0
15	16QAM	1	37	20.49	20.36	20.69		
15	16QAM	1	74	20.62	20.71	20.56		
15	16QAM	36	0	20.26	20.42	20.43	21	0
15	16QAM	36	20	20.27	20.55	20.42		
15	16QAM	36	39	20.23	20.47	20.22		
15	16QAM	75	0	20.21	20.47	20.39	21	0
15	64QAM	1	0	20.53	20.61	20.68		
15	64QAM	1	37	20.50	20.70	20.53		
15	64QAM	1	74	20.57	20.62	20.39	21	0
15	64QAM	36	0	20.32	20.48	20.42		
15	64QAM	36	20	20.34	20.57	20.45		
15	64QAM	36	39	20.39	20.49	20.26	21	0
15	64QAM	75	0	20.28	20.52	20.38		
Channel				26740	26865	26990	21	0
Frequency (MHz)				819	831.5	844		
10	QPSK	1	0	20.29	20.37	20.31		
10	QPSK	1	25	20.26	20.42	20.15	21	0
10	QPSK	1	49	20.28	20.36	20.18		
10	QPSK	25	0	20.32	20.51	20.35	21	0
10	QPSK	25	12	20.31	20.47	20.23		
10	QPSK	25	25	20.30	20.44	20.19		
10	QPSK	50	0	20.33	20.47	20.32	21	0
10	16QAM	1	0	20.56	20.68	20.65		
10	16QAM	1	25	20.50	20.69	20.45		
10	16QAM	1	49	20.63	20.71	20.49	21	0
10	16QAM	25	0	20.30	20.47	20.33		
10	16QAM	25	12	20.33	20.48	20.23		
10	16QAM	25	25	20.22	20.40	20.16	21	0
10	16QAM	50	0	20.30	20.45	20.29		
10	64QAM	1	0	20.53	20.51	20.51		
10	64QAM	1	25	20.43	20.66	20.33	21	0
10	64QAM	1	49	20.48	20.56	20.40		
10	64QAM	25	0	20.30	20.51	20.33		
10	64QAM	25	12	20.30	20.49	20.23	21	0
10	64QAM	25	25	20.24	20.43	20.17		
10	64QAM	50	0	20.25	20.48	20.34		
Channel				26715	26865	27015	21	0
Frequency (MHz)				816.5	831.5	846.5		
5	QPSK	1	0	20.17	20.70	20.43		
5	QPSK	1	12	20.10	20.40	20.35	21	0
5	QPSK	1	24	20.24	20.34	20.20		
5	QPSK	12	0	20.15	20.42	20.38	21	0
5	QPSK	12	7	20.26	20.41	20.29		



FCC SAR TEST REPORT

Report No. : FA992410-02A

5	QPSK	12	13	20.21	20.41	20.18		
5	QPSK	25	0	20.21	20.50	20.35		
5	16QAM	1	0	20.64	20.65	20.72		
5	16QAM	1	12	20.42	20.27	20.60	21	0
5	16QAM	1	24	20.56	20.62	20.53		
5	16QAM	12	0	20.21	20.34	20.37		
5	16QAM	12	7	20.17	20.52	20.41	21	0
5	16QAM	12	13	20.23	20.45	20.12		
5	16QAM	25	0	20.12	20.42	20.36		
5	64QAM	1	0	20.46	20.53	20.62	21	0
5	64QAM	1	12	20.48	20.64	20.49		
5	64QAM	1	24	20.52	20.62	20.29		
5	64QAM	12	0	20.27	20.42	20.37	21	0
5	64QAM	12	7	20.30	20.55	20.35		
5	64QAM	12	13	20.30	20.48	20.20		
5	64QAM	25	0	20.28	20.49	20.30		
Channel				26705	26865	27025	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				815.5	831.5	847.5		
3	QPSK	1	0	20.19	20.77	20.42	21	0
3	QPSK	1	8	20.08	20.37	20.30		
3	QPSK	1	14	20.20	20.39	20.19		
3	QPSK	8	0	20.19	20.43	20.33	21	0
3	QPSK	8	4	20.26	20.42	20.35		
3	QPSK	8	7	20.27	20.37	20.14		
3	QPSK	15	0	20.14	20.42	20.33	21	0
3	16QAM	1	0	20.56	20.65	20.63		
3	16QAM	1	8	20.47	20.27	20.60		
3	16QAM	1	14	20.53	20.69	20.46	21	0
3	16QAM	8	0	20.17	20.33	20.43		
3	16QAM	8	4	20.20	20.55	20.41		
3	16QAM	8	7	20.14	20.40	20.17	21	0
3	16QAM	15	0	20.11	20.46	20.29		
3	64QAM	1	0	20.49	20.59	20.62		
3	64QAM	1	8	20.47	20.62	20.46	21	0
3	64QAM	1	14	20.52	20.58	20.34		
3	64QAM	8	0	20.30	20.45	20.36		
3	64QAM	8	4	20.29	20.52	20.36	21	0
3	64QAM	8	7	20.34	20.49	20.22		
3	64QAM	15	0	20.24	20.46	20.36		
Channel				26697	26865	27033	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				814.7	831.5	848.3		
1.4	QPSK	1	0	20.20	20.77	20.39	21	0
1.4	QPSK	1	3	20.14	20.43	20.30		
1.4	QPSK	1	5	20.22	20.34	20.13		
1.4	QPSK	3	0	20.15	20.36	20.37		
1.4	QPSK	3	1	20.25	20.51	20.37		
1.4	QPSK	3	3	20.28	20.36	20.15		
1.4	QPSK	6	0	20.22	20.46	20.38	21	0
1.4	16QAM	1	0	20.61	20.58	20.68	21	0
1.4	16QAM	1	3	20.49	20.32	20.69		
1.4	16QAM	1	5	20.55	20.70	20.56		
1.4	16QAM	3	0	20.20	20.32	20.40		
1.4	16QAM	3	1	20.22	20.49	20.32		
1.4	16QAM	3	3	20.14	20.44	20.18		
1.4	16QAM	6	0	20.16	20.40	20.29	21	0
1.4	64QAM	1	0	20.44	20.57	20.58	21	0



FCC SAR TEST REPORT

Report No. : FA992410-02A

1.4	64QAM	1	3	20.41	20.70	20.47		
1.4	64QAM	1	5	20.55	20.62	20.29		
1.4	64QAM	3	0	20.22	20.38	20.35		
1.4	64QAM	3	1	20.25	20.53	20.35		
1.4	64QAM	3	3	20.36	20.46	20.23		
1.4	64QAM	6	0	20.18	20.52	20.38	21	0



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572	16.6	0
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	16.48	16.57	16.47		
20	QPSK	1	49	16.24	16.34	16.36	16.6	0
20	QPSK	1	99	16.38	16.28	16.36		
20	QPSK	50	0	16.47	16.51	16.48		
20	QPSK	50	24	16.40	16.44	16.42	16.6	0
20	QPSK	50	50	16.43	16.39	16.43		
20	QPSK	100	0	16.41	16.48	16.46		
20	16QAM	1	0	16.45	16.49	16.43	16.6	0
20	16QAM	1	49	16.54	16.44	16.41		
20	16QAM	1	99	16.46	16.43	16.45		
20	16QAM	50	0	16.50	16.51	16.48	16.6	0
20	16QAM	50	24	16.42	16.46	16.48		
20	16QAM	50	50	16.48	16.43	16.43		
20	16QAM	100	0	16.40	16.44	16.48	16.6	0
20	64QAM	1	0	16.46	16.49	16.42		
20	64QAM	1	49	16.54	16.42	16.54		
20	64QAM	1	99	16.55	16.51	16.49	16.6	0
20	64QAM	50	0	16.45	16.56	16.44		
20	64QAM	50	24	16.39	16.45	16.50		
20	64QAM	50	50	16.45	16.42	16.40	16.6	0
20	64QAM	100	0	16.40	16.43	16.51		
Channel				132047	132322	132597	16.6	0
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	16.45	16.56	16.38		
15	QPSK	1	37	16.20	16.29	16.33	16.6	0
15	QPSK	1	74	16.36	16.24	16.26		
15	QPSK	36	0	16.42	16.50	16.40		
15	QPSK	36	20	16.39	16.44	16.36	16.6	0
15	QPSK	36	39	16.43	16.31	16.43		
15	QPSK	75	0	16.40	16.46	16.44		
15	16QAM	1	0	16.37	16.44	16.43	16.6	0
15	16QAM	1	37	16.49	16.43	16.36		
15	16QAM	1	74	16.41	16.41	16.42		
15	16QAM	36	0	16.47	16.42	16.40	16.6	0
15	16QAM	36	20	16.37	16.43	16.48		
15	16QAM	36	39	16.41	16.40	16.36		
15	16QAM	75	0	16.37	16.37	16.47	16.6	0
15	64QAM	1	0	16.44	16.48	16.33		
15	64QAM	1	37	16.54	16.35	16.52		
15	64QAM	1	74	16.55	16.47	16.49	16.6	0
15	64QAM	36	0	16.35	16.49	16.34		
15	64QAM	36	20	16.32	16.44	16.43		
15	64QAM	36	39	16.43	16.39	16.36	16.6	0
15	64QAM	75	0	16.40	16.42	16.46		
Channel				132022	132322	132622	16.6	0
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	16.38	16.56	16.43		
10	QPSK	1	25	16.18	16.27	16.31	16.6	0
10	QPSK	1	49	16.38	16.22	16.27		
10	QPSK	25	0	16.39	16.49	16.47		
10	QPSK	25	12	16.35	16.43	16.38	16.6	0



FCC SAR TEST REPORT

Report No. : FA992410-02A

10	QPSK	25	25	16.42	16.36	16.42		
10	QPSK	50	0	16.39	16.41	16.46		
10	16QAM	1	0	16.42	16.49	16.34		
10	16QAM	1	25	16.48	16.35	16.34	16.6	0
10	16QAM	1	49	16.43	16.35	16.36		
10	16QAM	25	0	16.45	16.44	16.44		
10	16QAM	25	12	16.33	16.42	16.40	16.6	0
10	16QAM	25	25	16.41	16.36	16.39		
10	16QAM	50	0	16.33	16.38	16.45		
10	64QAM	1	0	16.42	16.40	16.34	16.6	0
10	64QAM	1	25	16.54	16.41	16.49		
10	64QAM	1	49	16.54	16.45	16.48		
10	64QAM	25	0	16.39	16.55	16.35	16.6	0
10	64QAM	25	12	16.33	16.44	16.48		
10	64QAM	25	25	16.45	16.35	16.40		
10	64QAM	50	0	16.31	16.42	16.46		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	16.47	16.47	16.44	16.6	0
5	QPSK	1	12	16.24	16.33	16.27		
5	QPSK	1	24	16.38	16.18	16.30		
5	QPSK	12	0	16.37	16.46	16.39	16.6	0
5	QPSK	12	7	16.32	16.43	16.41		
5	QPSK	12	13	16.40	16.30	16.36		
5	QPSK	25	0	16.38	16.45	16.41	16.6	0
5	16QAM	1	0	16.38	16.42	16.33		
5	16QAM	1	12	16.50	16.37	16.36		
5	16QAM	1	24	16.39	16.34	16.43	16.6	0
5	16QAM	12	0	16.48	16.50	16.47		
5	16QAM	12	7	16.42	16.43	16.42		
5	16QAM	12	13	16.44	16.40	16.38	16.6	0
5	16QAM	25	0	16.34	16.43	16.45		
5	64QAM	1	0	16.42	16.45	16.36		
5	64QAM	1	12	16.46	16.42	16.53	16.6	0
5	64QAM	1	24	16.53	16.42	16.42		
5	64QAM	12	0	16.36	16.50	16.43		
5	64QAM	12	7	16.31	16.35	16.50	16.6	0
5	64QAM	12	13	16.41	16.38	16.40		
5	64QAM	25	0	16.35	16.41	16.41		
Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	16.45	16.50	16.44	16.6	0
3	QPSK	1	8	16.22	16.32	16.26		
3	QPSK	1	14	16.38	16.23	16.28		
3	QPSK	8	0	16.37	16.48	16.46	16.6	0
3	QPSK	8	4	16.34	16.36	16.42		
3	QPSK	8	7	16.34	16.36	16.34		
3	QPSK	15	0	16.38	16.41	16.41	16.6	0
3	16QAM	1	0	16.35	16.42	16.36		
3	16QAM	1	8	16.47	16.34	16.31		
3	16QAM	1	14	16.43	16.39	16.45	16.6	0
3	16QAM	8	0	16.49	16.47	16.44		
3	16QAM	8	4	16.41	16.41	16.41		
3	16QAM	8	7	16.41	16.40	16.38	16.6	0
3	16QAM	15	0	16.40	16.37	16.44		
3	64QAM	1	0	16.46	16.45	16.39	16.6	0



FCC SAR TEST REPORT

Report No. : FA992410-02A

3	64QAM	1	8	16.49	16.36	16.51	16.6	0
3	64QAM	1	14	16.49	16.48	16.42		
3	64QAM	8	0	16.38	16.52	16.35		
3	64QAM	8	4	16.29	16.43	16.48		
3	64QAM	8	7	16.43	16.41	16.40		
3	64QAM	15	0	16.36	16.38	16.47		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	16.41	16.54	16.40	16.6	0
1.4	QPSK	1	3	16.19	16.31	16.33		
1.4	QPSK	1	5	16.33	16.25	16.27		
1.4	QPSK	3	0	16.38	16.48	16.43		
1.4	QPSK	3	1	16.34	16.43	16.36		
1.4	QPSK	3	3	16.38	16.31	16.40		
1.4	QPSK	6	0	16.40	16.39	16.37	16.6	0
1.4	16QAM	1	0	16.37	16.44	16.38	16.6	0
1.4	16QAM	1	3	16.51	16.43	16.38		
1.4	16QAM	1	5	16.38	16.42	16.43		
1.4	16QAM	3	0	16.49	16.49	16.47		
1.4	16QAM	3	1	16.40	16.36	16.39		
1.4	16QAM	3	3	16.39	16.38	16.35		
1.4	16QAM	6	0	16.34	16.36	16.42	16.6	0
1.4	64QAM	1	0	16.38	16.46	16.33	16.6	0
1.4	64QAM	1	3	16.49	16.42	16.52		
1.4	64QAM	1	5	16.55	16.51	16.42		
1.4	64QAM	3	0	16.38	16.53	16.44		
1.4	64QAM	3	1	16.32	16.44	16.45		
1.4	64QAM	3	3	16.38	16.41	16.34		
1.4	64QAM	6	0	16.35	16.37	16.49	16.6	0

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- “special subframe S” contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Special subframe (30720·T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.167)/5 = 63.3\%$
- for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.143)/5 = 62.9\%$
- For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

<Default Power Mode>
<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Middle Ch. / Freq.	Power Middle Ch. / Freq.	Power High Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				39750	40185	40620	41055	41490		
Frequency (MHz)				2506	2549.5	2593	2636.5	2680		
20	QPSK	1	0	22.56	22.42	22.76	22.74	22.57	23	0
20	QPSK	1	49	22.45	22.22	22.49	22.45	22.30		
20	QPSK	1	99	22.38	22.17	22.51	22.37	22.28		
20	QPSK	50	0	21.55	21.36	21.61	21.56	21.48	22	1
20	QPSK	50	24	21.50	21.25	21.55	21.46	21.34		
20	QPSK	50	50	21.45	21.19	21.53	21.36	21.27		
20	QPSK	100	0	21.49	21.25	21.55	21.45	21.35	22	1
20	16QAM	1	0	21.73	21.59	21.89	21.88	21.75		
20	16QAM	1	49	21.56	21.40	21.67	21.51	21.42		
20	16QAM	1	99	21.53	21.31	21.65	21.45	21.39	21	2
20	16QAM	50	0	20.55	20.37	20.65	20.57	20.51		
20	16QAM	50	24	20.52	20.31	20.61	20.52	20.40		
20	16QAM	50	50	20.52	20.23	20.56	20.43	20.33	21	2
20	16QAM	100	0	20.52	20.30	20.59	20.49	20.36		
20	64QAM	1	0	20.35	20.06	20.41	20.45	20.24		
20	64QAM	1	49	20.13	19.91	20.08	20.06	19.93	21	2
20	64QAM	1	99	20.04	19.87	20.15	19.97	19.95		
20	64QAM	50	0	19.56	19.34	19.60	19.53	19.51		
20	64QAM	50	24	19.51	19.25	19.59	19.45	19.38	20	3
20	64QAM	50	50	19.46	19.21	19.51	19.39	19.35		
20	64QAM	100	0	19.55	19.30	19.59	19.48	19.38		
Channel				39725	40173	40620	41068	41515	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2503.5	2548.3	2593	2637.8	2682.5		
15	QPSK	1	0	22.55	22.40	22.64	22.59	22.52	23	0
15	QPSK	1	37	22.45	22.22	22.52	22.41	22.30		
15	QPSK	1	74	22.43	22.21	22.52	22.37	22.28		
15	QPSK	36	0	21.46	21.27	21.54	21.47	21.34	22	1
15	QPSK	36	20	21.47	21.24	21.54	21.41	21.33		
15	QPSK	36	39	21.45	21.17	21.48	21.36	21.32		
15	QPSK	75	0	21.51	21.23	21.52	21.43	21.34	22	1
15	16QAM	1	0	21.69	21.56	21.78	21.75	21.67		
15	16QAM	1	37	21.60	21.37	21.65	21.54	21.41		
15	16QAM	1	74	21.54	21.32	21.66	21.43	21.42	21	2
15	16QAM	36	0	20.52	20.30	20.57	20.49	20.35		
15	16QAM	36	20	20.48	20.23	20.52	20.43	20.33		
15	16QAM	36	39	20.42	20.16	20.47	20.34	20.27	21	2
15	16QAM	75	0	20.52	20.28	20.55	20.48	20.38		
15	64QAM	1	0	20.34	20.05	20.27	20.32	20.24		
15	64QAM	1	37	20.16	19.86	20.09	20.05	20.00	21	2
15	64QAM	1	74	20.16	19.89	20.16	20.03	20.05		
15	64QAM	36	0	19.50	19.27	19.52	19.47	19.38		
15	64QAM	36	20	19.46	19.23	19.50	19.41	19.31	20	3
15	64QAM	36	39	19.43	19.14	19.46	19.36	19.29		
15	64QAM	75	0	19.50	19.29	19.57	19.46	19.38		
Channel				39700	40160	40620	41080	41540	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2501	2547	2593	2639	2685		
10	QPSK	1	0	22.45	22.31	22.56	22.49	22.41	23	0
10	QPSK	1	25	22.45	22.23	22.52	22.47	22.32		



FCC SAR TEST REPORT

Report No. : FA992410-02A


10	QPSK	1	49	22.40	22.20	22.49	22.41	22.32		
10	QPSK	25	0	21.48	21.30	21.56	21.47	21.35	22	1
10	QPSK	25	12	21.51	21.28	21.55	21.43	21.33		
10	QPSK	25	25	21.45	21.22	21.52	21.37	21.33		
10	QPSK	50	0	21.45	21.23	21.52	21.41	21.33		
10	16QAM	1	0	21.64	21.50	21.74	21.61	21.57	22	1
10	16QAM	1	25	21.55	21.38	21.71	21.53	21.50		
10	16QAM	1	49	21.51	21.29	21.59	21.45	21.42		
10	16QAM	25	0	20.47	20.28	20.53	20.46	20.40	21	2
10	16QAM	25	12	20.48	20.26	20.55	20.43	20.35		
10	16QAM	25	25	20.45	20.20	20.51	20.35	20.33		
10	16QAM	50	0	20.53	20.30	20.58	20.49	20.41		
10	64QAM	1	0	20.29	19.99	20.23	20.19	20.16	21	2
10	64QAM	1	25	20.17	19.92	20.10	20.10	19.98		
10	64QAM	1	49	20.13	19.80	20.07	20.03	20.03		
10	64QAM	25	0	19.52	19.33	19.60	19.50	19.45	20	3
10	64QAM	25	12	19.57	19.33	19.62	19.47	19.45		
10	64QAM	25	25	19.50	19.25	19.56	19.40	19.39		
10	64QAM	50	0	19.50	19.28	19.56	19.45	19.36		
Channel				39675	40148	40620	41093	41565	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2498.5	2545.8	2593	2640.30	2687.5		
5	QPSK	1	0	22.42	22.28	22.54	22.49	22.34	23	0
5	QPSK	1	12	22.43	22.25	22.52	22.43	22.31		
5	QPSK	1	24	22.37	22.16	22.48	22.37	22.26		
5	QPSK	12	0	21.43	21.26	21.55	21.43	21.35	22	1
5	QPSK	12	7	21.47	21.26	21.54	21.43	21.36		
5	QPSK	12	13	21.45	21.22	21.52	21.40	21.33		
5	QPSK	25	0	21.45	21.22	21.54	21.43	21.36		
5	16QAM	1	0	21.55	21.40	21.69	21.55	21.48	22	1
5	16QAM	1	12	21.57	21.31	21.65	21.55	21.51		
5	16QAM	1	24	21.57	21.38	21.62	21.51	21.46		
5	16QAM	12	0	20.41	20.26	20.54	20.40	20.34	21	2
5	16QAM	12	7	20.45	20.24	20.54	20.42	20.39		
5	16QAM	12	13	20.45	20.21	20.48	20.37	20.31		
5	16QAM	25	0	20.46	20.25	20.50	20.43	20.35		
5	64QAM	1	0	20.19	19.88	20.12	20.14	19.99	21	2
5	64QAM	1	12	20.22	19.84	20.11	20.03	19.99		
5	64QAM	1	24	20.20	19.82	20.12	20.00	20.02		
5	64QAM	12	0	19.53	19.31	19.54	19.51	19.41	20	3
5	64QAM	12	7	19.54	19.36	19.57	19.51	19.42		
5	64QAM	12	13	19.51	19.30	19.56	19.48	19.36		
5	64QAM	25	0	19.52	19.31	19.55	19.46	19.40		

<Reduced Power Mode>
<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Middle Ch. / Freq.	Power Middle Ch. / Freq.	Power High Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				39750	40185	40620	41055	41490		
Frequency (MHz)				2506	2549.5	2593	2636.5	2680		
20	QPSK	1	0	20.94	21.01	21.37	21.20	21.18	21.5	0
20	QPSK	1	49	20.79	20.83	20.99	20.90	20.85		
20	QPSK	1	99	20.81	20.88	21.00	20.90	20.78		
20	QPSK	50	0	20.92	20.97	21.11	21.02	21.08	21.5	0
20	QPSK	50	24	20.85	20.94	21.07	20.97	20.90		
20	QPSK	50	50	20.85	20.92	21.07	20.92	20.83		
20	QPSK	100	0	20.89	20.96	21.09	20.99	20.88	21.5	0
20	16QAM	1	0	21.08	21.36	21.31	21.30	21.32		
20	16QAM	1	49	20.91	21.00	21.19	21.12	21.01		
20	16QAM	1	99	20.86	21.04	21.14	20.98	20.90	21	0.5
20	16QAM	50	0	20.51	20.53	20.64	20.58	20.57		
20	16QAM	50	24	20.44	20.54	20.60	20.52	20.40		
20	16QAM	50	50	20.38	20.45	20.59	20.48	20.39	21	0.5
20	16QAM	100	0	20.40	20.49	20.59	20.50	20.42		
20	64QAM	1	0	20.32	20.25	20.54	20.53	20.42		
20	64QAM	1	49	20.10	20.14	20.26	20.16	20.15	21	0.5
20	64QAM	1	99	20.11	20.19	20.31	20.26	20.09		
20	64QAM	50	0	19.43	19.49	19.59	19.53	19.56		
20	64QAM	50	24	19.39	19.48	19.57	19.53	19.45	20	1.5
20	64QAM	50	50	19.35	19.43	19.53	19.45	19.36		
20	64QAM	100	0	19.40	19.48	19.58	19.52	19.44		
Channel				39725	40173	40620	41068	41515	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2503.5	2548.3	2593	2637.8	2682.5		
15	QPSK	1	0	20.88	21.00	21.24	21.17	21.15	21.5	0
15	QPSK	1	37	20.77	20.82	20.90	20.84	20.83		
15	QPSK	1	74	20.80	20.83	20.98	20.83	20.75		
15	QPSK	36	0	20.85	20.90	21.09	21.01	20.99	21.5	0
15	QPSK	36	20	20.80	20.87	21.03	20.91	20.81		
15	QPSK	36	39	20.82	20.91	21.03	20.90	20.77		
15	QPSK	75	0	20.84	20.86	21.03	20.93	20.85	21.5	0
15	16QAM	1	0	21.03	21.31	21.24	21.24	21.22		
15	16QAM	1	37	20.91	20.91	21.17	21.10	20.95		
15	16QAM	1	74	20.83	21.00	21.12	20.90	20.85	21	0.5
15	16QAM	36	0	20.49	20.52	20.63	20.48	20.57		
15	16QAM	36	20	20.44	20.52	20.52	20.42	20.31		
15	16QAM	36	39	20.30	20.45	20.53	20.45	20.31	21	0.5
15	16QAM	75	0	20.35	20.46	20.50	20.41	20.34		
15	64QAM	1	0	20.31	20.23	20.51	20.47	20.40		
15	64QAM	1	37	20.10	20.10	20.25	20.14	20.06	21	0.5
15	64QAM	1	74	20.09	20.19	20.21	20.25	20.03		
15	64QAM	36	0	19.40	19.46	19.50	19.51	19.55		
15	64QAM	36	20	19.30	19.39	19.54	19.47	19.41	20	1.5
15	64QAM	36	39	19.34	19.42	19.49	19.40	19.34		
15	64QAM	75	0	19.33	19.46	19.52	19.52	19.42		
Channel				39700	40160	40620	41080	41540	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2501	2547	2593	2639	2685		
10	QPSK	1	0	20.93	20.91	21.21	21.11	21.11	21.5	0
10	QPSK	1	25	20.77	20.77	20.95	20.90	20.85		

10	QPSK	1	49	20.80	20.83	21.00	20.86	20.70	21.5	0
10	QPSK	25	0	20.83	20.93	21.10	20.93	21.08		
10	QPSK	25	12	20.80	20.89	20.99	20.96	20.84		
10	QPSK	25	25	20.85	20.84	21.02	20.86	20.80		
10	QPSK	50	0	20.89	20.86	21.08	20.90	20.79	21.5	0
10	16QAM	1	0	20.98	21.36	21.25	21.23	21.32		
10	16QAM	1	25	20.88	20.96	21.12	21.10	20.92		
10	16QAM	1	49	20.80	20.94	21.05	20.95	20.81		
10	16QAM	25	0	20.44	20.46	20.59	20.49	20.48	21	0.5
10	16QAM	25	12	20.42	20.47	20.55	20.51	20.31		
10	16QAM	25	25	20.31	20.44	20.50	20.44	20.33		
10	16QAM	50	0	20.32	20.41	20.56	20.43	20.34		
10	64QAM	1	0	20.24	20.21	20.44	20.44	20.40	21	0.5
10	64QAM	1	25	20.04	20.08	20.16	20.13	20.08		
10	64QAM	1	49	20.04	20.17	20.30	20.16	20.06		
10	64QAM	25	0	19.38	19.46	19.52	19.45	19.48		
10	64QAM	25	12	19.39	19.43	19.54	19.47	19.37	20	1.5
10	64QAM	25	25	19.28	19.37	19.43	19.35	19.31		
10	64QAM	50	0	19.30	19.39	19.53	19.47	19.44		
Channel				39675	40148	40620	41093	41565	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2498.5	2545.8	2593	2640.30	2687.5		
5	QPSK	1	0	20.91	20.98	21.22	21.13	21.13	21.5	0
5	QPSK	1	12	20.78	20.81	20.91	20.85	20.77		
5	QPSK	1	24	20.74	20.84	20.98	20.80	20.75		
5	QPSK	12	0	20.89	20.87	21.02	20.93	21.07	21.5	0
5	QPSK	12	7	20.85	20.85	20.98	20.94	20.80		
5	QPSK	12	13	20.77	20.88	21.07	20.85	20.73		
5	QPSK	25	0	20.84	20.90	21.00	20.98	20.82		
5	16QAM	1	0	21.08	21.35	21.26	21.29	21.31	21.5	0
5	16QAM	1	12	20.88	20.96	21.09	21.12	20.91		
5	16QAM	1	24	20.79	21.00	21.04	20.93	20.89		
5	16QAM	12	0	20.49	20.53	20.55	20.57	20.47	21	0.5
5	16QAM	12	7	20.36	20.49	20.54	20.51	20.38		
5	16QAM	12	13	20.37	20.40	20.57	20.44	20.37		
5	16QAM	25	0	20.40	20.47	20.55	20.46	20.32		
5	64QAM	1	0	20.25	20.20	20.45	20.52	20.33	21	0.5
5	64QAM	1	12	20.09	20.07	20.18	20.06	20.12		
5	64QAM	1	24	20.04	20.17	20.29	20.23	20.03		
5	64QAM	12	0	19.41	19.40	19.51	19.53	19.53	20	1.5
5	64QAM	12	7	19.35	19.43	19.53	19.49	19.39		
5	64QAM	12	13	19.32	19.39	19.44	19.45	19.36		
5	64QAM	25	0	19.31	19.48	19.56	19.45	19.44		

13. Antenna Location


Edge3
Front View

The separation distance for antenna to edge :

Antenna	To Edge1 (mm)	To Edge2 (mm)	To Edge3 (mm)	To Edge4 (mm)
WWAN	<5	26.4	185	178
WLAN/BT Antenna 0	100	272	70	<5
WLAN Antenna 1	<5	182	195	90

<SAR test exclusion table>
General Note:

- The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
- Maximum power is the source-based time-average power and represents the maximum RF output power among production units
- Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
- Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

Exposure Position	Wireless Interface	WCDMA Band V	WCDMA Band IV	WCDMA Band II	LTE Band 12	LTE Band 14	LTE Band 13	LTE Band 5	LTE Band 26	LTE Band 4	LTE Band 66	LTE Band 2	LTE Band 7	LTE Band 41
	Calculated Frequency	846MHz	1750MHz	1907MHz	715MHz	793MHz	784MHz	848MHz	848MHz	1754MHz	1779MHz	1909MHz	2567MHz	2687MHz
	Maximum power (dBm)	24	24	24	24	24	24	24	24	24	24	24	23	23
	Maximum rated power(mW)	251.0	251.0	251.0	251.0	251.0	251.0	251.0	251.0	251.0	251.0	251.0	200.0	200.0
Bottom Face	Separation distance(mm)	5.0												
	exclusion threshold	46.2	66.4	69.3	42.5	42.4	44.5	46.2	46.2	66.5	67.0	69.4	64.1	65.6
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	5.0												
	exclusion threshold	46.2	66.4	69.3	42.5	42.4	44.5	46.2	46.2	66.5	67.0	69.4	64.1	65.6
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Edge 2	Separation distance(mm)	26.4												
	exclusion threshold	8.7	12.6	13.1	8.0	8.0	8.4	8.8	8.8	12.6	12.7	13.1	12.1	12.4
	Testing required?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Edge 3	Separation distance(mm)	185.0												
	exclusion threshold	924.0	1463.0	1459.0	821.0	819.0	875.0	926.0	926.0	1463.0	1462.0	1459.0	1444.0	1442.0
	Testing required?	No	No	No	No	No	No	No	No	No	No	No	No	No
Edge 4	Separation distance(mm)	178.0												
	exclusion threshold	885.0	1393.0	1389.0	788.0	786.0	838.0	887.0	887.0	1393.0	1392.0	1389.0	1374.0	1372.0
	Testing required?	No	No	No	No	No	No	No	No	No	No	No	No	No

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. For the exposure positions that proximity sensor power reduction is applied for SAR compliance, additional SAR testing with EUT transmitting full power in normal mode was performed; 20mm for bottom face, 22mm for edge1.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B12 / B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 4/5 SAR test was covered by Band 66/26; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

14.1 Body SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Accessories	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WCDMA II	RMC 12.2Kbps	Bottom Face	20mm		OFF	9400	1880	23.97	24.00	1.007	0.02	0.860	0.866
	WCDMA II	RMC 12.2Kbps	Bottom Face	20mm		OFF	9262	1852.4	23.89	24.00	1.026	0.01	1.090	1.118
	WCDMA II	RMC 12.2Kbps	Bottom Face	20mm		OFF	9538	1907.6	23.86	24.00	1.033	0.01	0.721	0.745
	WCDMA II	RMC 12.2Kbps	Edge 1	22mm		OFF	9400	1880	23.97	24.00	1.007	0.01	0.486	0.489
	WCDMA II	RMC 12.2Kbps	Bottom Face	0mm		ON	9262	1852.4	15.98	16.00	1.005	-0.15	1.090	1.095
	WCDMA II	RMC 12.2Kbps	Bottom Face	0mm		ON	9400	1880	15.93	16.00	1.016	-0.13	0.985	1.001
	WCDMA II	RMC 12.2Kbps	Bottom Face	0mm		ON	9538	1907.6	15.89	16.00	1.026	-0.11	0.892	0.915
	WCDMA II	RMC 12.2Kbps	Edge 1	0mm		ON	9262	1852.4	15.98	16.00	1.005	-0.17	0.618	0.621
	WCDMA II	RMC 12.2Kbps	Edge 2	0mm		OFF	9400	1880	23.97	24.00	1.007	0.04	0.261	0.263
	WCDMA II	RMC 12.2Kbps	Bottom Face	0mm	Scanner+Battery 2	ON	9262	1852.4	15.98	16.00	1.005	0.03	0.269	0.270
02	WCDMA II	RMC 12.2Kbps	Bottom Face	0mm	USB+Battery 2	ON	9262	1852.4	15.98	16.00	1.005	-0.11	0.245	0.246
	WCDMA IV	RMC 12.2Kbps	Bottom Face	20mm		OFF	1413	1732.6	23.97	24.00	1.007	0.03	0.653	0.658
	WCDMA IV	RMC 12.2Kbps	Edge 1	22mm		OFF	1413	1732.6	23.97	24.00	1.007	-0.02	0.400	0.403
	WCDMA IV	RMC 12.2Kbps	Bottom Face	0mm		ON	1413	1732.6	16.59	16.60	1.002	-0.03	0.942	0.944
	WCDMA IV	RMC 12.2Kbps	Bottom Face	0mm		ON	1312	1712.4	16.57	16.60	1.007	-0.09	0.792	0.797
	WCDMA IV	RMC 12.2Kbps	Bottom Face	0mm		ON	1513	1752.6	16.56	16.60	1.009	-0.08	1.020	1.029
	WCDMA IV	RMC 12.2Kbps	Edge 1	0mm		ON	1413	1732.6	16.59	16.60	1.002	-0.19	0.476	0.477
	WCDMA IV	RMC 12.2Kbps	Edge 2	0mm		OFF	1413	1732.6	23.97	24.00	1.007	0.02	0.141	0.142
	WCDMA IV	RMC 12.2Kbps	Bottom Face	0mm	Scanner+Battery 2	ON	1513	1752.6	16.56	16.60	1.009	0.15	0.206	0.208
	WCDMA IV	RMC 12.2Kbps	Bottom Face	0mm	USB+Battery 2	ON	1513	1752.6	16.56	16.60	1.009	0.02	0.195	0.197
03	WCDMA V	RMC 12.2Kbps	Bottom Face	20mm		OFF	4182	836.4	23.75	24.00	1.059	-0.06	0.219	0.232
	WCDMA V	RMC 12.2Kbps	Edge 1	22mm		OFF	4182	836.4	23.75	24.00	1.059	-0.04	0.082	0.087
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm		ON	4182	836.4	21.00	21.00	1.000	-0.16	1.020	1.020
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm		ON	4132	826.4	20.91	21.00	1.021	-0.14	0.963	0.983
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm		ON	4233	846.6	20.88	21.00	1.028	-0.01	0.989	1.017
	WCDMA V	RMC 12.2Kbps	Edge 1	0mm		ON	4182	836.4	21.00	21.00	1.000	-0.16	0.328	0.328
	WCDMA V	RMC 12.2Kbps	Edge 2	0mm		OFF	4182	836.4	23.75	24.00	1.059	0.01	0.145	0.154
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm	Scanner+Battery 2	ON	4182	836.4	21.00	21.00	1.000	-0.09	0.243	0.243
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm	USB+Battery 2	ON	4182	836.4	21.00	21.00	1.000	0	0.229	0.229
	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm										



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessories	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Bottom Face	20mm		OFF	19100	1900	24.00	24.00	1.000	-0.02	0.740	0.740
	LTE Band 2	20M	QPSK	50	0	Bottom Face	20mm		OFF	19100	1900	23.00	23.00	1.000	0	0.562	0.562
	LTE Band 2	20M	QPSK	1	0	Edge 1	22mm		OFF	19100	1900	24.00	24.00	1.000	-0.02	0.431	0.431
	LTE Band 2	20M	QPSK	50	0	Edge 1	22mm		OFF	19100	1900	23.00	23.00	1.000	-0.06	0.324	0.324
	LTE Band 2	20M	QPSK	1	0	Bottom Face	0mm		ON	19100	1900	15.99	16.00	1.002	-0.13	0.945	0.947
04	LTE Band 2	20M	QPSK	1	0	Bottom Face	0mm		ON	18700	1860	15.69	16.00	1.074	-0.14	0.956	1.027
	LTE Band 2	20M	QPSK	1	0	Bottom Face	0mm		ON	18900	1880	15.68	16.00	1.076	-0.15	0.924	0.995
	LTE Band 2	20M	QPSK	50	0	Bottom Face	0mm		ON	19100	1900	15.97	16.00	1.007	-0.13	0.925	0.931
	LTE Band 2	20M	QPSK	50	0	Bottom Face	0mm		ON	18700	1860	15.68	16.00	1.076	-0.17	0.948	1.020
	LTE Band 2	20M	QPSK	50	0	Bottom Face	0mm		ON	18900	1880	15.73	16.00	1.064	-0.14	0.925	0.984
	LTE Band 2	20M	QPSK	100	0	Bottom Face	0mm		ON	19100	1900	15.92	16.00	1.019	-0.13	0.913	0.930
	LTE Band 2	20M	QPSK	1	0	Edge 1	0mm		ON	19100	1900	15.99	16.00	1.002	-0.12	0.467	0.468
	LTE Band 2	20M	QPSK	50	0	Edge 1	0mm		ON	19100	1900	15.97	16.00	1.007	-0.18	0.448	0.451
	LTE Band 2	20M	QPSK	1	0	Edge 2	0mm		OFF	19100	1900	24.00	24.00	1.000	0.07	0.263	0.263
	LTE Band 2	20M	QPSK	50	0	Edge 2	0mm		OFF	19100	1900	23.00	23.00	1.000	0.02	0.205	0.205
	LTE Band 2	20M	QPSK	1	0	Bottom Face	0mm	Scanner+Battery 2	ON	18700	1860	15.69	16.00	1.074	-0.15	0.249	0.267
	LTE Band 2	20M	QPSK	1	0	Bottom Face	0mm	USB+Battery 2	ON	18700	1860	15.69	16.00	1.074	-0.02	0.219	0.235
	LTE Band 7	20M	QPSK	1	0	Bottom Face	20mm		OFF	20850	2510	22.49	23.00	1.125	-0.17	0.167	0.188
	LTE Band 7	20M	QPSK	50	0	Bottom Face	20mm		OFF	20850	2510	21.40	22.00	1.148	0.12	0.139	0.160
	LTE Band 7	20M	QPSK	1	0	Edge 1	22mm		OFF	20850	2510	22.49	23.00	1.125	0	0.250	0.281
	LTE Band 7	20M	QPSK	50	0	Edge 1	22mm		OFF	20850	2510	21.40	22.00	1.148	0	0.198	0.227
	LTE Band 7	20M	QPSK	1	0	Bottom Face	0mm		ON	20850	2510	19.82	20.00	1.042	-0.04	0.935	0.975
	LTE Band 7	20M	QPSK	1	0	Bottom Face	0mm		ON	21100	2535	19.63	20.00	1.089	-0.04	0.960	1.045
05	LTE Band 7	20M	QPSK	1	0	Bottom Face	0mm		ON	21350	2560	19.74	20.00	1.062	-0.09	1.110	1.178
	LTE Band 7	20M	QPSK	50	0	Bottom Face	0mm		ON	21350	2560	19.59	20.00	1.099	-0.07	0.972	1.068
	LTE Band 7	20M	QPSK	50	0	Bottom Face	0mm		ON	20850	2510	19.41	20.00	1.146	-0.12	0.936	1.072
	LTE Band 7	20M	QPSK	50	0	Bottom Face	0mm		ON	21100	2535	19.41	20.00	1.146	-0.11	0.982	1.125
	LTE Band 7	20M	QPSK	100	0	Bottom Face	0mm		ON	21100	2535	19.59	20.00	1.099	-0.13	0.876	0.963
	LTE Band 7	20M	QPSK	1	0	Edge 1	0mm		ON	21100	2535	19.82	20.00	1.042	-0.04	0.852	0.888
	LTE Band 7	20M	QPSK	1	0	Edge 1	0mm		ON	20850	2510	19.63	20.00	1.089	-0.07	0.871	0.948
	LTE Band 7	20M	QPSK	1	0	Edge 1	0mm		ON	21350	2560	19.74	20.00	1.062	-0.02	0.785	0.833
	LTE Band 7	20M	QPSK	50	0	Edge 1	0mm		ON	21350	2560	19.59	20.00	1.099	-0.1	0.766	0.842
	LTE Band 7	20M	QPSK	50	0	Edge 1	0mm		ON	20850	2510	19.41	20.00	1.146	-0.06	0.866	0.992
	LTE Band 7	20M	QPSK	50	0	Edge 1	0mm		ON	21100	2535	19.41	20.00	1.146	-0.1	0.794	0.910
	LTE Band 7	20M	QPSK	100	0	Edge 1	0mm		ON	21100	2535	19.59	20.00	1.099	-0.04	0.750	0.824
	LTE Band 7	20M	QPSK	1	0	Edge 2	0mm		OFF	20850	2510	22.49	23.00	1.125	0.14	0.274	0.308
	LTE Band 7	20M	QPSK	50	0	Edge 2	0mm		OFF	20850	2510	21.40	22.00	1.148	0.18	0.209	0.240
	LTE Band 7	20M	QPSK	1	0	Bottom Face	0mm	Scanner+Battery 2	ON	21350	2560	19.74	20.00	1.062	0.03	0.155	0.165
	LTE Band 7	20M	QPSK	1	0	Bottom Face	0mm	USB+Battery 2	ON	21350	2560	19.74	20.00	1.062	0.01	0.159	0.169



FCC SAR TEST REPORT

Report No. : FA992410-02A

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessories	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	0	Bottom Face	20mm		OFF	23095	707.5	23.53	24.00	1.114	-0.03	0.104	0.116
	LTE Band 12	10M	QPSK	25	0	Bottom Face	20mm		OFF	23095	707.5	22.50	23.00	1.122	0	0.084	0.094
	LTE Band 12	10M	QPSK	1	0	Edge 1	22mm		OFF	23095	707.5	23.53	24.00	1.114	0.1	0.027	0.030
	LTE Band 12	10M	QPSK	25	0	Edge 1	22mm		OFF	23095	707.5	22.50	23.00	1.122	0.09	0.022	0.025
06	LTE Band 12	10M	QPSK	1	0	Bottom Face	0mm		ON	23095	707.5	23.05	23.50	1.109	-0.07	1.080	1.198
	LTE Band 12	10M	QPSK	25	0	Bottom Face	0mm		ON	23095	707.5	22.54	23.00	1.112	-0.18	0.993	1.104
	LTE Band 12	10M	QPSK	50	0	Bottom Face	0mm		ON	23095	707.5	22.49	23.00	1.125	0.11	1.030	1.158
	LTE Band 12	10M	QPSK	1	0	Edge 1	0mm		ON	23095	707.5	23.05	23.50	1.109	-0.1	0.284	0.315
	LTE Band 12	10M	QPSK	25	0	Edge 1	0mm		ON	23095	707.5	22.54	23.00	1.112	-0.19	0.263	0.292
	LTE Band 12	10M	QPSK	1	0	Edge 2	0mm		OFF	23095	707.5	23.53	24.00	1.114	-0.03	0.110	0.123
	LTE Band 12	10M	QPSK	25	0	Edge 2	0mm		OFF	23095	707.5	22.50	23.00	1.122	0.01	0.088	0.099
	LTE Band 12	10M	QPSK	1	0	Bottom Face	0mm	Scanner+Battery 2	ON	23095	707.5	23.05	23.50	1.109	-0.01	0.249	0.276
	LTE Band 12	10M	QPSK	1	0	Bottom Face	0mm	USB+Battery 2	ON	23095	707.5	23.05	23.50	1.109	-0.03	0.135	0.150
	LTE Band 13	10M	QPSK	1	0	Bottom Face	20mm		OFF	23230	782	23.25	24.00	1.189	-0.04	0.139	0.165
	LTE Band 13	10M	QPSK	25	0	Bottom Face	20mm		OFF	23230	782	22.30	23.00	1.175	-0.03	0.117	0.137
	LTE Band 13	10M	QPSK	1	0	Edge 1	22mm		OFF	23230	782	23.25	24.00	1.189	0	0.044	0.052
	LTE Band 13	10M	QPSK	25	0	Edge 1	22mm		OFF	23230	782	22.30	23.00	1.175	0.01	0.038	0.045
	LTE Band 13	10M	QPSK	1	0	Bottom Face	0mm		ON	23230	782	20.14	20.50	1.086	0.09	0.856	0.930
	LTE Band 13	10M	QPSK	25	0	Bottom Face	0mm		ON	23230	782	19.91	20.50	1.146	0.05	0.895	1.025
07	LTE Band 13	10M	QPSK	50	0	Bottom Face	0mm		ON	23230	782	19.84	20.50	1.164	-0.06	0.895	1.042
	LTE Band 13	10M	QPSK	1	0	Edge 1	0mm		ON	23230	782	20.14	20.50	1.086	0.13	0.626	0.680
	LTE Band 13	10M	QPSK	25	0	Edge 1	0mm		ON	23230	782	19.91	20.50	1.146	0.14	0.531	0.608
	LTE Band 13	10M	QPSK	1	0	Edge 2	0mm		OFF	23230	782	23.25	24.00	1.189	0.1	0.121	0.144
	LTE Band 13	10M	QPSK	25	0	Edge 2	0mm		OFF	23230	782	22.30	23.00	1.175	0.08	0.100	0.117
	LTE Band 13	10M	QPSK	50	0	Bottom Face	0mm	Scanner+Battery 2	ON	23230	782	19.84	20.50	1.164	0.02	0.164	0.191
	LTE Band 13	10M	QPSK	50	0	Bottom Face	0mm	USB+Battery 2	ON	23230	782	19.84	20.50	1.164	-0.05	0.149	0.173
	LTE Band 14	10M	QPSK	1	0	Bottom Face	20mm		OFF	23330	793	23.40	24.00	1.148	-0.04	0.152	0.175
	LTE Band 14	10M	QPSK	25	0	Bottom Face	20mm		OFF	23330	793	22.34	23.00	1.164	-0.15	0.122	0.142
	LTE Band 14	10M	QPSK	1	0	Edge 1	22mm		OFF	23330	793	23.40	24.00	1.148	0.01	0.054	0.062
	LTE Band 14	10M	QPSK	25	0	Edge 1	22mm		OFF	23330	793	22.34	23.00	1.164	0.03	0.045	0.052
	LTE Band 14	10M	QPSK	1	0	Bottom Face	0mm		ON	23330	793	20.65	21.00	1.084	0.13	0.997	1.081
	LTE Band 14	10M	QPSK	25	25	Bottom Face	0mm		ON	23330	793	20.45	21.00	1.135	0.04	1.030	1.169
08	LTE Band 14	10M	QPSK	50	0	Bottom Face	0mm		ON	23330	793	20.33	21.00	1.167	0.15	1.010	1.178
	LTE Band 14	10M	QPSK	1	0	Edge 1	0mm		ON	23330	793	20.65	21.00	1.084	-0.18	0.683	0.740
	LTE Band 14	10M	QPSK	25	25	Edge 1	0mm		ON	23330	793	20.45	21.00	1.135	-0.16	0.577	0.655
	LTE Band 14	10M	QPSK	1	0	Edge 2	0mm		OFF	23330	793	23.40	24.00	1.148	0.09	0.115	0.132
	LTE Band 14	10M	QPSK	25	0	Edge 2	0mm		OFF	23330	793	22.34	23.00	1.164	-0.02	0.089	0.104
	LTE Band 14	10M	QPSK	50	0	Bottom Face	0mm	Scanner+Battery 2	ON	23330	793	20.33	21.00	1.167	0.05	0.199	0.232
	LTE Band 14	10M	QPSK	50	0	Bottom Face	0mm	USB+Battery 2	ON	23330	793	20.33	21.00	1.167	-0.15	0.186	0.217



FCC SAR TEST REPORT

Report No. : FA992410-02A

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessories	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 26	15M	QPSK	1	0	Bottom Face	20mm		OFF	26865	831.5	23.48	24.00	1.127	-0.04	0.201	0.227
	LTE Band 26	15M	QPSK	36	0	Bottom Face	20mm		OFF	26865	831.5	22.53	23.00	1.114	-0.04	0.162	0.181
	LTE Band 26	15M	QPSK	1	0	Edge 1	22mm		OFF	26865	831.5	23.48	24.00	1.127	0.01	0.084	0.095
	LTE Band 26	15M	QPSK	36	0	Edge 1	22mm		OFF	26865	831.5	22.53	23.00	1.114	0	0.068	0.076
	LTE Band 26	15M	QPSK	1	0	Bottom Face	0mm		ON	26865	831.5	20.79	21.00	1.050	-0.14	0.906	0.951
09	LTE Band 26	15M	QPSK	36	20	Bottom Face	0mm		ON	26865	831.5	20.51	21.00	1.119	-0.19	0.955	1.069
	LTE Band 26	15M	QPSK	75	0	Bottom Face	0mm		ON	26865	831.5	20.50	21.00	1.122	-0.17	0.948	1.064
	LTE Band 26	15M	QPSK	1	0	Edge 1	0mm		ON	26865	831.5	20.79	21.00	1.050	-0.14	0.342	0.359
	LTE Band 26	15M	QPSK	36	20	Edge 1	0mm		ON	26865	831.5	20.51	21.00	1.119	-0.13	0.356	0.399
	LTE Band 26	15M	QPSK	1	0	Edge 2	0mm		OFF	26865	831.5	23.48	24.00	1.127	-0.01	0.131	0.148
	LTE Band 26	15M	QPSK	36	0	Edge 2	0mm		OFF	26865	831.5	22.53	23.00	1.114	0.03	0.105	0.117
	LTE Band 26	15M	QPSK	36	20	Bottom Face	0mm	Scanner+Battery 2	ON	26865	831.5	20.51	21.00	1.119	0.04	0.233	0.261
	LTE Band 26	15M	QPSK	36	20	Bottom Face	0mm	USB+Battery 2	ON	26865	831.5	20.51	21.00	1.119	0.01	0.206	0.231
	LTE Band 66	20M	QPSK	1	0	Bottom Face	20mm		OFF	132322	1745	23.97	24.00	1.007	-0.02	0.631	0.635
	LTE Band 66	20M	QPSK	50	0	Bottom Face	20mm		OFF	132322	1745	22.90	23.00	1.023	0.03	0.529	0.541
	LTE Band 66	20M	QPSK	1	0	Edge 1	22mm		OFF	132322	1745	23.97	24.00	1.007	-0.04	0.402	0.405
	LTE Band 66	20M	QPSK	50	0	Edge 1	22mm		OFF	132322	1745	22.90	23.00	1.023	-0.03	0.334	0.342
	LTE Band 66	20M	QPSK	1	0	Bottom Face	0mm		ON	132322	1745	16.57	16.60	1.007	0.02	0.894	0.900
	LTE Band 66	20M	QPSK	1	0	Bottom Face	0mm		ON	132072	1720	16.48	16.60	1.028	0.03	0.736	0.757
	LTE Band 66	20M	QPSK	1	0	Bottom Face	0mm		ON	132572	1770	16.47	16.60	1.030	0.02	1.050	1.082
	LTE Band 66	20M	QPSK	50	0	Bottom Face	0mm		ON	132322	1745	16.51	16.60	1.021	0.05	0.927	0.946
	LTE Band 66	20M	QPSK	50	0	Bottom Face	0mm		ON	132072	1720	16.47	16.60	1.030	0.03	0.756	0.779
10	LTE Band 66	20M	QPSK	50	0	Bottom Face	0mm		ON	132572	1770	16.48	16.60	1.028	0.03	1.080	1.110
	LTE Band 66	20M	QPSK	100	0	Bottom Face	0mm		ON	132322	1745	16.48	16.60	1.028	0	0.943	0.969
	LTE Band 66	20M	QPSK	1	0	Edge 1	0mm		ON	132322	1745	16.57	16.60	1.007	-0.15	0.480	0.483
	LTE Band 66	20M	QPSK	50	0	Edge 1	0mm		ON	132322	1745	16.51	16.60	1.021	-0.17	0.497	0.507
	LTE Band 66	20M	QPSK	1	0	Edge 2	0mm		OFF	132322	1745	23.97	24.00	1.007	0.09	0.140	0.141
	LTE Band 66	20M	QPSK	50	0	Edge 2	0mm		OFF	132322	1745	22.90	23.00	1.023	0.1	0.113	0.116
	LTE Band 66	20M	QPSK	50	0	Bottom Face	0mm	Scanner+Battery 2	ON	132572	1770	16.48	16.60	1.028	-0.02	0.233	0.240
	LTE Band 66	20M	QPSK	50	0	Bottom Face	0mm	USB+Battery 2	ON	132572	1770	16.48	16.60	1.028	-0.13	0.220	0.226

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Accessories	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Bottom Face	20mm		OFF	40620	2593	22.76	23.00	1.057	62.9	1.006	0.04	0.115	0.122
	LTE Band 41	20M	QPSK	50	0	Bottom Face	20mm		OFF	40620	2593	21.61	22.00	1.094	62.9	1.006	0.08	0.087	0.096
	LTE Band 41	20M	QPSK	1	0	Edge 1	22mm		OFF	40620	2593	22.76	23.00	1.057	62.9	1.006	0.04	0.102	0.108
	LTE Band 41	20M	QPSK	50	0	Edge 1	22mm		OFF	40620	2593	21.61	22.00	1.094	62.9	1.006	0	0.077	0.085
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm		ON	40620	2593	21.37	21.50	1.030	62.9	1.006	-0.12	0.974	1.010
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm		ON	39750	2506	20.94	21.50	1.138	62.9	1.006	-0.07	0.878	1.005
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm		ON	40185	2549.5	21.01	21.50	1.119	62.9	1.006	-0.08	0.925	1.042
11	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm		ON	41055	2636.5	21.20	21.50	1.072	62.9	1.006	-0.03	1.090	1.175
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm		ON	41490	2680	21.18	21.50	1.076	62.9	1.006	-0.08	0.918	0.994
	LTE Band 41	20M	QPSK	50	0	Bottom Face	0mm		ON	40620	2593	21.11	21.50	1.094	62.9	1.006	-0.03	1.050	1.156
	LTE Band 41	20M	QPSK	50	0	Bottom Face	0mm		ON	39750	2506	20.92	21.50	1.143	62.9	1.006	-0.07	0.940	1.081
	LTE Band 41	20M	QPSK	50	0	Bottom Face	0mm		ON	40185	2549.5	20.97	21.50	1.130	62.9	1.006	-0.02	1.030	1.171
	LTE Band 41	20M	QPSK	50	0	Bottom Face	0mm		ON	41055	2636.5	21.02	21.50	1.117	62.9	1.006	-0.03	1.040	1.169
	LTE Band 41	20M	QPSK	50	0	Bottom Face	0mm		ON	41490	2680	21.08	21.50	1.102	62.9	1.006	-0.04	0.909	1.007
	LTE Band 41	20M	QPSK	100	0	Bottom Face	0mm		ON	40620	2593	21.09	21.50	1.099	62.9	1.006	-0.11	1.060	1.172
	LTE Band 41	20M	QPSK	1	0	Edge 1	0mm		ON	40620	2593	21.37	21.50	1.030	62.9	1.006	0.01	0.425	0.441
	LTE Band 41	20M	QPSK	50	0	Edge 1	0mm		ON	40620	2593	21.11	21.50	1.094	62.9	1.006	-0.07	0.425	0.468
	LTE Band 41	20M	QPSK	1	0	Edge 2	0mm		OFF	40620	2593	22.76	23.00	1.057	62.9	1.006	0.15	0.222	0.236
	LTE Band 41	20M	QPSK	50	0	Edge 2	0mm		OFF	40620	2593	21.61	22.00	1.094	62.9	1.006	0.12	0.170	0.187
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm	Scanner+Battery 2	ON	41055	2636.5	21.20	21.50	1.072	62.9	1.006	0.04	0.143	0.154
	LTE Band 41	20M	QPSK	1	0	Bottom Face	0mm	USB+Battery 2	ON	41055	2636.5	21.20	21.50	1.072	62.9	1.006	0.02	0.133	0.143

14.2 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	Bottom Face	20mm	OFF	9262	1852.4	23.89	24.00	1.026	0.01	1.090	-	1.118
2nd	WCDMA II	RMC 12.2Kbps	Bottom Face	20mm	OFF	9262	1852.4	23.89	24.00	1.026	0.06	1.040	1.05	1.067
1st	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm	ON	4182	836.4	21.00	21.00	1.000	-0.16	1.020	-	1.020
2nd	WCDMA V	RMC 12.2Kbps	Bottom Face	0mm	ON	4182	836.4	21.00	21.00	1.000	-0.14	0.995	1.03	0.995
1st	LTE Band 7	20M_QPSK_1_0	Bottom Face	0mm	ON	21350	2560	19.74	20.00	1.062	-0.09	1.110	-	1.178
2nd	LTE Band 7	20M_QPSK_1_0	Bottom Face	0mm	ON	21350	2560	19.74	20.00	1.062	-0.01	1.100	1.01	1.168
1st	LTE Band 12	10M_QPSK_1_0	Bottom Face	0mm	ON	23095	707.5	23.05	23.50	1.109	-0.07	1.080	-	1.198
2nd	LTE Band 12	10M_QPSK_1_0	Bottom Face	0mm	ON	23095	707.5	23.05	23.50	1.109	-0.09	1.060	1.02	1.176
1st	LTE Band 66	20M_QPSK_50_0	Bottom Face	0mm	ON	132572	1770	16.48	16.60	1.028	0.03	1.080	-	1.110
2nd	LTE Band 66	20M_QPSK_50_0	Bottom Face	0mm	ON	132572	1770	16.48	16.60	1.028	-0.13	1.030	1.05	1.059

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WWAN + 2.4GHz WLAN ANT 0 + 2.4GHz WLAN ANT 1	Yes
2.	WWAN + Bluetooth ANT 0 + 2.4GHz WLAN ANT 1	Yes
3.	WWAN + 5GHz WLAN ANT 0 + 5GHz WLAN ANT 1	Yes
4.	WWAN + Bluetooth ANT 0 + 5GHz WLAN ANT 1	Yes

General Note:

1. The WLAN / Bluetooth module is also integrated into this host, WLAN /Bluetooth power and WLAN SAR testing results which can be referred to Sporton SAR Test Report, Report No.: FA992410-01 (FCC ID: ACJFZA3A).
2. All licensed modes share the same antenna part and cannot transmit simultaneously.
3. For SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
4. WLAN and Bluetooth share the same antenna 0, and cannot transmit simultaneously.
5. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
6. The Scaled SAR summation is calculated based on the same configuration and test position.
7. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation $< 1.6\text{W/kg}$.
 - ii) $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.
 - v) The SPLSR calculated results please refer to section 15.2.

**15.1 Body Exposure Conditions**

WWAN Band			Exposure Position	1	2	3	4	5	6	1+2+3 Summed 1g SAR (W/kg)	1+4+5 Summed 1g SAR (W/kg)	1+3+6 Summed 1g SAR (W/kg)	1+5+6 Summed 1g SAR (W/kg)	1+2+3 SPLSR	1+2+3 Case No	1+4+5 SPLSR	1+4+5 Case No	1+3+6 SPLSR	1+3+6 Case No	1+5+6 SPLSR	1+5+6 Case No
				WWAN	2.4GHz WLAN Ant 0	2.4GHz WLAN Ant 1	5GHz WLAN Ant 0	5GHz WLAN Ant 1	Bluetooth Ant 0												
				1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)												
WCDMA	WCDMA II	Bottom Face at 20mm	1.118	0.906	0.718	0.811	1.056	0.314	2.742	2.985	2.150	2.488	0.02	Case 1	0.03	Case 23	0.02	Case 45	0.03	Case 60	
		Edge 1 at 22mm	0.489		0.414		0.572		0.903	1.061	0.903	1.061									
		Bottom Face at 0mm	1.095	0.906	0.718	0.811	1.056	0.314	2.719	2.962	2.127	2.465	0.02	Case 2	0.03	Case 24	0.02	Case 46	0.03	Case 61	
		Edge 1 at 0mm	0.621		0.414		0.572		1.035	1.193	1.035	1.193									
		Edge 2 at 0mm	0.263						0.263	0.263	0.263	0.263									
	WCDMA IV	Bottom Face at 20mm	0.658	0.906	0.718	0.811	1.056	0.314	2.282	2.525	1.690	2.028	0.02	Case 3	0.02	Case 25	0.01	Case 47	0.02	Case 62	
		Edge 1 at 22mm	0.403		0.414		0.572		0.817	0.975	0.817	0.975									
		Bottom Face at 0mm	1.029	0.906	0.718	0.811	1.056	0.314	2.653	2.896	2.061	2.399	0.02	Case 4	0.02	Case 26	0.02	Case 48	0.02	Case 63	
		Edge 1 at 0mm	0.477		0.414		0.572		0.891	1.049	0.891	1.049									
		Edge 2 at 0mm	0.142						0.142	0.142	0.142	0.142									
	WCDMA V	Bottom Face at 20mm	0.232	0.906	0.718	0.811	1.056	0.314	1.856	2.099	1.264	1.602	0.02	Case 5	0.02	Case 27			0.01	Case 75	
		Edge 1 at 22mm	0.087		0.414		0.572		0.501	0.659	0.501	0.659									
		Bottom Face at 0mm	1.020	0.906	0.718	0.811	1.056	0.314	2.644	2.887	2.052	2.390	0.02	Case 6	0.02	Case 28	0.02	Case 49	0.02	Case 64	
		Edge 1 at 0mm	0.328		0.414		0.572		0.742	0.900	0.742	0.900									
		Edge 2 at 0mm	0.154						0.154	0.154	0.154	0.154									
LTE	LTE Band 2	Bottom Face at 20mm	0.740	0.906	0.718	0.811	1.056	0.314	2.364	2.607	1.772	2.110	0.02	Case 7	0.02	Case 29	0.01	Case 50	0.02	Case 65	
		Edge 1 at 22mm	0.431		0.414		0.572		0.845	1.003	0.845	1.003									
		Bottom Face at 0mm	1.027	0.906	0.718	0.811	1.056	0.314	2.651	2.894	2.059	2.397	0.02	Case 8	0.02	Case 30	0.02	Case 51	0.02	Case 66	
		Edge 1 at 0mm	0.468		0.414		0.572		0.882	1.040	0.882	1.040									
		Edge 2 at 0mm	0.263						0.263	0.263	0.263	0.263									
	LTE Band 7	Bottom Face at 20mm	0.188	0.906	0.718	0.811	1.056	0.314	1.812	2.055	1.220	1.558	0.02	Case 9	0.02	Case 31					
		Edge 1 at 22mm	0.281		0.414		0.572		0.695	0.853	0.695	0.853									
		Bottom Face at 0mm	1.178	0.906	0.718	0.811	1.056	0.314	2.802	3.045	2.210	2.548	0.02	Case 10	0.02	Case 32	0.02	Case 52	0.02	Case 67	
		Edge 1 at 0mm	0.992		0.414		0.572		1.406	1.564	1.406	1.564									
		Edge 2 at 0mm	0.308						0.308	0.308	0.308	0.308									
	LTE Band 12	Bottom Face at 20mm	0.116	0.906	0.718	0.811	1.056	0.314	1.740	1.983	1.148	1.486	0.02	Case 11	0.02	Case 33					
		Edge 1 at 22mm	0.030		0.414		0.572		0.444	0.602	0.444	0.602									
		Bottom Face at 0mm	1.198	0.906	0.718	0.811	1.056	0.314	2.822	3.065	2.230	2.568	0.02	Case 12	0.03	Case 34	0.02	Case 53	0.03	Case 68	
		Edge 1 at 0mm	0.315		0.414		0.572		0.729	0.887	0.729	0.887									
		Edge 2 at 0mm	0.123						0.123	0.123	0.123	0.123									
	LTE Band 13	Bottom Face at 20mm	0.165	0.906	0.718	0.811	1.056	0.314	1.789	2.032	1.197	1.535	0.02	Case 13	0.02	Case 35					
		Edge 1 at 22mm	0.052		0.414		0.572		0.466	0.624	0.466	0.624									
		Bottom Face at 0mm	1.042	0.906	0.718	0.811	1.056	0.314	2.666	2.909	2.074	2.412	0.02	Case 14	0.02	Case 36	0.02	Case 54	0.02	Case 69	
		Edge 1 at 0mm	0.680		0.414		0.572		1.094	1.252	1.094	1.252									
		Edge 2 at 0mm	0.144						0.144	0.144	0.144	0.144									
	LTE Band 14	Bottom Face at 20mm	0.175	0.906	0.718	0.811	1.056	0.314	1.799	2.042	1.207	1.545	0.02	Case 15	0.02	Case 37					
		Edge 1 at 22mm	0.062		0.414		0.572		0.476	0.634	0.476	0.634									
		Bottom Face at 0mm	1.178	0.906	0.718	0.811	1.056	0.314	2.802	3.045	2.210	2.548	0.02	Case 16	0.03	Case 38	0.02	Case 55	0.03	Case 70	
		Edge 1 at 0mm	0.740		0.414		0.572		1.154	1.312	1.154	1.312									
		Edge 2 at 0mm	0.132						0.132	0.132	0.132	0.132									
	LTE Band 26	Bottom Face at 20mm	0.227	0.906	0.718	0.811	1.056	0.314	1.851	2.094	1.259	1.597	0.02	Case 17	0.02	Case 39			0.01	Case 76	
		Edge 1 at 22mm	0.095		0.414		0.572		0.509	0.667	0.509	0.667									
		Bottom Face at 0mm	1.069	0.906	0.718	0.811	1.056	0.314	2.693	2.936	2.101	2.439	0.02	Case 18	0.02	Case 40	0.02	Case 56	0.02	Case 71	
		Edge 1 at 0mm	0.399		0.414		0.572		0.813	0.971	0.813	0.971									
		Edge 2 at 0mm	0.148						0.148	0.148	0.148	0.148									
	LTE Band 41	Bottom Face at 20mm	0.122	0.906	0.718	0.811	1.056	0.314	1.746	1.989	1.154	1.492	0.02	Case 19	0.02	Case 41					
		Edge 1 at 22mm	0.108		0.414		0.572		0.522	0.680	0.522	0.680									
		Bottom Face at 0mm	1.175	0.906	0.718	0.811	1.056	0.314	2.799	3.042	2.207	2.545	0.02	Case 20	0.02	Case 42	0.02	Case 57	0.02	Case 72	
		Edge 1 at 0mm	0.468		0.414		0.572		0.882	1.040	0.882	1.040									
		Edge 2 at 0mm	0.236						0.236	0.236	0.236	0.236									



FCC SAR TEST REPORT


Report No. : FA992410-02A

LTE Band 66	Bottom Face at 20mm	0.635	0.906	0.718	0.811	1.056	0.314	2.259	2.502	1.667	2.005	0.02	Case 21	0.02	Case 43	0.01	Case 58	0.02	Case 73
	Edge 1 at 22mm	0.405		0.414		0.572		0.819	0.977	0.819	0.977								
	Bottom Face at 0mm	1.110	0.906	0.718	0.811	1.056	0.314	2.734	2.977	2.142	2.480	0.02	Case 22	0.03	Case 44	0.02	Case 59	0.03	Case 74
	Edge 1 at 0mm	0.507		0.414		0.572		0.921	1.079	0.921	1.079								
	Edge 2 at 0mm	0.141						0.141	0.141	0.141	0.141								

15.2 SPLSR Evaluation and Analysis

General Note:

1. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary
2. The detail hotspot point for each transmitter in each exposure condition are showing as below figure and the minimum 3D distance for each sum combination is used for SPLSR analysis.

Bottom Face											
											
	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 1	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	221.4	2.02	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	121.2	1.84	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 2	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	221.4	2.00	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	121.2	1.81	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 3	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	222.5	1.56	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	122.4	1.38	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Band	Position	SAR (W/kg)	Gap	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
				(mm)	X	Y	Z				
Case 4	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	222.5	1.94	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	122.4	1.75	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				



FCC SAR TEST REPORT

Report No. : FA992410-02A

	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 5	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	225.3	1.14	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	125.5	0.95	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 6	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	225.3	1.93	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	125.5	1.74	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 7	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	222.6	1.65	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	122.1	1.46	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 8	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	222.6	1.93	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	122.1	1.75	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 9	LTE Band 7	Bottom Face	0.188	20	74.4	103.6	-0.18	244.7	1.09	0.00	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 7	Bottom Face	0.188	20	74.4	103.6	-0.18	151.4	0.91	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 10	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	244.7	2.08	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	151.4	1.90	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 11	LTE Band 12	Bottom Face	0.116	20	85	76.4	2.78	224.2	1.02	0.00	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 12	Bottom Face	0.116	20	85	76.4	2.78	124.1	0.83	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				




FCC SAR TEST REPORT

Report No. : FA992410-02A

	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 12	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	224.2	2.10	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	124.1	1.92	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 13	LTE Band 13	Bottom Face	0.165	20	85	79.5	2.83	226.9	1.07	0.00	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 13	Bottom Face	0.165	20	85	79.5	2.83	127.2	0.88	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 14	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	226.9	1.95	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	127.2	1.76	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 15	LTE Band 14	Bottom Face	0.175	20	86.5	79.5	2.07	227.6	1.08	0.00	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 14	Bottom Face	0.175	20	86.5	79.5	2.07	127.2	0.89	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 16	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	227.6	2.08	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	127.2	1.90	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 17	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	228.0	1.13	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	130.2	0.95	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 18	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	228.0	1.98	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	130.2	1.79	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				

	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 19	LTE Band 41	Bottom Face	0.122	20	84	99.8	0.63	244.9	1.03	0.00	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 41	Bottom Face	0.122	20	84	99.8	0.63	147.4	0.84	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 20	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	244.9	2.08	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	147.4	1.89	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 21	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	224.0	1.54	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	123.7	1.35	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 22	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	224.0	2.02	0.01	Not required
	WLAN2.4GHz_Ant 0		0.906	0	-14.99	-124.2	-0.2				
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	123.7	1.83	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	WLAN2.4GHz_Ant 0	Bottom Face	0.906	0	-14.99	-124.2	-0.2	123.1	1.62	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				

Bottom Face											
											
Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 23	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	229.6	1.93	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	123.8	2.17	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 24	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	229.6	1.91	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	123.8	2.15	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 25	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	230.6	1.47	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	125.0	1.71	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 26	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	230.6	1.84	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	125.0	2.09	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 27	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	233.4	1.04	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	128.1	1.29	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				



FCC SAR TEST REPORT

Report No. : FA992410-02A

	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 28	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	233.4	1.83	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	128.1	2.08	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 29	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	230.8	1.55	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	124.6	1.80	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 30	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	230.8	1.84	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	124.6	2.08	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 31	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 7	Bottom Face	0.188	20	74.4	103.6	-0.18	251.7	1.00	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 7	Bottom Face	0.188	20	74.4	103.6	-0.18	154.2	1.24	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 32	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	251.7	1.99	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	154.2	2.23	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 33	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 12	Bottom Face	0.116	20	85	76.4	2.78	232.3	0.93	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 12	Bottom Face	0.116	20	85	76.4	2.78	126.6	1.17	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 34	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	232.3	2.01	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	126.6	2.25	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				




FCC SAR TEST REPORT

Report No. : FA992410-02A

	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 35	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 13	Bottom Face	0.165	20	85	79.5	2.83	235.0	0.98	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 13	Bottom Face	0.165	20	85	79.5	2.83	129.7	1.22	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 36	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	235.0	1.85	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	129.7	2.10	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 37	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 14	Bottom Face	0.175	20	86.5	79.5	2.07	235.7	0.99	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 14	Bottom Face	0.175	20	86.5	79.5	2.07	129.7	1.23	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 38	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	235.7	1.99	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	129.7	2.23	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 39	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	235.8	1.04	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	132.9	1.28	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 40	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	235.8	1.88	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	132.9	2.13	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 41	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41	Bottom Face	0.122	20	84	99.8	0.63	252.4	0.93	0.00	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 41	Bottom Face	0.122	20	84	99.8	0.63	150.0	1.18	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				

	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 42	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	252.4	1.99	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	150.0	2.23	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 43	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	232.2	1.45	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	126.2	1.69	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 44	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	232.2	1.92	0.01	Not required
	WLAN5GHz_Ant 0		0.811	0	-30	-125.4	0.43				
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	126.2	2.17	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	WLAN5GHz_Ant 0	Bottom Face	0.811	0	-30	-125.4	0.43	137.7	1.87	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				

Bottom Face											
											
Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 45	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	221.9	1.43	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	121.2	1.84	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 46	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	221.9	1.41	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	121.2	1.81	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 47	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	222.9	0.97	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	122.4	1.38	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 48	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	222.9	1.34	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	122.4	1.75	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 49	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	225.8	1.33	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	125.5	1.74	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				




FCC SAR TEST REPORT

Report No. : FA992410-02A

	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 50	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	223.1	1.05	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	122.1	1.46	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 51	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	223.1	1.34	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	122.1	1.75	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 52	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	245.2	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	151.4	1.90	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 53	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	224.6	1.51	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	124.1	1.92	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 54	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	227.4	1.36	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	127.2	1.76	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 55	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	228.1	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	127.2	1.90	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 56	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	228.5	1.38	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	130.2	1.79	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				

	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 57	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	245.4	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	147.4	1.89	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 58	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	224.5	0.95	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	123.7	1.35	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
Case 59	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	224.5	1.42	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	123.7	1.83	0.02	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	123.2	1.03	0.01	Not required
	WLAN2.4GHz_Ant 1		0.718	0	81.42	-47.6	-1.17				

Bottom Face											
											
Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 60	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	221.9	1.43	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA II	Bottom Face	1.118	20	84.5	73.6	-0.03	123.8	2.17	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 61	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	221.9	1.41	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA II	Bottom Face	1.095	0	84.5	73.6	-0.03	123.8	2.15	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 62	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	222.9	0.97	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA IV	Bottom Face	0.658	20	84.5	74.8	-0.02	125.0	1.71	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 63	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	222.9	1.34	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA IV	Bottom Face	1.029	0	84.5	74.8	-0.02	125.0	2.09	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 64	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	225.8	1.33	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA V	Bottom Face	1.02	0	84.6	77.9	-0.1	128.1	2.08	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				



FCC SAR TEST REPORT

Report No. : FA992410-02A

	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 65	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	223.1	1.05	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 2	Bottom Face	0.74	20	85.6	74.4	0.56	124.6	1.80	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 66	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	223.1	1.34	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
Case 67	LTE Band 2	Bottom Face	1.027	0	85.6	74.4	0.56	124.6	2.08	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 68	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	245.2	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 7	Bottom Face	1.178	0	74.4	103.6	-0.18	154.2	2.23	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 69	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	224.6	1.51	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 12	Bottom Face	1.198	0	85	76.4	2.78	126.6	2.25	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 70	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	227.4	1.36	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
Case 71	LTE Band 13	Bottom Face	1.042	0	85	79.5	2.83	129.7	2.10	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 72	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	228.1	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 14	Bottom Face	1.178	0	86.5	79.5	2.07	129.7	2.23	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 73	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	228.5	1.38	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 26	Bottom Face	1.069	0	81.1	82.6	-0.06	132.9	2.13	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				



FCC SAR TEST REPORT

Report No. : FA992410-02A

	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 72	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	245.4	1.49	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 41	Bottom Face	1.175	0	84	99.8	0.63	150.0	2.23	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 73	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	224.5	0.95	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 66	Bottom Face	0.635	20	85.5	76	0.42	126.2	1.69	0.02	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 74	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	224.5	1.42	0.01	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 66	Bottom Face	1.11	0	85.5	76	0.42	126.2	2.17	0.03	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 75	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	225.8	0.55	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	WCDMA V	Bottom Face	0.232	20	84.6	77.9	-0.1	128.1	1.29	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
Case 76	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	228.5	0.54	0.00	Not required
	Bluetooth_Ant 0		0.314	0	-14.37	-125	-1.91				
	LTE Band 26	Bottom Face	0.227	20	81.1	82.6	-0.06	132.9	1.28	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				
	Bluetooth_Ant 0	Bottom Face	0.314	0	-14.37	-125	-1.91	124.7	1.37	0.01	Not required
	WLAN5GHz_Ant 1		1.056	0	85.4	-50.2	-0.2				

Test Engineer : Jay Jian Randy Lin Carter Jhuang James Chou and Andy Chiang

16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [8] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [9] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [10] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [11] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.