




PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. 410.290.6652 / Fax 410.290.6654
http://www.pctestlab.com



MEASUREMENT REPORT FCC Part 15B

Applicant Name:

Panasonic Corporation of North America
Two Riverfront Plaza, 9th Floor
Newark, NJ 07102-5490
United States

Date of Testing:

12/08/2015 - 1/11/2016

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1512142140.ACJ

| | |
|-------------------|---|
| FCC ID: | ACJFZN1A |
| APPLICANT: | Panasonic Corporation of North America |

Application Type:

Certification

EUT Type:

Portable Handset

Model(s):

FZ-N1WF

FCC Rule Part(s):

FCC Part 15 Subpart B

FCC Classification:

Part 15 Class B Computing Device Peripheral (JBP)


Test Procedure:

ANSI C63.4-2009

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2009 (See Test Report). The results shown herein are also deemed satisfactory evidence of compliance with Industry Canada Interference-Causing Equipment Standard ICES-003. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.



I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

NVLAP accreditation does not constitute any product endorsement by NVLAP or any agency of the United States Government. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.





Randy Ortanez
President




| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 1 of 16 | |

T A B L E O F C O N T E N T S


| | | |
|---|--|----|
| FCC Class B MEASUREMENT REPORT | | 3 |
| 1.0 INTRODUCTION | | 4 |
| 1.1 Scope | | 4 |
| 1.2 PCTEST Test Location | | 4 |
| 2.0 PRODUCT INFORMATION..... | | 5 |
| 2.1 Equipment Description..... | | 5 |
| 2.2 Device Capabilities | | 5 |
| 2.3 Test Configuration | | 5 |
| 2.4 EMI Suppression Device(s)/Modifications | | 5 |
| 2.5 Labeling Requirements..... | | 5 |
| 3.0 DESCRIPTION OF TESTS | | 6 |
| 3.1 Evaluation Procedure | | 6 |
| 3.2 AC Line Conducted Emissions | | 6 |
| 3.3 Radiated Emissions..... | | 7 |
| 4.0 SAMPLE CALCULATIONS | | 8 |
| 4.1 Conducted Emission Measurement Sample Calculation | | 8 |
| 4.2 Radiated Emission Measurement Sample Calculation | | 8 |
| 5.0 TEST EQUIPMENT CALIBRATION DATA | | 9 |
| 6.0 ENVIRONMENTAL CONDITIONS..... | | 10 |
| 7.0 TEST DATA..... | | 11 |
| 7.1 Summary | | 11 |
| 7.2 Test Support Equipment..... | | 11 |
| 7.3 Radiated Measurement Data..... | | 12 |
| 7.4 Line Conducted Measurement Data | | 14 |
| 8.0 CONCLUSION..... | | 16 |

| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | | Page 2 of 16 |



MEASUREMENT REPORT

FCC Part 15B – Unintentional Radiators



§ 2.1033 General Information

APPLICANT: Panasonic Corporation of North America
APPLICANT ADDRESS: Two Riverfront Plaza, 9th Floor
 Newark, NJ 07102-5490
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): FCC Part 15 Subpart B
FCC ID: ACJFZN1A
Test Device Serial No.: 353550070002081 Production Pre-Production Engineering
FCC CLASSIFICATION: FCC Class B Digital Device (JBP)
DATE(S) OF TEST: 12/08/2015 - 1/11/2016



Test Methodology

Both conducted and radiated measurements were taken using the methods and procedures described in ANSI C63.4-2009. Radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility / NVLAP Accreditation

Conducted and radiated tests were performed at PCTEST Engineering Lab in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.

| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 3 of 16 | |

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'tl (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

| | | | | |
|--------------------------------------|---------------------------------------|---|--|---------------------------------|
| FCC ID: ACJFZN1A | | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) | | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | | Page 4 of 16 |

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Panasonic Portable Handset FCC ID: ACJFZN1A**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.

2.2 Device Capabilities

This device contains the following capabilities:

802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The Panasonic Portable Handset FCC ID: ACJFZN1A was tested with a laptop PC connected via USB interface port. The EUT was exercised during testing by means of software installed on the PC. Since the EUT is a peripheral device, the host PC was populated with another USB device and an additional peripheral device with a non-USB interface, as shown in Table 7-2, thus satisfying the minimum system requirement of two different I/O interfaces. All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2009 and manipulated to obtain worst case emissions.

For more information please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

2.4 EMI Suppression Device(s)/Modifications



No EMI suppression device(s) were added and no modifications were made during testing.

2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

| | | | | |
|--------------------------------------|---|---|---|---------------------------------|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 5 of 16 | |

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2009) was used in the measurement of the **Panasonic Portable Handset FCC ID: ACJFZN1A**.

Deviation from measurement procedure.....None



3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.4. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.



| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 6 of 16 | |

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by varying: the mode of operation or resolution, clock or data rate, scrolling H pattern to the EUT and/or support equipment, and changing the polarity of the receive antenna, whichever produced the worst-case emissions. To record the final measurements, the analyzer detector function was set to CISPR quasi-peak mode and the bandwidth of the spectrum analyzer was set to 120kHz for frequencies below 1GHz or 1MHz for frequencies above 1GHz. For average measurements above 1GHz, the analyzer was set to RMS detector with RBW = 1MHz and VBW = 3MHz.

| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 7 of 16 | |

4.0 SAMPLE CALCULATIONS

4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

| | | |
|-----------------------|---|--|
| Class B limit | = | 60.0 dB μ V (Quasi-peak limit) |
| Reading | = | - 57.8 dBm (calibrated quasi-peak level) |
| Convert to dB μ V | = | - 57.8 + 107 = 49.2 dB μ V |
| Margin | = | 49.2 - 60.0 = - 10.8 dB |
| | = | 10.8 dB below limit |

4.2 Radiated Emission Measurement Sample Calculation



@ 66.7 MHz

| | | |
|-----------------------------|---|-----------------------------------|
| Class B limit | = | 100 μ V/m = 40.0 dB μ V/m |
| Reading | = | - 76.0 dBm (calibrated level) |
| Convert to dB μ V | = | - 76.0 + 107 = 31.0 dB μ V |
| Antenna Factor + Cable Loss | = | 5.8 dB/m |
| Total | = | 36.8 dB μ V/m |
| Margin | = | 36.8 - 40.0 = - 3.2 dB |
| | = | 3.2 dB below limit |

Note:

$$\text{Level [dB}\mu\text{V]} = 20 \log_{10} (\text{Level } [\mu\text{V/m}])$$

$$\text{Level [dB}\mu\text{V]} = \text{Level [dBm]} + 107$$



| | | | | |
|--------------------------------------|---|---|---|---------------------------------|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 8 of 16 | |

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------|-----------|--|------------|--------------|------------|---------------|
| - | RE1 | Radiated Emissions Cable Set (UHF/EHF) | 4/28/2015 | Annual | 4/28/2016 | N/A |
| Agilent | 8447D | Broadband Amplifier | 6/12/2015 | Annual | 6/12/2016 | 1937A03348 |
| Agilent | N9038A | MXE EMI Receiver | 3/24/2015 | Annual | 3/24/2016 | MY51210133 |
| Emco | 6502 | Active Loop Antenna (10k - 30 MHz) | 6/24/2014 | Biennial | 6/24/2016 | 267 |
| ETS-Lindgren | 3816/2NM | Line Impedance Stabilization Network | 11/11/2014 | Biennial | 11/11/2016 | 114451 |
| Rohde & Schwarz | ESU26 | EMI Test Receiver (26.5GHz) | 3/12/2015 | Annual | 3/12/2016 | 100342 |
| Seekonk | NC-100 | Torque Wrench 5/16", 8" lbs | 3/18/2014 | Biennial | 3/18/2016 | N/A |
| Sunol | JB5 | Bi-Log Antenna (30M - 5GHz) | 1/28/2014 | Biennial | 1/28/2016 | A051107 |
| Sunol | DRH-118 | Horn Antenna (1-18 GHz) | 7/30/2015 | Biennial | 7/30/2017 | A042511 |
| VWR | 62344-734 | Thermometer with Clock | 2/20/2014 | Biennial | 2/20/2016 | 140140420 |

Table 5-1. Annual Test Equipment Calibration Schedule



| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 9 of 16 | |

6.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C.

The relative humidity is controlled within range of 10% to 75%.

The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 10 of 16 | |

7.0 TEST DATA

7.1 Summary

Test Date(s): 12/08/2015 - 1/11/2016

Test Engineer: Mohammed Ussaid

| FCC Part 15 Section | Description | Result |
|---------------------|---------------------|--------|
| 15.107 | Conducted Emissions | PASS |
| 15.109 | Radiated Emissions | PASS |

Table 7-1. Summary of Test Results

7.2 Test Support Equipment

| | | | |
|---|---|---|--------------------|
| 1 | Panasonic Data Link Cable | Model: N/A | S/N: N/A |
| | | 1.2m Shielded USB Cable | |
| 2 | Dell Notebook PC #2 w/ Dell AC Adapter | Model: Vostro 3555 (DoC) | A/N: N/A |
| | | Model: PA-1600-06D2 | S/N: N/A |
| | | 0.85m Unshielded AC power cord | |
| | | 1.80m Unshielded DC power cord with ferrite bead on notebook | |
| 3 | Dynex USB PC Camera | Model: DX-WC101 (DoC) | S/N: 122D05AC |
| | | 2.07m Shielded USB Cable | |
| 4 | Insignia 19" LCD Monitor | Model: NS-L19Q-10A (DoC) | S/N: V1297JA025798 |
| | | 1.92m Unshielded AC power cord | |

Table 7-2. Test Support Equipment Used

Note: See test setup photographs for actual system test setup.

7.3 Radiated Measurement Data

§15.109; RSS-Gen (6(a))

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Radiated Test Setup



| | | | |
|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 12 of 16 |

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [m] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dB μ V/m] | Limit [dB μ V/m] | Margin [dB] |
|-----------------|------------|-----------------|--------------------|----------------------------|----------------------|-------------|-------------------------------|----------------------|-------------|
| 76.63 | Quasi-Peak | H | 1.12 | 198 | -77.54 | 8.52 | 37.98 | 40.00 | -2.02 |
| 78.19 | Quasi-Peak | V | 1.58 | 300 | -77.25 | 8.47 | 38.22 | 40.00 | -1.78 |
| 333.12 | Quasi-Peak | V | 2.05 | 156 | -85.09 | 15.74 | 37.65 | 46.02 | -8.37 |
| 366.00 | Quasi-Peak | H | 1.01 | 289 | -79.25 | 16.70 | 44.45 | 46.02 | -1.57 |
| 597.38 | Quasi-Peak | H | 1.30 | 255 | -83.56 | 20.57 | 44.02 | 46.02 | -2.00 |
| 698.74 | Quasi-Peak | H | 1.45 | 190 | -91.67 | 22.05 | 37.38 | 46.02 | -8.64 |

Table 7-3. Radiated Measurements at 3-meters


Notes:

- All modes of operation were investigated and the worst-case emissions are reported.
- Radiated emissions were measured from 30MHz – 6GHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
- The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.109(a).
- All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
- AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
- Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
- Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
- Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a RMS detector using a resolution bandwidth of 1MHz and a video bandwidth of 3MHz.
- Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
- Calibrated low-loss microwaves cables and broadband amplifiers are used.

| | | | | |
|--------------------------------------|---|---|---|---------------------------------|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | Page 13 of 16 | |

7.4 Line Conducted Measurement Data

\$15.107; RSS-Gen (7.2.2)



Plot 7-1. Line Conducted Data (L1)


Notes:

- All Modes of operation were investigated and the worst-case emissions are reported.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Reading (dBµV) + Factor (dB)
- Margin (dB) = QP/AV Limit (dBµV) – QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

| | | | | |
|--------------------------------------|---------------------------------------|---|--|---------------------------------|
| FCC ID: ACJFZN1A | | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) | | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | | Page 14 of 16 |

Line Conducted Measurement Data (Cont'd)

\$15.107; RSS-Gen (7.2.2)



Plot 7-2. Line Conducted Data (LN)



Notes:

- All Modes of operation were investigated and the worst-case emissions are reported.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dB μ V) = QP/AV Reading (dB μ V) + Factor (dB)
- Margin (dB) = QP/AV Limit (dB μ V) – QP/AV Level (dB μ V)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

| | | | | |
|--------------------------------------|---------------------------------------|---|--|---------------------------------|
| FCC ID: ACJFZN1A | | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) | | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | | Page 15 of 16 |

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Panasonic Portable Handset FCC ID: ACJFZN1A** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC Rules and Industry Canada Standard ICES-003.

| | | | | |
|---|---|---|---|--|
| FCC ID: ACJFZN1A |  | FCC Pt. 15B MEASUREMENT REPORT (CERTIFICATION) |  | Reviewed by: Quality Manager |
| Test Report S/N: 0Y1512142140.ACJ | Test Dates: 12/08/2015 - 1/11/2016 | EUT Type: Portable Handset | | Page 16 of 16 |