



FCC SAR TEST REPORT

FCC ID : ACJFZT1A
Equipment : Tablet Computer
Brand Name : Panasonic
Model Name : FZ-T1BB, FZ-T1BC
Applicant : Panasonic Corporation of North America
Two Riverfront Plaza, 9th Floor, Newark, NJ
07102-5490
Manufacturer : Panasonic Mobile Communications Co., Ltd.
600 Saedo-cho, Tsuzuki-ku, Yokohama City
224-8539, Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Jul. 16, 2018 and testing was started from Jul. 16, 2018 and completed on Aug. 24, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	6
4. RF Exposure Limits.....	8
4.1 Uncontrolled Environment.....	8
4.2 Controlled Environment.....	8
5. Specific Absorption Rate (SAR).....	9
5.1 Introduction	9
5.2 SAR Definition.....	9
6. System Description and Setup	10
6.1 E-Field Probe	11
6.2 Data Acquisition Electronics (DAE)	11
6.3 Phantom.....	12
6.4 Device Holder.....	13
7. Measurement Procedures	14
7.1 Spatial Peak SAR Evaluation.....	14
7.2 Power Reference Measurement.....	15
7.3 Area Scan	15
7.4 Zoom Scan.....	16
7.5 Volume Scan Procedures.....	16
7.6 Power Drift Monitoring.....	16
8. Test Equipment List.....	17
9. System Verification	18
9.1 Tissue Simulating Liquids.....	18
9.2 Tissue Verification	19
9.3 System Performance Check Results.....	20
10. RF Exposure Positions	20
10.1 Ear and handset reference point.....	21
10.2 Definition of the cheek position	22
10.3 Definition of the tilt position	23
10.4 Body Worn Accessory	23
10.5 Product Specific Exposure	24
10.6 Wireless Router.....	24
11. Conducted RF Output Power (Unit: dBm).....	25
12. Antenna Location	41
13. SAR Test Results	42
13.1 Head SAR	44
13.2 Hotspot SAR	46
13.3 Product Specific SAR.....	49
13.4 Body Worn Accessory SAR.....	50
13.5 Repeated SAR Measurement	52
14. Simultaneous Transmission Analysis.....	53
14.1 Head Exposure Conditions	54
14.2 Hotspot Exposure Conditions.....	55
14.3 Product Specific Conditions	56
14.4 Body-Worn Accessory Exposure Conditions	56
14.5 SPLSR Evaluation and Analysis.....	57
15. Uncertainty Assessment	63
16. References.....	63
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASy Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA870417	01	Initial issue of report	Aug. 22, 2018
FA870417	02	Update section1, 8, 9, 13.2, 14.2, 14.5	Aug. 27, 2018

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Panasonic Corporation of North America, Tablet Computer, FZ-T1BB, FZ-T1BC, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary				Highest Simultaneous Transmission 1g SAR (W/kg)
		Head (Separation 0mm)	Body-worn (Separation 10mm)	Hotspot (Separation 10mm)	Product Specific (Separation 0mm)	
		1g SAR (W/kg)			10g SAR (W/kg)	
Licensed	WCDMA II	0.68	1.44	1.44	2.61	1.46
	WCDMA V	0.44	0.71	0.71		
	LTE Band 2	0.77	1.44	1.44	2.82	
	LTE Band 4	0.84	1.08	1.08		
	LTE Band 5	0.44	0.62	0.62		
	LTE Band 12	0.31	0.53	0.53		
	LTE Band 13	0.37	0.68	0.68		
DTS	2.4GHz WLAN	0.42	0.18	0.19		1.44
NII	5GHz WLAN	0.28	0.75	0.29	0.66	1.45
DSS	Bluetooth	0.03	0.02	0.02		1.46
Date of Testing:		2018/7/16 ~ 2018/8/24				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Eric Huang
Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Tablet Computer
Brand Name	Panasonic
Model Name	FZ-T1BB, FZ-T1BC
FCC ID	ACJFZT1A
IMEI Code	358384090005170
Wireless Technology and Frequency Range	WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	AMR / RMC 12.2Kbps HSDPA HSUPA LTE: QPSK, 16QAM 802.11a/b/g/n HT20/HT40 Bluetooth BR/EDR/LE
EUT Stage	Identical Prototype
Remark: 1. This device WLAN 2.4GHz supports Hotspot operation, Bluetooth support tethering applications, WLAN 5GHz B1/B4 support WiFi Direct group owner. 2. This product can be combined with a gun handle and the gun handle does not supports any RF transmitters, the hand SAR does not necessary, due to the device overall diagonal dimension > 16.0 cm has been considered basic hand SAR requirement according to KDB 648474 D04v01r03. 3. The device supports specific holster at body-worn condition, the test condition for body-worn with holster is not necessary, due to the distance is 20mm away human body when the device attach the holster is higher than the current body-worn test distance, please kindly refer appendix D. 4. WWAN function of Model: FZ-T1BC is disabled by the embedded software; cannot and will not be enabled via the end user or the grantee. 5. All the test results were performed with sample 1.	

Sample List	
Sample 1	FZ-T1BB
Sample 2	FZ-T1BC



3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	ACJFZT1A							
Equipment Name	Tablet Computer							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13: 779.5 MHz ~ 784.5 MHz							
Channel Bandwidth	LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 13: 5MHz, 10MHz							
uplink modulations used	QPSK / 16QAM							
LTE Voice / Data requirements	Voice and Data							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
	256 QAM	≥ 1						≤ 5
	LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)						
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1107	Feb. 27, 2018	Feb. 26, 2019
SPEAG	835MHz System Validation Kit	D835V2	4d167	Feb. 27, 2018	Feb. 26, 2019
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 15, 2017	Nov. 14, 2018
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Sep. 28, 2017	Sep. 27, 2018
SPEAG	2450MHz System Validation Kit	D2450V2	736	Sep. 18, 2017	Sep. 17, 2018
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 26, 2017	Sep. 25, 2018
SPEAG	Data Acquisition Electronics	DAE4	1424	Jan. 18, 2018	Jan. 17, 2019
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 16, 2017	Nov. 15, 2018
SPEAG	Data Acquisition Electronics	DAE4	778	May. 25, 2018	May. 24, 2019
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 25, 2017	Sep. 24, 2018
SPEAG	Data Acquisition Electronics	DAE4	853	Jul. 19, 2017	Jul. 18, 2018
SPEAG	Data Acquisition Electronics	DAE4	917	Dec. 14, 2017	Dec. 13, 2018
SPEAG	Data Acquisition Electronics	DAE3	495	May. 24, 2018	May. 23, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	3976	Jan. 23, 2018	Jan. 22, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 25, 2017	Sep. 24, 2018
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 29, 2017	Sep. 28, 2018
SPEAG	Dosimetric E-Field Probe	ES3DV3	3169	May. 28, 2018	May. 27, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3170	Oct. 26, 2017	Oct. 25, 2018
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	May. 31, 2018	May. 30, 2019
RCPTWN	Thermometer	HTC-1	TM560-1	Mar. 16, 2018	Mar. 15, 2019
Gencom	Thermometer	TE1	TM225-1	Mar. 16, 2018	Mar. 15, 2019
WonDer	Thermometer	WD-5016	TM642-1	Mar. 16, 2018	Mar. 15, 2019
WonDer	Thermometer	WD-5016	TM131-1	Mar. 16, 2018	Mar. 15, 2019
WonDer	Thermometer	WD-5016	TM132-1	Mar. 16, 2018	Mar. 15, 2019
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 17, 2018	Apr. 16, 2019
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 21, 2018	May. 20, 2019
R&S	BT Base Station	CBT	100815	Feb. 05, 2018	Feb. 04, 2019
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Dec. 07, 2017	Dec. 06, 2018
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 17, 2018	Jan. 16, 2019
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 26, 2017	Sep. 25, 2018
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 06, 2017	Sep. 05, 2018
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019
Anritsu	Power Meter	ML2495A	1218006	Oct. 06, 2017	Oct. 05, 2018
Anritsu	Power Sensor	MA2411B	1207363	Oct. 06, 2017	Oct. 05, 2018
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019
Mini-Circuits	Power Amplifier	ZVE-8G+	D120604	Mar. 12, 2018	Mar. 11, 2019
Mini-Circuits	Power Amplifier	ZHL-42W+	QA1344002	Mar. 12, 2018	Mar. 11, 2019
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005-3	N/A	Note 1	

General Note:

- Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.2	0.893	40.485	0.89	41.90	0.34	-3.38	±5	2018/7/18
750	MSL	22.6	0.972	54.534	0.96	55.50	1.25	-1.74	±5	2018/7/20
835	HSL	22.5	0.880	40.542	0.90	41.50	-2.22	-2.31	±5	2018/7/16
835	MSL	22.7	0.966	56.947	0.97	55.20	-0.41	3.16	±5	2018/7/19
1750	HSL	22.3	1.364	40.866	1.37	40.10	-0.44	1.91	±5	2018/7/18
1750	MSL	22.7	1.492	53.456	1.49	53.40	0.13	0.10	±5	2018/7/19
1900	HSL	22.3	1.447	39.730	1.40	40.00	3.36	-0.68	±5	2018/7/18
1900	HSL	22.4	1.420	40.800	1.40	40.00	1.43	2.00	±5	2018/7/25
1900	MSL	22.5	1.560	53.388	1.52	53.30	2.63	0.17	±5	2018/7/25
2450	HSL	22.6	1.846	38.765	1.80	39.20	2.56	-1.11	±5	2018/7/20
2450	HSL	22.5	1.780	40.500	1.80	39.20	-1.11	3.32	±5	2018/7/25
2450	MSL	22.5	1.975	51.195	1.95	52.70	1.28	-2.86	±5	2018/7/23
2450	MSL	22.4	1.996	53.444	1.95	52.70	2.36	1.41	±5	2018/7/26
5250	HSL	22.5	4.648	36.980	4.71	35.95	-1.32	2.87	±5	2018/7/24
5250	MSL	22.5	5.550	47.797	5.36	48.95	3.54	-2.36	±5	2018/7/23
5250	MSL	22.6	5.468	48.253	5.36	48.95	2.01	-1.42	±5	2018/8/24
5600	HSL	22.5	4.995	36.475	5.07	35.50	-1.48	2.75	±5	2018/7/24
5600	MSL	22.5	5.994	47.122	5.77	48.50	3.88	-2.84	±5	2018/7/23
5750	HSL	22.5	5.171	36.316	5.22	35.35	-0.94	2.73	±5	2018/7/24
5750	MSL	22.5	6.194	46.842	5.94	48.28	4.28	-2.98	±5	2018/7/23
5750	MSL	22.6	6.166	47.404	5.94	48.28	3.80	-1.81	±5	2018/8/24

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2018/7/18	750	HSL	250	D750V3-1107	ES3DV3 - SN3169	DAE3 Sn577	1.90	8.18	7.6	-7.09
2018/7/20	750	MSL	250	D750V3-1107	ES3DV3 - SN3169	DAE3 Sn577	2.16	8.52	8.64	1.41
2018/7/16	835	HSL	250	D835V2-4d167	ES3DV3 - SN3170	DAE4 Sn853	2.44	9.26	9.76	5.40
2018/7/19	835	MSL	250	D835V2-4d167	ES3DV3 - SN3169	DAE3 Sn577	2.39	9.62	9.56	-0.62
2018/7/18	1750	HSL	250	D1750V2-1068	ES3DV3 - SN3169	DAE3 Sn577	8.99	36.70	35.96	-2.02
2018/7/19	1750	MSL	250	D1750V2-1068	ES3DV3 - SN3169	DAE3 Sn577	9.39	37.20	37.56	0.97
2018/7/18	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3169	DAE3 Sn577	10.00	40.50	40	-1.23
2018/7/25	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3169	DAE4 Sn917	9.91	40.50	39.64	-2.12
2018/7/25	1900	MSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE4 Sn778	10.10	40.70	40.4	-0.74
2018/7/20	2450	HSL	250	D2450V2-736	ES3DV3 - SN3169	DAE3 Sn577	13.60	52.40	54.4	3.82
2018/7/25	2450	HSL	250	D2450V2-736	ES3DV3 - SN3169	DAE4 Sn917	13.00	52.40	52	-0.76
2018/7/23	2450	MSL	250	D2450V2-736	ES3DV3 - SN3169	DAE3 Sn577	12.70	50.80	50.8	0.00
2018/7/26	2450	MSL	250	D2450V2-736	ES3DV3 - SN3270	DAE4 Sn778	12.90	50.80	51.6	1.57
2018/7/24	5250	HSL	100	D5GHZV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	8.26	78.30	82.6	5.49
2018/7/23	5250	MSL	100	D5GHZV2-1006	EX3DV4 - SN3931	DAE4 Sn1399	7.23	77.00	72.3	-6.10
2018/8/24	5250	MSL	100	D5GHZV2-1006	EX3DV4 - SN3925	DAE3 Sn495	7.96	77.00	79.6	3.38
2018/7/24	5600	HSL	100	D5GHZV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	8.85	85.00	88.5	4.12
2018/7/23	5600	MSL	100	D5GHZV2-1006	EX3DV4 - SN3931	DAE4 Sn1399	8.10	80.10	81	1.12
2018/7/24	5750	HSL	100	D5GHZV2-1006	EX3DV4 - SN3976	DAE4 Sn1424	7.35	78.50	73.5	-6.37
2018/7/23	5750	MSL	100	D5GHZV2-1006	EX3DV4 - SN3931	DAE4 Sn1399	7.30	75.10	73	-2.80
2018/8/24	5750	MSL	100	D5GHZV2-1006	EX3DV4 - SN3925	DAE3 Sn495	7.10	75.10	71	-5.46

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2018/7/25	1900	MSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE4 Sn778	5.25	21.40	21	-1.87
2018/7/23	5250	MSL	100	D5GHZV2-1006	EX3DV4 - SN3931	DAE4 Sn1399	2.06	21.30	20.6	-3.29
2018/7/23	5600	MSL	100	D5GHZV2-1006	EX3DV4 - SN3931	DAE4 Sn1399	2.29	22.40	22.9	2.23




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11. Conducted RF Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes HSDPA / HSUPA are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		4132	4182	4233	
Rx Channel		9662	9800	9938		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	22.93	22.99	23.12	23.20	23.13	23.11	23.07	24.50
3GPP Rel 99	RMC 12.2Kbps	22.94	23.00	23.13	23.20	23.15	23.06	22.97	24.50
3GPP Rel 6	HSDPA Subtest-1	21.79	21.83	22.02	23.20	22.15	22.13	22.12	24.50
3GPP Rel 6	HSDPA Subtest-2	21.99	21.86	22.13	23.00	22.18	22.09	22.04	24.50
3GPP Rel 6	HSDPA Subtest-3	21.22	21.20	21.60	22.70	21.62	21.57	21.55	24.00
3GPP Rel 6	HSDPA Subtest-4	21.21	21.32	21.50	22.70	21.65	21.63	21.50	24.00
3GPP Rel 6	HSUPA Subtest-1	21.63	21.40	21.80	23.20	21.43	21.49	22.07	24.50
3GPP Rel 6	HSUPA Subtest-2	20.67	20.67	20.58	21.20	20.81	21.05	20.90	22.50
3GPP Rel 6	HSUPA Subtest-3	20.20	20.40	20.97	22.20	20.99	21.20	20.97	23.50
3GPP Rel 6	HSUPA Subtest-4	20.95	20.98	20.95	21.20	21.15	21.27	21.04	22.50
3GPP Rel 6	HSUPA Subtest-5	21.71	21.86	22.12	23.20	22.15	22.13	22.08	24.50

**<LTE Conducted Power>****General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 / B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.38	23.47	23.27	24	0
20	QPSK	1	49	23.80	23.62	23.76		
20	QPSK	1	99	23.53	23.27	23.16		
20	QPSK	50	0	22.44	22.36	22.42	23	1
20	QPSK	50	24	22.25	22.21	22.41		
20	QPSK	50	50	22.37	22.14	22.32		
20	QPSK	100	0	22.33	22.24	22.32		
20	16QAM	1	0	22.34	22.49	22.50	23	1
20	16QAM	1	49	22.04	22.05	22.78		
20	16QAM	1	99	22.11	21.96	22.53		
20	16QAM	50	0	21.43	21.45	21.27	22	2
20	16QAM	50	24	21.27	21.13	21.36		
20	16QAM	50	50	21.11	21.30	21.36		
20	16QAM	100	0	21.33	21.26	21.34		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.38	23.33	23.36	24	0
15	QPSK	1	37	23.47	23.22	23.45		
15	QPSK	1	74	23.23	23.29	23.45		
15	QPSK	36	0	22.19	22.28	22.55	23	1
15	QPSK	36	20	22.34	22.22	22.51		
15	QPSK	36	39	22.42	22.23	22.37		
15	QPSK	75	0	22.31	22.24	22.34		
15	16QAM	1	0	22.63	22.09	22.46	23	1
15	16QAM	1	37	22.65	21.94	22.40		
15	16QAM	1	74	22.51	22.08	22.41		
15	16QAM	36	0	21.17	21.17	21.36	22	2
15	16QAM	36	20	21.27	21.33	21.42		
15	16QAM	36	39	21.34	21.24	21.31		
15	16QAM	75	0	21.26	21.18	21.32		
Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.30	23.32	23.47	24	0
10	QPSK	1	25	23.42	23.48	23.52		
10	QPSK	1	49	23.37	23.14	23.40		
10	QPSK	25	0	22.39	22.26	22.50	23	1
10	QPSK	25	12	22.19	22.27	22.46		
10	QPSK	25	25	22.27	22.15	22.31		
10	QPSK	50	0	22.28	22.23	22.45		
10	16QAM	1	0	22.60	22.60	22.50	23	1
10	16QAM	1	25	22.95	22.71	22.59		
10	16QAM	1	49	22.91	22.28	22.44		
10	16QAM	25	0	21.14	21.18	21.62	22	2
10	16QAM	25	12	21.14	21.28	21.61		
10	16QAM	25	25	21.11	21.18	21.52		
10	16QAM	50	0	21.25	21.15	21.46		



FCC SAR TEST REPORT

Report No. : FA870417

Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.07	23.36	23.14	24	0
5	QPSK	1	12	23.00	23.49	23.19		
5	QPSK	1	24	22.98	23.30	23.26		
5	QPSK	12	0	22.14	22.12	22.25	23	1
5	QPSK	12	7	22.19	22.09	22.22		
5	QPSK	12	13	22.18	22.13	22.31		
5	QPSK	25	0	22.15	22.14	22.26	23	1
5	16QAM	1	0	22.24	22.74	22.58		
5	16QAM	1	12	22.37	22.15	22.56		
5	16QAM	1	24	22.67	22.31	22.79	22	2
5	16QAM	12	0	20.98	21.09	21.15		
5	16QAM	12	7	21.01	21.09	21.01		
5	16QAM	12	13	21.03	21.13	21.20	22	2
5	16QAM	25	0	21.10	21.14	21.25		
Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.28	23.26	23.24	24	0
3	QPSK	1	8	23.08	23.19	23.14		
3	QPSK	1	14	23.16	23.14	23.26		
3	QPSK	8	0	22.29	22.16	22.47	23	1
3	QPSK	8	4	22.23	22.20	22.52		
3	QPSK	8	7	22.29	22.23	22.39		
3	QPSK	15	0	22.25	22.21	22.40	23	1
3	16QAM	1	0	22.54	22.43	22.69		
3	16QAM	1	8	22.30	22.36	22.62		
3	16QAM	1	14	22.43	22.33	22.62	22	2
3	16QAM	8	0	21.01	21.02	21.35		
3	16QAM	8	4	20.96	20.96	21.26		
3	16QAM	8	7	21.11	20.99	21.46	22	2
3	16QAM	15	0	21.04	20.81	21.54		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.29	23.06	23.38	24	0
1.4	QPSK	1	3	23.21	23.13	23.40		
1.4	QPSK	1	5	23.21	22.97	23.32		
1.4	QPSK	3	0	23.27	23.19	23.50		
1.4	QPSK	3	1	23.40	23.24	23.61		
1.4	QPSK	3	3	23.34	23.24	23.48		
1.4	QPSK	6	0	22.37	22.23	22.41	23	1
1.4	16QAM	1	0	21.97	22.08	22.18	23	1
1.4	16QAM	1	3	22.13	22.42	22.46		
1.4	16QAM	1	5	21.96	21.99	22.44		
1.4	16QAM	3	0	22.10	21.96	22.53		
1.4	16QAM	3	1	22.44	22.24	22.44		
1.4	16QAM	3	3	22.44	22.00	22.33		
1.4	16QAM	6	0	21.14	20.92	21.41	22	2



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	24.11	23.63	23.67		
20	QPSK	1	49	24.00	23.77	23.84	24.5	0
20	QPSK	1	99	23.84	23.56	23.60		
20	QPSK	50	0	22.93	22.87	22.82		
20	QPSK	50	24	22.83	22.73	22.79	23.5	1
20	QPSK	50	50	22.73	22.69	22.77		
20	QPSK	100	0	22.79	22.78	22.84		
20	16QAM	1	0	22.77	22.90	22.87	23.5	1
20	16QAM	1	49	22.72	23.00	23.02		
20	16QAM	1	99	22.73	22.80	22.62		
20	16QAM	50	0	21.78	21.80	21.92	22.5	2
20	16QAM	50	24	21.74	21.70	21.79		
20	16QAM	50	50	21.90	21.64	21.64		
20	16QAM	100	0	21.83	21.70	21.83		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	24.02	23.87	23.89		
15	QPSK	1	37	24.01	23.74	24.05	24.5	0
15	QPSK	1	74	23.76	23.71	23.76		
15	QPSK	36	0	22.95	22.87	22.78		
15	QPSK	36	20	22.86	22.75	22.79	23.5	1
15	QPSK	36	39	22.90	22.76	22.79		
15	QPSK	75	0	22.97	22.81	22.73		
15	16QAM	1	0	23.37	23.22	23.13	23.5	1
15	16QAM	1	37	23.00	22.89	23.19		
15	16QAM	1	74	23.09	22.46	23.12		
15	16QAM	36	0	21.88	21.90	21.82	22.5	2
15	16QAM	36	20	21.74	21.80	21.75		
15	16QAM	36	39	21.82	21.68	21.71		
15	16QAM	75	0	22.01	21.86	21.81		
Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	23.97	23.91	23.65		
10	QPSK	1	25	24.10	24.00	23.90	24.5	0
10	QPSK	1	49	23.89	23.71	23.57		
10	QPSK	25	0	22.94	22.85	22.89		
10	QPSK	25	12	22.90	22.88	22.77	23.5	1
10	QPSK	25	25	22.93	22.77	22.75		
10	QPSK	50	0	22.89	22.83	22.77		
10	16QAM	1	0	23.29	22.85	23.04	23.5	1
10	16QAM	1	25	23.36	23.23	23.30		
10	16QAM	1	49	23.29	22.59	22.78		
10	16QAM	25	0	21.97	21.99	21.74	22.5	2
10	16QAM	25	12	21.94	21.76	21.74		
10	16QAM	25	25	21.97	21.84	21.71		
10	16QAM	50	0	21.94	21.88	21.83		



FCC SAR TEST REPORT

Report No. : FA870417

Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	23.60	23.85	23.63	24.5	0
5	QPSK	1	12	23.96	24.02	23.98		
5	QPSK	1	24	23.79	23.84	23.60		
5	QPSK	12	0	22.78	22.75	22.69	23.5	1
5	QPSK	12	7	22.79	22.75	22.74		
5	QPSK	12	13	22.79	22.74	22.67		
5	QPSK	25	0	22.84	22.69	22.72		
5	16QAM	1	0	23.12	22.88	23.28	23.5	1
5	16QAM	1	12	23.31	22.53	22.97		
5	16QAM	1	24	23.07	22.86	23.24		
5	16QAM	12	0	21.78	21.71	21.63	22.5	2
5	16QAM	12	7	21.73	21.78	21.60		
5	16QAM	12	13	21.72	21.88	21.63		
5	16QAM	25	0	21.83	21.74	21.57		
Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	24.00	23.75	23.84	24.5	0
3	QPSK	1	8	23.92	23.69	23.75		
3	QPSK	1	14	24.05	23.69	23.74		
3	QPSK	8	0	22.86	22.68	22.76	23.5	1
3	QPSK	8	4	22.89	22.73	22.72		
3	QPSK	8	7	22.84	22.74	22.69		
3	QPSK	15	0	22.80	22.70	22.64		
3	16QAM	1	0	22.67	22.94	22.46	23.5	1
3	16QAM	1	8	22.49	22.91	22.57		
3	16QAM	1	14	22.46	22.89	22.62		
3	16QAM	8	0	21.75	21.88	21.63	22.5	2
3	16QAM	8	4	21.90	21.89	21.74		
3	16QAM	8	7	21.82	21.74	21.61		
3	16QAM	15	0	21.85	21.51	21.61		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	23.86	23.69	23.71	24.5	0
1.4	QPSK	1	3	23.93	23.75	23.69		
1.4	QPSK	1	5	23.80	23.71	23.63		
1.4	QPSK	3	0	23.96	23.70	23.77		
1.4	QPSK	3	1	24.02	23.75	23.82		
1.4	QPSK	3	3	23.99	23.75	23.74		
1.4	QPSK	6	0	22.95	22.77	22.72	23.5	1
1.4	16QAM	1	0	22.83	22.88	22.57	23.5	1
1.4	16QAM	1	3	23.06	22.76	22.52		
1.4	16QAM	1	5	22.48	22.73	22.30		
1.4	16QAM	3	0	22.57	22.89	22.69		
1.4	16QAM	3	1	23.07	23.14	22.96		
1.4	16QAM	3	3	23.09	23.05	22.99		
1.4	16QAM	6	0	21.96	21.79	21.44	22.5	2

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	23.77	23.67	23.78	24.5	0
10	QPSK	1	25	23.90	23.85	23.96		
10	QPSK	1	49	23.60	23.39	23.54		
10	QPSK	25	0	22.85	22.71	22.72	23.5	1
10	QPSK	25	12	22.81	22.75	22.66		
10	QPSK	25	25	22.72	22.76	22.71		
10	QPSK	50	0	22.72	22.71	22.79		
10	16QAM	1	0	22.90	22.96	22.70	23.5	1
10	16QAM	1	25	22.51	22.73	22.88		
10	16QAM	1	49	22.87	22.76	22.50		
10	16QAM	25	0	21.69	21.66	21.91	22.5	2
10	16QAM	25	12	21.67	21.60	21.93		
10	16QAM	25	25	21.60	21.50	21.85		
10	16QAM	50	0	21.84	21.73	21.86		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	23.91	23.49	23.66	24.5	0
5	QPSK	1	12	23.92	23.62	23.85		
5	QPSK	1	24	23.87	23.49	23.61		
5	QPSK	12	0	22.74	22.67	22.73	23.5	1
5	QPSK	12	7	22.73	22.75	22.59		
5	QPSK	12	13	22.78	22.62	22.65		
5	QPSK	25	0	22.74	22.68	22.62		
5	16QAM	1	0	22.90	22.88	22.70	23.5	1
5	16QAM	1	12	22.72	22.88	22.62		
5	16QAM	1	24	22.60	22.72	22.51		
5	16QAM	12	0	21.77	21.63	21.54	22.5	2
5	16QAM	12	7	21.69	21.61	21.49		
5	16QAM	12	13	21.73	21.62	21.58		
5	16QAM	25	0	21.97	21.67	21.82		
Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	23.71	23.82	23.75	24.5	0
3	QPSK	1	8	23.59	23.69	23.72		
3	QPSK	1	14	23.71	23.60	23.56		
3	QPSK	8	0	22.82	22.71	22.81	23.5	1
3	QPSK	8	4	22.60	22.73	22.63		
3	QPSK	8	7	22.75	22.78	22.63		
3	QPSK	15	0	22.77	22.68	22.62		
3	16QAM	1	0	22.91	22.83	22.69	23.5	1
3	16QAM	1	8	22.86	22.86	22.56		
3	16QAM	1	14	22.81	22.76	22.50		
3	16QAM	8	0	21.91	21.52	21.57	22.5	2
3	16QAM	8	4	21.82	21.47	21.46		
3	16QAM	8	7	21.89	21.50	21.53		
3	16QAM	15	0	21.91	21.72	21.57		



FCC SAR TEST REPORT

Report No. : FA870417

Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	23.68	23.75	23.51	24.5	0
1.4	QPSK	1	3	23.65	23.72	23.55		
1.4	QPSK	1	5	23.50	23.65	23.50		
1.4	QPSK	3	0	23.72	23.69	23.76		
1.4	QPSK	3	1	23.65	23.79	23.61		
1.4	QPSK	3	3	23.78	23.76	23.54		
1.4	QPSK	6	0	22.81	22.82	22.53	23.5	1
1.4	16QAM	1	0	22.84	22.88	22.85	23.5	1
1.4	16QAM	1	3	22.69	22.77	22.74		
1.4	16QAM	1	5	22.98	22.87	22.51		
1.4	16QAM	3	0	22.77	22.83	22.52		
1.4	16QAM	3	1	22.75	22.72	22.78		
1.4	16QAM	3	3	22.64	22.95	22.66		
1.4	16QAM	6	0	21.83	21.75	21.64	22.5	2



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130	24.5	0
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.51	23.48	23.77		
10	QPSK	1	25	24.00	23.68	23.91	23.5	1
10	QPSK	1	49	23.49	23.23	23.57		
10	QPSK	25	0	22.69	22.61	22.66		
10	QPSK	25	12	22.64	22.62	22.69	23.5	1
10	QPSK	25	25	22.63	22.52	22.68		
10	QPSK	50	0	22.68	22.63	22.72		
10	16QAM	1	0	22.24	22.90	22.84	23.5	1
10	16QAM	1	25	22.69	22.95	23.23		
10	16QAM	1	49	22.37	22.35	22.71		
10	16QAM	25	0	21.71	21.86	21.58	22.5	2
10	16QAM	25	12	21.70	21.84	21.58		
10	16QAM	25	25	21.89	21.68	21.58		
10	16QAM	50	0	21.61	21.53	21.52	24.5	0
Channel				23035	23095	23155		
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.75	23.73	23.76	24.5	0
5	QPSK	1	12	23.83	23.63	23.84		
5	QPSK	1	24	23.84	23.46	23.84		
5	QPSK	12	0	22.60	22.64	22.61	23.5	1
5	QPSK	12	7	22.59	22.64	22.77		
5	QPSK	12	13	22.53	22.62	22.69		
5	QPSK	25	0	22.64	22.62	22.66	23.5	1
5	16QAM	1	0	22.56	23.09	23.13		
5	16QAM	1	12	22.63	22.92	22.77		
5	16QAM	1	24	22.90	23.19	23.27	22.5	2
5	16QAM	12	0	21.57	21.56	21.34		
5	16QAM	12	7	21.59	21.41	21.41		
5	16QAM	12	13	21.54	21.57	21.42	24.5	0
5	16QAM	25	0	21.43	21.67	21.66		
Channel				23025	23095	23165		
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.82	23.74	23.71	24.5	0
3	QPSK	1	8	23.77	23.51	23.80		
3	QPSK	1	14	23.74	23.49	23.71		
3	QPSK	8	0	22.55	22.53	22.58	23.5	1
3	QPSK	8	4	22.57	22.45	22.64		
3	QPSK	8	7	22.52	22.49	22.61		
3	QPSK	15	0	22.62	22.64	22.52	23.5	1
3	16QAM	1	0	22.45	23.11	23.04		
3	16QAM	1	8	22.62	22.94	22.76		
3	16QAM	1	14	22.93	23.13	23.23	22.5	2
3	16QAM	8	0	21.50	21.57	21.29		
3	16QAM	8	4	21.58	21.46	21.47		
3	16QAM	8	7	21.43	21.46	21.30	22.5	2
3	16QAM	15	0	21.38	21.63	21.49		



FCC SAR TEST REPORT

Report No. : FA870417

Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.59	23.67	23.57	24.5	0
1.4	QPSK	1	3	23.59	23.61	23.60		
1.4	QPSK	1	5	23.29	23.62	23.65		
1.4	QPSK	3	0	23.66	23.64	23.71		
1.4	QPSK	3	1	23.73	23.73	23.67		
1.4	QPSK	3	3	23.67	23.67	23.81		
1.4	QPSK	6	0	22.60	22.55	22.77	23.5	1
1.4	16QAM	1	0	22.63	22.89	23.13	23.5	1
1.4	16QAM	1	3	23.19	23.33	23.14		
1.4	16QAM	1	5	22.79	22.78	23.02		
1.4	16QAM	3	0	22.75	22.73	22.80		
1.4	16QAM	3	1	22.68	22.67	22.91		
1.4	16QAM	3	3	22.58	22.67	22.70		
1.4	16QAM	6	0	20.96	21.64	21.48	22.5	2



<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0	23.80			24.5	0
10	QPSK	1	25	23.89				
10	QPSK	1	49	23.52				
10	QPSK	25	0	22.76			23.5	1
10	QPSK	25	12	22.69				
10	QPSK	25	25	22.61				
10	QPSK	50	0	22.66				
10	16QAM	1	0	23.06			23.5	1
10	16QAM	1	25	23.42				
10	16QAM	1	49	22.83				
10	16QAM	25	0	21.58			22.5	2
10	16QAM	25	12	21.69				
10	16QAM	25	25	21.50				
10	16QAM	50	0	21.56				
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	23.68	23.67	23.61	24.5	0
5	QPSK	1	12	23.72	23.88	23.61		
5	QPSK	1	24	23.49	23.75	23.46		
5	QPSK	12	0	22.77	22.71	22.71	23.5	1
5	QPSK	12	7	22.79	22.75	22.63		
5	QPSK	12	13	22.66	22.71	22.61		
5	QPSK	25	0	22.65	22.68	22.67	23.5	1
5	16QAM	1	0	23.28	22.54	22.55		
5	16QAM	1	12	22.97	22.50	22.89		
5	16QAM	1	24	22.82	22.38	22.72	22.5	2
5	16QAM	12	0	21.46	21.57	21.65		
5	16QAM	12	7	21.52	21.65	21.43		
5	16QAM	12	13	21.46	21.63	21.49		
5	16QAM	25	0	21.58	21.68	21.58		

**<WLAN Conducted Power>****General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	19.25	19.50	100.00
		6	2437	19.32	19.50	
		11	2462	19.30	19.50	
	802.11g 6Mbps	1	2412	14.12	14.50	87.02
		6	2437	17.15	17.50	
		11	2462	14.08	14.50	
	802.11n-HT20 MCS0	1	2412	14.21	14.50	85.83
		6	2437	17.21	17.50	
		11	2462	14.36	14.50	

<5GHz WLAN >

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	14.42	14.50	86.69
		40	5200	14.45	14.50	
		44	5220	14.47	14.50	
		48	5240	14.14	14.50	
	802.11n-HT20 MCS0	36	5180	14.48	14.50	86.49
		40	5200	14.47	14.50	
		44	5220	14.49	14.50	
		48	5240	14.08	14.50	
	802.11n-HT40 MCS0	38	5190	14.19	14.50	85.37
		46	5230	14.09	14.50	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	17.22	17.50	86.69
		56	5280	17.23	17.50	
		60	5300	17.24	17.50	
		64	5320	14.33	14.50	
	802.11n-HT20 MCS0	52	5260	16.20	16.50	86.49
		56	5280	16.30	16.50	
		60	5300	16.48	16.50	
		64	5320	14.10	14.50	
	802.11n-HT40 MCS0	54	5270	14.33	14.50	85.37
		62	5310	14.46	14.50	

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	14.09	14.50	86.69
		116	5580	17.37	17.50	
		124	5620	17.35	17.50	
		132	5660	17.33	17.50	
		140	5700	14.17	14.50	
	802.11n-HT20 MCS0	100	5500	14.33	14.50	86.49
		116	5580	16.23	16.50	
		124	5620	16.20	16.50	
		132	5660	16.18	16.50	
		140	5700	14.43	14.50	
	802.11n-HT40 MCS0	102	5510	14.14	14.50	85.37
		110	5550	14.34	14.50	
		126	5630	14.30	14.50	
		134	5670	14.22	14.50	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	149	5745	17.18	17.50	86.69
		157	5785	17.42	17.50	
		165	5825	17.17	17.50	
	802.11n-HT20 MCS0	149	5745	16.33	16.50	86.49
		157	5785	16.36	16.50	
		165	5825	16.10	16.50	
	802.11n-HT40 MCS0	151	5755	14.14	14.50	85.37
		159	5795	14.10	14.50	

<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)			Tune-up Limit		
			1Mbps	2Mbps	3Mbps	1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	10.38	8.44	8.45	11.70	9.50	9.50
	CH 39	2441	10.21	8.40	8.41	11.70	9.50	9.50
	CH 78	2480	9.14	7.30	7.34	9.90	7.80	7.80


Mode	Channel	Frequency (MHz)	Average power (dBm)		Tune-up Limit	
			GFSK		GFSK	
LE	CH 00	2402	1.55		2.80	
	CH 19	2440	0.90		2.80	
	CH 39	2480	-0.43		0.80	

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.72% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.

12. Antenna Location

<Mobile Phone>



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB648474 D04v01r03, when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
5. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold, for this device only bottom side SAR for WWAN transmitter scaled to maximum output power is higher than 1.2W/kg of WCDMA B2 and LTE B2, therefore product specific SAR is necessary.
6. For 5GHz WLAN product specific SAR is necessary too, due to an overall diagonal dimension is > 16 cm.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B12 / B5 / B4 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

13.1 Head SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9538	1907.6	23.13	23.20	1.016	0.071	0.633	0.643
01	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9262	1852.4	22.94	23.20	1.062	0.056	0.644	0.684
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9400	1880	23.00	23.20	1.047	0.014	0.617	0.646
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9538	1907.6	23.13	23.20	1.016	-0.049	0.231	0.235
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	23.13	23.20	1.016	-0.039	0.401	0.408
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9538	1907.6	23.13	23.20	1.016	0.14	0.266	0.270
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4132	826.4	23.15	24.50	1.365	-0.07	0.291	0.397
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4132	826.4	23.15	24.50	1.365	-0.04	0.173	0.236
02	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	23.15	24.50	1.365	-0.02	0.323	0.441
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4182	836.4	23.06	24.50	1.393	0	0.316	0.440
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4233	846.6	22.97	24.50	1.422	0.06	0.303	0.431
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4132	826.4	23.15	24.50	1.365	0.1	0.163	0.222

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Right Cheek	0mm	18700	1860	23.80	24.00	1.047	-0.1	0.726	0.760
	LTE Band 2	20M	QPSK	1	49	Right Cheek	0mm	18900	1880	23.62	24.00	1.091	0.15	0.702	0.766
03	LTE Band 2	20M	QPSK	1	49	Right Cheek	0mm	19100	1900	23.76	24.00	1.057	0.02	0.727	0.768
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	18700	1860	22.44	23.00	1.138	0.06	0.595	0.677
	LTE Band 2	20M	QPSK	100	0	Right Cheek	0mm	18700	1860	22.33	23.00	1.167	0.12	0.588	0.686
	LTE Band 2	20M	QPSK	1	49	Right Tilted	0mm	18700	1860	23.80	24.00	1.047	0.02	0.339	0.355
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	18700	1860	22.44	23.00	1.138	0	0.261	0.297
	LTE Band 2	20M	QPSK	1	49	Left Cheek	0mm	18700	1860	23.80	24.00	1.047	0.04	0.459	0.481
	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	18700	1860	22.44	23.00	1.138	0.04	0.348	0.396
	LTE Band 2	20M	QPSK	1	49	Left Tilted	0mm	18700	1860	23.80	24.00	1.047	-0.07	0.365	0.382
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	18700	1860	22.44	23.00	1.138	0.13	0.281	0.320
04	LTE Band 4	20M	QPSK	1	49	Right Cheek	0mm	20175	1732.5	23.77	24.50	1.183	-0.06	0.708	0.838
	LTE Band 4	20M	QPSK	50	0	Right Cheek	0mm	20175	1732.5	22.87	23.50	1.156	0.05	0.567	0.656
	LTE Band 4	20M	QPSK	100	0	Right Cheek	0mm	20175	1732.5	22.78	23.50	1.180	0	0.565	0.667
	LTE Band 4	20M	QPSK	1	49	Right Tilted	0mm	20175	1732.5	23.77	24.50	1.183	0.14	0.297	0.351
	LTE Band 4	20M	QPSK	50	0	Right Tilted	0mm	20175	1732.5	22.87	23.50	1.156	-0.09	0.231	0.267
	LTE Band 4	20M	QPSK	1	49	Left Cheek	0mm	20175	1732.5	23.77	24.50	1.183	0.05	0.390	0.461
	LTE Band 4	20M	QPSK	50	0	Left Cheek	0mm	20175	1732.5	22.87	23.50	1.156	0.11	0.308	0.356
	LTE Band 4	20M	QPSK	1	49	Left Tilted	0mm	20175	1732.5	23.77	24.50	1.183	-0.15	0.345	0.408
	LTE Band 4	20M	QPSK	50	0	Left Tilted	0mm	20175	1732.5	22.87	23.50	1.156	0.1	0.257	0.297
	LTE Band 5	10M	QPSK	1	25	Right Cheek	0mm	20525	836.5	23.85	24.50	1.161	0.15	0.306	0.355
	LTE Band 5	10M	QPSK	25	25	Right Cheek	0mm	20525	836.5	22.76	23.50	1.186	0.13	0.241	0.286
	LTE Band 5	10M	QPSK	1	25	Right Tilted	0mm	20525	836.5	23.85	24.50	1.161	0.04	0.227	0.264
	LTE Band 5	10M	QPSK	25	25	Right Tilted	0mm	20525	836.5	22.76	23.50	1.186	0.02	0.181	0.215
05	LTE Band 5	10M	QPSK	1	25	Left Cheek	0mm	20525	836.5	23.85	24.50	1.161	0.02	0.377	0.438
	LTE Band 5	10M	QPSK	25	25	Left Cheek	0mm	20525	836.5	22.76	23.50	1.186	-0.07	0.297	0.352
	LTE Band 5	10M	QPSK	1	25	Left Tilted	0mm	20525	836.5	23.85	24.50	1.161	0.11	0.199	0.231
	LTE Band 5	10M	QPSK	25	25	Left Tilted	0mm	20525	836.5	22.76	23.50	1.186	-0.07	0.155	0.184

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 12	10M	QPSK	1	25	Right Cheek	0mm	23095	707.5	23.68	24.50	1.208	-0.08	0.255	0.308
	LTE Band 12	10M	QPSK	25	12	Right Cheek	0mm	23095	707.5	22.62	23.50	1.225	-0.1	0.198	0.242
	LTE Band 12	10M	QPSK	1	25	Right Tilted	0mm	23095	707.5	23.68	24.50	1.208	0.02	0.152	0.184
	LTE Band 12	10M	QPSK	25	12	Right Tilted	0mm	23095	707.5	22.62	23.50	1.225	0.03	0.115	0.141
	LTE Band 12	10M	QPSK	1	25	Left Cheek	0mm	23095	707.5	23.68	24.50	1.208	0.04	0.227	0.274
	LTE Band 12	10M	QPSK	25	12	Left Cheek	0mm	23095	707.5	22.62	23.50	1.225	0.02	0.179	0.219
	LTE Band 12	10M	QPSK	1	25	Left Tilted	0mm	23095	707.5	23.68	24.50	1.208	-0.17	0.131	0.158
	LTE Band 12	10M	QPSK	25	12	Left Tilted	0mm	23095	707.5	22.62	23.50	1.225	0.08	0.103	0.126
	LTE Band 13	10M	QPSK	1	25	Right Cheek	0mm	23230	782	23.89	24.50	1.151	0.04	0.267	0.307
	LTE Band 13	10M	QPSK	25	0	Right Cheek	0mm	23230	782	22.76	23.50	1.186	0.01	0.219	0.260
	LTE Band 13	10M	QPSK	1	25	Right Tilted	0mm	23230	782	23.89	24.50	1.151	-0.01	0.161	0.185
	LTE Band 13	10M	QPSK	25	0	Right Tilted	0mm	23230	782	22.76	23.50	1.186	-0.14	0.129	0.153
07	LTE Band 13	10M	QPSK	1	25	Left Cheek	0mm	23230	782	23.89	24.50	1.151	0.03	0.319	0.367
	LTE Band 13	10M	QPSK	25	0	Left Cheek	0mm	23230	782	22.76	23.50	1.186	0.02	0.249	0.295
	LTE Band 13	10M	QPSK	1	25	Left Tilted	0mm	23230	782	23.89	24.50	1.151	0.03	0.149	0.171
	LTE Band 13	10M	QPSK	25	0	Left Tilted	0mm	23230	782	22.76	23.50	1.186	0	0.121	0.143

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
08	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	6	2437	19.32	19.50	1.042	100	1.000	-0.02	0.406	0.423
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	1	2412	19.25	19.50	1.059	100	1.000	0	0.347	0.368
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	11	2462	19.30	19.50	1.047	100	1.000	0.07	0.373	0.391
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	6	2437	19.32	19.50	1.042	100	1.000	0.07	0.224	0.233
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	6	2437	19.32	19.50	1.042	100	1.000	0.1	0.189	0.197
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	6	2437	19.32	19.50	1.042	100	1.000	0.04	0.176	0.183
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.16	0.209	0.256
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	52	5260	17.22	17.50	1.067	86.69	1.154	0.1	0.222	0.273
09	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	56	5280	17.23	17.50	1.064	86.69	1.154	0.13	0.231	0.284
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	64	5320	14.33	14.50	1.040	86.69	1.154	0.12	0.121	0.145
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.17	0.146	0.179
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	0.03	0.151	0.185
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	0.14	0.129	0.158
10	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0.12	0.174	0.207
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	100	5500	14.09	14.50	1.099	86.69	1.154	0.15	0.109	0.138
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	132	5660	17.33	17.50	1.040	86.69	1.154	0.1	0.092	0.110
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	140	5700	14.17	14.50	1.079	86.69	1.154	-0.11	0.023	0.029
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0.15	0.117	0.139
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	-0.18	0.099	0.118
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	-0.19	0.081	0.096
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	157	5785	17.42	17.50	1.019	86.69	1.154	0.16	0.038	0.045
11	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	149	5745	17.18	17.50	1.076	86.69	1.154	0.08	0.042	0.052
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	165	5825	17.17	17.50	1.079	86.69	1.154	-0.02	0.033	0.041
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	157	5785	17.42	17.50	1.019	86.69	1.154	0.08	0.034	0.040
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	157	5785	17.42	17.50	1.019	86.69	1.154	0.17	0.031	0.036
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	157	5785	17.42	17.50	1.019	86.69	1.154	-0.13	0.032	0.038

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.128	0.013	0.019
12	Bluetooth	1Mbps	Right Cheek	0mm	39	2441	10.21	11.70	1.409	76.72	1.086	0.138	0.022	0.034
	Bluetooth	1Mbps	Right Cheek	0mm	78	2480	9.14	9.90	1.191	76.72	1.086	-0.1	0.015	0.019
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.12	0.011	0.016
	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.133	0.011	0.016
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	10.38	11.70	1.355	76.72	1.086	-0.185	0.011	0.016

13.2 Hotspot SAR
<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	9538	1907.6	23.13	23.20	1.016	-0.07	0.601	0.611
13	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.13	23.20	1.016	-0.17	1.420	1.443
	WCDMA II	RMC 12.2Kbps	Back	10mm	9262	1852.4	22.94	23.20	1.062	-0.11	1.260	1.338
	WCDMA II	RMC 12.2Kbps	Back	10mm	9400	1880	23.00	23.20	1.047	-0.14	1.310	1.372
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	9538	1907.6	23.13	23.20	1.016	-0.01	0.071	0.072
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	9538	1907.6	23.13	23.20	1.016	-0.03	0.634	0.644
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9538	1907.6	23.13	23.20	1.016	0	0.959	0.975
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9262	1852.4	22.94	23.20	1.062	0.07	0.817	0.867
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9400	1880	23.00	23.20	1.047	-0.16	0.843	0.883
	WCDMA V	RMC 12.2Kbps	Front	10mm	4132	826.4	23.15	24.50	1.365	-0.08	0.292	0.398
	WCDMA V	RMC 12.2Kbps	Back	10mm	4132	826.4	23.15	24.50	1.365	0.1	0.472	0.644
14	WCDMA V	RMC 12.2Kbps	Back	10mm	4182	836.4	23.06	24.50	1.393	0.02	0.506	0.705
	WCDMA V	RMC 12.2Kbps	Back	10mm	4233	846.6	22.97	24.50	1.422	0	0.485	0.690
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	4132	826.4	23.15	24.50	1.365	0.04	0.359	0.490
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	4132	826.4	23.15	24.50	1.365	-0.01	0.267	0.364
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	4132	826.4	23.15	24.50	1.365	-0.01	0.021	0.029

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Front	10mm	18700	1860	23.80	24.00	1.047	-0.07	0.588	0.616
	LTE Band 2	20M	QPSK	50	0	Front	10mm	18700	1860	22.44	23.00	1.138	-0.07	0.455	0.518
	LTE Band 2	20M	QPSK	1	49	Back	10mm	18700	1860	23.80	24.00	1.047	-0.14	1.260	1.319
	LTE Band 2	20M	QPSK	1	49	Back	10mm	18900	1880	23.62	24.00	1.091	-0.11	1.260	1.375
15	LTE Band 2	20M	QPSK	1	49	Back	10mm	19100	1900	23.76	24.00	1.057	-0.1	1.360	1.437
	LTE Band 2	20M	QPSK	50	0	Back	10mm	18700	1860	22.44	23.00	1.138	-0.12	1.010	1.149
	LTE Band 2	20M	QPSK	50	0	Back	10mm	18900	1880	22.36	23.00	1.159	-0.13	1.060	1.228
	LTE Band 2	20M	QPSK	50	0	Back	10mm	19100	1900	22.42	23.00	1.143	-0.01	1.090	1.246
	LTE Band 2	20M	QPSK	100	0	Back	10mm	18700	1860	22.33	23.00	1.167	-0.18	1.020	1.190
	LTE Band 2	20M	QPSK	1	49	Left Side	10mm	18700	1860	23.80	24.00	1.047	-0.18	0.062	0.065
	LTE Band 2	20M	QPSK	50	0	Left Side	10mm	18700	1860	22.44	23.00	1.138	0.03	0.049	0.056
	LTE Band 2	20M	QPSK	1	49	Right Side	10mm	18700	1860	23.80	24.00	1.047	0	0.551	0.577
	LTE Band 2	20M	QPSK	50	0	Right Side	10mm	18700	1860	22.44	23.00	1.138	-0.04	0.438	0.498
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	18700	1860	23.80	24.00	1.047	0.12	0.860	0.901
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	18900	1880	23.62	24.00	1.091	0.17	0.884	0.965
	LTE Band 2	20M	QPSK	1	49	Bottom Side	10mm	19100	1900	23.76	24.00	1.057	0.02	0.972	1.027
	LTE Band 2	20M	QPSK	50	0	Bottom Side	10mm	18700	1860	22.44	23.00	1.138	0.12	0.678	0.771
	LTE Band 2	20M	QPSK	100	0	Bottom Side	10mm	18700	1860	22.33	23.00	1.167	0.04	0.680	0.793



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 4	20M	QPSK	1	49	Front	10mm	20175	1732.5	23.77	24.50	1.183	-0.01	0.461	0.545
	LTE Band 4	20M	QPSK	50	0	Front	10mm	20175	1732.5	22.87	23.50	1.156	0.02	0.336	0.388
16	LTE Band 4	20M	QPSK	1	49	Back	10mm	20175	1732.5	23.77	24.50	1.183	0.13	0.915	1.082
	LTE Band 4	20M	QPSK	50	0	Back	10mm	20175	1732.5	22.87	23.50	1.156	0.1	0.660	0.763
	LTE Band 4	20M	QPSK	100	0	Back	10mm	20175	1732.5	22.78	23.50	1.180	0.02	0.679	0.801
	LTE Band 4	20M	QPSK	1	49	Left Side	10mm	20175	1732.5	23.77	24.50	1.183	-0.08	0.042	0.050
	LTE Band 4	20M	QPSK	50	0	Left Side	10mm	20175	1732.5	22.87	23.50	1.156	-0.03	0.030	0.035
	LTE Band 4	20M	QPSK	1	49	Right Side	10mm	20175	1732.5	23.77	24.50	1.183	0.04	0.339	0.401
	LTE Band 4	20M	QPSK	50	0	Right Side	10mm	20175	1732.5	22.87	23.50	1.156	0.09	0.263	0.304
	LTE Band 4	20M	QPSK	1	49	Bottom Side	10mm	20175	1732.5	23.77	24.50	1.183	0.02	0.576	0.681
	LTE Band 4	20M	QPSK	50	0	Bottom Side	10mm	20175	1732.5	22.87	23.50	1.156	-0.01	0.449	0.519
	LTE Band 5	10M	QPSK	1	25	Front	10mm	20525	836.5	23.85	24.50	1.161	0.18	0.325	0.377
	LTE Band 5	10M	QPSK	25	25	Front	10mm	20525	836.5	22.76	23.50	1.186	0.01	0.268	0.318
17	LTE Band 5	10M	QPSK	1	25	Back	10mm	20525	836.5	23.85	24.50	1.161	-0.12	0.531	0.617
	LTE Band 5	10M	QPSK	25	25	Back	10mm	20525	836.5	22.76	23.50	1.186	-0.06	0.446	0.529
	LTE Band 5	10M	QPSK	1	25	Left Side	10mm	20525	836.5	23.85	24.50	1.161	-0.07	0.496	0.576
	LTE Band 5	10M	QPSK	25	25	Left Side	10mm	20525	836.5	22.76	23.50	1.186	0.11	0.425	0.504
	LTE Band 5	10M	QPSK	1	25	Right Side	10mm	20525	836.5	23.85	24.50	1.161	0.18	0.326	0.379
	LTE Band 5	10M	QPSK	25	25	Right Side	10mm	20525	836.5	22.76	23.50	1.186	-0.06	0.277	0.328
	LTE Band 5	10M	QPSK	1	25	Bottom Side	10mm	20525	836.5	23.85	24.50	1.161	0.05	0.110	0.128
	LTE Band 5	10M	QPSK	25	25	Bottom Side	10mm	20525	836.5	22.76	23.50	1.186	0.1	0.088	0.104
	LTE Band 12	10M	QPSK	1	25	Front	10mm	23095	707.5	23.68	24.50	1.208	-0.08	0.293	0.354
	LTE Band 12	10M	QPSK	25	12	Front	10mm	23095	707.5	22.62	23.50	1.225	0.02	0.237	0.290
18	LTE Band 12	10M	QPSK	1	25	Back	10mm	23095	707.5	23.68	24.50	1.208	0.05	0.435	0.525
	LTE Band 12	10M	QPSK	25	12	Back	10mm	23095	707.5	22.62	23.50	1.225	-0.03	0.331	0.405
	LTE Band 12	10M	QPSK	1	25	Left Side	10mm	23095	707.5	23.68	24.50	1.208	-0.01	0.324	0.391
	LTE Band 12	10M	QPSK	25	12	Left Side	10mm	23095	707.5	22.62	23.50	1.225	0.03	0.254	0.311
	LTE Band 12	10M	QPSK	1	25	Right Side	10mm	23095	707.5	23.68	24.50	1.208	-0.04	0.269	0.325
	LTE Band 12	10M	QPSK	25	12	Right Side	10mm	23095	707.5	22.62	23.50	1.225	0.03	0.214	0.262
	LTE Band 12	10M	QPSK	1	25	Bottom Side	10mm	23095	707.5	23.68	24.50	1.208	0.11	0.013	0.016
	LTE Band 12	10M	QPSK	25	12	Bottom Side	10mm	23095	707.5	22.62	23.50	1.225	-0.14	0.009	0.012
	LTE Band 13	10M	QPSK	1	25	Front	10mm	23230	782	23.89	24.50	1.151	-0.08	0.362	0.417
	LTE Band 13	10M	QPSK	25	0	Front	10mm	23230	782	22.76	23.50	1.186	-0.06	0.278	0.330
19	LTE Band 13	10M	QPSK	1	25	Back	10mm	23230	782	23.89	24.50	1.151	-0.05	0.593	0.682
	LTE Band 13	10M	QPSK	25	0	Back	10mm	23230	782	22.76	23.50	1.186	0.03	0.442	0.524
	LTE Band 13	10M	QPSK	1	25	Left Side	10mm	23230	782	23.89	24.50	1.151	0.13	0.391	0.450
	LTE Band 13	10M	QPSK	25	0	Left Side	10mm	23230	782	22.76	23.50	1.186	-0.06	0.291	0.345
	LTE Band 13	10M	QPSK	1	25	Right Side	10mm	23230	782	23.89	24.50	1.151	0.07	0.348	0.400
	LTE Band 13	10M	QPSK	25	0	Right Side	10mm	23230	782	22.76	23.50	1.186	-0.08	0.252	0.299
	LTE Band 13	10M	QPSK	1	25	Bottom Side	10mm	23230	782	23.89	24.50	1.151	-0.07	0.062	0.071
	LTE Band 13	10M	QPSK	25	0	Bottom Side	10mm	23230	782	22.76	23.50	1.186	-0.13	0.047	0.056

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	6	2437	19.32	19.50	1.042	100	1.000	-0.01	0.095	0.099
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	6	2437	19.32	19.50	1.042	100	1.000	-0.02	0.170	0.177
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	6	2437	19.32	19.50	1.042	100	1.000	0.07	0.174	0.181
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	1	2412	19.25	19.50	1.059	100	1.000	0.14	0.169	0.179
20	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	11	2462	19.30	19.50	1.047	100	1.000	0.02	0.184	0.193
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	6	2437	19.32	19.50	1.042	100	1.000	0.04	0.095	0.099
	WLAN5GHz	802.11n-HT40 MCS0	Front	10mm	38	5190	14.19	14.50	1.074	85.37	1.171	0.02	0.009	0.012
	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	38	5190	14.19	14.50	1.074	85.37	1.171	-0.01	0.216	0.272
21	WLAN5GHz	802.11n-HT40 MCS0	Back	10mm	46	5230	14.09	14.50	1.099	85.37	1.171	-0.14	0.223	0.287
	WLAN5GHz	802.11n-HT40 MCS0	Left Side	10mm	38	5190	14.19	14.50	1.074	85.37	1.171	-0.06	0.060	0.075
	WLAN5GHz	802.11n-HT40 MCS0	Top Side	10mm	38	5190	14.19	14.50	1.074	85.37	1.171	0.02	0.031	0.039
	WLAN5GHz	802.11a 6Mbps	Front	10mm	157	5785	17.42	17.50	1.019	86.69	1.154	0.18	0.011	0.013
	WLAN5GHz	802.11a 6Mbps	Back	10mm	157	5785	17.42	17.50	1.019	86.69	1.154	-0.06	0.116	0.136
22	WLAN5GHz	802.11a 6Mbps	Back	10mm	149	5745	17.18	17.50	1.076	86.69	1.154	-0.04	0.133	0.165
	WLAN5GHz	802.11a 6Mbps	Back	10mm	165	5825	17.17	17.50	1.079	86.69	1.154	-0.04	0.087	0.108
	WLAN5GHz	802.11a 6Mbps	Left Side	10mm	157	5785	17.42	17.50	1.019	86.69	1.154	0.1	0.029	0.034
	WLAN5GHz	802.11a 6Mbps	Top Side	10mm	157	5785	17.42	17.50	1.019	86.69	1.154	-0.09	0.014	0.016

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	0	2402	10.38	11.70	1.355	76.72	1.086	-0.05	0.007	0.010
	Bluetooth	1Mbps	Back	10mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.16	0.012	0.018
	Bluetooth	1Mbps	Left Side	10mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.07	0.014	0.021
23	Bluetooth	1Mbps	Left Side	10mm	39	2441	10.21	11.70	1.409	76.72	1.086	0.07	0.016	0.024
	Bluetooth	1Mbps	Left Side	10mm	78	2480	9.14	9.90	1.191	76.72	1.086	-0.18	0.013	0.017
	Bluetooth	1Mbps	Top Side	10mm	0	2402	10.38	11.70	1.355	76.72	1.086	0.08	0.007	0.011

13.3 Product Specific SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Back	0mm	9538	1907.6	23.13	23.20	1.016	0.02	2.500	2.541
24	WCDMA II	RMC 12.2Kbps	Back	0mm	9262	1852.4	22.94	23.20	1.062	0.11	2.460	2.612
	WCDMA II	RMC 12.2Kbps	Back	0mm	9400	1880	23.00	23.20	1.047	0.17	2.480	2.597

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
25	LTE Band 2	20M	QPSK	1	49	Back	0mm	19100	1900	23.76	24.00	1.057	0.05	2.670	2.822
	LTE Band 2	20M	QPSK	1	49	Back	0mm	18700	1860	23.80	24.00	1.047	0.02	2.600	2.723
	LTE Band 2	20M	QPSK	1	49	Back	0mm	18900	1880	23.62	24.00	1.091	0.05	2.450	2.674

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	802.11a 6Mbps	Front	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.15	0.068	0.083
26	WLAN5GHz	802.11a 6Mbps	Back	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.19	0.542	0.664
	WLAN5GHz	802.11a 6Mbps	Back	0mm	56	5280	17.23	17.50	1.064	86.69	1.154	0.19	0.517	0.635
	WLAN5GHz	802.11a 6Mbps	Back	0mm	52	5260	17.22	17.50	1.067	86.69	1.154	-0.12	0.480	0.591
	WLAN5GHz	802.11a 6Mbps	Back	0mm	64	5320	14.33	14.50	1.040	86.69	1.154	0.04	0.259	0.311
	WLAN5GHz	802.11a 6Mbps	Left Side	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.1	0.458	0.561
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	60	5300	17.24	17.50	1.062	86.69	1.154	-0.14	0.107	0.131
	WLAN5GHz	802.11a 6Mbps	Front	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0	0.020	0.024
	WLAN5GHz	802.11a 6Mbps	Back	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0	0.141	0.168
27	WLAN5GHz	802.11a 6Mbps	Back	0mm	100	5500	14.09	14.50	1.099	86.69	1.154	-0.05	0.218	0.276
	WLAN5GHz	802.11a 6Mbps	Back	0mm	132	5660	17.33	17.50	1.040	86.69	1.154	-0.07	0.168	0.202
	WLAN5GHz	802.11a 6Mbps	Back	0mm	140	5700	14.17	14.50	1.079	86.69	1.154	0.16	0.047	0.059
	WLAN5GHz	802.11a 6Mbps	Left Side	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0	0.107	0.127
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	116	5580	17.37	17.50	1.030	86.69	1.154	0.03	0.024	0.029

13.4 Body Worn Accessory SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	-	9538	1907.6	23.13	23.20	1.016	-0.07	0.601	0.611
28	WCDMA II	RMC 12.2Kbps	Back	10mm	-	9538	1907.6	23.13	23.20	1.016	-0.17	1.420	1.443
	WCDMA II	RMC 12.2Kbps	Back	10mm	-	9262	1852.4	22.94	23.20	1.062	-0.11	1.260	1.338
	WCDMA II	RMC 12.2Kbps	Back	10mm	-	9400	1880	23.00	23.20	1.047	-0.14	1.310	1.372
	WCDMA II	RMC 12.2Kbps	Back	10mm	Headset	9538	1907.6	23.13	23.20	1.016	-0.09	1.410	1.433
	WCDMA V	RMC 12.2Kbps	Front	10mm	-	4132	826.4	23.15	24.50	1.365	-0.08	0.292	0.398
	WCDMA V	RMC 12.2Kbps	Back	10mm	-	4132	826.4	23.15	24.50	1.365	0.1	0.472	0.644
29	WCDMA V	RMC 12.2Kbps	Back	10mm	-	4182	836.4	23.06	24.50	1.393	0.02	0.506	0.705
	WCDMA V	RMC 12.2Kbps	Back	10mm	-	4233	846.6	22.97	24.50	1.422	0	0.485	0.690

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	49	Front	10mm	-	18700	1860	23.80	24.00	1.047	-0.07	0.588	0.616
	LTE Band 2	20M	QPSK	50	0	Front	10mm	-	18700	1860	22.44	23.00	1.138	-0.07	0.455	0.518
	LTE Band 2	20M	QPSK	1	49	Back	10mm	-	18700	1860	23.80	24.00	1.047	-0.14	1.260	1.319
	LTE Band 2	20M	QPSK	1	49	Back	10mm	-	18900	1880	23.62	24.00	1.091	-0.11	1.260	1.375
30	LTE Band 2	20M	QPSK	1	49	Back	10mm	-	19100	1900	23.76	24.00	1.057	-0.1	1.360	1.437
	LTE Band 2	20M	QPSK	50	0	Back	10mm	-	18700	1860	22.44	23.00	1.138	-0.12	1.010	1.149
	LTE Band 2	20M	QPSK	50	0	Back	10mm	-	18900	1880	22.36	23.00	1.159	-0.13	1.060	1.228
	LTE Band 2	20M	QPSK	50	0	Back	10mm	-	19100	1900	22.42	23.00	1.143	-0.01	1.090	1.246
	LTE Band 2	20M	QPSK	100	0	Back	10mm	-	18700	1860	22.33	23.00	1.167	-0.18	1.020	1.190
	LTE Band 2	20M	QPSK	1	49	Back	10mm	Headset	19100	1900	23.76	24.00	1.057	-0.07	1.350	1.427
	LTE Band 4	20M	QPSK	1	49	Front	10mm	-	20175	1732.5	23.77	24.50	1.183	-0.01	0.461	0.545
	LTE Band 4	20M	QPSK	50	0	Front	10mm	-	20175	1732.5	22.87	23.50	1.156	0.02	0.336	0.388
31	LTE Band 4	20M	QPSK	1	49	Back	10mm	-	20175	1732.5	23.77	24.50	1.183	0.13	0.915	1.082
	LTE Band 4	20M	QPSK	50	0	Back	10mm	-	20175	1732.5	22.87	23.50	1.156	0.1	0.660	0.763
	LTE Band 4	20M	QPSK	100	0	Back	10mm	-	20175	1732.5	22.78	23.50	1.180	0.02	0.679	0.801
	LTE Band 5	10M	QPSK	1	25	Front	10mm	-	20525	836.5	23.85	24.50	1.161	0.18	0.325	0.377
	LTE Band 5	10M	QPSK	25	25	Front	10mm	-	20525	836.5	22.76	23.50	1.186	0.01	0.268	0.318
32	LTE Band 5	10M	QPSK	1	25	Back	10mm	-	20525	836.5	23.85	24.50	1.161	-0.12	0.531	0.617
	LTE Band 5	10M	QPSK	25	25	Back	10mm	-	20525	836.5	22.76	23.50	1.186	-0.06	0.446	0.529
	LTE Band 12	10M	QPSK	1	25	Front	10mm	-	23095	707.5	23.68	24.50	1.208	-0.08	0.293	0.354
	LTE Band 12	10M	QPSK	25	12	Front	10mm	-	23095	707.5	22.62	23.50	1.225	0.02	0.237	0.290
33	LTE Band 12	10M	QPSK	1	25	Back	10mm	-	23095	707.5	23.68	24.50	1.208	0.05	0.435	0.525
	LTE Band 12	10M	QPSK	25	12	Back	10mm	-	23095	707.5	22.62	23.50	1.225	-0.03	0.331	0.405
	LTE Band 13	10M	QPSK	1	25	Front	10mm	-	23230	782	23.89	24.50	1.151	-0.08	0.362	0.417
	LTE Band 13	10M	QPSK	25	0	Front	10mm	-	23230	782	22.76	23.50	1.186	-0.06	0.278	0.330
34	LTE Band 13	10M	QPSK	1	25	Back	10mm	-	23230	782	23.89	24.50	1.151	-0.05	0.593	0.682
	LTE Band 13	10M	QPSK	25	0	Back	10mm	-	23230	782	22.76	23.50	1.186	0.03	0.442	0.524

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	-	6	2437	19.32	19.50	1.042	100	1.000	-0.01	0.095	0.099
35	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	-	6	2437	19.32	19.50	1.042	100	1.000	-0.02	0.170	0.177
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	-	1	2412	19.25	19.50	1.059	100	1.000	-0.12	0.162	0.172
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	-	11	2462	19.30	19.50	1.047	100	1.000	-0.12	0.160	0.168
	WLAN5GHz	802.11a 6Mbps	Front	10mm	-	60	5300	17.24	17.50	1.062	86.69	1.154	-0.12	0.051	0.062
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	60	5300	17.24	17.50	1.062	86.69	1.154	-0.07	0.597	0.731
36	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	56	5280	17.23	17.50	1.064	86.69	1.154	-0.01	0.609	0.748
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	52	5260	17.22	17.50	1.067	86.69	1.154	-0.04	0.575	0.708
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	64	5320	14.33	14.50	1.040	86.69	1.154	0.04	0.284	0.341
	WLAN5GHz	802.11a 6Mbps	Front	10mm	-	116	5580	17.37	17.50	1.030	86.69	1.154	0.11	0.015	0.018
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	116	5580	17.37	17.50	1.030	86.69	1.154	0.01	0.200	0.238
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	100	5500	14.09	14.50	1.099	86.69	1.154	0	0.242	0.307
37	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	132	5660	17.33	17.50	1.040	86.69	1.154	0.1	0.265	0.318
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	140	5700	14.17	14.50	1.079	86.69	1.154	-0.03	0.074	0.092
	WLAN5GHz	802.11a 6Mbps	Front	10mm	-	157	5785	17.42	17.50	1.019	86.69	1.154	0.18	0.011	0.013
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	157	5785	17.42	17.50	1.019	86.69	1.154	-0.06	0.116	0.136
38	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	149	5745	17.18	17.50	1.076	86.69	1.154	-0.04	0.133	0.165
	WLAN5GHz	802.11a 6Mbps	Back	10mm	-	165	5825	17.17	17.50	1.079	86.69	1.154	-0.04	0.087	0.108

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	-	0	2402	10.38	11.70	1.355	76.72	1.086	-0.05	0.007	0.010
	Bluetooth	1Mbps	Back	10mm	-	0	2402	10.38	11.70	1.355	76.72	1.086	0.16	0.012	0.018
39	Bluetooth	1Mbps	Back	10mm	-	39	2441	10.21	11.70	1.409	76.72	1.086	0.09	0.013	0.020
	Bluetooth	1Mbps	Back	10mm	-	78	2480	9.14	9.90	1.191	76.72	1.086	-0.05	0.010	0.013

13.5 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.13	23.20	1.016	-0.17	1.420		1.443
2nd	WCDMA II	RMC 12.2Kbps	Back	10mm	9538	1907.6	23.13	23.20	1.016	0.13	1.400	1.01	1.423
1st	LTE Band 4	20M_QPSK_1_49	Back	10mm	20175	1732.5	23.77	24.50	1.183	0.13	0.915		1.082
2nd	LTE Band 4	20M_QPSK_1_49	Back	10mm	20175	1732.5	23.77	24.50	1.183	0.05	0.858	1.07	1.015

No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	LTE Band 2	20M	QPSK	1	49	Back	0mm	19100	1900	23.76	24.00	1.057	0.05	2.670		2.822
2nd	LTE Band 2	20M	QPSK	1	49	Back	0mm	19100	1900	23.76	24.00	1.057	-0.07	2.640	1.01	2.790

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured* SAR.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product Specific
1.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
2.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA+ Bluetooth	Yes	Yes	Yes	Yes
4.	LTE + Bluetooth	Yes	Yes	Yes	Yes
5.	WCDMA + WLAN5GHz	Yes	Yes	Yes	Yes
6.	LTE + WLAN5GHz	Yes	Yes	Yes	Yes

General Note:

1. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. All licensed modes share the same antenna part and cannot transmit simultaneously.
4. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
5. The Scaled SAR summation is calculated based on the same configuration and test position.
6. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
 - v) The SPLSR calculated results please refer to section 14.5.

14.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
WCDMA	WCDMA II	Right Cheek	0.684	0.423	0.284	0.034	1.107	0.968	0.718
		Right Tilted	0.235	0.233	0.179	0.016	0.468	0.414	0.251
		Left Cheek	0.408	0.197	0.185	0.016	0.605	0.593	0.424
		Left Tilted	0.270	0.183	0.158	0.016	0.453	0.428	0.286
	WCDMA V	Right Cheek	0.397	0.423	0.284	0.034	0.820	0.681	0.431
		Right Tilted	0.236	0.233	0.179	0.016	0.469	0.415	0.252
		Left Cheek	0.441	0.197	0.185	0.016	0.638	0.626	0.457
		Left Tilted	0.222	0.183	0.158	0.016	0.405	0.380	0.238
LTE	LTE Band 2	Right Cheek	0.768	0.423	0.284	0.034	1.191	1.052	0.802
		Right Tilted	0.355	0.233	0.179	0.016	0.588	0.534	0.371
		Left Cheek	0.481	0.197	0.185	0.016	0.678	0.666	0.497
		Left Tilted	0.382	0.183	0.158	0.016	0.565	0.540	0.398
	LTE Band 4	Right Cheek	0.838	0.423	0.284	0.034	1.261	1.122	0.872
		Right Tilted	0.351	0.233	0.179	0.016	0.584	0.530	0.367
		Left Cheek	0.461	0.197	0.185	0.016	0.658	0.646	0.477
		Left Tilted	0.408	0.183	0.158	0.016	0.591	0.566	0.424
	LTE Band 5	Right Cheek	0.355	0.423	0.284	0.034	0.778	0.639	0.389
		Right Tilted	0.264	0.233	0.179	0.016	0.497	0.443	0.280
		Left Cheek	0.438	0.197	0.185	0.016	0.635	0.623	0.454
		Left Tilted	0.231	0.183	0.158	0.016	0.414	0.389	0.247
	LTE Band 12	Right Cheek	0.308	0.423	0.284	0.034	0.731	0.592	0.342
		Right Tilted	0.184	0.233	0.179	0.016	0.417	0.363	0.200
		Left Cheek	0.274	0.197	0.185	0.016	0.471	0.459	0.290
		Left Tilted	0.158	0.183	0.158	0.016	0.341	0.316	0.174
	LTE Band 13	Right Cheek	0.307	0.423	0.284	0.034	0.730	0.591	0.341
		Right Tilted	0.185	0.233	0.179	0.016	0.418	0.364	0.201
		Left Cheek	0.367	0.197	0.185	0.016	0.564	0.552	0.383
		Left Tilted	0.171	0.183	0.158	0.016	0.354	0.329	0.187



14.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2	1+3	1+4	1+2	1+2	1+3	1+3
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	SPLSR	Case No	SPLSR	Case No
WCDMA	WCDMA II	Front	0.611	0.099	0.013	0.010	0.710	0.624	0.621				
		Back	1.443	0.177	0.287	0.018	1.620	1.730	1.461	0.02	Case 1	0.02	Case 10
		Left side	0.072	0.193	0.075	0.024	0.265	0.147	0.096				
		Right side	0.644				0.644	0.644	0.644				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.975				0.975	0.975	0.975				
	WCDMA V	Front	0.398	0.099	0.013	0.010	0.497	0.411	0.408				
		Back	0.705	0.177	0.287	0.018	0.882	0.992	0.723				
		Left side	0.490	0.193	0.075	0.024	0.683	0.565	0.514				
		Right side	0.364				0.364	0.364	0.364				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.029				0.029	0.029	0.029				
LTE	LTE Band 2	Front	0.616	0.099	0.013	0.010	0.715	0.629	0.626				
		Back	1.437	0.177	0.287	0.018	1.614	1.724	1.455	0.02	Case 2	0.02	Case 11
		Left side	0.065	0.193	0.075	0.024	0.258	0.140	0.089				
		Right side	0.577				0.577	0.577	0.577				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	1.027				1.027	1.027	1.027				
	LTE Band 4	Front	0.545	0.099	0.013	0.010	0.644	0.558	0.555				
		Back	1.082	0.177	0.287	0.018	1.259	1.369	1.100				
		Left side	0.050	0.193	0.075	0.024	0.243	0.125	0.074				
		Right side	0.401				0.401	0.401	0.401				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.681				0.681	0.681	0.681				
	LTE Band 5	Front	0.377	0.099	0.013	0.010	0.476	0.390	0.387				
		Back	0.617	0.177	0.287	0.018	0.794	0.904	0.635				
		Left side	0.576	0.193	0.075	0.024	0.769	0.651	0.600				
		Right side	0.379				0.379	0.379	0.379				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.128				0.128	0.128	0.128				
	LTE Band 12	Front	0.354	0.099	0.013	0.010	0.453	0.367	0.364				
		Back	0.525	0.177	0.287	0.018	0.702	0.812	0.543				
		Left side	0.391	0.193	0.075	0.024	0.584	0.466	0.415				
		Right side	0.325				0.325	0.325	0.325				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.016				0.016	0.016	0.016				
	LTE Band 13	Front	0.417	0.099	0.013	0.010	0.516	0.430	0.427				
		Back	0.682	0.177	0.287	0.018	0.859	0.969	0.700				
		Left side	0.450	0.193	0.075	0.024	0.643	0.525	0.474				
		Right side	0.400				0.400	0.400	0.400				
		Top side		0.099	0.039	0.011	0.099	0.039	0.011				
		Bottom side	0.071				0.071	0.071	0.071				

14.3 Product Specific Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
WCDMA	WCDMA II	Front	-	-	0.083	-	0.000	0.083	0.000
		Back	2.612	-	0.664	-	2.612	3.276	2.612
		Left side	-	-	0.561	-	0.000	0.561	0.000
		Right side	-	-	-	-	0.000	0.000	0.000
		Top side	-	-	0.131	-	0.000	0.131	0.000
		Bottom side	-	-	-	-	0.000	0.000	0.000
LTE	LTE Band 2	Front	-	-	0.083	-	0.000	0.083	0.000
		Back	2.822	-	0.664	-	2.822	3.486	2.822
		Left side	-	-	0.561	-	0.000	0.561	0.000
		Right side	-	-	-	-	0.000	0.000	0.000
		Top side	-	-	0.131	-	0.000	0.131	0.000
		Bottom side	-	-	-	-	0.000	0.000	0.000

Note:

- According to KDB 941225 D06 v02r01 and KDB 648474 D04v01r03, for WWAN / 2.4GHz WLAN / Bluetooth and 5GHz WLAN SAR ("") was excluded, due to transmitting antenna located larger 25mm from that surface or edge and Hotspot SAR was < 1.2W/Kg.

14.4 Body-Worn Accessory Exposure Conditions


WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No	SPLSR	Case No
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth							
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)							
WCDMA	WCDMA II	Front	0.611	0.099	0.062	0.010	0.710	0.673	0.621				
		Back	1.443	0.177	0.748	0.020	1.620	2.191	1.463	0.02	Case 1	0.03	Case 5
		Back with Headset	1.433	0.177	0.748	0.020	1.610	2.181	1.453	0.02	Case 3	0.02	Case 6
	WCDMA V	Front	0.398	0.099	0.062	0.010	0.497	0.460	0.408				
		Back	0.705	0.177	0.748	0.020	0.882	1.453	0.725				
LTE	LTE Band 2	Front	0.616	0.099	0.062	0.010	0.715	0.678	0.626				
		Back	1.437	0.177	0.748	0.020	1.614	2.185	1.457	0.02	Case 2	0.02	Case 7
		Back with Headset	1.427	0.177	0.748	0.020	1.604	2.175	1.447	0.01	Case 4	0.02	Case 8
	LTE Band 4	Front	0.545	0.099	0.062	0.010	0.644	0.607	0.555				
		Back	1.082	0.177	0.748	0.020	1.259	1.830	1.102			0.02	Case 9
	LTE Band 5	Front	0.377	0.099	0.062	0.010	0.476	0.439	0.387				
		Back	0.617	0.177	0.748	0.020	0.794	1.365	0.637				
	LTE Band 12	Front	0.354	0.099	0.062	0.010	0.453	0.416	0.364				
		Back	0.525	0.177	0.748	0.020	0.702	1.273	0.545				
	LTE Band 13	Front	0.417	0.099	0.062	0.010	0.516	0.479	0.427				
		Back	0.682	0.177	0.748	0.020	0.859	1.430	0.702				

14.5 SPLSR Evaluation and Analysis


General Note:

1. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary


Case 1	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back	1.443	10mm	X	Y	Z	135.0	1.62	0.02	Not required
	WLAN2.4GHz		0.177	10mm	24	61	-1.16				




Case 2	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Back	1.437	10mm	X	Y	Z	134.8	1.61	0.02	Not required
	WLAN2.4GHz		0.177	10mm	24	61	-1.16				




Case 3	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back + Headset	1.433	10mm	X	Y	Z	135.5	1.61	0.02	Not required
	WLAN2.4GHz		0.177	10mm	24	61	-1.16				




Case 4	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Back+Headset	1.427	10mm	X	Y	Z	136.3	1.60	0.01	Not required
	WLAN2.4GHz		0.177	10mm	24	61	-1.16				




Case 5	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back	1.443	10mm	X	Y	Z	129.7	2.19	0.03	Not required
	WLAN5GHz		0.748	10mm	22	56	-0.39				




Case 6	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back + Headset	1.433	10mm	X	Y	Z	130.1	2.18	0.02	Not required
	WLAN5GHz		0.748	10mm	22	56	-0.39				




Case 7	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Back	1.437	10mm	X	Y	Z	129.5	2.19	0.02	Not required
	WLAN5GHz		0.748	10mm	22	56	-0.39				




Case 8	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 2	Back + Headset	1.427	10mm	X	Y	Z	131.0	2.18	0.02	Not required
	WLAN5GHz		0.748	10mm	22	56	-0.39				




Case 9	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE Band 4	Back	1.082	10mm	X	Y	Z	129.4	1.83	0.02	Not required
	WLAN5GHz		0.748	10mm	22	56	-0.39				



Case 10	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back	1.443	10mm	X	Y	Z	127.1	1.73	0.02	Not required
	WLAN5GHz		0.287	10mm	24	52.8	-2.03				



Case 11	Band	Position	SAR (W/kg)	Gap (cm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 2	Back	1.437	10mm	-11.3	-69.1	-1.13	126.9	1.72	0.02	Not required
	WLAN5GHz		0.287	10mm	24	52.8	-2.03				



Test Engineer : Bevis Chang Tom Jiang Kurt Liu Wilson Lin Jay Jian Willy Yu Andy Jiang Randy Lin
Neil Hsiang and White Huang



15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 648474 D03 v01r04, "Evaluation and Approval Considerations for Handsets with Specific Wireless Charging Battery Covers" Dec 2015.
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.