


FCC Co-Location Test Report

FCC ID : ACQ-VIP7802
Equipment : WiFi Set Top Box
Model No. : VIP7802
Brand Name : ARRIS
Applicant : ARRIS Group, Inc.
Address : 101 Tournament Drive, Horsham,
Pennsylvania, United States 19044
Standard : 47 CFR FCC Part 15.247
47 CFR FCC Part 15.407
Received Date : Feb. 03, 2021
Tested Date : Feb. 19 ~ Mar. 01, 2021

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Testing Laboratory
2732

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	The Equipment List	7
1.3	Test Standards	8
1.4	Reference Guidance	8
1.5	Deviation from Test Standard and Measurement Procedure.....	8
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION.....	9
2.1	Testing Facility	9
2.2	The Worst Test Modes and Channel Details	9
3	TRANSMITTER TEST RESULTS	10
3.1	Unwanted Emissions into Restricted Frequency Bands	10
4	TEST LABORATORY INFORMATION	20

Release Record

Report No.	Version	Description	Issued Date
FR120304CO	Rev. 01	Initial issue	May 04, 2021

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 2367.00MHz 52.59(Margin -1.41dB) - AV	Pass
15.209			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

WLAN	
Operating Frequency	802.11b/g/n/ax: 2412 MHz ~ 2462 MHz 802.11a/n/ac/ax: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz, 5745 MHz ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK/DQPSK/CCK) 802.11a/g/n/ac/ax: OFDM/OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)
Bluetooth	
Operating Frequency	2402 MHz ~ 2480 MHz
Modulation Type	Bluetooth 5.0 LE: GFSK Bluetooth BR(1Mbps): GFSK Bluetooth EDR (2Mbps): π/4-DQPSK Bluetooth EDR (3Mbps): 8-DPSK

1.1.2 Antenna Details of Specific platform

BT

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	PIFA	N/A	1.5	---

WiFi

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	Ant 1	Dipole	U.FL	3	3	3.1	4.4	4.3
2	Ant 2	Dipole	U.FL	3.2	3.2	3.6	4.5	4.6

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from adapter
-------------------	-------------------

1.1.4 Accessories of Specific platform

Accessories		
No.	Equipment	Description
1	Adapter	Brand: NeBit Model: NBS12F050200VU Power Rating: I/P: 100-240Vac, 50/60Hz, 0.3A O/P: 5Vdc, 2A Power Line: 0.75m non-shielded without core
2	Remote control	Brand: Bell Model: 2855-001
3	HDMI	1.83m shielded without core
4	SD card	Brand: SanDisk Model: SDSDQEC-008G Capacity: 8GB

1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber3 / (03CH03-WS)				
Tested Date	Feb. 19 ~ Mar. 01, 2021				
Instrument	Brand	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101658	Feb. 08, 2021	Feb. 07, 2022
Spectrum Analyzer	R&S	FSV40	101498	Dec. 04, 2020	Dec. 03, 2021
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 17, 2020	Nov. 16, 2021
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 29, 2020	Apr. 28, 2021
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Dec. 22, 2020	Dec. 21, 2021
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 06, 2020	Nov. 05, 2021
Preamplifier	EMC	EMC02325	980187	Aug. 05, 2020	Aug. 04, 2021
Preamplifier	Agilent	83017A	MY39501309	Sep. 02, 2020	Sep. 01, 2021
Preamplifier	EMC	EMC184045B	980192	Jul. 21, 2020	Jul. 20, 2021
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 06, 2020	Oct. 05, 2021
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Sep. 26, 2020	Sep. 25, 2021
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Sep. 26, 2020	Sep. 25, 2021
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Sep. 26, 2020	Sep. 25, 2021
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Sep. 26, 2020	Sep. 25, 2021
RF cable-8M	EMC	EMC104-SM-SM-800	181107	Sep. 26, 2020	Sep. 25, 2021
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Receiver	R&S	ESR3	101658	Feb. 08, 2021	Feb. 07, 2022

Note: Calibration Interval of instruments listed above is one year.

1.3 Test Standards

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

1.4 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

1.5 Deviation from Test Standard and Measurement Procedure

None

1.6 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission \leq 1GHz	± 3.96 dB
Radiated emission $>$ 1GHz	± 4.51 dB

2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corporation
Test Site	03CH03-WS
Address of Test Site	No.14-1, Lane 19, Wen San 3rd St., Kwei Shan Dist., Tao Yuan City 333, Taiwan (R.O.C.)

- FCC Designation No.: TW0009
- FCC site registration No.: 207696
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Test Mode	Test Configuration
Radiated Emissions	2.4G 11g CH6 + BT EDR CH00	---
	5G 11a CH157 + BT EDR CH00	---

Note: The selected channel is the maximum power channel of each Wireless function.

3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.1.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Test Mode	2.4G 11g CH6 + BT EDR CH00																																																																													
Polarization	Horizontal																																																																													
Test By	: Roger Lu		Temperature (°C): 23		Humidity (%): 65																																																																									
Level (dBuV/m)																																																																														
																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq. MHz</th> <th style="text-align: center;">Emission level dBuV/m</th> <th style="text-align: center;">Limit dBuV/m</th> <th style="text-align: center;">Margin dB</th> <th style="text-align: center;">SA reading dBuV</th> <th style="text-align: center;">Factor dB</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High cm</th> <th style="text-align: center;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">76.56</td> <td style="text-align: center;">29.12</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-10.88</td> <td style="text-align: center;">41.76</td> <td style="text-align: center;">-12.64</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>2</td> <td style="text-align: center;">93.05</td> <td style="text-align: center;">35.33</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-8.17</td> <td style="text-align: center;">49.98</td> <td style="text-align: center;">-14.65</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>3</td> <td style="text-align: center;">101.78</td> <td style="text-align: center;">36.14</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-7.36</td> <td style="text-align: center;">49.50</td> <td style="text-align: center;">-13.36</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>4</td> <td style="text-align: center;">208.86</td> <td style="text-align: center;">37.25</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-6.25</td> <td style="text-align: center;">49.44</td> <td style="text-align: center;">-12.19</td> <td style="text-align: center;">QP</td> <td style="text-align: center;">128</td> <td style="text-align: center;">251</td> </tr> <tr> <td>5</td> <td style="text-align: center;">301.60</td> <td style="text-align: center;">34.31</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-11.69</td> <td style="text-align: center;">42.88</td> <td style="text-align: center;">-8.57</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>6</td> <td style="text-align: center;">384.05</td> <td style="text-align: center;">32.52</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-13.48</td> <td style="text-align: center;">38.71</td> <td style="text-align: center;">-6.19</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> </tbody> </table>										Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	76.56	29.12	40.00	-10.88	41.76	-12.64	Peak	---	---	2	93.05	35.33	43.50	-8.17	49.98	-14.65	Peak	---	---	3	101.78	36.14	43.50	-7.36	49.50	-13.36	Peak	---	---	4	208.86	37.25	43.50	-6.25	49.44	-12.19	QP	128	251	5	301.60	34.31	46.00	-11.69	42.88	-8.57	Peak	---	---	6	384.05	32.52	46.00	-13.48	38.71	-6.19	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																					
1	76.56	29.12	40.00	-10.88	41.76	-12.64	Peak	---	---																																																																					
2	93.05	35.33	43.50	-8.17	49.98	-14.65	Peak	---	---																																																																					
3	101.78	36.14	43.50	-7.36	49.50	-13.36	Peak	---	---																																																																					
4	208.86	37.25	43.50	-6.25	49.44	-12.19	QP	128	251																																																																					
5	301.60	34.31	46.00	-11.69	42.88	-8.57	Peak	---	---																																																																					
6	384.05	32.52	46.00	-13.48	38.71	-6.19	Peak	---	---																																																																					
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																														


Test Mode	2.4G 11g CH6 + BT EDR CH00																																																																														
Polarization	Vertical																																																																														
Test By	:Roger Lu			Temperature(°C):23			Humidity(%):65																																																																								
 <p>The graph shows the measured spectral emissions (blue lines) and the emission limits (red lines) in dBuV/m versus frequency in MHz. The x-axis ranges from 30 to 1000 MHz, and the y-axis ranges from 0 to 90 dBuV/m. The red lines represent the limits for Class B, with a stepped profile. The blue lines represent the measured data, which are mostly below the limits, with some spikes at lower frequencies (labeled 1, 2, 3, 4, 5, 6) and a larger spike at 2.4 GHz.</p>																																																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq. MHz</th> <th style="text-align: center;">Emission level dBuV/m</th> <th style="text-align: center;">Margin dB</th> <th style="text-align: center;">SA reading dBuV</th> <th style="text-align: center;">Factor dB</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High cm</th> <th style="text-align: center;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">59.10</td> <td style="text-align: center;">35.74</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-4.26</td> <td style="text-align: center;">44.93</td> <td style="text-align: center;">-9.19</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>2</td> <td style="text-align: center;">67.83</td> <td style="text-align: center;">35.66</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-4.34</td> <td style="text-align: center;">46.08</td> <td style="text-align: center;">-10.42</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>3</td> <td style="text-align: center;">76.56</td> <td style="text-align: center;">35.79</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-4.21</td> <td style="text-align: center;">48.43</td> <td style="text-align: center;">-12.64</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>4</td> <td style="text-align: center;">93.05</td> <td style="text-align: center;">38.01</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-5.49</td> <td style="text-align: center;">52.66</td> <td style="text-align: center;">-14.65</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>5</td> <td style="text-align: center;">170.65</td> <td style="text-align: center;">33.99</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-9.51</td> <td style="text-align: center;">43.25</td> <td style="text-align: center;">-9.26</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>6</td> <td style="text-align: center;">207.51</td> <td style="text-align: center;">36.04</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-7.46</td> <td style="text-align: center;">48.24</td> <td style="text-align: center;">-12.20</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> </tbody> </table>												Freq. MHz	Emission level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	59.10	35.74	40.00	-4.26	44.93	-9.19	Peak	---	---	2	67.83	35.66	40.00	-4.34	46.08	-10.42	Peak	---	---	3	76.56	35.79	40.00	-4.21	48.43	-12.64	Peak	---	---	4	93.05	38.01	43.50	-5.49	52.66	-14.65	Peak	---	---	5	170.65	33.99	43.50	-9.51	43.25	-9.26	Peak	---	---	6	207.51	36.04	43.50	-7.46	48.24	-12.20	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																							
1	59.10	35.74	40.00	-4.26	44.93	-9.19	Peak	---	---																																																																						
2	67.83	35.66	40.00	-4.34	46.08	-10.42	Peak	---	---																																																																						
3	76.56	35.79	40.00	-4.21	48.43	-12.64	Peak	---	---																																																																						
4	93.05	38.01	43.50	-5.49	52.66	-14.65	Peak	---	---																																																																						
5	170.65	33.99	43.50	-9.51	43.25	-9.26	Peak	---	---																																																																						
6	207.51	36.04	43.50	-7.46	48.24	-12.20	Peak	---	---																																																																						

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


Test Mode	5G 11a CH157 + BT EDR CH00																																																																															
Polarization	Horizontal																																																																															
Test By	:Roger Lu			Temperature(°C):23	Humidity(%):65																																																																											
																																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq.</th> <th style="text-align: center;">Emission level</th> <th style="text-align: center;">Margin</th> <th style="text-align: center;">SA reading</th> <th style="text-align: center;">Factor</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High</th> <th style="text-align: center;">Turn Table</th> </tr> <tr> <th></th> <th style="text-align: center;">MHz</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dBuV/m</th> <th style="text-align: center;">dB</th> <th style="text-align: center;">dBuV</th> <th style="text-align: center;">dB</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">78.15</td> <td style="text-align: center;">31.02</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-8.98</td> <td style="text-align: center;">44.02</td> <td style="text-align: center;">-13.00</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> </tr> <tr> <td>2</td> <td style="text-align: center;">94.54</td> <td style="text-align: center;">36.22</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-7.28</td> <td style="text-align: center;">50.82</td> <td style="text-align: center;">-14.60</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> </tr> <tr> <td>3</td> <td style="text-align: center;">102.88</td> <td style="text-align: center;">37.05</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-6.45</td> <td style="text-align: center;">50.30</td> <td style="text-align: center;">-13.25</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> </tr> <tr> <td>4</td> <td style="text-align: center;">209.11</td> <td style="text-align: center;">37.52</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-5.98</td> <td style="text-align: center;">49.71</td> <td style="text-align: center;">-12.19</td> <td style="text-align: center;">QP</td> <td style="text-align: center;">130</td> </tr> <tr> <td>5</td> <td style="text-align: center;">302.58</td> <td style="text-align: center;">36.21</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-9.79</td> <td style="text-align: center;">44.75</td> <td style="text-align: center;">-8.54</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> </tr> <tr> <td>6</td> <td style="text-align: center;">383.11</td> <td style="text-align: center;">34.82</td> <td style="text-align: center;">46.00</td> <td style="text-align: center;">-11.18</td> <td style="text-align: center;">41.03</td> <td style="text-align: center;">-6.21</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> </tr> </tbody> </table>										Freq.	Emission level	Margin	SA reading	Factor	Remark	ANT High	Turn Table		MHz	dBuV/m	dBuV/m	dB	dBuV	dB			1	78.15	31.02	40.00	-8.98	44.02	-13.00	Peak	---	2	94.54	36.22	43.50	-7.28	50.82	-14.60	Peak	---	3	102.88	37.05	43.50	-6.45	50.30	-13.25	Peak	---	4	209.11	37.52	43.50	-5.98	49.71	-12.19	QP	130	5	302.58	36.21	46.00	-9.79	44.75	-8.54	Peak	---	6	383.11	34.82	46.00	-11.18	41.03	-6.21	Peak	---
	Freq.	Emission level	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																										
1	78.15	31.02	40.00	-8.98	44.02	-13.00	Peak	---																																																																								
2	94.54	36.22	43.50	-7.28	50.82	-14.60	Peak	---																																																																								
3	102.88	37.05	43.50	-6.45	50.30	-13.25	Peak	---																																																																								
4	209.11	37.52	43.50	-5.98	49.71	-12.19	QP	130																																																																								
5	302.58	36.21	46.00	-9.79	44.75	-8.54	Peak	---																																																																								
6	383.11	34.82	46.00	-11.18	41.03	-6.21	Peak	---																																																																								

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Test Mode	5G 11a CH157 + BT EDR CH00																																																																													
Polarization	Vertical																																																																													
Test By	:Roger Lu			Temperature(°C):23			Humidity(%):65																																																																							
 <p>The graph shows the measured spectral emissions (blue lines) and the emission limit (red line) in dBuV/m versus frequency in MHz. The x-axis ranges from 30 to 1000 MHz, and the y-axis ranges from 0 to 90 dBuV/m. The emission limit is a stepped red line starting at 40 dBuV/m from 30 MHz, rising to 45 dBuV/m at 100 MHz, 50 dBuV/m at 200 MHz, and 55 dBuV/m at 900 MHz, then dropping to 75 dBuV/m at 1000 MHz. Six spurious emissions are labeled with numbers 1 through 6, corresponding to the data in the table below. The measured levels for these spurs are consistently below the emission limit.</p>																																																																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq. MHz</th> <th style="text-align: center;">Emission level dBuV/m</th> <th style="text-align: center;">Margin dB</th> <th style="text-align: center;">SA reading dBuV</th> <th style="text-align: center;">Factor dB</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High cm</th> <th style="text-align: center;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">60.22</td> <td style="text-align: center;">36.00</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-4.00</td> <td style="text-align: center;">45.26</td> <td style="text-align: center;">-9.26</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>2</td> <td style="text-align: center;">66.99</td> <td style="text-align: center;">34.98</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-5.02</td> <td style="text-align: center;">45.34</td> <td style="text-align: center;">-10.36</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>3</td> <td style="text-align: center;">77.28</td> <td style="text-align: center;">36.08</td> <td style="text-align: center;">40.00</td> <td style="text-align: center;">-3.92</td> <td style="text-align: center;">48.97</td> <td style="text-align: center;">-12.89</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>4</td> <td style="text-align: center;">94.28</td> <td style="text-align: center;">39.10</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-4.40</td> <td style="text-align: center;">53.72</td> <td style="text-align: center;">-14.62</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>5</td> <td style="text-align: center;">171.52</td> <td style="text-align: center;">35.21</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-8.29</td> <td style="text-align: center;">44.55</td> <td style="text-align: center;">-9.34</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> <tr> <td>6</td> <td style="text-align: center;">205.84</td> <td style="text-align: center;">38.40</td> <td style="text-align: center;">43.50</td> <td style="text-align: center;">-5.10</td> <td style="text-align: center;">50.60</td> <td style="text-align: center;">-12.20</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">---</td> <td style="text-align: center;">---</td> </tr> </tbody> </table>											Freq. MHz	Emission level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	60.22	36.00	40.00	-4.00	45.26	-9.26	Peak	---	---	2	66.99	34.98	40.00	-5.02	45.34	-10.36	Peak	---	---	3	77.28	36.08	40.00	-3.92	48.97	-12.89	Peak	---	---	4	94.28	39.10	43.50	-4.40	53.72	-14.62	Peak	---	---	5	171.52	35.21	43.50	-8.29	44.55	-9.34	Peak	---	---	6	205.84	38.40	43.50	-5.10	50.60	-12.20	Peak	---	---
	Freq. MHz	Emission level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																						
1	60.22	36.00	40.00	-4.00	45.26	-9.26	Peak	---	---																																																																					
2	66.99	34.98	40.00	-5.02	45.34	-10.36	Peak	---	---																																																																					
3	77.28	36.08	40.00	-3.92	48.97	-12.89	Peak	---	---																																																																					
4	94.28	39.10	43.50	-4.40	53.72	-14.62	Peak	---	---																																																																					
5	171.52	35.21	43.50	-8.29	44.55	-9.34	Peak	---	---																																																																					
6	205.84	38.40	43.50	-5.10	50.60	-12.20	Peak	---	---																																																																					


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)


Test Mode	2.4G 11g CH6 + BT EDR CH00																																																											
Polarization	Horizontal																																																											
Test By	:Roger Lu			Temperature(°C):24			Humidity(%):65																																																					
 <p>The graph plots Emission Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent the limits: 'CLASS-B' at approximately 74 dBuV/m and 'CLASS-B (AVG)' at approximately 54 dBuV/m. Four vertical blue lines indicate measured data points: '2' at 2367.00 MHz (51.22 dBuV/m), '3' at 4839.00 MHz (32.30 dBuV/m), '4' at 4839.00 MHz (45.33 dBuV/m), and '1' at 2367.00 MHz (26.00 dBuV/m, not shown on the graph).</p>																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="text-align: center;">Freq. MHz</th> <th style="text-align: center;">Emission level dBuV/m</th> <th style="text-align: center;">Limit level dBuV/m</th> <th style="text-align: center;">Margin dB</th> <th style="text-align: center;">SA reading dBuV</th> <th style="text-align: center;">Factor dB</th> <th style="text-align: center;">Remark</th> <th style="text-align: center;">ANT High cm</th> <th style="text-align: center;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td style="text-align: center;">2367.00</td> <td style="text-align: center;">51.22</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-2.78</td> <td style="text-align: center;">52.86</td> <td style="text-align: center;">-1.64</td> <td style="text-align: center;">Average</td> <td style="text-align: center;">100</td> <td style="text-align: center;">173</td> </tr> <tr> <td>2</td> <td style="text-align: center;">2367.00</td> <td style="text-align: center;">61.00</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-13.00</td> <td style="text-align: center;">62.64</td> <td style="text-align: center;">-1.64</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">100</td> <td style="text-align: center;">173</td> </tr> <tr> <td>3</td> <td style="text-align: center;">4839.00</td> <td style="text-align: center;">32.30</td> <td style="text-align: center;">54.00</td> <td style="text-align: center;">-21.70</td> <td style="text-align: center;">27.26</td> <td style="text-align: center;">5.04</td> <td style="text-align: center;">Average</td> <td style="text-align: center;">100</td> <td style="text-align: center;">40</td> </tr> <tr> <td>4</td> <td style="text-align: center;">4839.00</td> <td style="text-align: center;">45.33</td> <td style="text-align: center;">74.00</td> <td style="text-align: center;">-28.67</td> <td style="text-align: center;">40.29</td> <td style="text-align: center;">5.04</td> <td style="text-align: center;">Peak</td> <td style="text-align: center;">100</td> <td style="text-align: center;">40</td> </tr> </tbody> </table>												Freq. MHz	Emission level dBuV/m	Limit level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	2367.00	51.22	54.00	-2.78	52.86	-1.64	Average	100	173	2	2367.00	61.00	74.00	-13.00	62.64	-1.64	Peak	100	173	3	4839.00	32.30	54.00	-21.70	27.26	5.04	Average	100	40	4	4839.00	45.33	74.00	-28.67	40.29	5.04	Peak	100	40
	Freq. MHz	Emission level dBuV/m	Limit level dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																			
1	2367.00	51.22	54.00	-2.78	52.86	-1.64	Average	100	173																																																			
2	2367.00	61.00	74.00	-13.00	62.64	-1.64	Peak	100	173																																																			
3	4839.00	32.30	54.00	-21.70	27.26	5.04	Average	100	40																																																			
4	4839.00	45.33	74.00	-28.67	40.29	5.04	Peak	100	40																																																			
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																												


Test Mode	2.4G 11g CH6 + BT EDR CH00																																																																					
Polarization	Vertical																																																																					
Test By	:Roger Lu			Temperature (°C) : 24			Humidity (%) : 65																																																															
																																																																						
<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; width: 15%;">Freq.</th> <th style="text-align: left; width: 15%;">Emission</th> <th style="text-align: left; width: 15%;">Limit</th> <th style="text-align: left; width: 15%;">Margin</th> <th style="text-align: left; width: 15%;">SA</th> <th style="text-align: left; width: 15%;">Factor</th> <th style="text-align: left; width: 15%;">Remark</th> <th style="text-align: left; width: 15%;">ANT</th> <th style="text-align: left; width: 15%;">Turn</th> <th style="text-align: left; width: 15%;">Table</th> </tr> <tr> <th style="text-align: left;">MHz</th> <th style="text-align: left;">level</th> <th style="text-align: left;">dBuV/m</th> <th style="text-align: left;">Margin</th> <th style="text-align: left;">reading</th> <th style="text-align: left;">dBuV</th> <th style="text-align: left;">Factor</th> <th style="text-align: left;">High</th> <th style="text-align: left;">deg</th> <th style="text-align: left;">cm</th> </tr> </thead> <tbody> <tr> <td style="text-align: left;">1</td> <td style="text-align: left;">2367.00</td> <td style="text-align: left;">52.59</td> <td style="text-align: left;">54.00</td> <td style="text-align: left;">-1.41</td> <td style="text-align: left;">54.23</td> <td style="text-align: left;">-1.64</td> <td style="text-align: left;">Average</td> <td style="text-align: left;">100</td> <td style="text-align: left;">214</td> </tr> <tr> <td style="text-align: left;">2</td> <td style="text-align: left;">2367.00</td> <td style="text-align: left;">63.30</td> <td style="text-align: left;">74.00</td> <td style="text-align: left;">-10.70</td> <td style="text-align: left;">64.94</td> <td style="text-align: left;">-1.64</td> <td style="text-align: left;">Peak</td> <td style="text-align: left;">100</td> <td style="text-align: left;">214</td> </tr> <tr> <td style="text-align: left;">3</td> <td style="text-align: left;">4839.00</td> <td style="text-align: left;">32.39</td> <td style="text-align: left;">54.00</td> <td style="text-align: left;">-21.61</td> <td style="text-align: left;">27.35</td> <td style="text-align: left;">5.04</td> <td style="text-align: left;">Average</td> <td style="text-align: left;">100</td> <td style="text-align: left;">90</td> </tr> <tr> <td style="text-align: left;">4</td> <td style="text-align: left;">4839.00</td> <td style="text-align: left;">45.72</td> <td style="text-align: left;">74.00</td> <td style="text-align: left;">-28.28</td> <td style="text-align: left;">40.68</td> <td style="text-align: left;">5.04</td> <td style="text-align: left;">Peak</td> <td style="text-align: left;">100</td> <td style="text-align: left;">90</td> </tr> </tbody> </table>											Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	Table	MHz	level	dBuV/m	Margin	reading	dBuV	Factor	High	deg	cm	1	2367.00	52.59	54.00	-1.41	54.23	-1.64	Average	100	214	2	2367.00	63.30	74.00	-10.70	64.94	-1.64	Peak	100	214	3	4839.00	32.39	54.00	-21.61	27.35	5.04	Average	100	90	4	4839.00	45.72	74.00	-28.28	40.68	5.04	Peak	100	90
Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn	Table																																																													
MHz	level	dBuV/m	Margin	reading	dBuV	Factor	High	deg	cm																																																													
1	2367.00	52.59	54.00	-1.41	54.23	-1.64	Average	100	214																																																													
2	2367.00	63.30	74.00	-10.70	64.94	-1.64	Peak	100	214																																																													
3	4839.00	32.39	54.00	-21.61	27.35	5.04	Average	100	90																																																													
4	4839.00	45.72	74.00	-28.28	40.68	5.04	Peak	100	90																																																													

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).





4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640
No.30-2, Ding Fwu Tsuen, Lin Kou
District, New Taipei City, Taiwan
(R.O.C.)

Kwei Shan

Tel: 886-3-271-8666
No.3-1, Lane 6, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 33381, Taiwan (R.O.C.)

Kwei Shan Site II

Tel: 886-3-271-8640
No.14-1, Lane 19, Wen San 3rd
St., Kwei Shan Dist., Tao Yuan
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

—END—