


# FCC RF Exposure Report

**FCC ID** : ACQ-VIP7802  
**Equipment** : WiFi Set Top Box  
**Model No.** : VIP7802  
**Brand Name** : ARRIS  
**Applicant** : ARRIS Group, Inc.  
**Address** : 101 Tournament Drive, Horsham,  
Pennsylvania, United States 19044  
**Standard** : 47 CFR FCC Part 2.1091  
**Received Date** : Feb. 03, 2021  
**Tested Date** : Feb. 19 ~ Mar. 30, 2021

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



## Table of Contents

<b>1</b>	<b>MPE EVALUATION OF MOBILE DEVICES .....</b>	<b>4</b>
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE.....	4
1.2	MPE EVALUATION FORMULA .....	4
1.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE .....	4
1.4	MEASUREMENT UNCERTAINTY.....	4
1.5	MPE EVALUATION RESULTS .....	5
1.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	6
<b>2</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>7</b>

## Release Record

Report No.	Version	Description	Issued Date
FA120304	Rev. 01	Initial issue	May 04, 2021

## 1 MPE EVALUATION OF MOBILE DEVICES

### 1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm <sup>2</sup> )	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

### 1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

### 1.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

### 1.4 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

#### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

#### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 1.5 MPE EVALUATION RESULTS

### Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
2412~2462	23.84	24	3.2	20	0.104	1	0.104	Pass
5180~5240	21.93	22	3.2	20	0.066	1	0.066	Pass
5260~5320	19.30	19.5	3.6	20	0.041	1	0.041	Pass
5500~5700	21.95	22	4.5	20	0.089	1	0.089	Pass
5745~5825	21.95	22	4.6	20	0.091	1	0.091	Pass
BT								
2402-2480 (BT-BR)	5.10	5.5	1.5	20	0.001	1	0.001	Pass
2402-2480 (BT-LE)	5.43	5.5	1.5	20	0.001	1	0.001	Pass

\*Ratio = Power density / Limit.

### Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
2412~2462	17.54	18	6.11	20	0.051	1	0.051	Pass
5180~5240	18.92	19	6.11	20	0.065	1	0.065	Pass
5260~5320	16.27	16.5	6.36	20	0.038	1	0.038	Pass
5500~5700	18.94	19	7.46	20	0.088	1	0.088	Pass
5745~5825	18.93	19	7.46	20	0.088	1	0.088	Pass

\*Ratio = Power density / Limit.

#### Note:

2412~2462MHz: Directional gain =  $10 * \log((10^{3/20}+10^{3.2/20})^2/2) = 6.11$  dBi

5150-5250MHz: Directional gain =  $10 * \log((10^{3/20}+10^{3.2/20}/2) = 6.11$  dBi

5250-5350MHz: Directional gain =  $10 * \log((10^{3.1/20}+10^{3.6/20}/2) = 6.36$  dBi

5470-5725MHz: Directional gain =  $10 * \log((10^{4.4/20}+10^{4.5/20}/2) = 7.46$  dBi

5725-5850MHz: Directional gain =  $10 * \log((10^{4.3/20}+10^{4.6/20}/2) = 7.46$  dBi

## 1.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Mode	Max Ratio of Each Mode	
	Non-beamforming	Beamforming
Wi-Fi 2.4 GHz	0.104	0.051
Wi-Fi 5 GHz	0.091	0.088
BT	0.001	0.001
Sum (Wi-Fi 2.4 GHz+ BT)	0.105	0.052
Sum (Wi-Fi 5 GHz+ BT)	0.092	0.089
Limit	1	1
Pass / Fail	Pass	Pass

## 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### Linkou

Tel: 886-2-2601-1640  
No.30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan  
(R.O.C.)

### Kwei Shan

Tel: 886-3-271-8666  
No.3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

### Kwei Shan Site II

Tel: 886-3-271-8640  
No.14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 333, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666  
Fax: 886-3-318-0345  
Email: ICC\_Service@icertifi.com.tw

—END—