

TEST REPORT

Report Number: 30760821

Project Number: 3076082

April 25, 2005

**Testing performed on the
Multi Trunk-Tracking Scanner**

Model Number: PRO-2054

FCC ID: ADV2000427

to

FCC Part 15, Subpart B

ICES 003

Class: B

For

General Research of Electronics, Inc.



A2LA Certificate Number: 1755-01

Test Performed by:

Intertek

1365 Adams Court

Menlo Park, CA 94025

Prepared by:


Bruce Gordon

Test Authorized by:


General Research of Electronics, Inc.

425 Harbor Blvd. Suit B

Belmont, CA 94002

Date: April 28, 2005

Reviewed by:


Ollie Moyrong

Date: April 28, 2005

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

VERIFICATION OF COMPLIANCE
Report No. 30760821


Verification is hereby issued to the named APPLICANT and is VALID ONLY for the equipment identified hereon for use under the rules and regulations listed below.

Equipment Under Test:	Multi Trunk-Tracking Scanner
Trade Name:	General Research of Electronics, Inc.
Model No.:	PRO-2054
Applicant:	General Research of Electronics, Inc.
Contact:	Mr. Teru Takahashi
Address:	425 Harbor Blvd. Suite B Belmont, CA 94002
Country	USA
Tel. number:	650-591-1400
Fax number:	650-591-2001
Applicable Regulation:	FCC Part 15, Subpart B Industry Canada ICES-003
Equipment Class:	Class B
Date of Test:	April 25 to 27, 2005

We attest to the accuracy of this report:



Bruce Gordon
Test Engineer



Ollie Moyrong
EMC Department Manager

TABLE OF CONTENTS

1.0	General Description	4
1.1	Product Description	4
1.2	Related Submittal(s) Grants	4
1.3	Test Methodology	4
1.4	Test Facility	4
1.5	Summary of Test Results	5
2.0	System Test Configuration.....	6
2.1	Justification.....	6
2.2	EUT Exercising Software	6
2.3	Mode of Operation.....	6
2.4	Support Equipment List and Description.....	7
2.5	Equipment Setup Block Diagram	7
2.6	Equipment Modification	8
3.0	Emission Test Results	9
3.1	Field Strength Calculation	10
3.2	Radiated Emission Data.....	11
3.3	AC Line Conducted Emission Data.....	13
3.4	Antenna Conducted Emission Data	16
4.0	List of Test Equipment	19
	Appendix A – EUT Specification.....	20
	Appendix B – Local Oscillator Frequency calculation.....	21
	Appendix C – Antenna Drawing	22

1.0 General Description

1.1 Product Description

The Equipment under Test (EUT) is Multi Trunk-Tracking Scanning Receiver, model PRO-2054

Please refer to the attached specifications sheets in Appendix A for more details.

A pre-production version of the sample was received on April 25, 2005 in good condition. As declared by the Applicant, it is identical to production units.

1.2 Related Submittal(s) Grants

This is a single application for certification of a scanning receiver.

1.3 Test Methodology

Both conducted (if applicable) and radiated emission measurements were performed according to the procedures in ANSI C63.4. All radiated measurements were performed in a semi-anechoic chamber. Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Data Section"** of this Application.

1.4 Test Facility

The test site and conducted measurement facility used to collect the radiated data is Site 1, a 10 meter semi-anechoic chamber. This test facility and site measurement data have been fully placed on file with the FCC and A2LA accredited.

1.5 Summary of Test Results

Model: PRO-2054
FCC ID: ADV2000427

TEST	REFERENCE	RESULTS
Radiated Emission	15.109	Complies
AC Line Conducted Emission	15.107	Complies
Antenna Conducted Emission	15.111	Complies
FCC Part 15. 121 Requirement	15.121	Complies *

* Refer to file: ADV2000427 REPORT FOR FCC RULE PART 15.121

2.0 System Test Configuration

2.1 Justification

The tests were performed according to the test procedure as outlined in CFR47 Part 15.31 and in ANSI C63.4.

For emission testing, the equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). During testing, all cables were manipulated to produce worst-case emissions.

For the measurements, the EUT is placed on top of a non-conductive table. If the EUT attaches to peripherals, they are connected and operational (as typical as possible).

For radiated emission measurements, the signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. All readings are extrapolated back to the equivalent three-meter reading using inverse scaling with distance if measured at a closer distance.

2.2 EUT Exercising Software

The unit was setup to receive continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing.

2.3 Mode of Operation

The EUT was tested in two modes:


Test Mode 1: The EUT was set to constantly receive at the low, middle and high channels of each band.

Test Mode 2: The EUT was set to constantly scan a particular band.

2.4 Support Equipment List and Description

Item #	Description	Model No.	Serial No.
1	External headphones	Avid	Not Labeled
2	External headphones	LConcepts	Not Labeled

2.5 Equipment Setup Block Diagram



¹ The AC adapter is manufactured by RadioShack®, Part number JOD(M)-48-A641

U: Unshielded
m: meter

2.6 Equipment Modification

Any modifications installed previous to testing by GRE will be incorporated in each production model sold/leased in the United States.

Intertek Testing Services installed no modifications.

3.0 Emission Test Results

AC line conducted emission measurements were performed from 0.15 MHz to 30 MHz. Analyzer resolution is 10 kHz or greater.

Radiated emission measurements and antenna conducted emission measurements were performed from 30 MHz to 8000 MHz. Analyzer resolution is 100 kHz or greater for frequencies from 30 MHz to 1000 MHz, 1 MHz - for frequencies above 1000 MHz.

Preliminary tests were performed to determine the worst-case emission with the EUT tuned to the low, middle and high channels of each band. From these preliminary measurements the EUT was tuned to the frequency with the highest emission and the final scan was performed using the automated test software.

The same procedure was used to determine the worst-case emission level with the EUT setup in scanning mode for each band.

The final recorded data reflects the worst-case result.

A sample calculation and data tables of the emissions are included.

All measurements were performed with peak detection unless otherwise specified.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG + DF$$

Where FS = Field Strength in dB(μ V/m)

RA = Receiver Amplitude (including preamplifier) in dB(μ V)

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB(1/m)

AG = Amplifier Gain in dB

DF = Distance Factor in dB

Assume a receiver reading of 52.0 dB(μ V) is obtained. The antennas factor of 7.4 dB(1/m) and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving field strength of 32 dB(μ V/m). This value in dB(μ V/m) was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}(\mu\text{V})$$

$$AF = 7.4 \text{ dB}(1/\text{m})$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$DF = 0 \text{ dB}$$

$$FS = 52 + 7.4 + 1.6 - 29.0 + 0 = 32 \text{ dB}(\mu\text{V}/\text{m})$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

3.2 Radiated Emission Data

Tested By:	Bruce Gordon
Test Date:	April 25 2005

Temperature (°C)	20°C
Relative Humidity (%)	50%

The results on the following page(s) were obtained when the device was tested in the condition described in Section 2.

Results:	Complies by 16.3 dB at 579.15 MHz
-----------------	--

3.2 Test Data (Continued)

Model: PR-2054

Test Mode: Receiving

Test distance: 3 m

FCC Part 15.109 Class B Radiated Emissions Data

Tuned Frequency	L.O. Frequency	Antenna Polarization	Corrected Reading	Limit at 3 m	Margin	SA Reading	Amp Gain	Cable Loss	Ant
MHz	MHz	H/V	dB(uV/m)	dB(uV/m)	dB	dBuV	dB	dB	dB/m
28.0	408.75	H	9.3	46.0	-33.7	22.4	32.3	3.1	16.1
41.0	421.80	H	9.2	46.0	-33.8	21.4	32.3	3.1	17.0
54.0	434.775	H	9.7	46.0	-33.3	22.4	32.3	3.1	16.5
108.0	488.775	H	12.0	46.0	-31.0	23.3	32.4	3.3	17.8
122.5	503.25	H	13.5	46.0	-29.5	24.4	32.4	3.4	18.1
137.0	517.80	H	6.2	46.0	-36.8	17.3	32.4	3.5	17.8
155.5	536.25	H	6.9	46.0	-36.1	17.3	32.4	3.5	18.5
174.0	554.775	H	16.7	46.0	-26.3	26.6	32.5	3.6	18.9
406.0	786.75	H	14.9	46.0	-28.1	21.7	32.5	4.3	21.4
438.0	818.775	H	15.5	46.0	-27.5	21.7	32.4	4.5	21.7
470.0	850.80	H	20.2	46.0	-22.8	25.5	32.2	4.8	22.1
491.0	871.80	H	20.3	46.0	-22.7	25.3	32.1	4.8	22.3
512.0	892.80	H	24.0	46.0	-19.0	28.0	32.0	4.8	23.1
806.0	425.175	H	9.2	46.0	-33.8	21.3	32.3	3.1	17.1
823.0	442.20	H	9.5	46.0	-33.5	22.1	32.3	3.1	16.6
849.0	468.15	H	11.9	46.0	-31.1	23.6	32.4	3.3	17.4
869.0	488.175	H	5.9	46.0	-37.1	17.2	32.4	3.3	17.7
894.0	513.15	H	13.2	46.0	-29.8	24.4	32.4	3.4	17.7
939.0	558.15	H	8.0	46.0	-35.0	18.0	32.5	3.7	18.8
960.0	579.15	H	26.7	46.0	-16.3	36.2	32.5	3.7	19.2

- Notes:
1. Negative signs (-) in the Margin column signify levels below the limit.
 2. All readings below 1 GHz are quasi-peak, above 1 GHz – average.
 3. All other readings not reported are at least 20 dB below the limit.
 4. For L.O. frequency calculation, see Appendix B
 5. The EUT was tested in two modes. The worst-case data is reported.

3.3 AC Line Conducted Emission Data


Tested By:	Bruce Gordon
Test Date:	April 27, 2005

Temperature	(°C)	20 ⁰ C
Relative Humidity	(%)	50%


The results on the following page(s) were obtained when the device was tested in the condition described in Section 2.

Results:	Complies by more than 8.5 dB at 2.61 MHz
-----------------	---

3.3 Test Data (Continued)



3.3 Test Data (Continued)




3.4 Antenna Conducted Emission Data

Tested By:	Bruce Gordon
Test Date:	April 26, 2005


Temperature	(°C)	20 ⁰ C
Relative Humidity	(%)	50%

The results on the following page(s) were obtained when the device was tested in the condition described in Section 2.

Results:	Complies by 4.5 dB at 1.812 GHz
-----------------	--



Date: 26.APR.2005 20:02:41



Date: 26.APR.2005 19:44:32

4.0 List of Test Equipment

Measurement equipment used for emission compliance testing utilized the equipment on the following list.

Equipment	Manufacturer	Model/Type	Serial #	Cal Int	Cal Due
Spectrum Analyzer	Rhode-Schwarz	FSP-40	100030	12	9/15/05
RF Filter Section	Hewlett Packard	85460A	3448A00267	12	9/10/05
EMI Receiver	Hewlett Packard	8546A	3710A00373	12	9/10/05
BI-Log Antenna	EMCO	3143	9509-1160	12	10/28/05
LISN	Fischer	FCC-LISN-50/250-60-2-02	01005	12	7/2/05
Pre-Amplifier	Sonoma Inst.	310	185634	12	3/29/06

Appendix A – EUT Specification

Refer to file: ADV2000427 SPECIFICATION

Appendix B – Local Oscillator Frequency calculation

Refer to file: ADV2000427 LOCAL OSC FREQ CALCULATION

Appendix C – Antenna Drawing

Refer to file: ADV2000427 Telescopic ANT Drawing