



PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.

TEL (410) 290-6652 · FAX (410) 290-6654

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 22 Certification

UNIDEN CORPORATION
2-12-7 Hatchobori Chuo-ku
Tokyo, 104 JAPAN

Dates of Tests: May 18-19, 2004
Test Report S/N: 22.240413244.AES
Test Site: PCTEST Lab, Columbia MD U.S.A.

FCC ID

AESUH053A

APPLICANT

UNIDEN CORPORATION

Classification: Non-Broadcast Transmitter Held to Ear (TNE)
FCC Rule Part(s): §22H
EUT Type: Cellular Operated Stolen Vehicle Recovery Unit
Model: MSZ100
Tx Frequency Range: 824.04 – 848.97MHz (AMPS)
Rx Frequency Range: 869.04 – 893.97MHz (AMPS)
Max. RF Output Power: 0.406 W ERP AMPS (26.085 dBm)
Emission Designator(s): 40K0F8W/ 40K0F1D (AMPS)
Test Device Serial No. Identical Prototype [S/N: 01283000]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant conditions: Power output listed is ERP. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian
Vice President Engineering




PCTEST® PT. 22 REPORT	FCC MEASUREMENT REPORT		Uniden®	Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 1 of 26

TABLE OF CONTENTS


1.1 SCOPE	3
2.1 INTRODUCTION	4
3.1 INSERTS	5
4.1 DESCRIPTION OF TESTS	6-8
5.1 EFFECTIVE RADIATED POWER OUTPUT	9
6.1 RADIATED MEASUREMENTS	10-12
7.1 FREQUENCY STABILITY	13-14
8.1 PLOTS OF EMISSIONS	15
9.1 LIST OF TEST EQUIPMENT	16
10.1 SAMPLE CALCULATIONS	17
11.1 CONCLUSION	18
EXHIBIT A: TEST PLOTS	19
EXHIBIT B: FCC ID LABEL / LOCATION	20
EXHIBIT C: TEST SETUP PHOTOGRAPHS	21
EXHIBIT D: EXTERNAL PHOTOGRAPHS	22
EXHIBIT E: INTERNAL PHOTOGRAPHS	23
EXHIBIT F: BLOCK/ SCHEMATIC DIAGRAMS	24
EXHIBIT G: OPERATIONAL DESCRIPTION	25
EXHIBIT H: USERS MANUAL	26

MEASUREMENT REPORT



1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.



§2.1033 General Information

Applicant Name:	UNIDEN CORPORATION
Address:	2-12-7 Hatchobori Chuo-ku Tokyo, 104 JAPAN

- FCC ID: **AESUH053A**
- Quantity: Quantity production is planned
- Emission Designators: 40K0F8W/ 40K0F1D (AMPS)
- Tx Freq. Range: 824.04 – 848.97 MHz (AMPS)
- Rx Freq. Range: 869.04 – 893.97MHz (AMPS)
- Max. Power Rating: 0.406 W ERP AMPS (26.085 dBm)
- FCC Classification(s): Non-Broadcast Transmitter Held to Ear (TNE)
- Equipment (EUT) Type: Cellular Operated Stolen Vehicle Recovery Unit
- Modulation(s): AMPS
- Frequency Tolerance: $\pm 0.00025\%$ (2.5 ppm)
- FCC Rule Part(s): §22H
- Dates of Tests: May 18-19, 2004
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 22.240413244.AES

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 3 of 26

2.1 INTRODUCTION




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at **PCTEST Engineering Laboratory, Inc.** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 2. Diagram of 3-meter outdoor test range

PCTEST® PT. 22 REPORT	FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A
Page 4 of 26			

3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.


PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.2 Occupied Bandwidth Emission Limits

- (a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- (b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- (c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- (d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

4.3 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

4.4 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.5 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

4.6 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.7 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A
Page 7 of 26			

5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at -30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 8 of 26

5.1 Test Data

5.2 Effective Radiated Power Output

A. POWER: Low (Analog Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)
824.04	-35.300	H	0.004	5.973
836.49	-35.500	H	0.004	5.929
848.97	-35.500	H	0.004	6.085

B. POWER: High (Analog Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.04	-15.300	H	0.396	25.973	Standard
836.49	-15.500	H	0.392	25.929	Standard
848.97	-15.500	H	0.406	26.085	Standard

NOTES:

Effective Radiated Power Output Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A
© 2004 PCTEST ENGINEERING LABORATORY, INC.			Page 9 of 26

6.1 Test Data

6.2 A MPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
 CHANNEL: 0991 (Low)
 MEASURED OUTPUT POWER: 26.085 dBm = 0.406 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.08 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1648.08	-45.88	6.10	-39.78	H	65.9
2472.12	-70.28	6.70	-63.58	H	89.7
3296.16	-81.68	6.80	-74.88	H	101.0
4120.20	-85.78	6.50	-79.28	H	105.4
4944.24	-84.38	7.00	-77.38	H	103.5

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

6.1 Test Data (Continued)

6.3 A MPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz
 CHANNEL: 0383 (Mid)
 MEASURED OUTPUT POWER: 26.085 dBm = 0.406 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.08 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1672.98	-47.98	6.10	-41.88	H	68.0
2509.47	-72.08	6.70	-65.38	H	91.5
3345.96	-81.48	6.80	-74.68	H	100.8
4182.45	-85.68	6.50	-79.18	H	105.3
5018.94	-83.88	7.00	-76.88	H	103.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

6.1 Test Data (Continued)

6.4 A MPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
 CHANNEL: 0799 (High)
 MEASURED OUTPUT POWER: 26.085 dBm = 0.406 W
 MODULATION SIGNAL: FM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.08 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1697.94	-47.98	6.10	-41.88	H	68.0
2546.91	-72.88	6.70	-66.18	H	92.3
3395.88	-76.28	6.80	-69.48	H	95.6
4244.85	-85.78	6.50	-79.28	H	105.4
5093.82	-83.98	7.00	-76.98	H	103.1

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A
Page 12 of 26			

7.1 Test Data

7.2 FREQUENCY STABILITY (AMPS)

OPERATING FREQUENCY: 836,520,003 Hz

CHANNEL: 384


REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,003	0.000000
100 %		- 30	836,519,928	0.000009
100 %		- 20	836,519,869	0.000016
100 %		- 10	836,519,819	0.000022
100 %		0	836,519,777	0.000027
100 %		+ 10	836,519,710	0.000035
100 %		+ 20	836,520,003	0.000000
100 %		+ 25	836,519,869	0.000016
100 %		+ 30	836,519,861	0.000017
100 %		+ 40	836,519,802	0.000024
100 %		+ 50	836,519,727	0.000033
100 %		+ 60	836,519,677	0.000039
85 %	3.15	+ 20	836,520,003	0.000000
115 %	4.26	+ 20	836,520,003	0.000000
BATT. ENDPOINT	2.92	+ 20	836,520,003	0.000000

7.1 Test Data (Continued)

7.3 FREQUENCY STABILITY (AMPS)



PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

8.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT A)

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 15 of 26

9.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	8566B (100Hz-22GHz) HP	08/15/04	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/05	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/04	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/04	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/04	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/05	0792-032
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/05	0805-03334
Ailtech/Eaton Receiver	NM17/27A (0.1-32MHz)	09/17/04	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/04	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/05	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5S1G4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30μW-3W)		2237A02084
Harmonic/Flicker	Test System HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design		1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB	Gain HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Environmental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT	Uniden	Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A

10.1 SAMPLE CALCULATIONS

A. Emission Designator

Emission Designator = 40K0F8W

Calculation: Voice + SAT

Modulation: Voice is 2.5 kHz and SAT is 6 kHz – Maximum modulation is $M = 6$ kHz

Deviation: Voice is 12 kHz and SAT is 2 kHz – Maximum deviation is $D = 12 + 2 = 14$ kHz

Bn = $2 \times M + 2 \times DK$ with $K = 1$

Bn = 40 kHz

Calculation: Signaling Tone (ST) + SAT

Modulation: ST is 10 kHz and SAT is 6 kHz – Maximum modulation is $M = 10$ kHz

Deviation: ST is 8 kHz and SAT is 2 kHz – Maximum deviation is $D = 8 + 2 = 10$ kHz

Bn = $2 \times M + 2 \times DK$ with $K = 1$

Bn = 40 kHz

Emission Designator = 40K0F1D

Calculation: Voice + SAT

Modulation: Wideband Data is 10 kHz and SAT is 6 kHz – Maximum modulation is $M = 10$ kHz

Deviation: Wideband Data is 8 kHz and SAT is 2 kHz – Maximum deviation is $D = 8 + 2 = 10$ kHz

Bn = $2 \times M + 2 \times DK$ with $K = 1$

Bn = 40 kHz

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 17 of 26



11.1 CONCLUSION



The data collected shows that the **UNIDEN CORPORATION Cellular Operated Stolen Vehicle Recovery Unit** **FCC ID: AESUH053A** complies with all the requirements of Parts 2 and 22 of the FCC rules.



PCTEST® PT. 22 REPORT		 FCC MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 18 of 26

EXHIBIT A – TEST PLOTS

PCTEST® PT. 22 REPORT		 FCC MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 19 of 26







PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID: ARESUH053A

UNIDEN Corp.


C. O. S. V. Recovery Unit

FM Channel 384

Operating Frequency: 836.520 MHz

Output Power : 25.6 dBm

Test Mode: SAT + ST



PCTEST Engineering Lab.

SPECTRUM ANALYZER PRESENTATION

FCC ID:AESUH053A

UNIDEN Corp.


C. O. S. V. Recovery Unit

FM Channel 384

Operating Frequency: 836.520 MHz

Output Power : 25.6 dBm

Test Mode:SAT




PCTEST Engineering Lab., Inc.

SUBJECT: Modulation Characteristics
FCC Part 22

Test Report No.: 22.24.0413244.AES
Test Date: 05/18-19/2004

EUT: Cellular Operated Stolen Vehicle Recovery Unit
Model: MSZ100
FCC ID: AESUH053A

REFERENCE: 1 kHz = 0 dB




PCTEST Engineering Lab., Inc.

SUBJECT: Modulation Characteristics
FCC Part 22

Test Report No.: 22.24.0413244.AES
Test Date: 05/18-19/2004

EUT: Cellular Operated Stolen Vehicle Recovery Unit
Model: MSZ100
FCC ID: AESUH053A

REFERENCE: 1 kHz = 0 dB



UNIDEN Cellular Operated Stolen Vehicle Recovery Unit
FCC ID: AESUH053A


PCTEST Engineering Lab., Inc.

SUBJECT: Modulation Characteristics
FCC Part 22

Test Report No.: 22.24.0413244.AES
Test Date: 05/18-19/2004

EUT: Cellular Operated Stolen Vehicle Recovery Unit
Model: MSZ100
FCC ID: AESUH053A

REFERENCE: 1 kHz = 0 dB



UNIDEN Cellular Operated Stolen Vehicle Recovery Unit
FCC ID: AESUH053A

EXHIBIT B – FCC ID LABEL AND LOCATION

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 20 of 26

EXHIBIT C – TEST SETUP PHOTOGRAPHS

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 21 of 26

EXHIBIT D – EXTERNAL PHOTOGRAPHS

PCTEST PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 22 of 26

EXHIBIT E – INTERNAL PHOTOGRAPHS

PCTEST® PT. 22 REPORT		 FCC MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 23 of 26

EXHIBIT F – BLOCK/ SCHEMATIC DIAGRAMS

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 24 of 26

EXHIBIT G – OPERATIONAL DESCRIPTION

PCTEST® PT. 22 REPORT	 FCC MEASUREMENT REPORT 			Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 25 of 26

EXHIBIT H – USER'S MANUAL

PCTEST® PT. 22 REPORT		 FCC MEASUREMENT REPORT 		Reviewed By: Quality Manager
Test Report S/N: 22.240413244.AES	Test Dates: May 18-19, 2004	Phone Type: Cellular Operated Stolen Vehicle Recovery Unit	FCC ID: AESUH053A	Page 26 of 26