

3. When measuring sidebands close to the fundamental, band reject filter Model 6N45-2450/60 (SER FK837-1) was employed.

REPORT OF MEASUREMENT (MICROWAVE OVEN TEST DATA SHEET B)

FCC ID : AEZM221 MODEL : EM-V3405SWT DATE : Nov. 21, 2001
 Nominal Frequency : 2,450 MHz TESTED BY : T. SUGIOKA

DATA SUMMARY (FCC MEASUREMENT PROCEDURE MP-5)

CALCULATION : $E < 300m > = K * 10^{((A+B+C+D+E)/20)}$

SAFETY CHECK (at 5 cm)
 FUNDAMENTAL Load : 275 ml/center
 Load : 1,000 ml/center

0.18 mW/sq.cm
 2,450 MHz

LIMIT = $25 * \sqrt{(power/500)}$: 38.7 $\mu V/m$

* Note : Location of load for the oven provided with the rotating tray is :
 Contiguous with the shelf circumference.

RADIATION FIELD STRENGTH ($\mu V/m$ at 300 m)

	Load (ml)	Location of Load	Emission Frequency (MHz)	Meter Reading (μBuV)	Antenna Factor (dB)	Cable Loss (dB)	Filter Loss (dB)	Calcu. Factor (dB)	The Value of K ($E < 300m > = K * 10^{((A+B+C+D+E)/20)}$)	Max. Field Strength ($\mu V/m$ at 300m)	Limit ($\mu V/m$ at 300m)
2nd Harmonic	300	Center	4,902	25.0	37.0	1.6	—	5	0.0100	26.9	38.7
2nd Harmonic	300	* Right/Front Corner	4,904	20.0	37.0	1.6	—	5	0.0100	15.1	38.7
2nd Harmonic	700	Center	4,906	26.0	37.0	1.6	—	5	0.0100	30.2	38.7
2nd Harmonic	700	* Right/Front Corner	4,904	20.0	37.0	1.6	—	5	0.0100	15.1	38.7
3rd Harmonic	300	Center	7,359	12.0	39.8	2.2	—	5	0.0100	8.9	38.7
3rd Harmonic	300	* Right/Front Corner	7,258	12.0	39.8	2.2	—	5	0.0100	8.9	38.7
3rd Harmonic	700	Center	7,363	13.0	39.8	2.2	—	5	0.0100	10.0	38.7
3rd Harmonic	700	* Right/Front Corner	7,363	13.0	39.8	2.2	—	5	0.0100	10.0	38.7
4th Harmonic	700	Center	8,604	13.0	39.8	2.7	—	5	0.0100	10.6	38.7
Spurious	700	Center	2,381	30.0	20.8	1.1	3	5	0.0060	6.0	38.7
Emission Sideband 2,400 MHz	700	Center	2,400	27.0	20.8	1.1	3	5	0.0061	4.3	38.7
Emission Sideband 2,500 MHz	700	Center	2,500	16.0	20.8	1.1	3	5	0.0064	1.3	38.7

Maximum Frequency Variation 1,000 ml load 2,449 to 2,454 M Hz. 1830 MHz - 2745 MHz 2.6230 * 10⁻³ * frequency : GHz) -0.0002
 Total Power Input to Oven 1,650 Watts 2745 MHz - 3660 MHz 2.1858 * 10⁻³ * frequency : GHz) +0.0010
 Power Development in dummy load (Thermal Method) 1,200 Watts (IEC705 Test Procedure) 3660 MHz - 4575 MHz 1.0929 * 10⁻³ * frequency : GHz) +0.0050
 Supply Voltage AC 120 V 60 Hz 4575 MHz and above 0.0100

FCC ID : AEZM221 MODEL : EM-V3405SWT DATE : Nov. 21, 2001

TESTED BY : T. SUGIOKA

T. Sugioka

Note : In order to convert the measured field strength at 3meters to the field at 300 meters, comply with FCC/OST MP-5 Appendix C "4.6.1 Computations to determine compliance". A calculation factor of 5 dB, this figure is fixed by SANYO, is introduced for adjusting a tolerance in measurement.
A calculation factor of 5 dB should be added to "METER READING" as shown in SAMPLE CALCULATION below.

SAMPLE CALUCULATION

(1) 2nd Harmonic with 700 ml/Center load

$$\begin{aligned}\text{Field Strength at 300 m} &= 0.0100 \times 10^{(26.0 + 37 + 1.6 + 5) \div 20} \\ &= 30.2 \text{ uV/m}\end{aligned}$$

(2) Emission sideband 2.400 M Hz., 700 ml/Center load

$$\begin{aligned}\text{Field Strength at 300 m} &= 0.0061 \times 10^{(27.0 + 20.8 + 1.1 + 3 + 5) \div 20} \\ &= 4.3 \text{ uV/m}\end{aligned}$$

REPORT OF MEASUREMENT (MICROWAVE OVEN TEST DATA)

- Measurement of Frequency VS Line Voltage Stability -

FCC ID : AEZM221 Model : EM-V3405SW Date : Nov. 21, 2001Nominal Frequency : 2.450 MHzTested by : T.SUGIOKA
T. Sugiooka

Line Voltage Variation [Volt]	Frequency [GHz]	Deviation for ISM Frequency [MHz]	Limit [MHz]
96 (- 20%)	2.452	+2	± 50
120 (± 0%)	2.454	+4	± 50
150 (+ 25%)	2.453	+3	± 50

[Environment]

Temperature : 25.0 °CHumidity : 54.0 %

[Sample Calculation]

Frequency : 2.454 GHz

Deviation for ISM Frequencies Calculated as follows,

$$\underline{2.4540} - 2.4500 = \underline{+0.0040} \text{ [GHz]} = \underline{+4.0} \text{ [MHz]}$$

[Summary of Test Results]

Above data shows that the test device do / do not complies with the requirements.