



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 22 Certification

**Applicant Name:**  
Sanyo Fisher Company  
21605 Plummer Street  
Chatsworth, CA 91311  
USA

**Date of Testing:**  
February 7, 2008  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0801300125.AEZ

<b>FCC ID:</b>	<b>AEZW63SA</b>
<b>APPLICANT:</b>	<b>SANYO FISHER COMPANY</b>


**Application Type:** Certification  
**FCC Classification:** Licensed Non-Broadcast Transmitter Held to Ear (TNE)  
**FCC Rule Part(s):** §2; §22(H)  
**EUT Type:** Cellular CDMA Phone with Bluetooth  
**Model(s):** W63SA  
**Tx Frequency Range:** 824.70 - 848.31MHz (Cell. CDMA)  
**Max. RF Output Power:** 0.27 W ERP Cell. CDMA (24.31 dBm)  
**Emission Designator(s):** 1M27F9W (CDMA)  
**Test Device Serial No.:** *identical prototype* [S/N: SSAEB000354]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is ERP for Part 22.

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*



Randy Ortanez  
President




FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 1 of 24

## T A B L E   O F   C O N T E N T S


---

FCC PART 22 MEASUREMENT REPORT.....	3
1.0 INTRODUCTION .....	4
1.1 SCOPE .....	4
1.2 TESTING FACILITY.....	4
2.0 PRODUCT INFORMATION.....	5
2.1 EQUIPMENT DESCRIPTION .....	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....	5
2.3 LABELING REQUIREMENTS.....	5
3.0 DESCRIPTION OF TESTS .....	6
3.1 MEASUREMENT PROCEDURE .....	6
3.2 OCCUPIED BANDWIDTH EMISSION LIMITS .....	6
3.3 CELLULAR - BASE FREQUENCY BLOCKS.....	7
3.4 CELLULAR - MOBILE FREQUENCY BLOCKS.....	7
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	8
3.6 RADIATED SPURIOUS AND HARMONIC EMISSIONS .....	8
3.7 FREQUENCY STABILITY / TEMPERATURE VARIATION .....	8
4.0 TEST EQUIPMENT CALIBRATION DATA .....	9
5.0 SAMPLE CALCULATIONS .....	10
6.0 TEST RESULTS.....	11
6.1 SUMMARY.....	11
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA .....	12
6.3 CELLULAR CDMA RADIATED MEASUREMENTS.....	13
6.4 CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS .....	16
7.0 PLOT(S) OF EMISSIONS .....	18
8.0 CONCLUSION.....	24

FCC ID: AEZW63SA	 <b>PCTEST®</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Reviewed by: Quality Manager Page 2 of 24



## MEASUREMENT REPORT FCC Part 22




### §2.1033 General Information

**APPLICANT:** Sanyo Fisher Company  
**APPLICANT ADDRESS:** 21605 Plummer Street  
**Chatsworth, CA 91311**  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22(H)  
**BASE MODEL:** W63SA  
**FCC ID:** AEZW63SA  
**FCC CLASSIFICATION:** Licensed Non-Broadcast Transmitter Held to Ear (TNE)  
**EMISSION DESIGNATOR(S):** 1M27F9W (CDMA)  
**MODE:** CDMA  
**FREQUENCY TOLERANCE:** ±0.00025 % (2.5 ppm)  
**Test Device Serial No.:** SSAEB000354  Production  Pre-Production  Engineering  
**DATE(S) OF TEST:** February 7, 2008  
**TEST REPORT S/N:** 0801300125.AEZ

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EVDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: AEZW63SA	PCTEST® ENGINEERING LABORATORY, INC.		FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: SANYO Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 3 of 24

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Intert'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see *Figure 1-1*).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: AEZW63SA	PCTEST® ENGINEERING LABORATORY, INC.		FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Page 4 of 24	

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **SANYO Cellular CDMA Phone with Bluetooth** **FCC ID: AEZW63SA**. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
SANYO / Model: W63SA	AEZW63SA	Cellular CDMA Phone with Bluetooth

Table 2-1. EUT Equipment Description

### 2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.


FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 5 of 24

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 3-1). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Deviation from Measurement Procedure.....None



**Figure 3-1. Diagram of 3-meter outdoor test range**


### 3.2 Occupied Bandwidth Emission Limits

#### §2.1049, 22.917(a)


- a. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- b. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- c. When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- d. The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

FCC ID: AEZW63SA	 <b>PCTEST®</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth			Page 6 of 24

### 3.3 Cellular - Base Frequency Blocks



### 3.4 Cellular - Mobile Frequency Blocks



FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 7 of 24

### 3.5 Spurious and Harmonic Emissions at Antenna Terminal

#### §2.1051, 22.917(a)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic.

### 3.6 Radiated Spurious and Harmonic Emissions

#### §2.1053, 22.917(a)

Spurious and harmonic radiated emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.

### 3.7 Frequency Stability / Temperature Variation

#### §2.1055, 22.355

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.*

#### Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 8 of 24

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model / Equipment	Calibration Date	Cal Interval	Calibration Due	Serial No.
Agilent	E4407B ESA Spectrum Analyzer	04/29/07	Annual	04/28/08	US39210313
Agilent	E5515C Wireless Communications Test Set	08/31/07	Biennial	08/30/09	GB41450275
Agilent	E5515C Wireless Communications Test Set	10/06/06	Biennial	10/05/08	GB43193972
Agilent	E5515C Wireless Communications Test Set	06/08/07	Biennial	06/07/09	GB46310798
EMCO	Model 3115 (1-18GHz) Horn Antenna	10/04/07	Biennial	10/03/09	9205-3874
EMCO	Model 3115 (1-18GHz) Horn Antenna	09/24/07	Biennial	09/23/09	9704-5182
Rohde & Schwarz	NRVS Power Meter	07/03/07	Biennial	07/02/09	835360/079
Rohde & Schwarz	NRV-Z53 Power Sensor	07/03/07	Biennial	07/02/09	846076/007
Rohde & Schwarz	CMU200 Base Station Simulator	12/06/07	Annual	12/05/08	107826
Rohde & Schwarz	CMU200 Base Station Simulator	09/07/07	Annual	09/06/08	833855/010
Rohde & Schwarz	CMU200 Base Station Simulator	05/24/07	Annual	05/23/08	836371/079
Agilent	E8257D (250kHz-20GHz) Signal Generator	03/08/07	Biennial	03/07/09	MY45470194
Agilent	HP 8449B (1-26.5GHz) Pre-Amplifier	12/13/07	Annual	12/12/08	3008A00985
Agilent	HP 8449B (1-26.5GHz) Pre-Amplifier	12/13/07	Annual	12/12/08	3008A00985
Agilent	HP 11713A Attenuation/Switch Driver	12/13/07	Annual	12/12/08	3439A02645
Agilent	HP 8566B Opt. 462 Impulse Bandwidth	12/13/07	Annual	12/12/08	3701A22204
EMCO	Dipole Pair	09/20/06	Biennial	09/19/08	23951
SOLAR	8012-50 LISN (2)	11/08/07	Biennial	11/07/09	0310233, 0310234
K & L	11SH10 Band Pass Filter	N/A	Annual	N/A	1300/4000
K & L	11SH10 Band Pass Filter	N/A	Annual	N/A	4000/12000
Agilent	HP 8495A (0-70dB) DC-4GHz Attenuator	N/A		N/A	N/A
-	263-10dB (DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
Pasternack	PE2208-6 Bidirectional Coupler	N/A		N/A	N/A
-	No.165 (30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166 (1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167 (100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Rohde & Schwarz	NRVD Dual Channel Power Meter	12/11/06	Biennial	12/10/08	101695
Rohde & Schwarz	NRV-Z33 Peak Power Sensor (1mW-20W)	11/28/06	Biennial	11/27/08	100004

Table 4-1. Test Equipment

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 9 of 24

## 5.0 SAMPLE CALCULATIONS

### Emission Designator

**Emission Designator = 1M25F9W**

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission - PCS Band

**Example: Channel 25 PCS Mode 2<sup>nd</sup> Harmonic (3702.50 MHz)**

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was  $25.501 \text{ dBm} - (-24.80) = 50.3 \text{ dBc}$ .

FCC ID: AEZW63SA	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 10 of 24

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Sanyo Fisher Company  
 FCC ID: AEZW63SA  
 FCC Classification: Licensed Non-Broadcast Transmitter Held to Ear (TNE)  
 Mode(s): CDMA

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
<b>TRANSMITTER MODE (TX)</b>					
2.1049, 22.917(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a)	Band Edge / Conducted Spurious Emissions	< 43 + 10log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
SAR Measurement Procedures for 3G Devices, June '06	Conducted Power Measurements for 3G Devices	N/A		PASS	FCC 3G Power Table
22.913(a)(2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
<b>RECEIVER MODE (RX) / DIGITAL EMISSIONS</b>					
15.107	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or	LINE CONDUCTED	PASS	Pt. 15B Test Report
15.109	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.209 limits or	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Pt. 15B Test Report
<b>RF EXPOSURE</b>					
2.1091 / 2.1093	SAR Test	1.6 W/kg (SAR Limit)	SAR	PASS	SAR Report

Table 6-1. Summary of Test Results

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Page 11 of 24	

## 6.2 Effective Radiated Power Output Data

§22.913(a)(2)

**POWER: "All Up" Bits (Cellular CDMA Mode)**

Frequency [MHz]	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Battery Type
824.70	-12.200	23.81	0.00	H	23.81	0.240	Standard
836.52	-12.070	23.94	0.00	H	23.94	0.248	Standard
848.31	-11.700	24.31	0.00	H	24.31	0.270	Standard

**Table 6-2. Effective Radiated Power Output Data**

**NOTES:**

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)			 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth			Page 12 of 24	

### 6.3 Cellular CDMA Radiated Measurements

§2.1053, 22.917(a)

#### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013  
 MEASURED OUTPUT POWER: 24.310 dBm = 0.270 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.31 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-53.37	6.32	-47.06	H	71.4
2474.10	-70.17	6.32	-63.86	H	88.2
3298.80	-67.68	7.69	-60.00	H	84.3
4123.50	-68.80	7.83	-60.96	H	85.3
4948.20	-92.95	7.84	-85.11	H	109.4

**Table 6-3. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 13 of 24

## Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz  
 CHANNEL: 384  
 MEASURED OUTPUT POWER: 24.310 dBm = 0.270 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.31 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-58.19	6.33	-51.87	H	76.2
2509.56	-62.86	7.75	-55.11	H	79.4
3346.08	-63.45	7.86	-55.59	H	79.9
4182.60	-93.02	8.07	-84.95	H	109.3
5019.12	-91.36	8.55	-82.81	H	107.1

Table 6-4. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 14 of 24

## Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MEASURED OUTPUT POWER: 24.310 dBm = 0.270 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.31 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-56.62	6.34	-50.28	H	74.6
2544.93	-64.50	7.74	-56.76	H	81.1
3393.24	-61.41	7.89	-53.52	H	77.8
4241.55	-93.08	8.30	-84.79	H	109.1
5089.86	-91.08	8.53	-82.55	H	106.9

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: AEZW63SA	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 15 of 24

## 6.4 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,520,010	10	0.000001
100 %		- 30	836,519,991	-9	-0.000001
100 %		- 20	836,520,012	12	0.000001
100 %		- 10	836,519,989	-11	-0.000001
100 %		0	836,519,986	-14	-0.000002
100 %		+ 10	836,520,008	8	0.000001
100 %		+ 20	836,520,010	10	0.000001
100 %		+ 30	836,519,987	-13	-0.000002
100 %		+ 40	836,520,015	15	0.000002
100 %		+ 50	836,519,983	-17	-0.000002
115 %		+ 20	836,520,010	10	0.000001
BATT. ENDPOINT	3.40	+ 20	836,520,022	22	0.000003

Table 6-6. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 16 of 24

## Cellular CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355






Figure 6-1. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Page 17 of 24

## 7.0 PLOT(S) OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)



Plot 7-2. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: AEZW63SA		FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Page 18 of 24




Plot 7-3. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-4. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth	Page 19 of 24




Plot 7-5. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: AEZW63SA	 <b>PCTEST</b> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 20 of 24




Plot 7-7. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-8. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: AEZW63SA	 <b>PCTEST</b> Engineering Laboratory, Inc.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 21 of 24




Plot 7-9. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)



Plot 7-10. Band Edge Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: AEZW63SA	<b>PCTEST</b> ENGINEERING LABORATORY, INC.		FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	<b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth			Page 22 of 24



Plot 7-11. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: AEZW63SA	 <b>PCTEST</b> <sup>®</sup> <small>ENGINEERING LABORATORY, INC.</small>	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)	 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth		Page 23 of 24

## 8.0 CONCLUSION

The data collected show that the **SANYO Cellular CDMA Phone with Bluetooth FCC ID: AEZW63SA** complies with all the requirements of Parts 2, and 22 of the FCC rules.

FCC ID: AEZW63SA	 <b>PCTEST</b> <sup>®</sup> ENGINEERING LABORATORY, INC.	FCC Pt. 22 CDMA MEASUREMENT REPORT (CERTIFICATION)		 <b>SANYO</b>	Reviewed by: Quality Manager
Test Report S/N: 0801300125.AEZ	Test Dates: February 7, 2008	EUT Type: Cellular CDMA Phone with Bluetooth			Page 24 of 24