

MPE CALCULATION

FCC ID: AFJ375000

RF Exposure Requirements: 47 CFR §1. 1307(b)
RF Radiation Exposure Limits: 47 CFR §1. 1310
RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65
EUT Frequency Band: 2402MHz-2480MHz

Limits for General Population/Uncontrolled Exposure in the band of:

Frequency Range (MHz)	Power Density (mW/cm ²)
1,500-100,000	1.0
300-1,500	f/1500

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20cm

(Bluetooth-BDR/EDR): Output Power = 5.03dBm, Antenna Gain = 2.7dBi , Power density =0.00118 mW/cm²

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
Bluetooth BDR/EDR	2402	5.03	2.7	±1dB	6.03	20	0.00118	1	Pass

The Above Result had shown that the Device complied with MPE requirement.

Gary Chou

Completed By: Gary Chou

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 10/30/2017