

FCC

ICOM **IC-F62D-UL**

LMR for Haz. Loc. CL I Div 1 Grp C D, CL II Div 1 Grp E F G, CL III. CL I Div 2 Grp A B C D. T3C. Tamb=-20°C to +60°C. INTRINSICALLY SAFE when used with Model BP-292UL battery pack.

 **LISTED E475176**

 Use with UL Listed ICOM batteries and ACC. See Instruction Manual.

FCC ID:AFJ395202
Contains
FCC ID:AFJ381510



SERIAL NO.
0 0 0 0 0 0 0 0
Icom Inc.
MADE IN JAPAN

 **ATTENTION!** Restricted to occupational use to satisfy FCC RF exposure limits. See user manual for operating requirements.



UL certification has not been obtained, UL Listing mark  is not printed. The contents may change after obtaining the certification.

See Pictures.pdf for serial plates photographs.

Serial Plate Location



ICOM
IC-F62D-UL
LMA for Haz. Loc. CL I Div 1 Grp C D
CL II Div 1 Grp E F G. CL I. CL II Div 2
Grp A B C D. T3C. Tamb=-20°C to
-60°C. INTRINSICALLY SAFE when
E475176 used with Model BP-292UL battery pack.
⚠ Use with UL listed ICOM batteries
and ACC. See Instruction Manual.

FCC ID: AFJ395202
Contains
FCC ID: AFJ381510



SERIAL NO.
22001451
Icom Inc.
MADE IN JAPAN

Restricted to occupational
use to satisfy FCC RF
exposure limits. See user
manual for operating
requirements.