



31040/SIT



C-1376



46390-2049



200093-0



00-034



3000 Bristol Circle,
Oakville, Ontario,
Canada L6H 6G4

Tel.: (905) 829-1570
Fax: (905) 829-8050

Website: www.ultratech-labs.com
Email: vic@ultratech-labs.com

Oct. 24, 2002

FEDERAL COMMUNICATIONS COMMISSION

7435 Oakland Mills Road
Columbia, MD 21046
USA

Subject: Type Acceptance Application under FCC CFR 47, Parts 2 and 80
(Subpart E) - Non-Broadcast Radio Transceivers Operating in the
frequency bands 156.050-157.425 MHz [Marine].

Applicant: ICOM Incorporated
Product: MOBILE VHF MARINE TRANSCEIVER (for Ship Station)
Model: IC-M602
FCC ID: AFJIC-M602

Dear Sir/Madam,

As appointed agent for **ICOM Incorporated**, we would like to submit the application to Federal Communications Commission for certification of the above product. Please review all necessary files uploaded to FCC OET site.

If you have any queries, please do not hesitate to contact us by our TOLL FREE number:

OUR TELEPHONE NO.: 1-877-765-4173


Yours truly,



Tri Minh Luu, P. Eng.,
V.P., Engineering

TML/DH

Encl.



3000 Bristol Circle,
Oakville, Ontario,
Canada L6H 6G4

Tel.: (905) 829-1570
Fax: (905) 829-8050

Website: www.ultratech-labs.com
Email: vic@ultratech-labs.com

Oct. 24, 2002

ICOM Incorporated
1-1-32, Kamiminami
Hirano-ku, Osaka
Japan, 547-0003

Attn.: Mr. Takashi Aoki

Subject: Certification Testing in accordance with FCC CFR 47, Parts 2 and 80 (Subpart E) - Non-Broadcast Radio Transceivers Operating in the frequency bands 156.050-157.425 MHz [Marine].

Product: MOBILE VHF MARINE TRANSCEIVER (for Ship Station)
Model: IC-M602

Dear Mr. Aoki,

The product sample has been tested in accordance with **FCC CFR 47, Parts 2 and 80 (Subpart E) - Non-Broadcast Radio Transceivers Operating in the frequency bands 156.050-157.425 MHz [Marine]**, and the results and observation were recorded in the engineering report, Our File No.: ICOM-043FCC80

Enclosed you will find copy of the engineering report. If you have any queries, please do not hesitate to contact us.


Yours truly,



Tri Minh Luu, P.Eng
Vice President - Engineering

Encl.

ENGINEERING TEST REPORT



MOBILE VHF MARINE TRANSCEIVER
(for Ship Station)
Model No.: IC-M602
FCC ID: AFJIC-M602

Applicant: **ICOM Incorporated**
1-1-32, Kamiminami
Hirano-ku, Osaka
Japan, 547-0003

Tested in Accordance With

Federal Communications Commission (FCC)
CFR 47, PARTS 2 and 80 (Subpart E)

UltraTech's File No.: ICOM-043FCC80

This Test report is Issued under the Authority of
Tri M. Luu, Professional Engineer,
Vice President of Engineering
UltraTech Group of Labs

Date: Oct. 24, 2002



Report Prepared by: Tri M. Luu, P.Eng.

Tested by: Hung Trinh

Issued Date: Oct. 24, 2002

Test Dates: Oct. 07-22/2002

*The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.
This report must not be used by the client to claim product endorsement by NVLAP or any agency of the US Government.*

UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4

Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: www.ultratech-labs.com Email: vic@ultratech-labs.com, Email: tri@ultratech-labs.com



31040/SIT

C-1376

46390-2049

200093-0

00-034

TABLE OF CONTENTS

EXHIBIT 1.	SUBMITTAL CHECK LIST.....	3
EXHIBIT 2.	INTRODUCTION	4
2.1.	SCOPE.....	4
2.2.	RELATED SUBMITAL(S)/GRANT(S).....	4
2.3.	NORMATIVE REFERENCES	4
EXHIBIT 3.	PERFORMANCE ASSESSMENT	5
3.1.	CLIENT INFORMATION.....	5
3.2.	EQUIPMENT UNDER TEST (EUT) INFORMATION	5
3.3.	EUT'S TECHNICAL SPECIFICATIONS	6
3.4.	LIST OF EUT'S PORTS.....	6
3.5.	ANCILLARY EQUIPMENT	6
EXHIBIT 4.	EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS	7
4.1.	CLIMATE TEST CONDITIONS.....	7
4.2.	OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS	7
EXHIBIT 5.	SUMMARY OF TEST RESULTS.....	8
5.1.	LOCATION OF TESTS	8
5.2.	APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS.....	8
5.3.	MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES.....	9
5.4.	DEVIATION OF STANDARD TEST PROCEDURES	9
EXHIBIT 6.	MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS	10
6.1.	TEST PROCEDURES.....	10
6.2.	MEASUREMENT UNCERTAINTIES.....	10
6.3.	MEASUREMENT EQUIPMENT USED:.....	10
6.4.	ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:.....	10
6.5.	TRANSMITTER POWER @ FCC 2.1046 & 80.215.....	11
6.5.1.	<i>Limits @ FCC 80.215.....</i>	<i>11</i>
6.5.2.	<i>Method of Measurements.....</i>	<i>11</i>
6.5.3.	<i>Test Equipment List</i>	<i>11</i>
6.5.4.	<i>Test Arrangement</i>	<i>11</i>
6.5.5.	<i>Test Data.....</i>	<i>12</i>
6.6.	RF EXPOSURE REQUIRMENTS @ 1.1310 & 2.1091	13
6.6.1.	<i>Limits.....</i>	<i>13</i>
6.6.2.	<i>Method of Measurements.....</i>	<i>13</i>
6.6.3.	<i>Test Data.....</i>	<i>15</i>
6.7.	TRANSMITTER FREQUENCY TOLERANCE @ FCC 2.1055 & 80.209.....	16
6.7.1.	<i>Limits @ FCC 80.209.....</i>	<i>16</i>
6.7.2.	<i>Method of Measurements.....</i>	<i>16</i>
6.7.3.	<i>Test Equipment List</i>	<i>16</i>
6.7.4.	<i>Test Arrangement.....</i>	<i>16</i>

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.7.5.	Test Data.....	17
6.8.	AUDIO FREQUENCY RESPONSE / MODULATION REQUIREMENTS @ FCC 2.1047(A) & 80.213(E).....	18
6.8.1.	Limits @ FCC 2.1047(a) & 80.231(e)	18
6.8.2.	Method of Measurements.....	18
6.8.3.	Test Equipment List	18
6.8.4.	Test Arrangement.....	18
6.8.5.	Test Data.....	19
6.9.	MODULATION LIMITING @ FCC 2.1047(B).....	21
6.9.1.	Limits @ FCC 2.1047(b).....	21
6.9.2.	Method of Measurements.....	21
6.9.3.	Test Equipment List	21
6.9.4.	Test Arrangement.....	21
6.9.5.	Test Data.....	22
6.10.	EMISSION LIMITATIONS @ FCC 2.1049 & 80.211(2).....	24
6.10.1.	Limits.....	24
6.10.2.	Method of Measurements.....	24
6.10.3.	Test Equipment List	24
6.10.4.	Test Arrangement.....	24
6.10.5.	Test Data.....	25
6.11.	TRANSMITTER ANTENNA POWER SPURIOUS/HARMONIC CONDUCTED EMISSIONS @ FCC 80.211(2).....	26
6.11.1.	Limits @ 80.211(e).....	26
6.11.2.	Method of Measurements.....	26
6.11.3.	Test Equipment List	26
6.11.4.	Test Arrangement.....	26
6.11.5.	Test Data.....	27
6.12.	TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 80.211(2)	29
6.12.1.	Limits @ FCC 80.211(2).....	29
6.12.2.	Method of Measurements.....	29
6.12.3.	Test Equipment List	29
6.12.4.	Test Setup	29
6.12.5.	Test Data.....	30
EXHIBIT 7.	MEASUREMENT UNCERTAINTY.....	32
7.1.	RADIATED EMISSION MEASUREMENT UNCERTAINTY.....	32
EXHIBIT 8.	MEASUREMENT METHODS.....	33
8.1.	CONDUCTED POWER MEASUREMENTS.....	33
8.2.	RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD.....	34
8.2.1.	Maximizing RF Emission Level (E-Field)	34
8.2.2.	Measuring the EIRP of Spurious/Harmonic Emissions using Substitution Method	35
8.3.	TRANSMITTER FREQUENCY TOLERANCE.....	37
8.4.	EMISSION MASK	38
8.5.	SPURIOUS EMISSIONS (CONDUCTED).....	38

EXHIBIT 1. SUBMITTAL CHECK LIST

Annex No.	Exhibit Type	Description of Contents	Quality Check (OK)
--	Test Report	- Exhibit 1: Submittal check lists - Exhibit 2: Introduction - Exhibit 3: Performance Assessment - Exhibit 4: EUT Operation and Configuration during Tests - Exhibit 5: Summary of test Results - Exhibit 6: Measurement Data - Exhibit 7: Measurement Uncertainty - Exhibit 8: Measurement Methods	OK
1	Test Report - Plots of Measurement Data	Plots # 1 to 26	OK
2	Test Setup Photos	Photos # 1 to 2	OK
3	External Photos of EUT	Photos # 1 to 8	OK
4	Internal Photos of EUT	Photos of 1 to 22	OK
5	Cover Letters	- Letter from Ultratech for Certification Request - Letter from the Applicant to appoint Ultratech to act as an agent - Letter from the Applicant to request for Confidentiality Filing	OK OK OK
6	Attestation Statements		OK
7	ID Label/Location Info	ID Label Location of ID Label	OK OK
8	Block Diagrams	Block Diagrams	OK
9	Schematic Diagrams	Schematic Diagrams	OK
10	Parts List/Tune Up Info	Parts List/Tune Up Info	OK
11	Operational Description	Operational Description	OK
12	RF Exposure Info	RF Exposure Info	OK
13	Users Manual	Users Manual	OK

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 2. INTRODUCTION

2.1. SCOPE

Reference:	FCC Parts 2 and 80
Title:	Telecommunication - Code of Federal Regulations, CFR 47, Parts 2 & 90
Purpose of Test:	To gain FCC Certification Authorization for Radio operating in the frequency bands 156.050-157.425 MHz [Marine].
Test Procedures:	Both conducted and radiated emissions measurements were conducted in accordance with American National Standards Institute ANSI C63.4 - American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
Marine Categories of Station:	• Ship Station

2.2. RELATED SUBMITAL(S)/GRANT(S)

None

2.3. NORMATIVE REFERENCES

Publication	Year	Title
FCC CFR Parts 0-19, 80-End	2001	Code of Federal Regulations – Telecommunication
ANSI C63.4	1992	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
CISPR 22 & EN 55022	1997 1998	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
CISPR 16-1		Specification for Radio Disturbance and Immunity measuring apparatus and methods

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 3. PERFORMANCE ASSESSMENT

3.1. CLIENT INFORMATION

APPLICANT	
Name:	Icom Incorporated
Address:	1-1-32, Kamiminami Hirano-ku, Oaska Japan, 547-0003
Contact Person:	Mr. Takashi Aoki Phone #: +81-66-793-5302 Fax #: +81-66-793-0013 Email Address: export@icom.co.jp

MANUFACTURER	
Name:	Icom Incorporated
Address:	1-1-32, Kamiminami Hirano-ku, Oaska Japan, 547-0003
Contact Person:	Mr. Takashi Aoki Phone #: +81-66-793-5302 Fax #: +81-66-793-0013 Email Address: export@icom.co.jp

3.2. EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information (with the exception of the Date of Receipt) has been supplied by the applicant.

Brand Name:	ICOM Incorporated
Product Name:	MOBILE VHF MARINE TRANSCEIVER
Model Name or Number:	IC-M602
Serial Number:	3
Type of Equipment:	Non-broadcast Radio Communication Equipment
External Power Supply:	N/A
Transmitting/Receiving Antenna Type:	Non-integral
Primary User Functions of EUT:	Voice wireless communication for Marine use

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

3.3. EUT'S TECHNICAL SPECIFICATIONS

TRANSMITTER	
Equipment Type:	Mobile (Ship Station)
Intended Operating Environment:	Marine used as Coast and Ship Station
Power Supply Requirement:	13.8 Vdc
RF Output Power Rating:	25 Watts (High) or 1 Watt (Low)
Operating Frequency Range:	156.050-157.425 MHz [Marine]
RF Output Impedance:	50 Ohms
Channel Spacing:	25 kHz
Input Impedance (MIC)	2000 Ohms
Occupied Bandwidth (99%):	14.3 kHz maximum
Emission Designation*:	16K0F3E (FM Analog), 16K0G3E (Scrambler) and 16K0G2B (DSC)
Antenna Connector Type:	N

* For an average case of commercial telephony, the Necessary Bandwidth is calculated as follows:

For FM Voice Modulation:

Channel Spacing = 25 KHz, D = 5 KHz max, K = 1, M = 3 KHz

$B_n = 2M + 2DK = 2(3) + 2(5)(1) = \underline{16 \text{ KHz}}$

emission designation: 16K0F3E

RECEIVER	
Power Supply Requirement:	13.8 Vdc
Operating Frequency Range:	156.050-163.275 MHz
RF Input Impedance:	50 Ohms
Channel Spacing:	25 kHz
IF Frequencies	31.05 MHz (1 st IF), 21.7 MHz (1 st IF for DSC Ch70 Receiver), 450 kHz (2 nd IF for both)
Antenna Connector Type:	N

3.4. LIST OF EUT'S PORTS

Port Number	EUT's Port Description	Number of Identical Ports	Connector Type	Cable Type (Shielded/Non-shielded)
1	RF Input/Output Port	1	N	Shielded
2	13.8 Vdc voltage input port	1	Wireleads	Non-shielded

3.5. ANCILLARY EQUIPMENT

N/A

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4

Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80

Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 4. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS

4.1. CLIMATE TEST CONDITIONS

The climate conditions of the test environment are as follows:

Temperature:	21°C
Humidity:	51%
Pressure:	102 kPa
Power input source:	13.8 Vdc

4.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS

Operating Modes:	The transmitter was operated in a continuous transmission mode with the carrier modulated as specified in the Test Data.
Special Test Software:	N/A
Special Hardware Used:	N/A
Transmitter Test Antenna:	The EUT is tested with the transmitter antenna port terminated to a 50 Ohms RF Load.

Transmitter Test Signals	
Frequency Band(s):	Near lowest, near middle & near highest frequencies in each frequency bands that the transmitter covers:
156.050 - 157.425 MHz band:	156.050 and 157.425 MHz
Transmitter Wanted Output Test Signals:	
- Transmitter Power (measured maximum output power): - Normal Test Modulation - Modulating signal source:	25 Watts High and 1 Watts Low - FM & DSC - external

EXHIBIT 5. SUMMARY OF TEST RESULTS

5.1. LOCATION OF TESTS

All of the measurements described in this report were performed at Ultratech Group of Labs located in the city of Oakville, Province of Ontario, Canada.

- AC Powerline Conducted Emissions were performed in UltraTech's shielded room, 16'(L) by 12'(W) by 12'(H).
- Radiated Emissions were performed at the Ultratech's 3 Meter Open Field Test Site (OFTS) situated in the Town of Oakville, province of Ontario.

The above sites have been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec. 2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville Open Field Test Site has been filed with FCC office (FCC File No.: 31040/SIT 1300B3) and Industry Canada office (Industry Canada File No.: IC2049). Last Date of Site Calibration: Aug. 10, 2002.

5.2. APPLICABILITY & SUMMARY OF EMC EMISSION TEST RESULTS

FCC PARAGRAPH.	TEST REQUIREMENTS	APPLICABILITY (YES/NO)
80.215 & 2.1046	Transmitter Power	Yes
1.1307, 1.1310, 2.1091 & 2.1093	RF Exposure Limit	Yes
80.209 & 2.1055	Transmitter Frequency Tolerance	Yes
2.1047(a) & 80.213(e)	Audio Frequency Response / Modulation Requirements	Yes
2.1047(b)	Modulation Limiting	Yes
80.211 & 2.1049	Emission Limitation	Yes
80.211, 2.1057 & 2.1051	Emission Limits - Spurious Emissions at Antenna Terminal	Yes
80.211, 2.1057 & 2.1053	Emission Limits - Field Strength of Spurious Emissions	Yes
MOBILE VHF MARINE TRANSCEIVER, Model No.: IC-M602, by ICOM Incorporated has also been tested and found to comply with FCC Part 15, Subpart B - Radio Receivers and Class A Digital Devices. The engineering test report has been documented and kept in file and it is available anytime upon FCC request.		

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

5.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None

5.4. DEVIATION OF STANDARD TEST PROCEDURES

None

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 6. MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS

6.1. TEST PROCEDURES

This section contains test results only. Details of test methods and procedures can be found in Exhibit 8 of this report

6.2. MEASUREMENT UNCERTAINTIES

The measurement uncertainties stated were calculated in accordance with requirements of UKAS Document NIS 81 with a confidence level of 95%. Please refer to Exhibit 7 for Measurement Uncertainties.

6.3. MEASUREMENT EQUIPMENT USED:

The measurement equipment used complied with the requirements of the Standards referenced in the Methods & Procedures ANSI C63.4:1992 and CISPR 16-1.

6.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:

The essential function of the EUT is to correctly communicate data to and from radios over RF link.

6.5. TRANSMITTER POWER @ FCC 2.1046 & 80.215

6.5.1. Limits @ FCC 80.215

Please refer to FCC CFR 47, Part 80, Subpart I, Para. 80.215 for specification details.

- **Coast Stations in 156.050-157.425 MHz:** 50 Watts (at the input terminal of the station antenna). The frequencies 156.375 and 156.65 are primarily intership frequencies. When authorized for coast station on secondary basis, the normal output power must not exceed 1 Watt and the maximum output power must not exceed 10 Watts.
- **Ship Stations in 156.050-157.425 MHz:** 25 Watts (at the input terminal of the station antenna)

6.5.2. Method of Measurements


Please refer to Exhibit 8, § 8.1 (Conducted) and § 8.2 (Radiated) for test procedures and test setup.

6.5.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Hewlett Packard	HP 8546A	...	9 kHz to 5.6 GHz with built-in 30 dB Gain Pre-selector, QP, Average & Peak Detectors.
Attenuator(s)	Bird	...	...	DC – 22 GHz
Spectrum Analyzer/ EMI Receiver	Advantest	R3271	15050203	100 Hz – 26.5 GHz
Attenuator(s)	Weinschel Corp	24-20-34	BJ2357	DC – 8.5 GHz
Dipole Antenna	EMCO	3121C	8907-440	30 MHz – 1 GHz
Dipole Antenna	EMCO	3121C	8907-434	30 MHz – 1 GHz
Power Meter	Hewlett Packard	436A	1725A02249	10 kHz – 50 GHz, sensor dependent
Power Sensor	Hewlett Packard	8481A	2702A68983	10 MHz – 18 GHz
Synthesize Sweeper	Hewlett Packard	83752B	3610A00457	0.01 – 20 GHz

6.5.4. Test Arrangement

Power at Transmitter Power Terminals



6.5.5. Test Data

Power Setting: 25 Watts (High)			
Transmitter Channel Output	Fundamental Frequency (MHz)	Measured (Average) Conducted Power (Watts)	Power Rating (Watts)
Lowest	156.050	25.0	25.0
Highest	157.425	25.0	25.0
Note: There is no change in rf output power with different modulations: FM analog, Scrambler and DSC			

Power Setting: 1 Watt (Low)			
Transmitter Channel Output	Fundamental Frequency (MHz)	Measured (Average) Conducted Power (Watts)	Power Rating (Watts)
Lowest	156.050	1.0	1.0
Highest	157.425	1.0	1.0
Note: There is no change in rf output power with different modulations: FM analog, Scrambler and DSC			

6.6. RF EXPOSURE REQUIRMENTS @ 1.1310 & 2.1091

6.6.1. Limits

- FCC 1.1310:-** The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
30-300	61.4	0.163	1.0	6
(B) Limits for General Population/Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30

F = Frequency in MHz

6.6.2. Method of Measurements

Refer to FCC @ 1.1310, 2.1091 and Public Notice DA 00-705 (March 30, 2000)

- Spread spectrum transmitters operating under section 15.247 are categorically from routine environmental evaluation to demonstrating RF exposure compliance with respect to MPE and/or SAR limits. These devices are not exempted from compliance (As indicated in Section 15.247(b)(4), these transmitters are required to operate in a manner that ensures that exposure to public users and nearby persons) does not exceed the Commission's RF exposure guidelines (see Section 1.1307 and 2.1093). Unless a device operates at substantially low power levels, with a low gain antenna(s), supporting information is generally needed to establish the various potential operating configurations and exposure conditions of a transmitter and its antenna(s) in order to determine compliance with the RF exposure guidelines.
- In order to demonstrate compliance with MPE requirements (see Section 2.1091), the following information is typically needed:

Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.

Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement

Any caution statements and/or warning labels that are necessary in order to comply with the exposure limits

Any other RF exposure related issues that may affect MPE compliance

Calculation Method of RF Safety Distance:

$$S = PG/4\pi r^2 = EIRP/4\pi r^2$$

Where: P: power input to the antenna in mW
EIRP: Equivalent (effective) isotropic radiated power.
S: power density mW/cm²
G: numeric gain of antenna relative to isotropic radiator
r: distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{PG/4\pi S}$$

FCC radio frequency exposure limits may not be exceeded at distances closer than r cm from the antenna of this device

- For portable transmitters (see Section 2.1093), or devices designed to operate next to a person's body, compliance is determined with respect to the SAR limit (define in the body tissues) for near-field exposure conditions. If the maximum average output power, operating condition configurations and exposure conditions are comparable to those of existing cellular and PCS phones., an SAR evaluation may be required in order to determine if such a device complies with SAR limit. When SAR evaluation data is not available, and the additional supporting information cannot assure compliance, the Commission may request that an SAR evaluation be performed, as provided for in Section 1.1307(d)

6.6.3. Test Data

Antenna Gain Limit specified by Manufacturer: 9 dBi

Frequency (MHz)	Measured RF Conducted (Watts)	Calculated EIRP (Watts)	Laboratory's Recommended Minimum RF Safety Distance r (meters)	Manufacturer's Minimum RF Safety Distance (meters)
156.050	25.0	199.53	1.26	5.0
157.425	25.0	199.53	1.26	5.0

Note 1: RF EXPOSURE DISTANCE LIMITS: $r = (PG/4P S)^{1/2} = (EIRP/4P S)^{1/2}$
S = 1.0 mW/cm² for Limits for Occupational/Control Exposures

Evaluation of RF Exposure Compliance Requirements	
RF Exposure Requirements	Compliance with FCC Rules
Minimum calculated separation distance between antenna and persons required: 1.26 meters	Manufacturer' instruction for separation distance between antenna and persons required: 5 meters. Please refer to page # iii of the Users/ Manual and Radio Operator Warning

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.7. TRANSMITTER FREQUENCY TOLERANCE @ FCC 2.1055 & 80.209

6.7.1. Limits @ FCC 80.209

Please refer to FCC CFR 47, Part 80, Subpart I, Para. 80.209 for specification details.

Operating Frequency Band (MHz)	Ship Stations
156.050-157.425 MHz	10 ppm


6.7.2. Method of Measurements

Refer to Exhibit 8, § 8.3 of this report for measurement details

6.7.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	..	...	DC – 22 GHz
Temperature & Humidity Chamber	Tenney	T5	9723B	-40° to +60 ° C range

6.7.4. Test Arrangement



6.7.5. Test Data

Product Name:	MOBILE VHF MARINE TRANSCEIVER
Model No.:	IC-M602
Center Frequency:	156.05 MHz
Full Power Level:	25 Watts
Frequency Tolerance Limit:	± 10 ppm (for ship station)
Max. Frequency Tolerance Measured:	-784 Hz or +5.0 ppm
Input Voltage Rating:	13.8 Vdc

CENTER FREQUENCY & TRANSMITTER POWER VARIATION			
Ambient Temperature (°C)	Supply Voltage (Nominal) 13.8 Volts dc	Supply Voltage (85% of Nominal) 11.7 Volts dc	Supply Voltage (115% of Nominal) 15.9 Volts dc
	Hz	Hz	Hz
-30	-784	N/A	N/A
-20	-193	N/A	N/A
-10	-110	N/A	N/A
0	-95	N/A	N/A
+10	+24	N/A	N/A
+20	+26	+28	+43
+30	+29	N/A	N/A
+40	+129	N/A	N/A
+50	+286	N/A	N/A

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.8. AUDIO FREQUENCY RESPONSE / MODULATION REQUIREMENTS @ FCC 2.1047(A) & 80.213(E)

6.8.1. Limits @ FCC 2.1047(a) & 80.231(e)

The coast station transmitter operated in 156.050-157.425 MHz must be equipped with a lowpass filter. The filter must be installed between the modulation limiter and the modulated radio frequency stages. The audio lowpass filter shall meet the following characteristics:

RF Band	Audio band	Minimum Attenuation Rel. to 1 kHz Attenuation
156.050-157.425 MHz	3 –20 kHz 15 – 30 kHz	$60 \log_{10}(f/3)$ dB where f is in kHz 50dB


6.8.2. Method of Measurements

The rated audio input signal was applied to the input of the audio lowpass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT (Audio) spectrum analyzer. Tests were repeated at different audio signal frequencies from 0 to 50 kHz.

6.8.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
FFT (audio) Spectrum Analyzer	Advantest	R9211E	...	10 mHz – 100 kHz, 1 MHz Input Impedance
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz

6.8.4. Test Arrangement




6.8.5. Test Data

6.8.5.1. F3E, Frequency of All Modulation States*

FREQUENCY (kHz)	AUDIO IN (dBV)	AUDIO OUT (dBV)	ATTEN. (OUT - IN) (dB)	ATTEN. wrt. 1 kHz (dB)	FCC LIMIT (dB)	PASS/ FAIL
0.10	-45.2	-18.2	27.0	-24.5	0	PASS
0.20	-45.2	-10.4	34.8	-16.7	0.0	PASS
0.40	-45.2	-2.8	42.4	-9.1	0.0	PASS
0.60	-45.2	1.4	46.6	-4.9	0.0	PASS
0.80	-45.2	4.2	49.4	-2.1	0.0	PASS
1.00	-45.2	6.3	51.5	0.0	0.0	PASS
1.50	-45.2	8.6	53.8	2.3	0.0	PASS
2.00	-45.2	9.0	54.2	2.7	0.0	PASS
2.50	-45.2	8.5	53.7	2.2	0.0	PASS
3.00	-45.2	6.7	51.9	0.4	0.0	PASS
3.50	-45.2	3.6	48.8	-2.7	-4.0	PASS
4.00	-45.2	0.0	45.2	-6.3	-7.5	PASS
4.50	-45.2	-3.4	41.8	-9.7	-10.6	PASS
5.00	-45.2	-6.8	38.4	-13.1	-13.3	PASS
6.00	-45.2	-13.0	32.2	-19.3	-18.1	PASS
7.00	-45.2	-18.4	26.8	-24.7	-22.1	PASS
8.00	-45.2	-23.1	22.1	-29.4	-25.6	PASS
9.00	-45.2	-27.2	18.0	-33.5	-28.6	PASS
10.00	-45.2	-30.4	14.8	-36.7	-31.4	PASS
12.00	-45.2	-38.9	6.3	-45.2	-36.1	PASS
14.00	-45.2	-43.5	1.7	-49.8	-40.1	PASS
16.00	-45.2	<-50.0	<-4.8	<-56.3	-43.6	PASS
18.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
20.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
25.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
30.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
35.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
40.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS
50.00	-45.2	<-50.0	<-4.8	<-56.3	-50.0	PASS

AUDIO FREQUENCY REPSONSE OF ALL MODULATION STAGES
@ FCC 2.987(a) & 8013(e)
ICOM VHF Radio Transceiver, Model IC-M602 [25 kHz Channel Spacing]



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.9. MODULATION LIMITING @ FCC 2.1047(B)

6.9.1. Limits @ FCC 2.1047(b)

Recommended frequency deviation characteristics are give below:

Frequency Range (MHz)	Maximum Authorized BW (KHz)	Channel Spacing (KHz)	Recommended Frequency Deviation (KHz)
156.050-157.425	20.0	25.0	5.0

6.9.2. Method of Measurements


For Audio Transmitter:- The carrier frequency deviation was measured with the tone input signal level varied from 0 Vp to audio input rating level plus 16 dB at frequencies 0.1, 0.5, 1.0, 3.0 and 5.0 kHz. The maximum deviation was recorded at each test condition.

For Data Transmitter with Maximum Frequency Deviation set by Factory:- The EUT was set at maximum frequency deviation, and its peak frequency deviation was then measured using EUT's internal random data source.

6.9.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Communication Analyzer	Rohde & Schawrz	SMF02	879988/057	400 kHz - 1000 MHz including AF & RF Signal Generators, SINAD, DISTORTION, DEVIATION meters and etc

6.9.4. Test Arrangement



6.9.5. Test Data

6.9.5.1. Voice Modulation Limiting:

MODULATING SIGNAL LEVEL (mVrms)	PEAK FREQUENCY DEVIATION (kHz) at the following modulating frequency:					MAXIMUM LIMIT (kHz)
	0.1 kHz	0.5 kHz	1.0 kHz	3.0 kHz	5.0 kHz	
2	0.1	0.5	1.1	2.3	0.6	5.0
4	0.2	1.0	2.2	3.1	0.7	5.0
6	0.2	1.5	3.2	3.2	0.7	5.0
8	0.3	2.0	3.7	3.3	0.7	5.0
10	0.3	2.5	3.9	3.3	0.7	5.0
12	0.4	2.9	4.0	3.3	0.7	5.0
14	0.5	3.4	4.1	3.4	0.7	5.0
16	0.5	3.7	4.1	3.4	0.7	5.0
18	0.6	3.7	4.2	3.4	0.7	5.0
20	0.7	3.7	4.2	3.4	0.7	5.0
25	0.8	3.8	4.2	3.4	0.7	5.0
30	1.0	3.8	4.3	3.4	0.7	5.0
35	1.0	3.8	4.3	3.4	0.7	5.0
40	1.3	3.9	4.3	3.4	0.7	5.0
45	1.5	4.0	4.3	3.3	0.7	5.0
50	1.7	4.0	4.3	3.3	0.7	5.0
60	2.0	4.1	4.3	3.3	0.7	5.0
70	2.3	4.2	4.3	3.3	0.7	5.0
80	2.7	4.3	4.3	3.3	0.7	5.0
90	3.0	4.3	4.3	3.3	0.7	5.0
100	3.8	4.3	4.3	3.3	0.7	5.0

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Voice Signal Input Level = STD MOD Level + 16 dB = -45.2dBVrms + 16 = 29.2 dBmV or 34.7 mV

MODULATING FREQUENCY (KHz)	PEAK FREQUENCY DEVIATION (KHz)	MAXIMUM LIMIT (KHz)
0.1	1.1	5.0
0.2	2.8	5.0
0.4	3.8	5.0
0.6	4.0	5.0
0.8	4.2	5.0
1.0	4.3	5.0
1.2	4.2	5.0
1.4	4.2	5.0
1.6	4.2	5.0
1.8	4.2	5.0
2.0	4.3	5.0
2.5	4.1	5.0
3.0	3.4	5.0
3.5	2.3	5.0
4.0	1.5	5.0
4.5	1.0	5.0
5.0	0.7	5.0
6.0	0.4	5.0
7.0	0.2	5.0
8.0	0.1	5.0
9.0	0.1	5.0
10.0	0.1	5.0

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.10. EMISSION LIMITATIONS @ FCC 2.1049 & 80.211(2)

6.10.1. Limits

Emissions shall be attenuated below the mean output power of the transmitter as follows:

Frequency Range (MHz)	Maximum Authorized BW (KHz)	Channel Spacing (KHz)	Recommended Frequency Deviation (KHz)	FCC Applicable Mask
156.050-157.425	20.0	25.0	5.0	For other stations: 80.211(2)


6.10.2. Method of Measurements

Refer to Exhibit 8, § 8.4 of this report for measurement details

6.10.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	..	...	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz

6.10.4. Test Arrangement



6.10.5. Test Data

Conform. Please refer to Plots 1 through # 6 in Annex 1 for Details of measurements

6.10.5.1. 99% Occupied Bandwidth

Frequency (MHz)	Channel Spacing (kHz)	Modulation	Measured 99% OBW at Maximum Freq. Deviation (kHz)	Recommended 99% OBW (kHz)
156.050	25.0	FM with 2.5 kHz sine wave signal	14.2	16.0
157.425	25.0	FM with 2.5 kHz sine wave signal	14.3	16.0
156.050	25.0	DSC 1300 Hz	11.6	16.0
157.425	25.0	DSC 1300 Hz	11.7	16.0
156.050	25.0	FM with 2.5 kHz sine wave signal with Scrambler function	11.2	16.0
157.425	25.0	FM with 2.5 kHz sine wave signal with Scrambler function	11.3	16.0

6.10.5.2. Emission Masks

Conform.

- Plots # 7 through # 8 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = Low (1 Watt), Modulation: FM with 2.5 kHz Sine wave Signal.
- Plots # 9 through # 10 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = High (25 Watts), Modulation: FM with 2.5 kHz Sine wave Signal.
- Plots # 11 through # 12 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = Low (1 Watt), Modulation: DSC 1300 Hz.
- Plots # 13 through # 14 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = Low (1 Watt), Modulation: DSC 1300 Hz.
- Plots # 15 through # 16 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = Low (1 Watt), Modulation: FM with 2.5 kHz Sine wave Signal with Scrambler.
- Plots # 17 through # 18 in Annex 1 show Emissions Masks B for 25 KHz Channel Spacing Operation, RF Output Power = High (25 Watt), Modulation: FM with 2.5 kHz Sine wave Signal with Scrambler.

6.11. TRANSMITTER ANTENNA POWER SPURIOUS/HARMONIC CONDUCTED EMISSIONS @ FCC 80.211(2)

6.11.1. Limits @ 80.211(e)

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Frequency Range	Attenuation Limit (dBc)
80.211(e)	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	43+10*log(P)


6.11.2. Method of Measurements

Refer to Exhibit 8 § 8.5 of this report for measurement details

6.11.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	..	...	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz
Highpass Filter, Microphase	Microphase	CR220HID	IITI11000AC	Cut-off Frequency at 600 MHz, 1.3 GHz or 4 GHz

6.11.4. Test Arrangement



6.11.5. Test Data

6.11.5.1. Lowest Channel Frequency (156.050 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 1.0 Watts (Low))

FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
156.050	30.0	--	--	--	--
468.150	-25.9	-55.9	-43.0	-12.9	PASS
- The emissions were scanned from 10 MHz to 2 GHz and all emissions within 30 dB below the limits were recorded. - Please refer to Plot # 19-20 in Annex 1 for Detailed Measurements - Prescans showed no difference in test results when transmitter was tested with and without the Scrambler function or DSC 1300 Hz functions.					

6.11.5.2. Highest Channel Frequency (157.425 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 1.0 Watts (Low))

FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
157.425	30.0	--	--	--	--
10 - 2000	<<	<<	-43.0	<<	PASS
- The emissions were scanned from 10 MHz to 2 GHz and no emissions less than 30 dB below the limits were found. - Please refer to Plot # 21-22 in Annex 1 for Detailed Measurements - Prescans showed no difference in test results when transmitter was tested with and without the Scrambler function or DSC 1300 Hz functions.					

6.11.5.3. Lowest Channel Frequency (156.050 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 25 Watts (High))

FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
156.050	44.0	--	--	--	--
312.100	-37.6	-81.6	-57.0	-24.6	PASS
468.150	-20.1	-64.1	-57.0	-7.1	PASS
- The emissions were scanned from 10 MHz to 2 GHz and all emissions within 30 dB below the limits were recorded. - Please refer to Plot # 23-24 in Annex 1 for Detailed Measurements - Prescans showed no difference in test results when transmitter was tested with and without the Scrambler function or DSC 1300 Hz functions.					

6.11.5.4. Highest Channel Frequency (157.425 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 25 Watts (High))

FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
157.425	44.0	--	--	--	--
314.845	-36.0	-80.0	-57.0	-23.0	PASS
629.695	-26.4	-70.4	-57.0	-13.4	PASS
- The emissions were scanned from 10 MHz to 2 GHz and all emissions within 30 dB below the limits were recorded. - Please refer to Plot # 25-26 in Annex 1 for Detailed Measurements - Prescans showed no difference in test results when transmitter was tested with and without the Scrambler function or DSC 1300 Hz functions.					

6.12. TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 80.211(2)

6.12.1. Limits @ FCC 80.211(2)

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Frequency Range	Attenuation Limit (dBc)
80.211(2)	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	43+10*log(P)

6.12.2. Method of Measurements

The spurious/harmonic ERP measurements are using substitution method specified in Exhibit 8, § 8.2 of this report and its value in dBc is calculated as follows:

- If the transmitter's antenna is an integral part of the EUT, the ERP is measured using substitution method.
- If the transmitter's antenna is non-integral and diverse, the lowest ERP of the carrier with 0 dBi antenna gain is used for calculation of the spurious/harmonic emissions in dBc:

$$\text{Lowest ERP of the carrier} = \text{EIRP} - 2.15 \text{ dB} = P_c + G - 2.15 \text{ dB} = \text{xxx dBm (conducted)} + 0 \text{ dBi} - 2.15 \text{ dB}$$
- Spurious /harmonic emissions levels expressed in dBc (dB below carrier) are as follows:

$$\text{ERP of spurious/harmonic (dBc)} = \text{ERP of carrier (dBm)} - \text{ERP of spurious/harmonic emission (dBm)}$$

6.12.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Advantest	R3271	15050203	100 Hz to 32 GHz with external mixer for frequency above 32 GHz
Microwave Amplifier	Hewlett Packard	HP 83017A	3116A00661	1 GHz to 26.5 GHz
Active Loop Antenna	EMCO	6507	8906-1167	1 kHz – 30 MHz
Biconilog Antenna	EMCO	3143	1029	20 MHz to 2 GHz
Horn Antenna	EMCO	3155	9701-5061	1 GHz – 18 GHz
Horn Antenna with Mixer	EMCO	3160-09	1007	18 GHz – 26.5 GHz
Horn Antenna with Mixer	EMCO	3160-10	1001	26.5 GHz – 40 GHz

6.12.4. Test Setup

Please refer to Photos # 1 to 2 in Annex 2 for detailed of test setup.

6.12.5. Test Data


Remarks:

- (1) The transmitter radiated emissions were conducted at High RF Output Power (25 Watts) since the Transmitter Conducted Tests show they were higher than those at Low RF Output Power (1 Watt).
- (2) Complete radiated emissions tests at different modulations such as DSC 1300 Hz and Scrambler are not necessary to be repeated since the prescans show no difference in spurious/harmonic emissions with different modulation operations.

6.12.5.1. Lowest Channel Frequency (156.050 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 25 Watts (High))

FREQUENCY (MHz)	E-FIELD @3m (dBuV/m)	ERP measured by Substitution Method (dBm) (dBc)		EMI DETECTOR (Peak/QP)	ANTENNA POLARIZATION (H/V)	LIMIT (dBc)	MARGIN (dB)	PASS/FAIL
1248.40	68.1	-36.3	-80.3	PEAK	H	-57.0	-23.3	PASS
1248.40	65.8	-40.0	-84.0	PEAK	V	-57.0	-27.0	PASS

The emissions were scanned from 10 MHz to 2 GHz and all emissions within 30 dB below the limits were recorded.



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: ICOM-043FCC80
Oct. 24, 2002

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.12.5.2. Highest Channel Frequency (157.425 MHz, FM Modulation with 2.5 kHz Sine Wave Signal, RF Power: 25 Watts (High))

FREQUENCY (MHz)	E-FIELD @3m (dBuV/m)	ERP measured by Substitution Method (dBm) (dBc)		EMI DETECTOR (Peak/QP)	ANTENNA POLARIZATION (H/V)	LIMIT (dBc)	MARGIN (dB)	PASS/FAIL
1259.40	61.6	-42.7	-86.7	PEAK	H	-57.0	-29.7	PASS
1259.40	62.1	-42.7	-86.7	PEAK	V	-57.0	-29.7	PASS

The emissions were scanned from 10 MHz to 2 GHz and all emissions within 30 dB below the limits were recorded.




EXHIBIT 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994)

7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY

CONTRIBUTION (Radiated Emissions)	PROBABILITY DISTRIBUTION	UNCERTAINTY ($\pm$ dB)	
		3 m	10 m
Antenna Factor Calibration	Normal (k=2)	± 1.0	± 1.0
Cable Loss Calibration	Normal (k=2)	± 0.3	± 0.5
EMI Receiver specification	Rectangular	± 1.5	± 1.5
Antenna Directivity	Rectangular	± 0.5	± 0.5
Antenna factor variation with height	Rectangular	± 2.0	± 0.5
Antenna phase center variation	Rectangular	0.0	± 0.2
Antenna factor frequency interpolation	Rectangular	± 0.25	± 0.25
Measurement distance variation	Rectangular	± 0.6	± 0.4
Site imperfections	Rectangular	± 2.0	± 2.0
Mismatch: Receiver VRC $\Gamma_1 = 0.2$ Antenna VRC $\Gamma_R = 0.67(Bi) 0.3 (Lp)$ Uncertainty limits $20\text{Log}(1 \pm \Gamma_1 \Gamma_R)$	U-Shaped	+1.1 -1.25	± 0.5
System repeatability	Std. Deviation	± 0.5	± 0.5
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	+2.19 / -2.21	+1.74 / -1.72
Expanded uncertainty U	Normal (k=2)	+4.38 / -4.42	+3.48 / -3.44

Calculation for maximum uncertainty when 3m biconical antenna including a factor of k=2 is used:

$$U = 2u_c(y) = 2x(+2.19) = +4.38 \text{ dB} \quad \text{And} \quad U = 2u_c(y) = 2x(-2.21) = -4.42 \text{ dB}$$

EXHIBIT 8. MEASUREMENT METHODS

8.1. CONDUCTED POWER MEASUREMENTS

The following shall be applied to the combination(s) of the radio device and its intended antenna(e).

- If the RF level is user adjustable, all measurements shall be made with the highest power level available to the user for that combination.
- The following method of measurement shall apply to both conducted and radiated measurements.
- The radiated measurements are performed at the Ultratech Calibrated Open Field Test Site.
- The measurement shall be performed using normal operation of the equipment with modulation.

Test procedure shall be as follows:

Step 1: Duty Cycle measurements if the transmitter's transmission is transient

- * Using a EMI Receiver with the frequency span set to 0 Hz and the sweep time set at a suitable value to capture the envelope peaks and the duty cycle of the transmitter output signal;
- * The duty cycle of the transmitter, $x = \text{Tx on} / (\text{Tx on} + \text{Tx off})$ with $0 < x < 1$, is measure and recorded in the test report. For the purpose of testing, the equipment shall be operated with a duty cycle that is equal or more than 0.1.


Step 2: Calculation of Average EIRP. See Figure 1

- * The average output power of the transmitter shall be determined using a wideband, calibrated RF average power meter with the power sensor with an integration period that exceeds the repetition period of the transmitter by a factor 5 or more. The observed value shall be recorded as "A" (in dBm);
- * The e.i.r.p. shall be calculated from the above measured power output "A", the observed duty cycle x, and the applicable antenna assembly gain "G" in dBi, according to the formula:

$$\text{EIRP} = A + G + 10\log(1/x)$$

{ $X = 1$ for continuous transmission $\Rightarrow 10\log(1/x) = 0 \text{ dB}$ }

Figure 1.



8.2. RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD

8.2.1. Maximizing RF Emission Level (E-Field)

- The measurements was performed with full rf output power and modulation.
- Test was performed at listed 3m open area test site (listed with FCC, IC, ITI, NVLAP, ACA & VCCI).
- The transmitter under test was placed at the specified height on a non-conducting turntable (80 cm height) The BICONILOG antenna (20 MHz to 1 GHz) or HORN antenna (1 GHz to 18 GHz) was used for measuring.
- Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- Set the EMI Receiver #1 and #2 as follows:

Center Frequency:	test frequency
Resolution BW:	100 kHz
Video BW:	same
Detector Mode:	positive
Average:	off
Span:	3 x the signal bandwidth

- The test antenna was lowered or raised from 1 to 4 meters until the maximum signal level was detected.
- The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
- The test antenna was lowered or raised again from 1 to 4 meters until a maximum was obtained. This level was recorded.
- The recorded reading was corrected to the true field strength level by adding the antenna factor, cable loss and subtracting the pre-amplifier gain.
- The above steps were repeated with both transmitters' antenna and test receiving antenna placed in vertical and horizontal polarization. Both readings with the antennas placed in vertical and horizontal polarization shall be recorded.
- Repeat for all different test signal frequencies

8.2.2. Measuring the EIRP of Spurious/Harmonic Emissions using Substitution Method

- Set the EMI Receiver (for measuring E-Field) and Receiver #2 (for measuring EIRP) as follows:

Center Frequency:	equal to the signal source
Resolution BW:	10 kHz
Video BW:	same
Detector Mode:	positive
Average:	off
Span:	3 x the signal bandwidth

- Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- Select the frequency and E-field levels obtained in the Section 8.2.1 for ERP/EIRP measurements.
- Substitute the EUT by a signal generator and one of the following transmitting antenna (substitution antenna):
 - DIPOLE antenna for frequency from 30-1000 MHz or
 - HORN antenna for frequency above 1 GHz }.
- Mount the transmitting antenna at 1.5 meter high from the ground plane.
- Use one of the following antenna as a receiving antenna:
 - DIPOLE antenna for frequency from 30-1000 MHz or
 - HORN antenna for frequency above 1 GHz }.
- If the DIPOLE antenna is used, tune it's elements to the frequency as specified in the calibration manual.
- Adjust both transmitting and receiving antenna in a VERTICAL polarization.
- Tune the EMI Receivers to the test frequency.
- Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
- The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
- Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
- Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.
- Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P1 - L1 = (P2 + L2) - L1 = P3 + A + L2 - L1$$

$$EIRP = P + G1 = P3 + L2 - L1 + A + G1$$

$$ERP = EIRP - 2.15 \text{ dB}$$

$$\text{Total Correction factor in EMI Receiver \# 2} = L2 - L1 + G1$$

Where: P: Actual RF Power fed into the substitution antenna port after corrected.
P1: Power output from the signal generator
P2: Power measured at attenuator A input
P3: Power reading on the Average Power Meter
EIRP: EIRP after correction
ERP: ERP after correction

Adjust both transmitting and receiving antenna in a HORIZONTAL polarization, then repeat step (k) to (o)

- Repeat step (d) to (o) for different test frequency
- Repeat steps (c) to (j) with the substitution antenna oriented in horizontal polarization.

- Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.:

Figure 2





Figure 3



8.3. TRANSMITTER FREQUENCY TOLERANCE

Refer to FCC @ 2.1055.

- (a) The Transmitter Frequency Tolerance shall be measured with variation of ambient temperature as follows: From -30 to +50 centigrade except that specified in subparagraph (2) & (3) of this paragraph.
- (b) Frequency measurements shall be made at extremes of the specified temperature range and at intervals of not more than 10 centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stability circuitry need be subjected to the temperature variation test.
- (d) The Transmitter Frequency Tolerance supply shall be measured with variation of primary supply voltage as follows:
 - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
 - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
 - (3) The supply voltage shall be measured at the input to the cable normally provide with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.
- (e) When deemed necessary, the Commission may require tests of Transmitter Frequency Tolerance under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment).

8.4. EMISSION MASK

Voice or Digital Modulation Through a Voice Input Port @ 2.1049(c)(i):- The transmitter was modulated by a 2.5 KHz tone signal at an input level 16 dB greater than that required to produce 50% modulation (e.g.: ± 2.5 KHz peak deviation at 1 KHz modulating frequency). The input level was established at the frequency of maximum response of the audio modulating circuit.

Digital Modulation Through a Data Input Port @ 2.1049(h):- Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the Emission Masks shall be shown for operation with any devices used for modifying the spectrum when such devices are operational at the discretion of the user.

The following EMI Receiver bandwidth shall be used for measurement of Emission Mask/Out-of-Band Emission Measurements:

For 25 kHz Channel Spacing: RBW = 300 Hz

The all cases the Video Bandwidth shall be equal or greater than the measuring bandwidth.

8.5. SPURIOUS EMISSIONS (CONDUCTED)

With transmitter modulation characteristics described in Out-of-Band Emissions measurements @ 2.1049, the transmitter spurious and harmonic emissions were scanned. The spurious and harmonic emissions were measured with the EMI Receiver controls set as RBW = 30 kHz minimum, VBW $\geq$ RBW and SWEEP TIME = AUTO). The transmitter was operated at a full rated power output, and modulated as follows:

FCC CFR 47, Para. 2.1057 - Frequency spectrum to be investigated:- The spectrum was investigated from the lowest radio generated in the equipment up to at least the 10th harmonic of the carrier frequency or to the highest frequency practicable in the present state of the art of measuring techniques, whichever is lower. Particular attention should be paid to harmonics and subharmonics of the carrier frequency. Radiation at the frequencies of multiplier stages should be checked. The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

FCC CFR 47, Para. 2.1051 - Spurious Emissions at Antenna Terminal:- The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of the harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.