

Jinan Qianxi Yahu Industry Co.,Ltd

Yahu Wireless Room Access System(Indoor Unit)

Main Model: T600-2001




Serial Model: See P5

February 18, 2014

Report No.: 14050001-FCC-H-I



(This report supersedes none)

Modifications made to the product : None		
This Test Report is Issued Under the Authority of:		
		
Deon Dai Compliance Engineer	Alex Liu Technical Manager	

This test report may be reproduced in full only.

Test result presented in this test report is applicable to the representative sample only.

RF Exposure Evaluation Report
To: §15.247 (i), §2.1093

SIEMIC, INC.
Accessing global markets



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to [testing](#) and [certification](#), SIEMIC provides initial design reviews and [compliance management](#) through out a project. Our extensive experience with [China](#), [Asia Pacific](#), [North America](#), [European](#), and [international](#) compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the [global markets](#).

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC , RF/Wireless , Telecom
Canada	EMC, RF/Wireless , Telecom
Taiwan	EMC, RF, Telecom , Safety
Hong Kong	RF/Wireless ,Telecom
Australia	EMC, RF, Telecom , Safety
Korea	EMI, EMS, RF , Telecom, Safety
Japan	EMI, RF/Wireless, Telecom
Singapore	EMC , RF , Telecom
Europe	EMC, RF, Telecom , Safety



SIEMIC, INC.

Title: RF Exposure Evaluation Report for Yahu Wireless Room Access System(Indoor Unit)
Main Model: T600-2001
Serial Model: See P5
To: § 15.247 (i), §2.1093

Report No.: 14050001-FCC-H-I
Issue Date: February 18, 2014
Page: 3 of 9
www.siemic.com.cn

This page has been left blank intentionally.



SIEMIC, INC.

Title: RF Exposure Evaluation Report for Yahu Wireless Room Access System(Indoor Unit)
Main Model: T600-2001
Serial Model: See P5
To: § 15.247 (i), §2.1093

Report No.: 14050001-FCC-H-I
Issue Date: February 18, 2014
Page: 4 of 9
www.siemic.com.cn

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION.....	7
4	TEST SUMMARY.....	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Jinan Qianxi Yahu Industry Co.,Ltd, Yahu Wireless Room Access System(Indoor Unit) and model: T600-2001 against the current Stipulated Standards. The Yahu Wireless Room Access System(Indoor Unit) has demonstrated compliance with the § 15.247 (i), §2.1093.

EUT Information

EUT Description	Yahu Wireless Room Access System(Indoor Unit)
Main Model	T600-2001
Serial Model	C200-2001, C500-2001, F200-2001, F600-2001, F700-2001, F900-2001, F910-2001
Series Number	201309
Antenna Gain	2 dBi
Input Power	Battery: Model:XL-753048 1200mAh 3.7V Adapter: Model: FC06PA-050S100C2C Input: AC 100-240V 50/60Hz 0.3A Output: DC 5.0V 1A
Classification Per Stipulated Test Standard	§ 15.247 (i), §2.1093

Note: All models have the same constructions, circuit diagram and PCB layout. Only model name are different.“2001” refers is our Wireless Room Access system, before "-" difference is that the auxiliary lock is different.

**SIEMIC, INC.**

Title: RF Exposure Evaluation Report for Yahu Wireless Room Access System(Indoor Unit)
Main Model: T600-2001
Serial Model: See P5
To: § 15.247 (i), §2.1093

Report No.: 14050001-FCC-H-I
Issue Date: February 18, 2014
Page: 6 of 9
www.siemic.com.cn

2 TECHNICAL DETAILS

Purpose	Compliance testing of Yahu Wireless Room Access System(Indoor Unit) with stipulated standard
Applicant / Client	Jinan Qianxi Yahu Industry Co.,Ltd Building 3, No. 322, Shunfeng Road,High tech Zone of Jinan,Shandong
Manufacturer	Jinan Qianxi Yahu Industry Co.,Ltd Building 3, No. 322, Shunfeng Road,High tech Zone of Jinan,Shandong
Laboratory performing the tests	SIEMIC (Nanjing-China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com.cn
Test report reference number	14050001-FCC-H-I
Date EUT received	September 13, 2013
Standard applied	§ 15.247 (i), §2.1093
Dates of test (from – to)	11th November to 20th December, 2013
No of Units :	#1
Equipment Category :	Spread Spectrum System/Device
Trade Name :	Yahu
RF Operating Frequency (ies)	2410.875 MHz~2471.625MHz
Number of Channels	19CH
Modulation	GFSK
FCC ID	AGS-INDOOR

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications.
All testing has been performed according to below product classification:

Test Results Summary

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 §15.247 (i) and §2.1093/ – RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT (FHSS product). The minimum separation distances is 5 mm.

The maximum average output power(turn-up power) in low channel of FHSS product is 0.17 dBm=1.04 mW

The calculation results= $1.04/5 \cdot \sqrt{2410.875}=0.32 < 3$

The maximum average output power(turn-up power) in middle channel of FHSS product is 1.04 dBm=1.27 mW

The calculation results= $1.27/5 \cdot \sqrt{2441.250}=0.40 < 3$

The maximum average output power(turn-up power) in high channel of FHSS product is 1.96 dBm=1.57 mW

The calculation results= $1.57/5 \cdot \sqrt{2471.625}=0.49 < 3$

According to KDB 447498, no stand-alone required for FHSS product, and no simultaneous SAR measurement is required .

Test Result: Pass