

RF Exposure / SAR Statement

No. : 30KE0186-YK-01-A

Applicant : PIONEER CORPORATION

Type of Equipment : CD RDS Receiver

Model No. : DEH-7300BT

FCC ID : AJDK033

PIONEER CORPORATION declares that Model : CD RDS Receiver complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "DEH-7300BT" has 0.73 mW of conducted Peak Output power and 0.44 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "DEH-7300BT" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 0.73 mW (Maximum peak output power)

G = 0.60 Numerical Antenna gain; equal -2.20 dBi

r = 20.0 cm

For: DEH-7300BT

S = 0.00009 mW/cm²

UL Japan, Inc. Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401