

RF Exposure / SAR Statement

No. : 32EE0124-SH-01-A

Applicant : PIONEER CORPORATION
Type of Equipment : CD RDS RECEIVER
Model No. : DEH-80PRS
FCC ID : AJDK047

PIONEER CORPORATION declares that Model : CD RDS RECEIVER complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "DEH-80PRS" has 2.51 mW of conducted Peak Output power and 0.5 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "DEH-80PRS" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 2.51 mW (Maximum peak output power)
G = 0.20 Numerical Antenna gain; equal -7.00 dBi
r = 20.0 cm

For: DEH-80PRS

S = 0.00010 mW/cm²

**UL Japan, Inc.
Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400
Facsimile : +81 463 50 6401