

RF Exposure / SAR Statement

No. : 32KE0042-SH-02-A

Applicant : PIONEER CORPORATION
Type of Equipment : Bluetooth CD RDS RECEIVER
Model No. : DEH-X9500BHS
FCC ID : AJDK056

PIONEER CORPORATION declares that Model : Bluetooth CD RDS RECEIVER complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "DEH-X9500BHS" has 1.53 mW of conducted Peak Output power and 0.92 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "DEH-X9500BHS" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 1.53 mW (Maximum peak output power)
G = 0.60 Numerical Antenna gain; equal -2.20 dBi
r = 20.0 cm

For: DEH-X9500BHS

S = 0.00018 mW/cm²

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400
Facsimile: +81 463 50 6401