RF Exposure / SAR Statement

No.: 32KE0188-SH-02-A

Applicant : PIONEER CORPORATION

Type of Equipment: DVD AV RECEIVER Model No. : AVH-X5500BHS

FCC ID : AJDK058

PIONEER CORPORATION declares that Model: DVD AV RECEIVER complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "AVH-X5500BHS" has 1.09 mW of conducted Peak Output power and 0.64 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "AVH-X5500BHS" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm^2 uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4* \pi * r^2)$$

Where

P = 1.09 mW (Maximum peak output power)

G = 0.59 Numerical Antenna gain; equal -2.30 dBi

r = 20.0 cm

For: AVH-X5500BHS $S = 0.00013 \text{ mW/cm}^2$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400 Facsimile : +81 463 50 6401