

FCC / IC – Test report

Report Number	: 60/760.11.318.04	Date of Issue: <u>October 23, 2014</u>
Model	: SGY-CS500	
Product Type	: <u>Speed & Cadence Sensor</u>	
Applicant	: <u>Pioneer Corporation.</u>	
Address	: <u>1-1, Shin-ogura, Saiwai-ku, Kawasaki-shi, Kanagawa-ken, Japan</u>	
Production Facility	: <u>Kendy Enterprise Ltd.</u>	
Address	: <u>2-12 Kwai Fat Road, 11-A Kwai Chung, New Territories, Hong Kong</u>	
Test Result	: ■ Positive <input type="checkbox"/> Negative	
Total pages including Appendices	: <u>29</u>	

TÜV SÜD Hong Kong Ltd. is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Hong Kong Ltd. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Hong Kong Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Hong Kong Ltd. issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test.....	4
4	Summary of Test Standards/ Results.....	5
5	General Remarks.....	6
6	Emission Test Results.....	7
6.1	Radiated Emission Test.....	7
6.2	20dB and 99% Bandwidth measurement.....	16
6.3	Band edge measurement.....	18
7	Appendix A.....	20
	Photographs of EUT	
8	Appendix B.....	25
	Photographs of Test Set Up	
9	Appendix C.....	27
	Product Information	

2 Details about the Test Laboratory

Details about the Test Laboratory

Company name: TÜV SÜD HONG KONG LTD.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin
HK.

Telephone: 852 2776 1323
Fax: 852 2776 1372

Test site

Company name: Neutron Engineering Inc.
3,Jinshagang 1st Road,
ShiXia, Dalang Town,
DongGuan, China

FCC Registered Test Site Number 319330
Open area test site Industry Canada Number: 4428B

3 Description of the Equipment Under Test

Description of the Equipment Under Test

Product: Speed & Cadence Sensor

Model no.: SGY-CS500

Serial number: NIL

Options and accessories: NIL

FCC ID: AJDK084

IC: 775E-K084

Opreating Frequency: 2457MHz

Rated Voltage: 3 VDC

Rated Current: NIL

Rated Power: NIL

Frequency: NIL

Description of the EUT: EUT Main unit size: 6 cm x 5 cm x 2 cm
Supply by 1 x 3 VDC (CR2032 battery cell)

4 Summary of Test Standards and Results

Test Condition	Pages	Test Result		
		Pass	Fail	N/A
Conducted Emission (47 CFR 15.207, 15.209 & RSS-GEN 7.2.4)	NIL	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> *
Radiated Emission (47 CFR 15.249, 15.209 & RSS-210 A2.9, GEN 7.2.5 & RSS-GEN 6.1)	7	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth (47 CFR 15.215)	16	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
99% occupied bandwidth (RSS-GEN 4.6.1)	16	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Bandedge Emission (47 CFR 15.249)	18	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark: 1. NA: Battery operated only.

2. For Spurious Radiated Emissions test, three set-up directions(X,Y,Z) were pretested, but only direction X test data was recorded in this report for it is the worst case.

5 General Remarks

Remarks

NIL

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: October 3, 2014

Testing Start Date: October 6, 2014

Testing End Date: October 16, 2014

- TÜV SÜD HONG KONG LTD. -

Reviewed by:

Edmond FUNG



Prepared by:

CHAN Kwong Ngai

6 Emission Test Results

6.1 Radiated Emission Test (Fundamental and Harmonic)

Date of test : 14 October 2014

Test Result


Passed
 Not Passed

Test requirement : FCC Part 15.249 & RSS-210, A2.9

Operating mode : Transmitting mode

Antenna polarity : Horizontal

Remarks : Fundament and Harmonic frequency



Freq. (MHz)	Ant.Pol. H/V	Reading	Ant./CF CF(dB)	Average factor (dB)	Act.		Limit	
		Peak (dBuV/m)			Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)
2457.00	H	66.44	-31.84	51.06	98.28	47.22	114.00	94.00

Remark: The EUT was placed on the top of the turntable in test site area.
 The resolution bandwidth setting on the test receiver was 9 KHz, Detector function peak (9kHz~30MHz).
 The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).
 The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~26.5GHz).
 The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 For emissions measurement, the receiving antenna was placed 3 meters far away from the turntable.
 The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
 Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
 Adjust the emission and slightly height of the antenna to locate the position with maximum reading.
 If the peak scan value lower limit more than 20dB, then this signal data does not show in graph
 9kHz -30MHz and 18500 MHz to 26500MHz only have the background noise, the test date and graph does not show on the test report

Radiated Emission Test (Fundamental)

Date of test : 14 October 2014


Test Result
 Passed
 Not Passed

Test requirement : FCC Part 15.249 & RSS-210, A2.9

Operating mode : Transmitting mode

Antenna polarity : Vertical

Remarks : Fundamental and



Freq. (MHz)	Ant.Pol. H/V	Reading	Ant./CF CF(dB)	Average factor (dB)	Act.		Limit	
		Peak (dBuV/m)			Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)
2456.75	V	52.95	-31.84	51.06	84.79	33.73	114.00	94.00

Remark: The EUT was placed on the top of the turntable in test site area.
 The resolution bandwidth setting on the test receiver was 9 KHz, Detector function peak (9kHz~30MHz).
 The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).
 The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~26.5GHz).
 The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 For emissions measurement, the receiving antenna was placed 3 meters far away from the turntable.
 The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
 Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
 Adjust the emission and slightly height of the antenna to locate the position with maximum reading.
 If the peak scan value lower limit more than 20dB, then this signal data does not show in graph
 9kHz -30MHz and 18500 MHz to 26500MHz only have the background noise, the test date and graph does not show on the test report

Radiated Emission Test (Duty cycle)


Date of test : 14 October 2014

Test Result
 Passed
 Not Passed

Test requirement : FCC Part 15 & RSS-210

Operating mode : Transmitting mode

Remarks : Detector function = peak



EUT data packet 1 has the period of 0.28ms

Radiated Emission Test (Duty cycle)


Date of test : 14 October 2014

Test Result
 Passed
 Not Passed

Test requirement : RSS-210

Operating mode : Transmitting mode

Remarks : Detector function = peak



EUT data packet off has the period of 246 ms

Therefore, the total signal "on" time of on successful period is = 246 ms.

And the pulse train time should be 100ms according to FCC and IC rules.

Average factor: $20 \log 1/(0.28/100) = 51.06 \text{ dB}$ Average = Peak – Average Factor

Radiated Emission Test 9kHz – 1000MHz

Date of test : 14 October 2014

Test Result
 Passed
 Not Passed


Test requirement : FCC Part 15 & ICES-003

Test method : CISPR 22

Operating mode : Operating (During the measurement of the speed, it will transmit the corresponding data) (worst case)

Antenna Polarity : Horizontal

Remarks : Other than the Fundament



Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
34.85	H	41.05	-17.22	23.83	40.00	-16.17	
71.23	H	33.75	-18.21	15.54	40.00	-24.46	
265.23	H	29.80	-12.20	17.60	46.00	-28.40	
439.83	H	29.59	-9.00	20.59	46.00	-25.41	
580.48	H	29.64	-5.76	23.88	46.00	-22.12	
728.40	H	28.73	-4.91	23.82	46.00	-22.18	

Remark: The EUT was placed on the top of the turntable in test site area.
 The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).
 The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~5GHz).
 The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 For emissions measurement, the receiving antenna was placed 10 meters far away from the turntable.
 The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
 Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
 Adjust the emission and slightly height of the antenna to locate the position with maximum reading.
 If the peak scan value lower limit more than 20dB, then this signal data does not show in graph

Radiated Emission Test 1000MHz – 25000MHz

Date of test : 14 October 2014

Test Result
 Passed
 Not Passed


Test requirement : FCC Part 15 & ICES-003

Test method : ANSI C63.4:2009

Operating mode : Operating (During the measurement of the speed, it will transmit the corresponding data) (worst case)

Antenna Polarity : Horizontal

Remarks : Other than the Fundament



Freq. (MHz)	Ant.Pol. H/V	Reading	Ant./CF CF(dB)	Average factor (dB)	Act.		Limit	
		Peak (dBuV/m)			Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)
2483.50	H	23.75	-31.80	51.06	55.55	4.49	74.00	54.00
4914.11	H	51.64	-5.71	51.06	57.35	6.29	74.00	54.00

Remark:

The EUT was placed on the top of the turntable in test site area.
The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).
The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~5GHz).
The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
For emissions measurement, the receiving antenna was placed 10 meters far away from the turntable.
The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
Adjust the emission and slightly height of the antenna to locate the position with maximum reading.
If the peak scan value lower limit more than 20dB, then this signal data does not show in graph

Radiated Emission Test 9kHz – 1000MHz

Date of test : 14 October 2014

Test Result
 Passed
 Not Passed

Test requirement : FCC Part 15 & ICES-003

Test method : ANSI C63.4:2009

Operating mode : Operating (During the measurement of the speed, it will transmit the corresponding data) (worst case)

Antenna Polarity : Vertical

Remarks : Other than the Fundament and Harmonic frequency



Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
39.70	V	40.33	-17.18	23.15	40.00	-16.85	
168.23	V	39.28	-14.40	24.88	43.50	-18.62	
287.05	V	29.87	-11.26	18.61	46.00	-27.39	
401.03	V	29.92	-9.71	20.21	46.00	-25.79	
587.75	V	29.39	-5.64	23.75	46.00	-22.25	
757.50	V	28.47	-4.82	23.65	46.00	-22.35	

Remark: The EUT was placed on the top of the turntable in test site area.
 The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).

The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~5GHz).

The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.

For emissions measurement, the receiving antenna was placed 10 meters far away from the turntable.

The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.

Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.

Adjust the emission and slightly height of the antenna to locate the position with maximum reading.

If the peak scan value lower limit more than 20dB, then this signal data does not show in graph

Radiated Emission Test 1000MHz – 25000MHz

Date of test : 14 October 2014

Test Result
 Passed
 Not Passed

Test requirement : FCC Part 15 & ICES-003

Test method : ANSI C63.4:2009

Operating mode : Operating (During the measurement of the speed, it will transmit the corresponding data) (worst case)

Antenna Polarity : Vertical

Remarks : Other than the Fundament and Harmonic frequency



Freq. (MHz)	Ant.Pol. H/V	Reading	Ant./CF CF(dB)	Average factor (dB)	Act.		Limit	
		Peak (dBuV/m)			Peak (dBuV/m)	AV (dBuV/m)	Peak (dBuV/m)	AV (dBuV/m)
2483.50	V	23.26	-31.80	51.06	55.06	4.00	74.00	54.00
4914.04	V	53.62	-5.71	51.06	59.33	8.27	74.00	54.00

Remark: The EUT was placed on the top of the turntable in test site area.
 The resolution bandwidth setting on the test receiver was 120 KHz, Detector function peak (30 MHz~1000MHz).

The resolution bandwidth setting on the test receiver was 1MHz, Detector function peak (1 GHz~5GHz).

The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.

For emissions measurement, the receiving antenna was placed 10 meters far away from the turntable.

The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.

Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.

Adjust the emission and slightly height of the antenna to locate the position with maximum reading.

If the peak scan value lower limit more than 20dB, then this signal data does not show in graph

Test Equipment List

Radiated Emission Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
Horn Antenna	ETS	3115	00075789	May.11.2015
Amplifier	Agilent	8449B	3008A02274	May.25.2015
Spectrum	Agilent	E4408B	US39240143	Nov.15.2014
Test Cable	HUBER+SUHNER	CB03 High Fre	N/A	May.02.2015
Bi-log Antenna	Schwarzbeck	VULB9160	9160-3232	May.25.2015
Amplifier	HP	8447D	2944A09673	May.25.2015
Test Receiver	R&S	ESCI	100895	May.25.2015
Test Cable	N/A	C-01_CB03	N/A	Jul.04.2015
Controller	CT	SC100	N/A	N/A
Triple Loop Antenna	R&S	HFH2-Z2	830749/020	May.26.2015
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	May.11.2015

Uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Total uncertainty at a minimum confidence level of 95%	Normal (k=2)	± 2.66 (correct to 1 decimal place)

6.2 20dB down and 99% Occupied Bandwidth measurement

Date of test : 14 October 2014


Test Result	
<input checked="" type="checkbox"/> Passed	<input type="checkbox"/> Not Passed

Test requirement : FCC Part 15.215 & RSS-210

Test method : ANSI C63.4:2009

Operating mode : Transmitting mode

Remarks : NIL



20 dBc Bandwidth : 1.12 MHz
 99% Occupied BW: 1.04 MHz

Remark: Span: the minimum span to fully display the emission and approximately 20 dB below the peak level

Resolution BW: Set to 1% to 3% of the approximate emission width

Video BW: 3 times the Resolution BW

Video Averaging: None

Sweep time: Coupled

Detector: Sample

Compute the combined power of all signal responses contained in the trace by recovering all the data points, converting them to power and summing all the values. For 99% occupied BW, place the markers at the frequency at which 0.5% of the power lies to the right of the right marker and 0.5% of the power lies to the left of the left marker. The 99% of the power lies between the markers. The 20dB measurement method is a secondary alternative to the 99% Occupied BW method, if it is performed as illustrated below. The spectrum analyzer is set to a resolution and video bandwidth far greater than the emission bandwidth and the peak of the signal is set to the top line of the analyzer. The marker is placed on the trace at the point left of centre that displays a value that is 20 dB below the value of the reference level. The delta marker is evoked and placed at the point to the right of centre that displays 0 dB differential. The frequency differential is the occupied bandwidth as shown.


Test Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2014

6.3 Bandedge measurement

Date of test : 14 October 2014
 Test requirement : FCC Part 15 & RSS-210
 Test method :
 Operating mode : Transmitting mode
 Remarks : NIL

Test Result
 Passed
 Not Passed



Remark: Use the following spectrum analyzer settings:
 Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation
 RBW \geq 1% of the span
 VBW \geq RBW
 Sweep = auto
 Detector function = peak
 Trace = max hold
 Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section. Submit this plot. Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit. Submit this plot.

Test Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
Spectrum Analyzer	R&S	FSP 40	100185	Nov.26.2014

Uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Total uncertainty at a minimum confidence level of 95%	Normal (k=2)	± 2.66 (correct to 1 decimal place)


7 Appendix A





Appendix A





Appendix A



Appendix A




Appendix A





8 Appendix B

Radiated Emission Test Set Up



30MHz-1GHz

Appendix B



1GHz above

9 Appendix C

