



Test report No. : 31KE0212-SH-02-B
Page : 1 of 70
Issued date : July 20, 2011
Revised date : July 28, 2011
FCC ID : AK8PRST1

RADIO TEST REPORT

Test Report No.: 31KE0212-SH-02-B

Applicant : Sony Corporation
Type of Equipment : Digital Book Reader
Model No. : PRS-T1
FCC ID : AK8PRST1
Test regulation : FCC Part15 Subpart C: 2010
Test result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: June 23 to July 9, 2011

Representative test engineer:

Hikaru Shirasawa
Engineer of WiSE Japan,
UL Verification Service

Approved by :

Ichiro Isozaki
Leader of WiSE Japan,
UL Verification Service

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".



UL Japan, Inc.
Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN
Telephone : +81 463 50 6400
Facsimile : +81 463 50 6401

13-EM-F0429

Contents

Page

SECTION 1: Customer information	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures & results	4
SECTION 4: Operation of E.U.T. during testing.....	7
SECTION 5: Conducted emission.....	8
SECTION 6: 6dB bandwidth & Occupied bandwidth (99%)	8
SECTION 7: Maximum peak output power.....	9
SECTION 8: Spurious emission (Antenna port conducted)	9
SECTION 9: Radiated emission.....	10
SECTION 10: Peak Power density.....	11
Contents of APPENDIXES.....	12
APPENDIX 1: Photographs of test setup.....	13
APPENDIX 2: Test data.....	16
APPENDIX 3: Test instruments.....	69

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 1: Customer information

Company Name : Sony Corporation
Brand Name : SONY
Address : Shinagawa INTERCITY C Tower 2-15-3, Konan Minato-ku, Tokyo, 108-6201 Japan
Telephone Number : +81 3 5769 5222
Facsimile Number : +81 3 5769 5901
Contact Person : Shinichi Maru

SECTION 2: Equipment under test (E.U.T.)**2.1 Identification of E.U.T.**

Type of Equipment : Digital Book Reader
Model Number : PRS-T1
Serial Number : Refer to Section 4.2
Rating : DC 4.2V
Country of Mass-production : China
Condition of EUT : Engineering prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample : June 23, 2011
Modification of EUT : No modification by the test lab.

2.2 Product description

Model: PRS-T1 (referred to as the EUT in this report) is a Digital Book Reader.

Clock frequency(ies) in the system : CPU 24MHz, WLAN 26MHz, PMIC 32kHz

Equipment type : Transceiver
Frequency of operation : 2412-2462MHz
Bandwidth & channel spacing : 20MHz & 5MHz
Type of modulation : IEEE802.11b: DSSS (DBPSK, DQPSK, CCK)
IEEE802.11g/n(20HT): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna type : Pattern
Antenna gain with cable loss : 1.07dBi (2412MHz), 2.06dBi (2436MHz), 1.25dBi (2472MHz)
Antenna connector type : U.FL
ITU code : D1D, G1D
Operation temperature range : +5 to +35 deg.C.

FCC Part15.31 (e)

This EUT provides stable voltage (DC3.3V and DC1.8V) constantly to RF Module regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part15.203

The EUT has a unique coupling/antenna connector (U.FL). Therefore the equipment complies with the requirement of 15.203.

UL Japan, Inc.**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 3: Test specification, procedures & results**3.1 Test specification**

Test specification : FCC Part 15 Subpart C: 2010, final revised on December 6, 2010
and effective January 5, 2011

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.209 Radiated emission limits, general requirements
Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz,
and 5725-5850MHz

The EUT complies with FCC Part 15 Subpart B: 2010. Refer to the test report: 31KE0212-SH-02-A.

3.2 Procedures & Results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC 15.207	-	N/A	27.5dB Freq.: 0.15000MHz Phase: L1 Mode: IEEE802.11b Tx 2412MHz	Complied
6dB bandwidth	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.247 (a)(2) & 15.209	Conducted	N/A	See data	Complied
Maximum peak output power	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.247 (b)(3) & 15.209	Conducted	N/A		Complied
Spurious emission & Restricted band edges	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.109, 15.247 (d) & 15.209	Conducted / Radiated	N/A	4.0dB Freq.: 2483.5MHz Polarization: Vertical Detection: Average Mode: IEEE 802.11n(20HT) Tx 2462MHz	Complied
Power density	"Guidance on Measurement for Digital Transmission Systems Section 15.247" & ANSI C63.4:2003 13. Measurement of intentional radiators	FCC 15.247 (e)	Conducted	N/A	See data	Complied

Note: UL Japan's Work Procedures No. 13-EM-W0420 and 13-EM-W0422

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied Bandwidth (99%)	ANSI C63.4:2003 13. Measurement of intentional radiators, RSS-Gen 4.6.1	RSS-Gen 4.6.1	Conducted	-	-
Note: UL Japan's Work Procedures No.13-EM-W0420 and 13-EM-W0422					

* Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Item	Frequency range	No.1 SAC* ¹ /SR* ² (±)	No.2 SAC/SR (±)	No.3 SAC/SR (±)
Conducted emission (AC Mains) AMN/LISN	150kHz-30MHz	3.0 dB	2.7 dB	3.1 dB
Radiated emission (Measurement distance: 3m)	9kHz-30MHz	3.3 dB	2.7 dB	3.4 dB
	30MHz-300MHz	4.7 dB	4.5 dB	4.7 dB
	300MHz-1GHz	4.5 dB	4.6 dB	4.6 dB
	1GHz-13GHz	3.9 dB	3.9 dB	4.0 dB
Radiated emission (Measurement distance: 1m)	13GHz-18GHz	4.8 dB	4.8 dB	4.8 dB
	18GHz-40GHz	4.4 dB	4.2 dB	4.2 dB

*1: SAC=Semi-Anechoic Chamber

*2: SR= Shielded Room is applied besides radiated emission

Conducted emission test

The data listed in this test report has enough margin, more than site margin.

Radiated emission test

The data listed in this test report has enough margin, more than site margin.

Antenna port conducted test

Power Measurement uncertainty above 1GHz for this test was: (±) 1.3dB

Spurious emission (Conducted), Power density Measurement (below 1GHz) uncertainty for this test was: (±) 1.9dB

Spurious emission (Conducted), Power density Measurement (1G-3GHz) uncertainty for this test was: (±) 2.5dB

Spurious emission (Conducted), Power density Measurement (3G-18GHz) uncertainty for this test was: (±) 3.8dB

Spurious emission (Conducted), Power density Measurement (18G-26.5GHz) uncertainty for this test was: (±) 4.1dB

Bandwidth Measurement uncertainty for this test was: (±) 5.4%

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

3.5 Test location

UL Japan, Inc. Shonan EMC Lab.

1-22-3, Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number : +81 463 50 6400

Facsimile number : +81 463 50 6401

JAB Accreditation No. : RTL02610

	FCC Registration No.	IC Registration No.	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Maximum measurement distance
☐ No.1 Semi-anechoic chamber	697847	2973D-1	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☒ No.2 Semi-anechoic chamber	697847	2973D-2	20.6 x 11.3 x 7.65	20.6 x 11.3	10m
☒ No.3 Semi-anechoic chamber	697847	2973D-3	12.7 x 7.7 x 5.35	12.7 x 7.7	5m
☐ No.4 Full-anechoic chamber	-	-	8.1 x 5.1 x 3.55	8.1 x 5.1	-
☐ No.1 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☐ No.2 shielded room	-	-	6.8 x 4.1 x 2.7	6.8 x 4.1	-
☒ No.3 shielded room	-	-	6.3 x 4.7 x 2.7	6.3 x 4.7	-
☐ No.4 shielded room	-	-	4.4 x 4.7 x 2.7	4.4 x 4.7	-
☐ No.5 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-
☒ No.6 shielded room	-	-	7.8 x 6.4 x 2.7	7.8 x 6.4	-

3.6 Test setup, Data of test & Test instruments

Refer to Appendix 1 to 3.

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 4: Operation of E.U.T. during testing


4.1 Operating mode

The EUT exercise program used during testing was designed to exercise the various system components in a manner similar to typical use.

Test item	Mode	Tested frequency	Power setting *1)	Worst data rate *2)
All items	Transmitting IEEE 802.11b	2412MHz, 2437MHz, 2462MHz	13dBm	11Mbps, PN9
	Transmitting IEEE 802.11g	2412MHz, 2437MHz, 2462MHz	9dBm	6Mbps, PN9
	Transmitting IEEE 802.11n (20HT)	2412MHz, 2437MHz, 2462MHz	13dBm	MCS3, PN9
*1) Software: Tera Term (Version 4.67)				
*2) The worst condition was determined based on the test result of Maximum Peak Output Power (Mid Channel)				

Justification: The system was configured in typical fashion (as customer would normally use it) for testing.

4.2 Configuration and peripherals



* Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Digital Book Reader	PRS-T1	497 *1), 465 *2)	Sony	EUT
B	Headphone	MDR-EX10LP	-	Sony	-
C	AC adapter	PRSA-AC10	-	Sony	*3)
D	Micro SD	SR-8A4	-	Sony	-

*1) Used for Radiated emission tests and Maximum peak output power measurement test

*2) Used for Antenna terminal conducted tests except Maximum peak output power measurement test

*3) The EUT has two-type of AC adapter (PRSA-AC1 and PRSA-AC10). Pre-check measurement of conducted emission and radiated emission was performed and there was no difference on the results. Therefore, PRSA-AC10 was used for the test.

List of cables used

No.	Cable name	Length (m)	Shield	
			Cable	Connector
1	USB	1.5	Shielded	Shielded
2	Headphone	1.1	Unshielded	Unshielded

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 5: Conducted emission

5.1 Operating environment

The test was carried out in No.3 shielded room.

Temperature : Refer to test data (APPENDIX 2)

Humidity : Refer to test data (APPENDIX 2)

5.2 Test configuration

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The table is made of Styrofoam and covered with polyvinyl chloride. That has very low permittivity.

The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT was aligned and was flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from LISN and excess AC cable was bundled in center.

Photographs of the set up are shown in Appendix 1.

5.3 Test conditions

Frequency range : 0.15 - 30MHz

EUT position : Table top

5.4 Test procedure

The AC Mains Terminal Continuous disturbance Voltage had been measured with the EUT within a screened room. The EUT was connected to a Line Impedance Stabilization Network (LISN).

An overview sweep with peak detection has been performed.

The measurements had been performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver.

Detector Type : Quasi-Peak/ Average

IF Bandwidth : 9kHz

5.5 Results

Summary of the test results : Pass

Refer to APPENDIX 2

SECTION 6: 6dB bandwidth & Occupied bandwidth (99%)

Test procedure

The bandwidth was measured with a spectrum analyzer connected to the antenna port.

Summary of the test results: Pass

Refer to APPENDIX 2

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 7: Maximum peak output power

Test procedure

The Maximum Peak Output Power was measured with a power meter connected to the antenna port.

Summary of the test results: Pass
Refer to APPENDIX 2

SECTION 8: Spurious emission (Antenna port conducted)

Test procedure

The spurious emission was measured with a spectrum analyzer connected to the antenna port.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.
(9kHz-150kHz:RBW=200Hz, 150kHz-30MHz:RBW=10kHz)

Summary of the test results: Pass
Refer to APPENDIX 2

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

SECTION 9: Radiated emission

9.1 Operating environment

The test was carried out in No.2 / No.3 Semi-Anechoic Chamber.

Temperature : Refer to test data (APPENDIX 2)

Humidity : Refer to test data (APPENDIX 2)

9.2 Test configuration

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The table is made of Styrofoam and covered with polyvinyl chloride. That has very low permittivity.

The rear of EUT, including its peripherals was aligned and flushed with rear of tabletop.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

Photographs of the set up are shown in Appendix 1.

9.3 Test conditions

Frequency range : 30MHz to 26.5GHz

EUT position : Table top

9.4 Test procedure

The Radiated Electric Field Strength intensity has been measured on a semi-anechoic chamber with a ground plane and at a distance of 3m (below 13GHz) / 1m (above 13GHz). Measurements were performed with quasi-peak, peak and average detector. The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detection of the test receiver and Spectrum Analyzer.

Frequency	:	30-1000MHz	1000-26500MHz	
Detection Type	:	Quasi-Peak	Peak	* Average
IF Bandwidth	:	120kHz	RBW: 1MHz/VBW: 3MHz	RBW: 1MHz/VBW: 10Hz

* When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

* The VBW was based on the inverse of the duty cycle (Refer to Appendix 2) (duty = 100%).

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Worst position:

	Frequency	Carrier	Spurious			
			30M-1GHz	1-13GHz	13-18GHz	18-26.5GHz
EUT	Horizontal	Y	X	Y	Y	Y
	Vertical	Z	X	Z	Z	Z


UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Figure 1. Antenna angle

11.5 Band edge

Band edge level at 2397.484MHz and 2400MHz are less than 20dB of peak point of the carrier.
Band edge level at 2390MHz and 2483.5MHz are below the limits of FCC 15.209. Refer to the data.

11.6 Results

Summary of the test results : Pass *No noise was detected above the 8th order harmonics.
Refer to APPENDIX 2

SECTION 10: Peak Power density

Test procedure

The peak power density was measured with a spectrum analyzer connected to the antenna port.

Instrument used : Spectrum Analyzer *1)
RBW / VBW : 30kHz / 100kHz *2)

*1) PSD Option 1 of " Measurement of Digital Transmission Systems Operating under Section 15.247".

*2) The test was not performed at RBW: 3kHz that was stated in the Regulation. However, the measurement value with RBW: 3kHz is less than the value of RBW: 30kHz and the test data met the limit with RBW: 30kHz.

Summary of the test results: Pass
Refer to APPENDIX 2

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401

Contents of APPENDIXES

APPENDIX 1: Photographs of test setup

Conducted emission
Radiated emission
Pre-check of the worst position

APPENDIX 2: Test data

Conducted emission
6dB bandwidth
Maximum peak output power
Radiated emission
Spurious emission (Antenna port conducted)
Peak power density
99% Occupied bandwidth

APPENDIX 3: Test instruments

Test instruments