



SAR TEST REPORT

Test Report No. : 29EE0190-HO-04-A

Applicant : Sony Computer Entertainment Inc.
Type of Equipment : PSP
Model No. : PSP-3001
FCC ID : AK8PSP3001B
Test regulation : FCC47CFR 2.1093
FCC OET BULLETIN 65, SUPPLEMENT C
Test Result : Complied
Max. SAR Value : 0.251W/kg (Body, 2437MHz)

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Date of test:

February 6, 2009

Tested by:

Miyo Kishimoto
EMC Services

Approved by :

Tetsuo Maeno
Site Manager of EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address, <http://uljapan.co.jp/emc/nvlap.htm>

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (09.01.08)

CONTENTS	PAGE
SECTION 1: Customer information.....	3
SECTION 2: Equipment under test (E.U.T.).....	3
2.1 Identification of E.U.T.....	3
2.2 Product Description	4
SECTION 3 : Test standard information.....	5
3.1 Requirements for compliance testing defined by the FCC.....	5
3.2 Procedure and result.....	6
3.3 Exposure limit	6
3.4 Test Location	7
3.5 Confirmation before SAR testing.....	7
3.6 Confirmation after SAR testing	7
3.7 Measurement procedure.....	8
3.8 Test setup of EUT	9
SECTION 4 : Operation of E.U.T. during testing.....	10
4.1 Operating modes for SAR testing	10
SECTION 5 : Test surrounding	11
5.1 Measurement uncertainty	11
SECTION 6 : Confirmation before testing	12
6.1 Correlation of EMC power and SAR power	12
SECTION 7 : Measurement results	13
7.1 Body SAR 2450MHz	13
APPENDIX 1 : Photographs of test setup	14
1. Photograph of EUT	15
2. Photograph of EUT with accessories (Body-worn setup).....	16
3. Photograph of Battery.....	17
4. Photograph of test setup.....	18
APPENDIX 2 : SAR Measurement data	26
1. Evaluation procedure	27
2. Measurement data (SAR 2450MHz)	28
APPENDIX 3 : Test instruments	41
1. Equipment used	42
2. Dosimetry assessment setup	43
3. Configuration and peripherals	44
4. System components	45
5. Test system specifications	47
6. Simulated Tissues Composition of 2450MHz	48
7. Validation Measurement.....	48
8. System validation data	49
9. Validation uncertainty	50
10. Validation Measurement data	51
11. System Validation Dipole (D2450V2,S/N: 713)	52
12. Dosimetric E-Field Probe Calibration (EX3DV3,S/N: 3540).....	62
13. References	70

SECTION 1: Customer information

Company Name	Sony Computer Entertainment Inc.
Brand name	Sony
Address	2-6-21 Minami-Aoyama, Minato-ku, Tokyo, 107-0062, Japan
Telephone Number	+81-3-6483-8023
Facsimile Number	+81-3-6483-8642
Contact Person	Tatsuya Suzuki

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment		PSP
Model No.		PSP-3001
Serial No.		-0100000696-PSPXXXX
WLAN Module		Module 1
Country of Manufacture		China
Condition of EUT		Production prototype (Not for sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample		December 20, 2008
Normal Battery	Type	Li-ion Battery
	Model name	PSP-S110
	Rating	DC3.6V/1200mAh
	Manufacturer	SONY
Option Battery 1	Type	Li-ion Battery
	Model name	PSP-110
	Rating	DC3.6V/1800mAh
	Manufacturer	SONY
Option Battery 2	Type	Li-ion Battery
	Model name	PSP-280
	Rating	DC3.6V/2200mAh
	Manufacturer	SONY
Category Identified		Portable device
Accessories		Earphone, USB cable

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

2.2 Product Description

Radio Specification

Wireless LAN Module (IEEE802.11b)

Equipment Type	Transceiver
Frequency of Operation	2412-2462 MHz
Clock Frequency	40MHz
ITU Code	G1D
Type of Modulation	DSSS
Method of frequency generation	Crystal
Antenna model	HBS01-SO01
Antenna type	Inverted F antenna
Antenna Gain	+3.5 dBi (Max.)

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 3 : Test standard information

3.1 Requirements for compliance testing defined by the FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at

maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

1 Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).

2 IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

3.2 Procedure and result

No.	Item	Test Procedure	Limit	Remarks	Exclusion	Result
1	Human Exposure	FCC OET BULLETIN 65, SUPPLEMENT C	FCC47CFR 2.1093	SAR Measurement	N/A	Complied Max.SAR = 0.251 W/kg
Note: UL Japan, Inc. 's SAR Work Procedures QPM46 and QPM47						

Result of Max. SAR value

Max. SAR Value: 0.251W/kg (Body, 2437MHz)

3.3 Exposure limit

(A) Limits for Occupational/Controlled Exposure (W/kg)

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.4	8.0	20.0

(B) Limits for General population/Uncontrolled Exposure (W/kg)

Spatial Average (averaged over the whole body)	Spatial Peak (averaged over any 1g of tissue)	Spatial Peak (hands/wrists/feet/ankles averaged over 10g)
0.08	1.6	4.0

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**NOTE:GENERAL POPULATION/UNCONTROLLED EXPOSURE
SPATIAL PEAK(averaged over any 1g of tissue) LIMIT
1.6 W/kg**

3.4 Test Location

*Shielded room for SAR testings

UL Japan, Inc. Head Office EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

3.5 Confirmation before SAR testing

Correlation of Output Power between EMC and SAR tests (WLAN IEEE802.11b)

It was checked that the antenna port power was correlated within 0~+5% (FCC requirements)
The result is shown in Section 6.1.

- **Peak power in EMC test (January 27, 2009)**
EMC power was measured for SAR test sample (S/N: -0100000696-PSPXXXX)
- **Peak power in SAR test (February 6, 2009)**
SAR power was measured for SAR test sample (S/N: -0100000696-PSPXXXX).

Average power in SAR test

- **Average power in SAR test (February 6, 2009)**
SAR power was measured for SAR test sample (S/N: -0100000696-PSPXXXX).
- **Confirmation of Data rate**
The average power by the data rate was checked in the middle channel (2437 MHz.)

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within $\pm 5\%$. The verification of power drift during the SAR test is that DASY4 system calculates the power drift by measuring the E-field at the same location at beginning and the end of the scan measurement for each test position.

DASY4 system calculation Power drift value[dB] = $20\log(E_a)/(E_b)$
Before SAR testing : E_b [V/m]
After SAR testing : E_a [V/m]

Limit of power drift[W] = $\pm 5\%$
 $X[\text{dB}] = 10\log[P] = 10\log(1.05/1) = 10\log(1.05) - 10\log(1) = 0.212\text{dB}$

from E-field relations with power.
 $S = E^2/H = E^2/\eta = P/4\pi r^2$ (η : Space impedance)
 $P = E^2 \cdot 4\pi r^2/\eta$
Therefore, The correlation of power and the E-field
 $X_{\text{dB}} = 10\log(P) = 10\log(E^2) = 20\log(E)$

From the above mentioned,
The calculated power drift of DASY4 System must be the less than $\pm 0.212\text{dB}$.

3.7 Measurement procedure

IEEE 802.11b(Radiated power is always monitored by Spectrum Analyzer.)

The 11b (DSSS) mode test was performed on the CCK[11Mbps] modulation, because it was the highest average power and maximum data rate.

Step1. The searching for the worst position

Step2. Change to the Low and High channels

This test was performed at the worst position of Step 1.

Step3. Change to the option battery.

This test was performed at the worst conditions of Step 2.

Change distance between EUT and SAM Twin Phantom

Step4. Change separation

The measurement was performed with the distance, 5mm and 10mm to check if the shortest distance may not have the worst value at the conditions of the highest SAR value.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

3.8 Test setup of EUT

When users operate or carry the EUT, it could be considered to touch or get close to their bodies. In order to assume this situation, we performed the test at the following positions. Please refer to "APPENDIX 1" for more details.

(1) Front:

The test was performed in touch with Front surface of the EUT to the flat phantom.

(2) Rear :

The test was performed in touch with Rear surface of the EUT to the flat phantom.

(3) Top :

The test was performed in touch with Top edge of the EUT to the flat phantom.

(4) Bottom :

The test was performed in touch with Bottom edge of the EUT to the flat phantom.

(5) Left side :

The test was performed in touch with left side of the EUT to the flat phantom.

(6) Right side :

The test was performed in touch with right side of the EUT to the flat phantom.

(7) Front (5mm) :

The measurement opened 5mm distance between the EUT and flat phantom.

(8) Front (10mm) :

The measurement opened 10mm distance between the EUT and flat phantom.

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 4 : Operation of E.U.T. during testing

4.1 Operating modes for SAR testing

4.1.1 Setting of EUT

This EUT has IEEE.802.11b continuous transmitting modes.

The frequency band and the modulation used in the testing of IEEE.802.11b is shown as a following.

1. IEEE 802.11b mode
Tx frequency band : 2412-2462MHz
Channel : 1ch(2412MHz),6ch(2437MHz),11ch(2462MHz)
Modulation : DSSS (CCK)
Crest factor : Refer to the following

Note: Details of crest factor (PAR)

The data of worst SAR result and maximum PAR was used for the following PAR value.

Modulation (data)	Frequency[MHz]	PK	AVG	Crest factor (PAR)
CCK (11Mbps)	2412	15.60	8.61	1.8
CCK (11Mbps)	2437	18.71	9.59	2.0
CCK (11Mbps)	2462	18.97	9.48	2.0

Crest factor (PAR) = PK power / AVG power

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 5 : Test surrounding

5.1 Measurement uncertainty

The uncertainty budget has been determined for the DASY4 measurement system according to the SPEAG documents[6][7] and is given in the following Table.

Error Description	Uncertainty value $\pm$ %	Probability distribution	divisor	(ci) 1g	Standard Uncertainty (1g)	vi or veff
Measurement System						
Probe calibration	± 6.8	Normal	1	1	± 6.8	∞
Axial isotropy of the probe	± 4.7	Rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	± 1.9	∞
Spherical isotropy of the probe	± 9.6	Rectangular	$\sqrt{3}$	$(cp)^{1/2}$	± 3.9	∞
Boundary effects	± 2.0	Rectangular	$\sqrt{3}$	1	± 1.2	∞
Probe linearity	± 4.7	Rectangular	$\sqrt{3}$	1	± 2.7	∞
Detection limit	± 1.0	Rectangular	$\sqrt{3}$	1	± 0.6	∞
Readout electronics	± 0.3	Normal	1	1	± 0.3	∞
Response time	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Integration time	± 2.6	Rectangular	$\sqrt{3}$	1	± 1.5	∞
RF ambient Noise	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
RF ambient Reflections	± 3.0	Rectangular	$\sqrt{3}$	1	± 1.7	∞
Probe Positioner	± 0.8	Rectangular	$\sqrt{3}$	1	± 0.5	∞
Probe positioning	± 9.9	Rectangular	$\sqrt{3}$	1	± 5.7	∞
Max.SAR Eval.	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Test Sample Related						
Device positioning	± 2.9	Normal	1	1	± 2.9	11
Device holder uncertainty	± 3.6	Normal	1	1	± 3.6	7
Power drift	± 5.0	Rectangular	$\sqrt{3}$	1	± 5.8	∞
Phantom and Setup						
Phantom uncertainty	± 4.0	Rectangular	$\sqrt{3}$	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.64	± 1.8	∞
Liquid conductivity (meas.)	± 5.0	Rectangular	1	0.64	± 3.2	∞
Liquid permittivity (target)	± 5.0	Rectangular	$\sqrt{3}$	0.6	± 1.7	∞
Liquid permittivity (meas.)	± 5.0	Rectangular	1	0.6	± 3.0	∞
Combined Standard Uncertainty					± 14.360	
Expanded Uncertainty (k=2)					± 28.7	

SECTION 6 : Confirmation before testing

6.1 Correlation of EMC power and SAR power

6.1.1 EMC power

This data is reference data of EMC test(Report No. 29EE0190-HO-01-A).

Date of test: January 27, 2009

IEEE802.11b , 11Mbps (Module 1)

Ch	Freq. [MHz]	P/M Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
					[dBm]	[mW]
Low	2412.0	0.66	1.10	9.98	11.74	14.93
Mid	2437.0	1.63	1.10	9.98	12.71	18.66
High	2462.0	1.69	1.10	9.98	12.77	18.92

Sample Calculation:

Result = Reading + Cable Loss (supplied by customer) + Attenuator

6.1.2 SAR power

Date of test: February 6, 2009

IEEE802.11b , 11Mbps (Module 1)

Ch	Frequency [MHz]	P/M Reading [dBm]		Cable Loss [dB]	Atten. [dB]	Result			
		PK	AVG			[dBm]		[mW]	
						PK	AVG	PK	AVG
Low	2412.0	0.74	-1.84	1.10	10.09	11.93	9.35	15.60	8.61
Mid	2437.0	1.53	-1.37	1.10	10.09	12.72	9.82	18.71	9.59
High	2462.0	1.59	-1.42	1.10	10.09	12.78	9.77	18.97	9.48

Sample Calculation:

Result = Reading + Cable Loss (supplied by customer) + Attenuator

6.1.3 Reference data of SAR test (Data rate determination)

Date of test: February 6, 2009

Average power

[IEEE802.11b] Rate check

Modulation	Data rate	Freq.	P/M Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result	
	[Mbps]	[MHz]				[dBm]	[mW]
DBPSK	1	2437.0	-1.44	1.10	10.09	9.75	9.44
DQPSK	2	2437.0	-1.43	1.10	10.09	9.76	9.46
CCK	5.5	2437.0	-1.39	1.10	10.09	9.80	9.55
	11	2437.0	-1.37	1.10	10.09	9.82	9.59

Sample Calculation:

Result = Reading + Cable Loss + Attenuator

UL Japan, Inc.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

UL Japan, Inc.
Head Office EMC Lab.
 4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
 Telephone : +81 596 24 8116
 Facsimile : +81 596 24 8124