

# RF MEASUREMENT REPORT

---

**FCC ID:** AL8-PBVL50  
**Applicant:** HP Inc.  
**Product:** Bluetooth headset  
**Model No.:** PBVL50  
**Trademark:**   
**FCC Classification:** Digital Transmission System (DTS)  
**FCC Rule Part(s):** Part 15 Subpart C (Section 15.247)  
**Result:** Complies  
**Received Date:** 2024-09-10  
**Test Date:** 2024-09-23 ~ 2024-09-30

**Reviewed By:**

\_\_\_\_\_  
Vincent Yu

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
2409RSU021-U2	V01	Initial Report	2024-10-21	Valid

---

## CONTENTS

Description	Page
<b>1. General Information .....</b>	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Testing Facility .....	5
1.4. Product Information.....	6
1.5. Radio Specification under Test .....	6
1.6. Working Frequencies .....	7
<b>2. Test Configuration .....</b>	<b>8</b>
2.1. Test Mode.....	8
2.2. Test System Connection Diagram.....	8
2.3. Test Software .....	9
2.4. Applied Standards.....	9
2.5. Test Environment Condition .....	9
<b>3. Antenna Requirements .....</b>	<b>10</b>
<b>4. Measuring Instrument .....</b>	<b>11</b>
<b>5. Decision Rules and Measurement Uncertainty .....</b>	<b>12</b>
5.1. Decision Rules .....	12
5.2. Measurement Uncertainty .....	12
<b>6. Test Result.....</b>	<b>13</b>
6.1. Summary.....	13
6.2. 6dB Bandwidth Measurement.....	14
6.2.1. Test Limit .....	14
6.2.2. Test Procedure.....	14
6.2.3. Test Setting .....	14
6.2.4. Test Setup .....	14
6.2.5. Test Result .....	14
6.3. Output Power Measurement .....	15
6.3.1. Test Limit .....	15
6.3.2. Test Procedure.....	15
6.3.3. Test Setting .....	15
6.3.4. Test Setup .....	15
6.3.5. Test Result .....	15
6.4. Power Spectral Density Measurement .....	16
6.4.1. Test Limit .....	16
6.4.2. Test Procedure.....	16

6.4.3.	Test Setting .....	16
6.4.4.	Test Setup .....	16
6.4.5.	Test Result .....	16
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement .....	17
6.5.1.	Test Limit .....	17
6.5.2.	Test Procedure .....	17
6.5.3.	Test Settintg .....	17
6.5.4.	Test Setup .....	18
6.5.5.	Test Result .....	18
6.6.	Radiated Spurious Emission Measurement.....	19
6.6.1.	Test Limit .....	19
6.6.2.	Test Procedure .....	19
6.6.3.	Test Setting .....	19
6.6.4.	Test Setup .....	21
6.6.5.	Test Result .....	22
6.7.	Radiated Restricted Band Edge Measurement .....	23
6.7.1.	Test Limit .....	23
6.7.2.	Test Procedure .....	24
6.7.3.	Test Setting .....	24
6.7.4.	Test Setup .....	25
6.7.5.	Test Result .....	26
6.8.	AC Conducted Emissions Measurement .....	27
6.8.1.	Test Limit .....	27
6.8.2.	Test Setup .....	27
6.8.3.	Test Result .....	27
<b>Appendix A - Test Result.....</b>		<b>28</b>
A.1	Duty Cycle Test Result .....	28
A.2	6dB Bandwidth Test Result .....	29
A.3	Output Power Test Result .....	31
A.4	Power Spectral Density Test Result.....	32
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	34
A.6	Radiated Spurious Emission Test Result .....	38
A.7	Radiated Restricted Band Edge Test Result.....	42
<b>Appendix B - Test Setup Photograph .....</b>		<b>58</b>
<b>Appendix C - EUT Photograph .....</b>		<b>59</b>



#### 1.4. Product Information

Product Name	Bluetooth headset
Model No.	PBVL50
Serial No.	21VNP43100RZ240431AAL
Bluetooth Specification	BR/EDR/BLE
Antenna Information	Refer to Section 1.5
Power Type	Power by built-in battery
Operating Temperature	0 ~ 45 °C
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

#### 1.5. Radio Specification under Test

Bluetooth Frequency	2402 ~ 2480MHz
Channel Number	40
Type of modulation	GFSK
Data Rate	1Mbps & 2Mbps
Antenna Type	Monopole Antenna
Antenna Gain	-0.19dBi

**1.6. Working Frequencies**

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--


## 2. Test Configuration

### 2.1. Test Mode

Mode 1: Transmit by BLE-1Mbps
Mode 2: Transmit by BLE-2Mbps

### 2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing.



### 2.3. Test Software

The test utility software used during testing was “BlueTest3”, and the version was 3.3.15.

### 2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

### 2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~75%RH

### 3. Antenna Requirements

**Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

**Conclusion:**

The unit complies with the requirement of §15.203.

#### 4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Thermohygrometer	testo	608-H1	MRTSUE11022	1 year	2024-10-28	SIP-TR1
Signal Analyzer	Keysight	N9030B	MRTSUE06395	1 year	2025-06-21	SIP-TR1
USB Power Sensor	Keysight	U2021XA	MRTSUE06596	1 year	2025-07-23	SIP-TR1
Horn Antenna	ETS	3117	MRTSUE06257	1 year	2025-09-08	WJ-AC1
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2024-12-04	WJ-AC1
EMI Test Receiver	R&S	ESR3	MRTSUE07110	1 year	2025-04-24	WJ-AC1
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07096	1 year	2025-04-24	WJ-AC1
Anechoic Chamber	TDK	WJ-AC1	MRTSUE07115	1 year	2025-05-17	WJ-AC1
Broadband Preamplifier	Schwarzbeck	BBV 9745	MRTSUE07180	1 year	2025-06-05	WJ-AC1
Thermohygrometer	testo	608-H1	MRTSUE11333	1 year	2025-06-24	WJ-AC1
EXA Signal Analyzer	Keysight	N9010B	MRTSUE07147	1 year	2025-04-28	WJ-AC1/WJ-AC2
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07097	1 year	2025-04-24	WJ-AC2
Preamplifier	EMCI	EMC118A45SE	MRTSUE07102	1 year	2025-04-11	WJ-AC2
Horn Antenna	EMCI	DRH18-E	MRTSUE07105	1 year	2025-05-12	WJ-AC2
Anechoic Chamber	TDK	WJ-AC2	MRTSUE07117	1 year	2025-05-14	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11315	1 year	2025-06-24	WJ-AC2

Software	Version	Function
e3	230711	EMI Test Software
CONTROLLER CO3000	v 1.03.02	RE Antenna & Turntable
Agilent Power Analyzer/Agilent Power Panel	V R03.09.00	Power

## 5. Decision Rules and Measurement Uncertainty

### 5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>AC Conducted Emission Measurement</b>
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
<b>Radiated Emission Measurement</b>
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.61dB Coplanar: 9kHz~30MHz: 2.62dB Horizontal: 30MHz~200MHz: 3.79dB 200MHz~1GHz: 3.91dB 1GHz~40GHz: 4.99dB Vertical: 30MHz~200MHz: 4.06dB 200MHz~1GHz: 5.21dB 1GHz~40GHz: 4.90dB
<b>Spurious Emissions, Conducted</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 2.2dB
<b>Output Power</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.4dB
<b>Power Spectrum Density</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 2.2dB
<b>Occupied Bandwidth</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 2.7%

## 6. Test Result

### 6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	N/A

#### Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.
- "N/A" means that this item is not applicable, and the detail information refer to relevant section.

## 6.2. 6dB Bandwidth Measurement

### 6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

### 6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 6$ . The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3.  $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

### 6.2.4. Test Setup



### 6.2.5. Test Result

Refer to Appendix A.2.

### 6.3. Output Power Measurement

#### 6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.1.3

ANSI C63.10 - 2013 - Section 11.9.2.3.2

#### 6.3.3. Test Setting


##### **Method PKPM1 (Peak Power Measurement of Signals with DTS BW $\leq$ 50MHz)**

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

##### **Average Power Measurement**

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

#### 6.3.4. Test Setup



#### 6.3.5. Test Result

Refer to Appendix A.3.

## 6.4. Power Spectral Density Measurement

### 6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


### 6.4.2. Test Procedure

ANSI C63.10-2013 Section 11.10.2

### 6.4.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### 6.4.4. Test Setup



### 6.4.5. Test Result

Refer to Appendix A.4.

## **6.5. Conducted Band Edge and Out-of-Band Emissions Measurement**

### **6.5.1. Test Limit**

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

### **6.5.2. Test Procedure**

ANSI C63.10-2013 - Section 11.11

### **6.5.3. Test Setting**

#### **Reference level measurement**


1. Set instrument center frequency to DTS channel center frequency
2. Set the span to  $\geq 1.5$  times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW  $\geq 3 \times$  RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

#### **Emission level measurement**


1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

#### 6.5.4. Test Setup

Spectrum Analyzer



DC Block  
&  
Attenuator



#### 6.5.5. Test Result

Refer to Appendix A.5.

## 6.6. Radiated Spurious Emission Measurement

### 6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

### 6.6.3. Test Setting

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

**Quasi-Peak Measurements below 1GHz**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

**Peak Measurements above 1GHz**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

**Average Measurements above 1GHz (Method VB)**


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10Hz  
If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

### 6.6.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

## 6.7. Radiated Restricted Band Edge Measurement

### 6.7.1. Test Limit

#### For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

### 6.7.3. Test Setting

#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle  $\geq 98\%$ , set VBW = 10 Hz.

If the EUT duty cycle is  $< 98\%$ , set VBW  $\geq 1/T$ . T is the minimum transmission duration.

4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

#### 6.7.4. Test Setup



#### **6.7.5. Test Result**

Refer to Appendix A.7.

## 6.8. AC Conducted Emissions Measurement


### 6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 6.8.2. Test Setup



### 6.8.3. Test Result


The product is supplied by battery, so this item is not applicable.

## Appendix A - Test Result

### A.1 Duty Cycle Test Result

Test Site	SIP-TR1	Test Engineer	Ryan Wang
Test Date	2024-09-30		


Test Mode	Duty Cycle
BLE-1Mbps	62.00%
BLE-2Mbps	32.67%
Duty Cycle (T = Transmission Duration)	
BLE-1Mbps (T = 387.9µs)	BLE-2Mbps (T = 203.9µs)




**A.2 6dB Bandwidth Test Result**

Test Site	SIP-TR1	Test Engineer	Ryan Wang
Test Date	2024-09-29		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
BLE	1Mbps	00	2402	0.7196	≥ 0.5
BLE	1Mbps	19	2440	0.7143	≥ 0.5
BLE	1Mbps	39	2480	0.7063	≥ 0.5
BLE	2Mbps	00	2402	1.213	≥ 0.5
BLE	2Mbps	19	2440	1.262	≥ 0.5
BLE	2Mbps	39	2480	1.213	≥ 0.5





**A.3 Output Power Test Result**

Test Site	SIP-TR1	Test Engineer	Ryan Wang
Test Date	2024-09-30		

**Test Result of Peak Output Power**

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	6.95	≤ 30.00	Pass
BLE	1Mbps	19	2440	6.84	≤ 30.00	Pass
BLE	1Mbps	39	2480	6.61	≤ 30.00	Pass
BLE	2Mbps	00	2402	6.95	≤ 30.00	Pass
BLE	2Mbps	19	2440	6.85	≤ 30.00	Pass
BLE	2Mbps	39	2480	6.64	≤ 30.00	Pass


**Test Result of Average Output Power (Reporting Only)**

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Average Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	6.81	≤ 30.00	Pass
BLE	1Mbps	19	2440	6.70	≤ 30.00	Pass
BLE	1Mbps	39	2480	6.48	≤ 30.00	Pass
BLE	2Mbps	00	2402	6.79	≤ 30.00	Pass
BLE	2Mbps	19	2440	6.71	≤ 30.00	Pass
BLE	2Mbps	39	2480	6.49	≤ 30.00	Pass

**A.4 Power Spectral Density Test Result**

Test Site	SIP-TR1	Test Engineer	Ryan Wang
Test Date	2024-09-29		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1Mbps	00	2402	-8.27	≤ 8.00	Pass
BLE	1Mbps	19	2440	-8.36	≤ 8.00	Pass
BLE	1Mbps	39	2480	-8.52	≤ 8.00	Pass
BLE	2Mbps	00	2402	-11.84	≤ 8.00	Pass
BLE	2Mbps	19	2440	-11.83	≤ 8.00	Pass
BLE	2Mbps	39	2480	-12.08	≤ 8.00	Pass



BLE-2Mbps PSD

Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



### A.5 Conducted Band Edge and Out-of-Band Emissions Test Result

Test Site	SIP-TR1	Test Engineer	Ryan Wang
Test Date	2024-09-28		

Test Mode	Data Rate / Mbps	Channel No.	Frequency (MHz)	Limit	Result
BLE	1	00	2402	20	Pass
BLE	1	19	2440	20	Pass
BLE	1	39	2480	20	Pass
BLE	2	00	2402	20	Pass
BLE	2	19	2440	20	Pass
BLE	2	39	2480	20	Pass

**BLE-1Mbps Out-of-Band Emissions**  
**Channel 00 (2402MHz)**


100kHz PSD Reference Level	Low Band Edge

### Channel 19 (2440MHz)

#### 100kHz PSD Reference Level



#### Spurious Emission 30MHz ~ 25GHz



### Channel 39 (2480MHz)

#### 100kHz PSD Reference Level



#### High Band Edge



#### Spurious Emission 30MHz ~ 25GHz



## BLE-2Mbps Out-of-Band Emissions

### Channel 00 (2402MHz)


#### 100kHz PSD Reference Level



#### Low Band Edge



#### Spurious Emission 30MHz ~ 25GHz



### Channel 19 (2440MHz)

#### 100kHz PSD Reference Level




#### Spurious Emission 30MHz ~ 25GHz



### Channel 39 (2480MHz)


#### 100kHz PSD Reference Level



#### High Band Edge



#### Spurious Emission 30MHz ~ 25GHz



**A.6 Radiated Spurious Emission Test Result**

Test Site	WJ-AC2	Test Engineer	Carl Jiang
Test Date	2024-09-26	Test Mode	BLE-1Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not shown in the report.		

Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	8306.6	40.5	5.8	46.3	74.0	-27.7	Peak	Horizontal
	11538.3	43.1	5.1	48.2	74.0	-25.8	Peak	Horizontal
	12425.7	44.5	4.7	49.2	74.0	-24.8	Peak	Horizontal
	11279.9	42.5	5.3	47.8	74.0	-26.2	Peak	Vertical
	12213.2	44.2	4.9	49.1	74.0	-24.9	Peak	Vertical
	17784.1	47.8	4.4	52.2	74.0	-21.8	Peak	Vertical
	17790.6	36.1	4.4	40.5	54.0	-13.5	Average	Vertical
19	11329.2	43.1	5.4	48.5	74.0	-25.5	Peak	Horizontal
	12582.1	43.6	5.2	48.8	74.0	-25.2	Peak	Horizontal
	17785.8	47.9	4.4	52.3	74.0	-21.7	Peak	Horizontal
	17786.5	36.2	4.4	40.6	54.0	-13.4	Average	Horizontal
	9394.6	41.2	6.1	47.3	74.0	-26.7	Peak	Vertical
	12170.7	43.3	5.1	48.4	74.0	-25.6	Peak	Vertical
	12425.7	44.7	4.7	49.4	74.0	-24.6	Peak	Vertical
39	11490.7	43.0	5.3	48.3	74.0	-25.7	Peak	Horizontal
	12220.0	45.1	4.8	49.9	74.0	-24.1	Peak	Horizontal
	13335.2	44.0	5.1	49.1	74.0	-24.9	Peak	Horizontal
	8474.9	41.2	6.0	47.2	74.0	-26.8	Peak	Vertical
	11473.7	42.6	5.4	48.0	74.0	-26.0	Peak	Vertical
	12554.9	44.1	5.2	49.3	74.0	-24.7	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

Test Site	WJ-AC2	Test Engineer	Carl Jiang
Test Date	2024-09-26	Test Mode	BLE-2Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not shown in the report.		


Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	8141.7	40.9	5.7	46.6	74.0	-27.4	Peak	Horizontal
	11740.6	43.7	4.8	48.5	74.0	-25.5	Peak	Horizontal
	12313.5	44.9	4.7	49.6	74.0	-24.4	Peak	Horizontal
	9064.8	41.5	6.5	48.0	74.0	-26.0	Peak	Vertical
	11772.9	43.6	4.7	48.3	74.0	-25.7	Peak	Vertical
	12663.7	43.7	5.6	49.3	74.0	-24.7	Peak	Vertical
19	9046.1	41.1	6.6	47.7	74.0	-26.3	Peak	Horizontal
	11466.9	42.9	5.4	48.3	74.0	-25.7	Peak	Horizontal
	12192.8	44.0	5.0	49.0	74.0	-25.0	Peak	Horizontal
	9143.0	40.7	6.4	47.1	74.0	-26.9	Peak	Vertical
	11405.7	43.0	5.5	48.5	74.0	-25.5	Peak	Vertical
	12271.0	45.1	4.8	49.9	74.0	-24.1	Peak	Vertical
39	8209.7	41.1	5.7	46.8	74.0	-27.2	Peak	Horizontal
	11439.7	42.7	5.3	48.0	74.0	-26.0	Peak	Horizontal
	12634.8	43.6	5.5	49.1	74.0	-24.9	Peak	Horizontal
	9090.3	40.7	6.5	47.2	74.0	-26.8	Peak	Vertical
	11434.6	42.8	5.3	48.1	74.0	-25.9	Peak	Vertical
	12180.9	44.3	5.1	49.4	74.0	-24.6	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre\_Amplifier Gain (dB)

**The Result of Radiated Emission below 1GHz:**

Site	WJ-AC1	Test Date	2024-09-23
Test Engineer	Simon Lu	Temp./Humidity	19.9°C /65.2%
Factor	AC1 9163-25-1000MHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dB $\mu$ V)	C.F (dB/m)	Measurement (dB $\mu$ V/m)	Margin (dB)	Limit (dB $\mu$ V/m)	Detector
1		78.221	0.30	13.58	13.88	-26.12	40.00	QP
2		186.368	2.60	16.64	19.24	-24.26	43.50	QP
3		287.990	0.30	20.38	20.68	-25.32	46.00	QP
4		349.172	1.20	22.37	23.57	-22.43	46.00	QP
5	*	367.080	2.90	22.28	25.18	-20.82	46.00	QP
6		869.740	-9.20	30.41	21.21	-24.79	46.00	QP

**Notes:**

1. " \* ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement(dB $\mu$ V/m) = Reading(dB $\mu$ V) + C.F (dB/m).
4. QP measurement was not performed when peak measure level was lower than the QP limit.
5. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

Site	WJ-AC1	Test Date	2024-09-23
Test Engineer	Simon Lu	Temp./Humidity	19.9°C /65.2%
Factor	AC1 9163-25-1000MHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dB $\mu$ V)	C.F (dB/m)	Measurement (dB $\mu$ V/m)	Margin (dB)	Limit (dB $\mu$ V/m)	Detector
1	*	78.386	3.60	13.58	17.18	-22.82	40.00	QP
2		188.280	1.30	16.87	18.17	-25.33	43.50	QP
3		245.775	-3.70	19.33	15.63	-30.37	46.00	QP
4		293.561	-0.80	20.48	19.68	-26.32	46.00	QP
5		333.657	-2.30	21.71	19.41	-26.59	46.00	QP
6		409.318	-1.40	23.39	21.99	-24.01	46.00	QP

## Notes:

1. " \* ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m)+ Cable Loss (dB).
3. Measurement(dB $\mu$ V/m) = Reading(dB $\mu$ V) + C.F (dB/m).
4. QP measurement was not performed when peak measure level was lower than the QP limit.
5. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

**A.7 Radiated Restricted Band Edge Test Result**

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2352.208	24.50	36.79	61.29	-12.71	74.00	Peak
2		2390.000	19.47	36.88	56.36	-17.64	74.00	Peak
3	*	2401.722	67.46	36.94	104.40	30.40	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2383.426	8.67	36.86	45.53	-8.47	54.00	Average
2		2390.000	5.98	36.88	42.87	-11.13	54.00	Average
3	*	2401.998	66.70	36.94	103.64	49.64	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2383.103	23.82	36.86	60.68	-13.32	74.00	Peak
2		2390.000	19.82	36.88	56.70	-17.30	74.00	Peak
3	*	2401.732	60.83	36.94	97.77	23.77	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2362.507	9.15	36.82	45.97	-8.03	54.00	Average
2		2390.000	6.59	36.88	43.47	-10.53	54.00	Average
3	*	2402.027	60.04	36.94	96.98	42.98	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2480.255	64.29	37.04	101.34	27.34	74.00	Peak
2		2483.500	24.59	37.05	61.65	-12.35	74.00	Peak
3		2499.545	25.27	37.10	62.37	-11.63	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2480.031	63.21	37.04	100.25	46.25	54.00	Average
2		2483.500	6.82	37.05	43.87	-10.13	54.00	Average
3		2484.906	8.98	37.06	46.04	-7.96	54.00	Average

Notes:

1. "\*" , means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2479.756	63.14	37.04	100.18	26.18	74.00	Peak
2		2483.500	21.84	37.05	58.89	-15.11	74.00	Peak
3		2490.036	25.20	37.07	62.27	-11.73	74.00	Peak

Notes:

1. "\*" , means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 1M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2480.020	62.31	37.04	99.36	45.36	54.00	Average
2		2483.500	8.02	37.05	45.08	-8.92	54.00	Average
3		2485.137	9.41	37.06	46.47	-7.53	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2382.447	24.88	36.86	61.75	-12.25	74.00	Peak
2		2390.000	20.90	36.88	57.79	-16.21	74.00	Peak
3	*	2401.476	65.91	36.94	102.85	28.85	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2342.604	11.01	36.77	47.78	-6.22	54.00	Average
2		2390.000	9.56	36.88	46.44	-7.56	54.00	Average
3	*	2402.008	62.98	36.94	99.92	45.92	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2322.587	25.21	36.64	61.85	-12.15	74.00	Peak
2		2390.000	21.33	36.88	58.22	-15.78	74.00	Peak
3	*	2402.530	64.85	36.94	101.80	27.80	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2376.452	10.84	36.84	47.69	-6.31	54.00	Average
2		2390.000	9.29	36.88	46.17	-7.83	54.00	Average
3	*	2401.998	61.19	36.94	98.13	44.13	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2479.448	64.10	37.04	101.14	27.14	74.00	Peak
2		2483.500	23.43	37.05	60.48	-13.52	74.00	Peak
3		2493.589	25.18	37.08	62.26	-11.74	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Horizontal
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2480.020	61.49	37.04	98.53	44.53	54.00	Average
2		2483.500	11.36	37.05	48.41	-5.59	54.00	Average
3		2486.974	10.96	37.06	48.02	-5.98	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2479.487	62.00	37.04	99.04	25.04	74.00	Peak
2		2483.500	22.14	37.05	59.19	-14.81	74.00	Peak
3		2491.092	25.02	37.08	62.10	-11.90	74.00	Peak

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC1	Test Date	2024-09-24
Test Engineer	Simon Lu	Temp./Humidity	22.4°C /60.3%
Factor	Horn 3117_1-18GHz	Polarity	Vertical
EUT	Bluetooth headset	Test Voltage	By Battery
Test Mode	Transmit by BLE 2M at 2480MHz		



No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2480.022	59.60	37.04	96.65	42.65	54.00	Average
2		2483.500	10.71	37.05	47.77	-6.23	54.00	Average
3		2486.263	10.95	37.06	48.01	-5.99	54.00	Average

Notes:

1. " \*", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - AMP (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

## **Appendix B - Test Setup Photograph**

Refer to "2409RSU021-UT" file.

## Appendix C - EUT Photograph

Refer to "2409RSU021-UE" file.

\_\_\_\_\_ The End \_\_\_\_\_